

Package ‘RcppParallel’

August 27, 2026

Type Package

Title Parallel Programming Tools for 'Rcpp'

Version 6.2.1

Description High level functions for parallel programming with 'Rcpp'.

For example, the 'parallelFor()' function can be used to convert the work of a standard serial ``for" loop into a parallel one and the 'parallelReduce()' function can be used for accumulating aggregate or other values.

Depends R (>= 3.6.0)

Suggests Rcpp, knitr, rmarkdown

SystemRequirements CMake (>= 3.5)

License GPL (>= 3)

URL <https://rcppcore.github.io/RcppParallel/>,
<https://github.com/RcppCore/RcppParallel>

BugReports <https://github.com/RcppCore/RcppParallel/issues>

Biarch TRUE

RoxygenNote 7.3.3

Encoding UTF-8

NeedsCompilation yes

Author Kevin Ushey [aut, cre] (ORCID: <<https://orcid.org/0000-0003-2880-7407>>),
JJ Allaire [aut],
Romain Francois [aut, cph],
Gregory Vandenbrouck [aut],
Marcus Geelnard [aut, cph] (TinyThread library,
<https://tinythreadpp.bitsnbites.eu/>),
Hamada S. Badr [ctb] (ORCID: <<https://orcid.org/0000-0002-9808-2344>>),
Dirk Eddelbuettel [aut] (ORCID:
<<https://orcid.org/0000-0001-6419-907X>>),
Intel [aut, cph] (oneTBB library),
UXL Foundation [aut, cph] (oneTBB library),
Microsoft [cph],
Posit, PBC [cph]

Maintainer Kevin Ushey <kevin@rstudio.com>
Repository CRAN
Date/Publication 2026-08-27 05:10:40 UTC

Contents

RcppParallel-package	2
flags	2
isProcessForkedChild	3
RcppParallel.package.skeleton	4
setThreadOptions	5
tbbLibraryPath	6
Index	7

RcppParallel-package	<i>Parallel programming tools for Rcpp</i>
----------------------	--

Description

High level functions for doing parallel programming with Rcpp. For example, the `parallelFor()` function can be used to convert the work of a standard serial "for" loop into a parallel one, and the `parallelReduce()` function can be used for accumulating aggregate or other values.

Details

The high level interface enables safe and robust parallel programming without direct manipulation of operating system threads. On Windows, macOS, and Linux systems the underlying implementation is based on Intel TBB (Threading Building Blocks). On other platforms, a less-performant fallback implementation based on the TinyThread library is used.

For additional documentation, see the package website at:

<https://rcppcore.github.io/RcppParallel/>

flags	<i>Compilation flags for RcppParallel</i>
-------	---

Description

Output the compiler or linker flags required to build against RcppParallel.

Usage

```
CxxFlags()
```

```
LdFlags()
```

```
RcppParallelLibs()
```

Details

These functions are typically called from Makevars as follows:

```
PKG_LIBS += $(shell "${R_HOME}/bin/Rscript" -e "RcppParallel::LdFlags()")
```

What is emitted depends on how TBB is resolved at runtime on each platform. On Windows, every symbol has to be resolved at link time, so the flags name both the TBB libraries RcppParallel ships and RcppParallel itself. On macOS, they name the TBB libraries along with an `-rpath` entry, so that the resulting binary can find them without relying on RcppParallel having been loaded first. On Linux, the output is empty: TBB symbols are left undefined at link time and resolved from the libraries RcppParallel loads.

R packages using RcppParallel should also add the following to their `NAMESPACE` file:

```
importFrom(RcppParallel, RcppParallelLibs)
```

This is necessary to ensure that **RcppParallel** (and so, TBB) is loaded and available.

Value

Returns `NULL`, invisibly. These functions are called for their side effects (writing the associated flags to stdout).

`isProcessForkedChild` *Is the Current Process a Forked Child?*

Description

Returns `TRUE` if the current process is a `fork()` of the process in which RcppParallel was originally loaded.

Usage

```
isProcessForkedChild()
```

Details

Intel TBB — the parallel backend used by `parallelFor()` and `parallelReduce()` — does not support being used in a child process after `fork()`. Packages that may be invoked from within `parallel::mclapply()` or similar fork-based parallelism should call `isProcessForkedChild()` and fall back to a serial code path when it returns `TRUE`.

On Windows, which has no `fork()`, this always returns `FALSE`.

Value

A length-one logical.

Examples

```
## Not run:
library(RcppParallel)
isProcessForkedChild()
parallel::mclapply(1:2, function(i) RcppParallel::isProcessForkedChild())

## End(Not run)
```

RcppParallel.package.skeleton

Create a skeleton for a new package depending on RcppParallel

Description

RcppParallel.package.skeleton automates the creation of a new source package that intends to use features of RcppParallel.

Usage

```
RcppParallel.package.skeleton(name = "anRpackage", example_code = TRUE, ...)
```

Arguments

name	The name of your R package.
example_code	If TRUE, example C++ code using RcppParallel is added to the package.
...	Optional arguments passed to Rcpp.package.skeleton .

Details

It is based on the [package.skeleton](#) function which it executes first.

In addition to [Rcpp.package.skeleton](#) :

The ‘DESCRIPTION’ file gains an Imports line requesting that the package depends on RcppParallel and a LinkingTo line so that the package finds RcppParallel header files.

The ‘NAMESPACE’ gains a useDynLib directive as well as an importFrom(RcppParallel, evalCpp to ensure instantiation of RcppParallel.

The ‘src’ directory is created if it does not exists and a ‘Makevars’ file is added setting the environment variables ‘PKG_LIBS’ to accomodate the necessary flags to link with the RcppParallel library.

If the example_code argument is set to TRUE, example files ‘vector-sum.cpp’ is created in the ‘src’ directory. Rcpp::compileAttributes() is then called to generate src/RcppExports.cpp and R/RcppExports.R. These files are given as an example and should eventually be removed from the generated package.

Value

Nothing, used for its side effects

References

Read the *Writing R Extensions* manual for more details.

Once you have created a *source* package you need to install it: see the *R Installation and Administration* manual, [INSTALL](#) and [install.packages](#).

See Also

[package.skeleton](#)

Examples

```
## Not run:
# simple package
RcppParallel::package.skeleton("foobar")

## End(Not run)
```

setThreadOptions	<i>Thread options for RcppParallel</i>
------------------	--

Description

Set thread options (number of threads to use for task scheduling and stack size per-thread) for RcppParallel.

Usage

```
setThreadOptions(numThreads = "auto", stackSize = "auto")

defaultNumThreads()
```

Arguments

numThreads	Number of threads to use for task scheduling. Call defaultNumThreads() to determine the the default value used for "auto".
stackSize	Stack size (in bytes) to use for worker threads. The default used for "auto" is 2MB on 32-bit systems and 4MB on 64-bit systems (note that this parameter has no effect on Windows).

Details

RcppParallel is automatically initialized with the default number of threads and thread stack size when it loads. You can call `setThreadOptions()` at any time to change the defaults.

The `parallelFor()` and `parallelReduce()` also accept `numThreads` as an argument, if you'd like to control the number of threads specifically to be made available for a particular parallel function call. Note that this value is advisory, and TBB may choose a smaller number of threads if the number of requested threads cannot be honored on the system.

Value

`defaultNumThreads()` returns the default number of threads used by RcppParallel, if another value isn't specified either via `setThreadOptions()` or explicitly in calls to `parallelFor()` and `parallelReduce()`.

Examples

```
## Not run:
library(RcppParallel)
setThreadOptions(numThreads = 4)
defaultNumThreads()

## End(Not run)
```

tbbLibraryPath

Get the Path to a TBB Library

Description

Retrieve the path to a TBB library. This can be useful for R packages using RcppParallel that wish to use, or re-use, the version of TBB that RcppParallel has been configured to use.

Usage

```
tbbLibraryPath(name = NULL)
```

Arguments

name	The name of the TBB library to be resolved. Normally, this is one of <code>tbb</code> , <code>tbbmalloc</code> , or <code>tbbmalloc_proxy</code> . When <code>NULL</code> , the library path containing the TBB libraries is returned instead.
------	--

Index

- * **package**
 - RcppParallel-package, [2](#)
- * **parallel**
 - RcppParallel-package, [2](#)
- * **programming**
 - RcppParallel.package.skeleton, [4](#)
- CxxFlags (flags), [2](#)
- defaultNumThreads (setThreadOptions), [5](#)
- flags, [2](#)
- INSTALL, [5](#)
- install.packages, [5](#)
- isProcessForkedChild, [3](#)
- LdFlags (flags), [2](#)
- package.skeleton, [4](#), [5](#)
- Rcpp.package.skeleton, [4](#)
- RcppParallel (RcppParallel-package), [2](#)
- RcppParallel-package, [2](#)
- RcppParallel.package.skeleton, [4](#)
- RcppParallelLibs (flags), [2](#)
- setThreadOptions, [5](#)
- tbbLibraryPath, [6](#)