

# Package ‘TrialEmulation’

August 25, 2026

**Title** Causal Analysis of Observational Time-to-Event Data

**Version** 0.0.5

**Description** Implements target trial emulation methods to apply randomized clinical trial design and analysis in an observational setting. Using marginal structural models, it can estimate intention-to-treat and per-protocol effects in emulated trials using electronic health records. A description and application of the method can be found in Danaei et al (2013) <[doi:10.1177/0962280211403603](https://doi.org/10.1177/0962280211403603)>.

**License** Apache License (>= 2)

**URL** <https://causal-lda.github.io/TrialEmulation/>,  
<https://github.com/Causal-LDA/TrialEmulation>

**BugReports** <https://github.com/Causal-LDA/TrialEmulation/issues>

**Depends** R (>= 4.1.0)

**Imports** broom (>= 0.7.10), checkmate, data.table (>= 1.9.8), DBI,  
duckdb, formula.tools, lifecycle, lmtest, methods, mvtnorm,  
Rcpp, sandwich, future.apply

**Suggests** knitr, parsnip, rmarkdown, rpart, testthat (>= 3.0.0), withr

**LinkingTo** Rcpp

**VignetteBuilder** knitr

**Config/testthat/edition** 3

**Encoding** UTF-8

**Language** en-GB

**LazyData** true

**LazyDataCompression** xz

**Collate** 'RcppExports.R' 'bootstrap.R' 'bootstrap\_helpers.R'  
'calculate\_weights.R' 'data.R' 'data\_extension.R'  
'data\_manipulation.R' 'data\_preparation.R' 'data\_simulation.R'  
'data\_utils.R' 'expand\_trials.R' 'generics.R' 'initiators.R'  
'lr\_utils.R' 'te\_model\_fitter.R' 'te\_outcome\_model.R'  
'te\_datastore.R' 'te\_weights.R' 'te\_data.R' 'te\_expansion.R'

```
'trial_sequence.R' 'modelling.R' 'package.R' 'predict.R'
'robust.R' 'sampling.R' 'te_datastore_csv.R'
'te_datastore_duckdb.R' 'te_parsnip.R' 'te_stats_glm_logit.R'
'utils.R' 'weighting.R'
```

**Config/roxygen2/version** 8.1.0

**Config/Needs/website** rmarkdown

**NeedsCompilation** yes

**Author** Isaac Gravestock [aut, cre] (ORCID:

<<https://orcid.org/0000-0003-0283-2065>>),

Li Su [aut],

Roonak Rezvani [aut] (ORCID: <<https://orcid.org/0000-0001-5580-5058>>),

Original package author),

Julia Moesch [aut],

Juliette Limozin [aut] (ORCID: <<https://orcid.org/0000-0002-1140-2350>>),

Medical Research Council (MRC) [fnd],

F. Hoffmann-La Roche AG [cph, fnd]

**Maintainer** Isaac Gravestock <isaac.gravestock@gmail.com>

**Repository** CRAN

**Date/Publication** 2026-08-25 10:50:13 UTC

## Contents

|                                        |    |
|----------------------------------------|----|
| calculate_weights . . . . .            | 3  |
| case_control_sampling_trials . . . . . | 4  |
| data_censored . . . . .                | 5  |
| data_preparation . . . . .             | 6  |
| expand_trials . . . . .                | 9  |
| fit_msm . . . . .                      | 10 |
| fit_weights_model . . . . .            | 11 |
| initiators . . . . .                   | 12 |
| ipw_data . . . . .                     | 16 |
| load_expanded_data . . . . .           | 17 |
| outcome_data . . . . .                 | 18 |
| parsnip_model . . . . .                | 19 |
| predict_marginal . . . . .             | 20 |
| print.TE_weight_summary . . . . .      | 23 |
| read_expanded_data . . . . .           | 24 |
| sample_expanded_data . . . . .         | 25 |
| save_expanded_data . . . . .           | 26 |
| save_to_csv . . . . .                  | 26 |
| save_to_datatable . . . . .            | 27 |
| save_to_duckdb . . . . .               | 28 |
| set_censor_weight_model . . . . .      | 28 |
| set_data . . . . .                     | 30 |
| set_expansion_options . . . . .        | 32 |
| set_outcome_model . . . . .            | 34 |

|                                     |    |
|-------------------------------------|----|
| set_switch_weight_model . . . . .   | 35 |
| show_weight_models . . . . .        | 37 |
| stats_glm_logit . . . . .           | 37 |
| summary.TE_data_prep . . . . .      | 38 |
| te_data-class . . . . .             | 39 |
| te_datastore-class . . . . .        | 39 |
| te_data_ex . . . . .                | 39 |
| te_model_ex . . . . .               | 40 |
| te_model_fitter-class . . . . .     | 41 |
| te_outcome_data-class . . . . .     | 41 |
| te_outcome_fitted-class . . . . .   | 41 |
| te_outcome_model-class . . . . .    | 42 |
| trial_example . . . . .             | 42 |
| trial_msm . . . . .                 | 43 |
| trial_sequence . . . . .            | 45 |
| trial_sequence-class . . . . .      | 46 |
| vignette_switch_data . . . . .      | 46 |
| weight_model_data_indices . . . . . | 47 |

|              |           |
|--------------|-----------|
| <b>Index</b> | <b>49</b> |
|--------------|-----------|

|                   |                                                           |
|-------------------|-----------------------------------------------------------|
| calculate_weights | <i>Calculate Inverse Probability of Censoring Weights</i> |
|-------------------|-----------------------------------------------------------|

## Description

[Experimental]

## Usage

```
calculate_weights(object, ...)
```

```
## S4 method for signature 'trial_sequence_ITT'
```

```
calculate_weights(object, quiet = FALSE)
```

```
## S4 method for signature 'trial_sequence_AT'
```

```
calculate_weights(object, quiet = FALSE)
```

```
## S4 method for signature 'trial_sequence_PP'
```

```
calculate_weights(object, quiet = FALSE)
```

## Arguments

|        |                                         |
|--------|-----------------------------------------|
| object | A <a href="#">trial_sequence</a> object |
| ...    | Other arguments used by methods.        |
| quiet  | Prints model summaries is TRUE.         |

**Value**

A [trial\\_sequence](#) object with updated `tensor_weights` and/or `switch_weights` slots

**Examples**

```
save_dir <- file.path(tempdir(), "switch_models")
ts <- trial_sequence("PP") |>
  set_data(
    data = data_censored,
    id = "id",
    period = "period",
    treatment = "treatment",
    outcome = "outcome",
    eligible = "eligible"
  ) |>
  set_switch_weight_model(
    numerator = ~ age + x1 + x3,
    denominator = ~age,
    model_fitter = stats_glm_logit(save_path = save_dir)
  ) |>
  calculate_weights()
```

---

case\_control\_sampling\_trials

*Case-control sampling of expanded data for the sequence of emulated trials*

---

**Description**

[Stable]

**Usage**

```
case_control_sampling_trials(
  data_prep,
  p_control = NULL,
  subset_condition,
  sort = FALSE
)
```

**Arguments**

|                               |                                                                                                     |
|-------------------------------|-----------------------------------------------------------------------------------------------------|
| <code>data_prep</code>        | Result from <a href="#">data_preparation()</a> .                                                    |
| <code>p_control</code>        | Control sampling probability for selecting potential controls at each follow-up time of each trial. |
| <code>subset_condition</code> | Expression used to <a href="#">subset()</a> the trial data before case-control sampling.            |

**sort** Sort data before applying case-control sampling to make sure that the resulting data are identical when sampling from the expanded data created with `separate_files = TRUE` or `separate_files = FALSE`.

## Details

Perform case-control sampling of expanded data to create a data set of reduced size and calculate sampling weights to be used in `trial_msm()`.

## Value

A data.frame or a `split()` data.frame if `length(p_control) > 1`. An additional column `sample_weight` containing the sample weights will be added to the result. These can be included in the models fit with `trial_msm()`.

## Examples

```
# If necessary reduce the number of threads for data.table
data.table::setDTthreads(2)

data("te_data_ex")
samples <- case_control_sampling_trials(te_data_ex, p_control = 0.01)
```

---

|               |                                                                                         |
|---------------|-----------------------------------------------------------------------------------------|
| data_censored | <i>Example of longitudinal data for sequential trial emulation containing censoring</i> |
|---------------|-----------------------------------------------------------------------------------------|

---

## Description

This data contains data from 89 patients followed for up to 19 periods.

## Usage

```
data_censored
```

## Format

A data frame with 725 rows and 12 variables:

**id** patient identifier

**period** time period

**treatment** indicator for receiving treatment in this period, 1=treatment, 0=non-treatment

**x1** A time-varying categorical variable relating to treatment and the outcome

**x2** A time-varying numeric variable relating to treatment and the outcome

**x3** A fixed categorical variable relating to treatment and the outcome

**x4** A fixed categorical variable relating to treatment and the outcome

**age** patient age in years

**age\_s** patient age

**outcome** indicator for outcome in this period, 1=event occurred, 0=no event

**censored** indicator for patient being censored in this period, 1=censored, 0=not censored

**eligible** indicator for eligibility for trial start in this period, 1=yes, 0=no

---

data\_preparation

*Prepare data for the sequence of emulated target trials*

---

## Description

[Stable]

## Usage

```
data_preparation(
  data,
  id = "id",
  period = "period",
  treatment = "treatment",
  outcome = "outcome",
  eligible = "eligible",
  model_var = NULL,
  outcome_cov = ~1,
  estimand_type = c("ITT", "PP", "As-Treated"),
  switch_n_cov = ~1,
  switch_d_cov = ~1,
  first_period = NA,
  last_period = NA,
  use_censor_weights = FALSE,
  cense = NA,
  pool_cense = c("none", "both", "numerator"),
  cense_d_cov = ~1,
  cense_n_cov = ~1,
  eligible_wts_0 = NA,
  eligible_wts_1 = NA,
  where_var = NULL,
  data_dir,
  save_weight_models = FALSE,
  glm_function = "glm",
  chunk_size = 500,
  separate_files = FALSE,
  quiet = FALSE,
  ...
)
```

**Arguments**

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>data</code>               | A <code>data.frame</code> containing all the required variables in the person-time format, i.e., the 'long' format.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <code>id</code>                 | Name of the variable for identifiers of the individuals. Default is 'id'.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <code>period</code>             | Name of the variable for the visit/period. Default is 'period'.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <code>treatment</code>          | Name of the variable for the treatment indicator at that visit/period. Default is 'treatment'.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <code>outcome</code>            | Name of the variable for the indicator of the outcome event at that visit/period. Default is 'outcome'.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <code>eligible</code>           | Name of the variable for the indicator of eligibility for the target trial at that visit/period. Default is 'eligible'.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <code>model_var</code>          | Treatment variables to be included in the marginal structural model for the emulated trials. <code>model_var = "assigned_treatment"</code> will create a variable <code>assigned_treatment</code> that is the assigned treatment at the trial baseline, typically used for ITT and per-protocol analyses. <code>model_var = "dose"</code> will create a variable <code>dose</code> that is the cumulative number of treatments received since the trial baseline, typically used in as-treated analyses.                                                                                                                                                                                                                              |
| <code>outcome_cov</code>        | A RHS formula with baseline covariates to be adjusted for in the marginal structural model for the emulated trials. Note that if a time-varying covariate is specified in <code>outcome_cov</code> , only its value at each of the trial baselines will be included in the expanded data.                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <code>estimand_type</code>      | Specify the estimand for the causal analyses in the sequence of emulated trials. <code>estimand_type = "ITT"</code> will perform intention-to-treat analyses, where treatment switching after trial baselines are ignored. <code>estimand_type = "PP"</code> will perform per-protocol analyses, where individuals' follow-ups are artificially censored and inverse probability of treatment weighting is applied. <code>estimand_type = "As-Treated"</code> will fit a standard marginal structural model for all possible treatment sequences, where individuals' follow-ups are not artificially censored but treatment switching after trial baselines are accounted for by applying inverse probability of treatment weighting. |
| <code>switch_n_cov</code>       | A RHS formula to specify the logistic models for estimating the numerator terms of the inverse probability of treatment weights. A derived variable named <code>time_on_regime</code> containing the duration of time that the individual has been on the current treatment/non-treatment is available for use in these models.                                                                                                                                                                                                                                                                                                                                                                                                       |
| <code>switch_d_cov</code>       | A RHS formula to specify the logistic models for estimating the denominator terms of the inverse probability of treatment weights.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>first_period</code>       | First time period to be set as trial baseline to start expanding the data.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <code>last_period</code>        | Last time period to be set as trial baseline to start expanding the data.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <code>use_censor_weights</code> | Require the inverse probability of censoring weights. If <code>use_censor_weights = TRUE</code> , then the variable name of the censoring indicator needs to be provided in the argument <code>cense</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>cense</code>              | Variable name for the censoring indicator. Required if <code>use_censor_weights = TRUE</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>pool_cense</code>         | Fit pooled or separate censoring models for those treated and those untreated at the immediately previous visit. Pooling can be specified for the models for the numerator and denominator terms of the inverse probability of censoring weights. One of "none", "numerator", or "both" (default is "none" except when <code>estimand_type</code> = "ITT" then default is "numerator").                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <code>cense_d_cov</code>        | A RHS formula to specify the logistic models for estimating the denominator terms of the inverse probability of censoring weights.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <code>cense_n_cov</code>        | A RHS formula to specify the logistic models for estimating the numerator terms of the inverse probability of censoring weights.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>eligible_wts_0</code>     | See definition for <code>eligible_wts_1</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <code>eligible_wts_1</code>     | Exclude some observations when fitting the models for the inverse probability of treatment weights. For example, if it is assumed that an individual will stay on treatment for at least 2 visits, the first 2 visits after treatment initiation by definition have a probability of staying on the treatment of 1.0 and should thus be excluded from the weight models for those who are on treatment at the immediately previous visit. Users can define a variable that indicates that these 2 observations are ineligible for the weight model for those who are on treatment at the immediately previous visit and add the variable name in the argument <code>eligible_wts_1</code> . Similar definitions are applied to <code>eligible_wts_0</code> for excluding observations when fitting the models for the inverse probability of treatment weights for those who are not on treatment at the immediately previous visit. |
| <code>where_var</code>          | Specify the variable names that will be used to define subgroup conditions when fitting the marginal structural model for a subgroup of individuals. Need to specify jointly with the argument <code>where_case</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <code>data_dir</code>           | Directory to save model objects when <code>save_weight_models</code> =TRUE and expanded data as separate CSV files names as <code>trial_i.csvs</code> if <code>separate_files</code> = TRUE. If the specified directory does not exist it will be created. If the directory already contains trial files, an error will occur, other files may be overwritten.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <code>save_weight_models</code> | Save model objects for estimating the weights in <code>data_dir</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <code>glm_function</code>       | Deprecated as <code>parglm</code> is no longer available on CRAN. This option will be ignored and "glm" will be used for model fitting.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <code>chunk_size</code>         | Number of individuals whose data to be processed in one chunk when <code>separate_files</code> = TRUE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <code>separate_files</code>     | Save expanded data in separate CSV files for each trial.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <code>quiet</code>              | Suppress the printing of progress messages and summaries of the fitted models.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <code>...</code>                | Additional arguments passed to <code>glm_function</code> . This may be used to specify initial values of parameters or arguments to control. See <a href="#">stats::glm</a> for more information.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

## Details

This function expands observational data in the person-time format (i.e., the 'long' format) to emulate a sequence of target trials and also estimates the inverse probability of treatment and censoring weights as required.

The arguments `chunk_size` and `separate_files` allow for processing of large datasets that would not fit in memory once expanded. When `separate_files = TRUE`, the input data are processed in chunks of individuals and saved into separate files for each emulated trial. These separate files can be sampled by case-control sampling to create a reduced dataset for the modelling.

### Value

An object of class `TE_data_prep`, which can either be sampled from ([case\\_control\\_sampling\\_trials](#)) or directly used in a model ([trial\\_msm](#)). It contains the elements

**data** the expanded dataset for all emulated trials. If `separate_files = FALSE`, it is a `data.table`; if `separate_files = TRUE`, it is a character vector with the file path of the expanded data as CSV files.

**min\_period** index for the first trial in the expanded data

**max\_period** index for the last trial in the expanded data

**N** the total number of observations in the expanded data

**data\_template** a zero-row `data.frame` with the columns and attributes of the expanded data

**switch\_models** a list of summaries of the models fitted for inverse probability of treatment weights, if `estimand_type` is "PP" or "As-Treated"

**censor\_models** a list of summaries of the models fitted for inverse probability of censoring weights, if `use_censor_weights=TRUE`

**args** a list contain the parameters used to prepare the data and fit the weight models

---

expand\_trials

*Expand trials*

---

### Description

[Experimental]

### Usage

```
expand_trials(object)
```

### Arguments

object                    A [trial\\_sequence](#) object

### Value

The [trial\\_sequence](#) object with a data set containing the full sequence of target trials. The data is stored according to the options set with [set\\_expansion\\_options\(\)](#) and especially the `save_to_*` function.

fit\_msm

*Fit the marginal structural model for the sequence of emulated trials***Description****[Experimental]****Usage**

```
fit_msm(
  object,
  weight_cols = c("weight", "sample_weight"),
  modify_weights = NULL
)

## S4 method for signature 'trial_sequence'
fit_msm(
  object,
  weight_cols = c("weight", "sample_weight"),
  modify_weights = NULL
)
```

**Arguments**

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object         | A trial_sequence object                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| weight_cols    | character vector of column names in expanded outcome dataset, ie outcome_data(object). If multiple columns are specified, the element wise product will be used. Specify NULL if no weight columns should be used.                                                                                                                                                                                                                                                                                                                                                                                           |
| modify_weights | a function to transform the weights (or NULL for no transformation). Must take a numeric vector of weights and a vector of positive, finite weights of the same length. See examples for some possible function definitions.<br>Before the outcome marginal structural model can be fit, the outcome model must be specified with <a href="#">set_outcome_model()</a> and the data must be expanded into the trial sequence with <a href="#">expand_trials()</a> .<br>The model is fit based on the model_fitter specified in <a href="#">set_outcome_model</a> using the internal fit_outcome_model method. |

**Value**

A modified trial\_sequence object with updated outcome\_model slot.

**Examples**

```
trial_seq_object <- trial_sequence("ITT") |>
  set_data(data_censored) |>
  set_outcome_model(
    adjustment_terms = ~age_s,
```

```

    followup_time_terms = ~ stats::poly(followup_time, degree = 2)
  ) |>
  set_expansion_options(output = save_to_datatable(), chunk_size = 500) |>
  expand_trials() |>
  load_expanded_data()

fit_msm(trial_seq_object)

# Using modify_weights functions ----

# returns a function that truncates weights to limits
limit_weight <- function(lower_limit, upper_limit) {
  function(w) {
    w[w > upper_limit] <- upper_limit
    w[w < lower_limit] <- lower_limit
    w
  }
}

# calculate 1st and 99th percentile limits and truncate
p99_weight <- function(w) {
  p99 <- quantile(w, prob = c(0.01, 0.99), type = 1)
  limit_weight(p99[1], p99[2])(w)
}

# set all weights to 1
all_ones <- function(w) {
  rep(1, length(w))
}

fit_msm(trial_seq_object, modify_weights = limit_weight(0.01, 4))
fit_msm(trial_seq_object, modify_weights = p99_weight)

```

---

|                   |                                         |
|-------------------|-----------------------------------------|
| fit_weights_model | <i>Method for fitting weight models</i> |
|-------------------|-----------------------------------------|

---

## Description

Method for fitting weight models

## Usage

```
fit_weights_model(object, data, formula, label)
```

## Arguments

|         |                                                                                                              |
|---------|--------------------------------------------------------------------------------------------------------------|
| object  | The object determining which method should be used, containing any slots containing user defined parameters. |
| data    | data.frame containing outcomes and covariates as defined in formula.                                         |
| formula | formula describing the model.                                                                                |
| label   | A short string describing the model.                                                                         |

**Value**

An object of class `te_weights_fitted`

**Examples**

```
fitter <- stats_glm_logit(tempdir())
data(data_censored)
# Not usually called directly by a user
fitted <- fit_weights_model(
  object = fitter,
  data = data_censored,
  formula = 1 - censored ~ x1 + age_s + treatment,
  label = "Example model for censoring"
)
fitted
unlink(fitted@summary$save_path$path)
```

---

|            |                                                                                                                 |
|------------|-----------------------------------------------------------------------------------------------------------------|
| initiators | <i>A wrapper function to perform data preparation and model fitting in a sequence of emulated target trials</i> |
|------------|-----------------------------------------------------------------------------------------------------------------|

---

**Description**

[Stable]

**Usage**

```
initiators(
  data,
  id = "id",
  period = "period",
  treatment = "treatment",
  outcome = "outcome",
  eligible = "eligible",
  outcome_cov = ~1,
  estimand_type = c("ITT", "PP", "As-Treated"),
  model_var = NULL,
  switch_n_cov = ~1,
  switch_d_cov = ~1,
  first_period = NA,
  last_period = NA,
  first_followup = NA,
  last_followup = NA,
  use_censor_weights = FALSE,
  save_weight_models = FALSE,
  analysis_weights = c("asis", "unweighted", "p99", "weight_limits"),
  weight_limits = c(0, Inf),
  cense = NA,
```

```

pool_cense = c("none", "both", "numerator"),
cense_d_cov = ~1,
cense_n_cov = ~1,
include_followup_time = ~followup_time + I(followup_time^2),
include_trial_period = ~trial_period + I(trial_period^2),
eligible_wts_0 = NA,
eligible_wts_1 = NA,
where_var = NULL,
where_case = NA,
data_dir,
glm_function = "glm",
quiet = FALSE,
...
)

```

## Arguments

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| data          | A data.frame containing all the required variables in the person-time format, i.e., the ‘long’ format.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| id            | Name of the variable for identifiers of the individuals. Default is ‘id’.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| period        | Name of the variable for the visit/period. Default is ‘period’.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| treatment     | Name of the variable for the treatment indicator at that visit/period. Default is ‘treatment’.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| outcome       | Name of the variable for the indicator of the outcome event at that visit/period. Default is ‘outcome’.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| eligible      | Name of the variable for the indicator of eligibility for the target trial at that visit/period. Default is ‘eligible’.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| outcome_cov   | A RHS formula with baseline covariates to be adjusted for in the marginal structural model for the emulated trials. Note that if a time-varying covariate is specified in outcome_cov, only its value at each of the trial baselines will be included in the expanded data.                                                                                                                                                                                                                                                                                                                                                                                                                    |
| estimand_type | Specify the estimand for the causal analyses in the sequence of emulated trials. estimand_type = "ITT" will perform intention-to-treat analyses, where treatment switching after trial baselines are ignored. estimand_type = "PP" will perform per-protocol analyses, where individuals’ follow-ups are artificially censored and inverse probability of treatment weighting is applied. estimand_type = "As-Treated" will fit a standard marginal structural model for all possible treatment sequences, where individuals’ follow-ups are not artificially censored but treatment switching after trial baselines are accounted for by applying inverse probability of treatment weighting. |
| model_var     | Treatment variables to be included in the marginal structural model for the emulated trials. model_var = "assigned_treatment" will create a variable assigned_treatment that is the assigned treatment at the trial baseline, typically used for ITT and per-protocol analyses. model_var = "dose" will create a variable dose that is the cumulative number of treatments received since the trial baseline, typically used in as-treated analyses.                                                                                                                                                                                                                                           |

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| switch_n_cov          | A RHS formula to specify the logistic models for estimating the numerator terms of the inverse probability of treatment weights. A derived variable named <code>time_on_regime</code> containing the duration of time that the individual has been on the current treatment/non-treatment is available for use in these models.                                                                                                                                                                                                                                           |
| switch_d_cov          | A RHS formula to specify the logistic models for estimating the denominator terms of the inverse probability of treatment weights.                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| first_period          | First time period to be set as trial baseline to start expanding the data.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| last_period           | Last time period to be set as trial baseline to start expanding the data.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| first_followup        | First follow-up time/visit in the trials to be included in the marginal structural model for the outcome event.                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| last_followup         | Last follow-up time/visit in the trials to be included in the marginal structural model for the outcome event.                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| use_censor_weights    | Require the inverse probability of censoring weights. If <code>use_censor_weights = TRUE</code> , then the variable name of the censoring indicator needs to be provided in the argument <code>cense</code> .                                                                                                                                                                                                                                                                                                                                                             |
| save_weight_models    | Save model objects for estimating the weights in <code>data_dir</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| analysis_weights      | Choose which type of weights to be used for fitting the marginal structural model for the outcome event. <ul style="list-style-type: none"> <li>• "asis": use the weights as calculated.</li> <li>• "p99": use weights truncated at the 1st and 99th percentiles (based on the distribution of weights in the entire sample).</li> <li>• "weight_limits": use weights truncated at the values specified in <code>weight_limits</code>.</li> <li>• "unweighted": set all analysis weights to 1, even if treatment weights or censoring weights were calculated.</li> </ul> |
| weight_limits         | Lower and upper limits to truncate weights, given as <code>c(lower, upper)</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| cense                 | Variable name for the censoring indicator. Required if <code>use_censor_weights = TRUE</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| pool_cense            | Fit pooled or separate censoring models for those treated and those untreated at the immediately previous visit. Pooling can be specified for the models for the numerator and denominator terms of the inverse probability of censoring weights. One of "none", "numerator", or "both" (default is "none" except when <code>estimand_type = "ITT"</code> then default is "numerator").                                                                                                                                                                                   |
| cense_d_cov           | A RHS formula to specify the logistic models for estimating the denominator terms of the inverse probability of censoring weights.                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| cense_n_cov           | A RHS formula to specify the logistic models for estimating the numerator terms of the inverse probability of censoring weights.                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| include_followup_time | The model to include the follow up time/visit of the trial ( <code>followup_time</code> ) in the marginal structural model, specified as a RHS formula.                                                                                                                                                                                                                                                                                                                                                                                                                   |
| include_trial_period  | The model to include the trial period ( <code>trial_period</code> ) in the marginal structural model, specified as a RHS formula.                                                                                                                                                                                                                                                                                                                                                                                                                                         |

|                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>eligible_wts_0</code> | See definition for <code>eligible_wts_1</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <code>eligible_wts_1</code> | Exclude some observations when fitting the models for the inverse probability of treatment weights. For example, if it is assumed that an individual will stay on treatment for at least 2 visits, the first 2 visits after treatment initiation by definition have a probability of staying on the treatment of 1.0 and should thus be excluded from the weight models for those who are on treatment at the immediately previous visit. Users can define a variable that indicates that these 2 observations are ineligible for the weight model for those who are on treatment at the immediately previous visit and add the variable name in the argument <code>eligible_wts_1</code> . Similar definitions are applied to <code>eligible_wts_0</code> for excluding observations when fitting the models for the inverse probability of treatment weights for those who are not on treatment at the immediately previous visit. |
| <code>where_var</code>      | Specify the variable names that will be used to define subgroup conditions when fitting the marginal structural model for a subgroup of individuals. Need to specify jointly with the argument <code>where_case</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <code>where_case</code>     | Define conditions using variables specified in <code>where_var</code> when fitting a marginal structural model for a subgroup of the individuals. For example, if <code>where_var = "age"</code> , <code>where_case = "age &gt;= 30"</code> will only fit the marginal structural model to the subgroup of individuals. who are 30 years old or above.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <code>data_dir</code>       | Directory to save model objects in.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>glm_function</code>   | Deprecated as <code>parglm</code> is no longer available on CRAN. This option will be ignored and <code>"glm"</code> will be used for model fitting.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <code>quiet</code>          | Suppress the printing of progress messages and summaries of the fitted models.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <code>...</code>            | Additional arguments passed to <code>glm_function</code> . This may be used to specify initial values of parameters or arguments to control. See <a href="#">stats::glm</a> for more information.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

## Details

An all-in-one analysis using a sequence of emulated target trials. This provides a simplified interface to the main functions [data\\_preparation\(\)](#) and [trial\\_msm\(\)](#).

## Value

Returns the result of [trial\\_msm\(\)](#) from the expanded data. An object of class `TE_msm` containing

**model** a `glm` object

**robust** a list containing a summary table of estimated regression coefficients and the robust covariance matrix

ipw\_data

*IPW Data Accessor and Setter***Description****[Experimental]****Usage**

```

ipw_data(object)

ipw_data(object) <- value

## S4 method for signature 'trial_sequence'
ipw_data(object)

## S4 replacement method for signature 'trial_sequence'
ipw_data(object) <- value

```

**Arguments**

|        |                                           |
|--------|-------------------------------------------|
| object | trial_sequence object                     |
| value  | data.table to replace and update in @data |

**Details**

Generic function to access and update the data used for inverse probability weighting.

The setter method `ipw_data(object) <- value` does not perform the same checks and manipulations as `set_data()`. To completely replace the data please use `set_data()`. This `ipw_data<-` method allows small changes such as adding a new column.

**Value**

The data from the @data slot of object used for inverse probability weighting.

**Examples**

```

ts <- trial_sequence("ITT")
ts <- set_data(ts, data_censored)
ipw_data(ts)
data.table::set(ipw_data(ts), j = "dummy", value = TRUE)

# or with the setter method:
new_data <- ipw_data(ts)
new_data$x2sq <- new_data$x2^2
ipw_data(ts) <- new_data

```

---

|                    |                                                        |
|--------------------|--------------------------------------------------------|
| load_expanded_data | <i>Method to read, subset and sample expanded data</i> |
|--------------------|--------------------------------------------------------|

---

**Description****[Experimental]****Usage**

```
load_expanded_data(
  object,
  p_control = NULL,
  period = NULL,
  subset_condition = NULL,
  seed = NULL
)

## S4 method for signature 'trial_sequence'
load_expanded_data(
  object,
  p_control = NULL,
  period = NULL,
  subset_condition = NULL,
  seed = NULL
)
```

**Arguments**

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object           | An object of class <a href="#">trial_sequence</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| p_control        | Probability of selecting a control, NULL for no sampling (default).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| period           | An integerish vector of non-zero length to select trial period(s) or NULL (default) to select all trial periods.                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| subset_condition | <p>A string or NULL (default). subset_condition will be translated to a call (in case the expanded data is saved as a data.table or in the csv format) or to a SQL-query (in case the expanded data is saved as a duckdb file).</p> <p>The operators "==" , "!=" , "&gt;" , "&gt;=" , "&lt;" , "&lt;=" , "%in%" , "&amp;" , " " are supported. Numeric vectors can be written as c(1, 2, 3) or 1:3. Variables are not supported.</p> <p><i>Note:</i> Make sure numeric vectors written as 1:3 are surrounded by spaces, e.g. a %in% c( 1:4 , 6:9 ), otherwise the code will fail.</p> |
| seed             | <p>An integer seed or NULL (default).</p> <p><i>Note:</i> The same seed will return a different result depending on the class of the <a href="#">te_datastore</a> object contained in the <a href="#">trial_sequence</a> object.</p>                                                                                                                                                                                                                                                                                                                                                  |

## Details

This method is used on [trial\\_sequence](#) objects to read, subset and sample expanded data.

## Value

An updated [trial\\_sequence](#) object, the data is stored in slot @outcome\_data as a [te\\_outcome\\_data](#) object.

## Examples

```
# create a trial_sequence-class object
trial_itt_dir <- file.path(tempdir(), "trial_itt")
dir.create(trial_itt_dir)
trial_itt <- trial_sequence(estimand = "ITT") |>
  set_data(data = data_censored) |>
  set_outcome_model(adjustment_terms = ~ x1 + x2)

trial_itt_csv <- set_expansion_options(
  trial_itt,
  output = save_to_csv(file.path(trial_itt_dir, "trial_csvs")),
  chunk_size = 500
) |>
  expand_trials()

# load_expanded_data default behaviour returns all trial_periods and doesn't sample
load_expanded_data(trial_itt_csv)

# load_expanded_data can subset the data before sampling
load_expanded_data(
  trial_itt_csv,
  p_control = 0.2,
  period = 1:20,
  subset_condition = "followup_time %in% 1:20 & x2 < 1",
)

# delete after use
unlink(trial_itt_dir, recursive = TRUE)
```

---

outcome\_data

Outcome Data Accessor and Setter

---

## Description

**[Experimental]**

**Usage**

```
outcome_data(object)

outcome_data(object) <- value

## S4 method for signature 'trial_sequence'
outcome_data(object)

## S4 replacement method for signature 'trial_sequence'
outcome_data(object) <- value
```

**Arguments**

```
object      trial_sequence object
value       data.table to replace and update in @outcome_data
```

**Details**

Generic function to outcome data

**Value**

The object with updated outcome data

**Examples**

```
ts <- trial_sequence("ITT")
new_data <- data.table::data.table(vignette_switch_data[1:200, ])
new_data$weight <- 1
outcome_data(ts) <- new_data
```

---

|               |                                                |
|---------------|------------------------------------------------|
| parsnip_model | <i>Fit outcome models using parsnip models</i> |
|---------------|------------------------------------------------|

---

**Description**

**[Experimental]**

**Usage**

```
parsnip_model(model_spec, save_path)
```

**Arguments**

```
model_spec  A parsnip model definition with mode = "classification".
save_path   Directory to save models. Set to NA if models should not be saved.
```

## Details

Specify that the models should be fit using a classification model specified with the `parsnip` package.

Warning: This functionality is experimental and not recommended for use in analyses. *sqrtn*-consistency estimation and valid inference of the parameters in marginal structural models for emulated trials generally require that the weights for treatment switching and censoring be estimated at parametric rates, which is generally not possible when using data-adaptive estimation of high-dimensional regressions. Therefore, we only recommend using `stats_glm_logit()`.

## Value

An object of class `te_parsnip_model` inheriting from `te_model_fitter` which is used for dispatching methods for the fitting models.

## See Also

Other `model_fitter`: `stats_glm_logit()`, `te_model_fitter-class`

## Examples

```
## Not run:
if (
  requireNamespace("parsnip", quietly = TRUE) &&
  requireNamespace("rpart", quietly = TRUE)
) {
  # Use a decision tree model fitted with the rpart package
  parsnip_model(
    model_spec = parsnip::decision_tree(tree_depth = 30) |>
      set_mode("classification") |>
      set_engine("rpart"),
    save_path = tempdir()
  )
}

## End(Not run)
```

---

predict\_marginal

*Predict marginal cumulative incidences with confidence intervals for a target trial population*

---

## Description

[Stable]

**Usage**

```

predict(object, ...)

## S4 method for signature 'trial_sequence_ITT'
predict(
  object,
  newdata,
  predict_times,
  conf_int = TRUE,
  ci_type = "sandwich",
  samples = 100,
  type = c("cum_inc", "survival")
)

## S4 method for signature 'trial_sequence_PP'
predict(
  object,
  newdata,
  predict_times,
  conf_int = TRUE,
  samples = 100,
  ci_type = c("sandwich", "Nonpara. bootstrap", "LEF outcome", "LEF both",
    "Jackknife Wald", "Jackknife MVN"),
  type = c("cum_inc", "survival")
)

## S3 method for class 'TE_msm'
predict(
  object,
  newdata,
  predict_times,
  conf_int = TRUE,
  samples = 100,
  type = c("cum_inc", "survival"),
  ...
)

```

**Arguments**

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>object</code>        | Object from <code>trial_msm()</code> or <code>initiators()</code> or <code>trial_sequence</code> .                                                                                                                                                                                                                                                                                                                                              |
| <code>...</code>           | Further arguments passed to or from other methods.                                                                                                                                                                                                                                                                                                                                                                                              |
| <code>newdata</code>       | Baseline trial data that characterise the target trial population that marginal cumulative incidences or survival probabilities are predicted for. <code>newdata</code> must have the same columns and formats of variables as in the fitted marginal structural model specified in <code>trial_msm()</code> or <code>initiators()</code> . If <code>newdata</code> contains rows with <code>followup_time &gt; 0</code> these will be removed. |
| <code>predict_times</code> | Specify the follow-up visits/times where the marginal cumulative incidences or survival probabilities are predicted.                                                                                                                                                                                                                                                                                                                            |

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>conf_int</code> | Construct the point-wise 95-percent confidence intervals of cumulative incidences for the target trial population under treatment and non-treatment and their differences. The default confidence interval construction methods simulates the parameters in the marginal structural model from a multivariate normal distribution with the mean equal to the marginal structural model parameter estimates and the variance equal to the estimated robust covariance matrix. |
| <code>ci_type</code>  | Specify the method used to construct the confidence interval for a per-protocol estimand ( <code>estimand_type = "PP"</code> ) (only available for <a href="#">trial_sequence</a> object). 'sandwich': using the estimated robust sandwich covariance matrix; 'Nonpara. bootstrap', 'LEF outcome', 'LEF both', 'Jackknife Wald', 'Jackknife MVN'                                                                                                                             |
| <code>samples</code>  | Number of samples used to construct the simulation-based confidence intervals.                                                                                                                                                                                                                                                                                                                                                                                               |
| <code>type</code>     | Specify cumulative incidences or survival probabilities to be predicted. Either cumulative incidence ( <code>"cum_inc"</code> ) or survival probability ( <code>"survival"</code> ).                                                                                                                                                                                                                                                                                         |

## Details

This function predicts the marginal cumulative incidences when a target trial population receives either the treatment or non-treatment at baseline (for an intention-to-treat analysis) or either sustained treatment or sustained non-treatment (for a per-protocol analysis). The difference between these cumulative incidences is the estimated causal effect of treatment. Currently, the `predict` function only provides marginal intention-to-treat and per-protocol effects, therefore it is only valid when `estimand_type = "ITT"` or `estimand_type = "PP"`.

The width of the confidence intervals for resampling-based methods ('Nonpara. bootstrap', 'LEF outcome', 'LEF both', 'Jackknife Wald') is determined by the presence of an `id` column in `newdata`. If included, the function accounts for sampling variation in the target population, which typically yields wider intervals. If omitted, the target population is treated as a fixed group, and the intervals reflect only the uncertainty from the original source model.

## Value

A list of three data frames containing the cumulative incidences for each of the assigned treatment options (treatment and non-treatment) and the difference between them.

## Examples

```
# Prediction for initiators() or trial_msm() objects -----

# If necessary set the number of `data.table` threads
data.table::setDTthreads(2)

data("te_model_ex")
predicted_ci <- predict(te_model_ex, predict_times = 0:30, samples = 10)

# Plot the cumulative incidence curves under treatment and non-treatment
plot(predicted_ci[[1]]$followup_time, predicted_ci[[1]]$cum_inc,
     type = "l",
     xlab = "Follow-up Time", ylab = "Cumulative Incidence",
     ylim = c(0, 0.7)
)
```

```

lines(predicted_ci[[1]]$followup_time, predicted_ci[[1]]$`2.5%`, lty = 2)
lines(predicted_ci[[1]]$followup_time, predicted_ci[[1]]$`97.5%`, lty = 2)

lines(predicted_ci[[2]]$followup_time, predicted_ci[[2]]$cum_inc, type = "l", col = 2)
lines(predicted_ci[[2]]$followup_time, predicted_ci[[2]]$`2.5%`, lty = 2, col = 2)
lines(predicted_ci[[2]]$followup_time, predicted_ci[[2]]$`97.5%`, lty = 2, col = 2)
legend("topleft", title = "Assigned Treatment", legend = c("0", "1"), col = 1:2, lty = 1)

# Plot the difference in cumulative incidence over follow up
plot(predicted_ci[[3]]$followup_time, predicted_ci[[3]]$cum_inc_diff,
     type = "l",
     xlab = "Follow-up Time", ylab = "Difference in Cumulative Incidence",
     ylim = c(0.0, 0.5)
)
lines(predicted_ci[[3]]$followup_time, predicted_ci[[3]]$`2.5%`, lty = 2)
lines(predicted_ci[[3]]$followup_time, predicted_ci[[3]]$`97.5%`, lty = 2)

```

---

```
print.TE_weight_summary
```

*Print a weight summary object*

---

## Description

[Stable]

## Usage

```
## S3 method for class 'TE_weight_summary'
print(x, full = TRUE, ...)
```

## Arguments

|      |                                                        |
|------|--------------------------------------------------------|
| x    | print TE_weight_summary object.                        |
| full | Print full or short summary.                           |
| ...  | Arguments passed to <a href="#">print.data.frame</a> . |

## Value

No return value, only for printing.

---

|                    |                                     |
|--------------------|-------------------------------------|
| read_expanded_data | <i>Method to read expanded data</i> |
|--------------------|-------------------------------------|

---

## Description

This method is used on [te\\_datastore](#) objects to read selected data and return one `data.table`.

## Usage

```
read_expanded_data(object, period = NULL, subset_condition = NULL)

## S4 method for signature 'te_datastore_datatable'
read_expanded_data(object, period = NULL, subset_condition = NULL)
```

## Arguments

|                               |                                                                                                          |
|-------------------------------|----------------------------------------------------------------------------------------------------------|
| <code>object</code>           | An object of class <a href="#">te_datastore</a> .                                                        |
| <code>period</code>           | An integerish vector of non-zero length to select trial period(s) or NULL (default) to select all files. |
| <code>subset_condition</code> | A string of length 1 or NULL (default).                                                                  |

## Value

A `data.frame` of class `data.table`.

## Examples

```
# create a te_datastore_csv object and save some data
temp_dir <- tempfile("csv_dir_")
dir.create(temp_dir)
datastore <- save_to_csv(temp_dir)
data(vignette_switch_data)
expanded_csv_data <- save_expanded_data(datastore, vignette_switch_data[1:200, ])

# read expanded data
read_expanded_data(expanded_csv_data)

# delete after use
unlink(temp_dir, recursive = TRUE)
```

---

sample\_expanded\_data    *Internal method to sample expanded data*

---

### Description

Internal method to sample expanded data

### Usage

```
sample_expanded_data(
  object,
  p_control,
  period = NULL,
  subset_condition = NULL,
  seed
)

## S4 method for signature 'te_datastore'
sample_expanded_data(
  object,
  p_control,
  period = NULL,
  subset_condition = NULL,
  seed
)
```

### Arguments

|                  |                                                                                                                  |
|------------------|------------------------------------------------------------------------------------------------------------------|
| object           | An object of class <a href="#">te_datastore</a> .                                                                |
| p_control        | Probability of selecting a control.                                                                              |
| period           | An integerish vector of non-zero length to select trial period(s) or NULL (default) to select all trial periods. |
| subset_condition | A string or NULL.                                                                                                |
| seed             | An integer seed or NULL (default).                                                                               |

### Value

A data.frame of class data.table.

### Examples

```
# Data object normally created by [expand_trials]
datastore <- new("te_datastore_datatable", data = te_data_ex$data, N = 50139L)

sample_expanded_data(datastore, period = 260:275, p_control = 0.2, seed = 123)
```

---

|                    |                                     |
|--------------------|-------------------------------------|
| save_expanded_data | <i>Method to save expanded data</i> |
|--------------------|-------------------------------------|

---

### Description

This method is used internally by [expand\\_trials](#) to save the data to the "datastore" defined in [set\\_expansion\\_options](#).

### Usage

```
save_expanded_data(object, data)

## S4 method for signature 'te_datastore_datatable'
save_expanded_data(object, data)
```

### Arguments

|        |                                                                                                                                                                                                                                        |
|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object | An object of class <a href="#">te_datastore</a> or a child class.                                                                                                                                                                      |
| data   | A data frame containing the expanded trial data. The columns <code>trial_period</code> and <code>id</code> are present, which may be used in methods to save the data in an optimal way, such as with indexes, keys or separate files. |

### Value

An updated object with the data stored. Notably `object@N` should be increased

### Examples

```
temp_dir <- tempfile("csv_dir_")
dir.create(temp_dir)
datastore <- save_to_csv(temp_dir)
data(vignette_switch_data)
save_expanded_data(datastore, vignette_switch_data[1:200, ])

# delete after use
unlink(temp_dir, recursive = TRUE)
```

---

|             |                                  |
|-------------|----------------------------------|
| save_to_csv | <i>Save expanded data as CSV</i> |
|-------------|----------------------------------|

---

### Description

**[Experimental]**

### Usage

```
save_to_csv(path)
```

**Arguments**

path                      Directory to save CSV files in. Must be empty.

**Value**

A [te\\_datastore\\_csv](#) object.

**See Also**

Other save\_to: [save\\_to\\_datatable\(\)](#), [save\\_to\\_duckdb\(\)](#), [set\\_expansion\\_options\(\)](#)

**Examples**

```
csv_dir <- file.path(tempdir(), "expanded_trials_csv")
dir.create(csv_dir)
csv_datastore <- save_to_csv(path = csv_dir)

trial_to_expand <- trial_sequence("ITT") |>
  set_data(data = data_censored) |>
  set_expansion_options(output = csv_datastore, chunk_size = 500)

# Delete directory after use
unlink(csv_dir)
```

---

|                   |                                           |
|-------------------|-------------------------------------------|
| save_to_datatable | <i>Save expanded data as a data.table</i> |
|-------------------|-------------------------------------------|

---

**Description**

**[Experimental]**

**Usage**

```
save_to_datatable()
```

**See Also**

Other save\_to: [save\\_to\\_csv\(\)](#), [save\\_to\\_duckdb\(\)](#), [set\\_expansion\\_options\(\)](#)

**Examples**

```
trial_to_expand <- trial_sequence("ITT") |>
  set_data(data = data_censored) |>
  set_expansion_options(output = save_to_datatable(), chunk_size = 500)
```

---

|                |                                     |
|----------------|-------------------------------------|
| save_to_duckdb | <i>Save expanded data to DuckDB</i> |
|----------------|-------------------------------------|

---

**Description****[Experimental]****Usage**

```
save_to_duckdb(path)
```

**Arguments**

|      |                                            |
|------|--------------------------------------------|
| path | Directory to save DuckDB database file in. |
|------|--------------------------------------------|

**Value**

A [te\\_datastore\\_duckdb](#) object.

**See Also**

Other save\_to: [save\\_to\\_csv\(\)](#), [save\\_to\\_datatable\(\)](#), [set\\_expansion\\_options\(\)](#)

**Examples**

```
if (require(duckdb)) {
  duckdb_dir <- file.path(tempdir(), "expanded_trials_duckdb")

  trial_to_expand <- trial_sequence("ITT") |>
    set_data(data = data_censored) |>
    set_expansion_options(output = save_to_duckdb(path = duckdb_dir), chunk_size = 500)

  # Delete directory after use
  unlink(duckdb_dir)
}
```

---

|                         |                                   |
|-------------------------|-----------------------------------|
| set_censor_weight_model | <i>Set censoring weight model</i> |
|-------------------------|-----------------------------------|

---

**Description****[Experimental]**

**Usage**

```
set_censor_weight_model(  
  object,  
  censor_event,  
  numerator,  
  denominator,  
  pool_models = NULL,  
  model_fitter  
)  
  
## S4 method for signature 'trial_sequence'  
set_censor_weight_model(  
  object,  
  censor_event,  
  numerator,  
  denominator,  
  pool_models = c("none", "both", "numerator"),  
  model_fitter = stats_glm_logit()  
)  
  
## S4 method for signature 'trial_sequence_PP'  
set_censor_weight_model(  
  object,  
  censor_event,  
  numerator,  
  denominator,  
  pool_models = "none",  
  model_fitter = stats_glm_logit()  
)  
  
## S4 method for signature 'trial_sequence_ITT'  
set_censor_weight_model(  
  object,  
  censor_event,  
  numerator,  
  denominator,  
  pool_models = "numerator",  
  model_fitter = stats_glm_logit()  
)  
  
## S4 method for signature 'trial_sequence_AT'  
set_censor_weight_model(  
  object,  
  censor_event,  
  numerator,  
  denominator,  
  pool_models = "none",  
  model_fitter = stats_glm_logit()  
)
```

)

Arguments

|              |                                                                                                                                                                                                                                                                                                                                                                       |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object       | trial_sequence.                                                                                                                                                                                                                                                                                                                                                       |
| censor_event | string. Name of column containing censoring indicator.                                                                                                                                                                                                                                                                                                                |
| numerator    | A RHS formula to specify the logistic models for estimating the numerator terms of the inverse probability of censoring weights.                                                                                                                                                                                                                                      |
| denominator  | A RHS formula to specify the logistic models for estimating the denominator terms of the inverse probability of censoring weights.                                                                                                                                                                                                                                    |
| pool_models  | Fit pooled or separate censoring models for those treated and those untreated at the immediately previous visit. Pooling can be specified for the models for the numerator and denominator terms of the inverse probability of censoring weights. One of "none", "numerator", or "both" (default is "none" except when estimand = "ITT" then default is "numerator"). |
| model_fitter | An object of class te_model_fitter which determines the method used for fitting the weight models. For logistic regression use <a href="#">stats_glm_logit()</a> .                                                                                                                                                                                                    |

Value

object is returned with @censor\_weights set

Examples

```
trial_sequence("ITT") |>
  set_data(data = data_censored) |>
  set_censor_weight_model(
    censor_event = "censored",
    numerator = ~ age_s + x1 + x3,
    denominator = ~ x3 + x4,
    pool_models = "both",
    model_fitter = stats_glm_logit(save_path = tempdir())
  )
```

---

|          |                           |
|----------|---------------------------|
| set_data | <i>Set the trial data</i> |
|----------|---------------------------|

---

Description

[Experimental]

**Usage**

```

set_data(object, data, ...)

## S4 method for signature 'trial_sequence_ITT,data.frame'
set_data(
  object,
  data,
  id = "id",
  period = "period",
  treatment = "treatment",
  outcome = "outcome",
  eligible = "eligible"
)

## S4 method for signature 'trial_sequence_AT,data.frame'
set_data(
  object,
  data,
  id = "id",
  period = "period",
  treatment = "treatment",
  outcome = "outcome",
  eligible = "eligible"
)

## S4 method for signature 'trial_sequence_PP,data.frame'
set_data(
  object,
  data,
  id = "id",
  period = "period",
  treatment = "treatment",
  outcome = "outcome",
  eligible = "eligible"
)

```

**Arguments**

|           |                                                                                                                                                            |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object    | A <a href="#">trial_sequence</a> object                                                                                                                    |
| data      | A <code>data.frame</code> containing all the required variables in the person-time format, i.e., the <code>&lt;U+2018&gt;long&lt;U+2019&gt;</code> format. |
| ...       | Other arguments used by methods internally.                                                                                                                |
| id        | Name of the variable for identifiers of the individuals. Default is <code>&lt;U+2018&gt;id&lt;U+2019&gt;</code> .                                          |
| period    | Name of the variable for the visit/period. Default is <code>&lt;U+2018&gt;period&lt;U+2019&gt;</code> .                                                    |
| treatment | Name of the variable for the treatment indicator at that visit/period. Default is <code>&lt;U+2018&gt;treatment&lt;U+2019&gt;</code> .                     |

|          |                                                                                                                                       |
|----------|---------------------------------------------------------------------------------------------------------------------------------------|
| outcome  | Name of the variable for the indicator of the outcome event at that visit/period. Default is <U+2018>outcome<U+2019>.                 |
| eligible | Name of the variable for the indicator of eligibility for the target trial at that visit/period. Default is <U+2018>eligible<U+2019>. |

**Value**

An updated [trial\\_sequence](#) object with data

**Examples**

```
data(trial_example)
trial_sequence("ITT") |>
  set_data(
    data = trial_example,
    id = "id",
    period = "period",
    eligible = "eligible",
    treatment = "treatment"
  )
```

---

set\_expansion\_options *Set expansion options*

---

**Description**

**[Experimental]**

**Usage**

```
set_expansion_options(object, ...)

## S4 method for signature 'trial_sequence_ITT'
set_expansion_options(
  object,
  output,
  chunk_size,
  first_period = 0,
  last_period = Inf
)

## S4 method for signature 'trial_sequence_PP'
set_expansion_options(
  object,
  output,
  chunk_size,
  first_period = 0,
```

```

    last_period = Inf
  )

  ## S4 method for signature 'trial_sequence_ITT'
  set_expansion_options(
    object,
    output,
    chunk_size,
    first_period = 0,
    last_period = Inf
  )

```

### Arguments

|              |                                                                                        |
|--------------|----------------------------------------------------------------------------------------|
| object       | A <a href="#">trial_sequence</a> object                                                |
| ...          | Arguments used in methods                                                              |
| output       | A <a href="#">te_datastore</a> object as created by a <code>save_to_*</code> function. |
| chunk_size   | An integer specifying the number of patients to include in each expansion iteration    |
| first_period | An integer specifying the first period to include in the expansion                     |
| last_period  | An integer specifying the last period to include in the expansion                      |

### Value

object is returned with @expansion set

### See Also

Other `save_to_`: [save\\_to\\_csv\(\)](#), [save\\_to\\_datatable\(\)](#), [save\\_to\\_duckdb\(\)](#)

### Examples

```

output_dir <- file.path(tempdir(check = TRUE), "expanded_data")
ITT_trial <- trial_sequence("ITT") |>
  set_data(data = data_censored) |>
  set_expansion_options(output = save_to_csv(output_dir), chunk_size = 500)

# Delete directory
unlink(output_dir, recursive = TRUE)

```

---

|                   |                                  |
|-------------------|----------------------------------|
| set_outcome_model | <i>Specify the outcome model</i> |
|-------------------|----------------------------------|

---

## Description

### [Experimental]

The time-to-event model for outcome is specified with this method. Any adjustment terms can be specified. For ITT and PP estimands the treatment\_var is not specified as it is automatically defined as assigned\_treatment. Importantly, the modelling of "time" is specified in this model with arguments for trial start time and follow up time within the trial.

## Usage

```
set_outcome_model(object, ...)

## S4 method for signature 'trial_sequence'
set_outcome_model(
  object,
  treatment_var = ~0,
  adjustment_terms = ~1,
  followup_time_terms = ~followup_time + I(followup_time^2),
  trial_period_terms = ~trial_period + I(trial_period^2),
  model_fitter = stats_glm_logit(save_path = NA)
)

## S4 method for signature 'trial_sequence_ITT'
set_outcome_model(
  object,
  adjustment_terms = ~1,
  followup_time_terms = ~followup_time + I(followup_time^2),
  trial_period_terms = ~trial_period + I(trial_period^2),
  model_fitter = stats_glm_logit(save_path = NA)
)

## S4 method for signature 'trial_sequence_PP'
set_outcome_model(
  object,
  adjustment_terms = ~1,
  followup_time_terms = ~followup_time + I(followup_time^2),
  trial_period_terms = ~trial_period + I(trial_period^2),
  model_fitter = stats_glm_logit(save_path = NA)
)

## S4 method for signature 'trial_sequence_AT'
set_outcome_model(
  object,
```

```

    treatment_var = "dose",
    adjustment_terms = ~1,
    followup_time_terms = ~followup_time + I(followup_time^2),
    trial_period_terms = ~trial_period + I(trial_period^2),
    model_fitter = stats_glm_logit(save_path = NA)
  )

```

## Arguments

|                     |                                                                                                             |
|---------------------|-------------------------------------------------------------------------------------------------------------|
| object              | A trial_sequence object                                                                                     |
| ...                 | Parameters used by methods                                                                                  |
| treatment_var       | The treatment term, only used for "as treated" estimands. PP and ITT are fixed to use "assigned_treatment". |
| adjustment_terms    | Formula terms for any covariates to adjust the outcome model.                                               |
| followup_time_terms | Formula terms for followup_time, the time period relative to the start of the trial.                        |
| trial_period_terms  | Formula terms for trial_period, the time period of the start of the trial.                                  |
| model_fitter        | A te_model_fitter object, e.g. from stats_glm_logit().                                                      |

## Value

A modified object with the outcome\_model slot set

## Examples

```

trial_sequence("ITT") |>
  set_data(data_censored) |>
  set_outcome_model(
    adjustment_terms = ~age_s,
    followup_time_terms = ~ stats::poly(followup_time, degree = 2)
  )

```

---

```
set_switch_weight_model
```

*Set switching weight model*

---

## Description

**[Experimental]**

**Usage**

```
set_switch_weight_model(object, numerator, denominator, model_fitter, ...)
```

```
## S4 method for signature 'trial_sequence'
```

```
set_switch_weight_model(
  object,
  numerator,
  denominator,
  model_fitter,
  eligible_wts_0 = NULL,
  eligible_wts_1 = NULL
)
```

```
## S4 method for signature 'trial_sequence_ITT'
```

```
set_switch_weight_model(object, numerator, denominator, model_fitter)
```

**Arguments**

|                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>object</code>         | A <a href="#">trial_sequence</a> object.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <code>numerator</code>      | Right hand side formula for the numerator model                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <code>denominator</code>    | Right hand side formula for the denominator model                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>model_fitter</code>   | A <a href="#">te_model_fitter</a> object, such as <a href="#">stats_glm_logit</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>...</code>            | Other arguments used by methods.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>eligible_wts_0</code> | Name of column containing indicator (0/1) for observation to be excluded/included in weight model.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <code>eligible_wts_1</code> | Exclude some observations when fitting the models for the inverse probability of treatment weights. For example, if it is assumed that an individual will stay on treatment for at least 2 visits, the first 2 visits after treatment initiation by definition have a probability of staying on the treatment of 1.0 and should thus be excluded from the weight models for those who are on treatment at the immediately previous visit. Users can define a variable that indicates that these 2 observations are ineligible for the weight model for those who are on treatment at the immediately previous visit and add the variable name in the argument <code>eligible_wts_1</code> . Similar definitions are applied to <code>eligible_wts_0</code> for excluding observations when fitting the models for the inverse probability of treatment weights for those who are not on treatment at the immediately previous visit. |

**Value**

`object` is returned with `@switch_weights` set

**Examples**

```
trial_sequence("PP") |>
  set_data(data = data_censored) |>
  set_switch_weight_model(
```

```

    numerator = ~ age_s + x1 + x3,
    denominator = ~ x3 + x4,
    model_fitter = stats_glm_logit(tempdir())
  )

```

---

|                    |                                    |
|--------------------|------------------------------------|
| show_weight_models | <i>Show Weight Model Summaries</i> |
|--------------------|------------------------------------|

---

## Description

**[Experimental]**

## Usage

```
show_weight_models(object)
```

## Arguments

object            A [trial\\_sequence](#) object after fitting weight models with [calculate\\_weights\(\)](#)

## Value

Prints summaries of the censoring models

---

|                 |                                            |
|-----------------|--------------------------------------------|
| stats_glm_logit | <i>Fit outcome models using stats::glm</i> |
|-----------------|--------------------------------------------|

---

## Description

**[Experimental]**

## Usage

```
stats_glm_logit(save_path)
```

## Arguments

save\_path            Directory to save models. Set to NA if models should not be saved.

## Details

Specify that the pooled logistic regression outcome models should be fit using [stats::glm](#) with `family = binomial(link = "logit")`.

Outcome models additional calculate robust variance estimates using `sandwich::vcovCL`.

**Value**

An object of class `te_stats_glm_logit` inheriting from `te_model_fitter` which is used for dispatching methods for the fitting models.

**See Also**

Other model\_fitter: `parsnip_model()`, `te_model_fitter-class`

**Examples**

```
stats_glm_logit(save_path = tempdir())
```

---

|                      |                        |
|----------------------|------------------------|
| summary.TE_data_prep | <i>Summary methods</i> |
|----------------------|------------------------|

---

**Description**

**[Stable]** Print summaries of data and model objects produced by TrialEmulation.

**Usage**

```
## S3 method for class 'TE_data_prep'
summary(object, ...)

## S3 method for class 'TE_data_prep_sep'
summary(object, ...)

## S3 method for class 'TE_data_prep_dt'
summary(object, ...)

## S3 method for class 'TE_msm'
summary(object, ...)

## S3 method for class 'TE_robust'
summary(object, ...)
```

**Arguments**

|        |                                               |
|--------|-----------------------------------------------|
| object | Object to print summary                       |
| ...    | Additional arguments passed to print methods. |

**Value**

No value, displays summaries of object.

---

|               |                                  |
|---------------|----------------------------------|
| te_data-class | <i>TrialEmulation Data Class</i> |
|---------------|----------------------------------|

---

**Description**

TrialEmulation Data Class

**Slots**

data A data.table object with columns "id", "period", "treatment", "outcome", "eligible"

---

|                    |                     |
|--------------------|---------------------|
| te_datastore-class | <i>te_datastore</i> |
|--------------------|---------------------|

---

**Description**

This is the parent class for classes which define how the expanded trial data should be stored. To define a new storage type, a new class should be defined which inherits from te\_datastore. In addition, methods [save\\_expanded\\_data](#) and read\_expanded\_data need to be defined for the new class.

**Value**

A 'te\_datastore' object

**Slots**

N The number of observations in this data. Initially 0.

---

|            |                                          |
|------------|------------------------------------------|
| te_data_ex | <i>Example of a prepared data object</i> |
|------------|------------------------------------------|

---

**Description**

A small example object from [data\\_preparation](#) used in examples. It is created with the following code:

**Usage**

te\_data\_ex

**Format**

An object of class TE\_data\_prep\_dt (inherits from TE\_data\_prep) of length 6.

**Details**

```

dat <- trial_example[trial_example$id < 200, ]

te_data_ex <- data_preparation(
  data = dat,
  outcome_cov = c("nvarA", "catvarA"),
  first_period = 260,
  last_period = 280
)

```

**See Also**

[te\\_model\\_ex](#)

---

te\_model\_ex

*Example of a fitted marginal structural model object*


---

**Description**

A small example object from [trial\\_msm](#) used in examples. It is created with the following code:

**Usage**

```
te_model_ex
```

**Format**

An object of class TE\_msm of length 3.

**Details**

```

te_model_ex <- trial_msm(
  data = data_subset,
  outcome_cov = c("catvarA", "nvarA"),
  last_followup = 40,
  model_var = "assigned_treatment",
  include_followup_time = ~followup_time,
  include_trial_period = ~trial_period,
  use_sample_weights = FALSE,
  quiet = TRUE,
  glm_function = "glm"
)

```

**See Also**

[te\\_data\\_ex](#)

---

te\_model\_fitter-class *Outcome Model Fitter Class*


---

### Description

This is a virtual class which other outcome model fitter classes should inherit from. Objects of these class exist to define how the outcome models are fit. They are used for the dispatch of the internal methods [fit\\_outcome\\_model](#), [fit\\_weights\\_model](#) and [predict](#).

### See Also

Other model\_fitter: [parsnip\\_model\(\)](#), [stats\\_glm\\_logit\(\)](#)

---

te\_outcome\_data-class *TrialEmulation Outcome Data Class*


---

### Description

TrialEmulation Outcome Data Class

### Slots

data A data.table object with columns "id", "period",  
n\_rows Number of rows  
n\_ids Number of IDs  
periods Vector of periods "treatment", "outcome", "eligible"

---

te\_outcome\_fitted-class  
*Fitted Outcome Model Object*


---

### Description

Fitted Outcome Model Object

### Slots

model list containing fitted model objects.  
summary list of data.frames. Tidy model summaries a la [broom\(\)](#) and [glance\(\)](#)

---

te\_outcome\_model-class

*Fitted Outcome Model Object*


---

## Description

Fitted Outcome Model Object

## Slots

formula formula object for the model fitting  
 adjustment\_vars character. Adjustment variables  
 treatment\_var Variable used for treatment  
 stabilised\_weights\_terms formula. Adjustment terms from numerator models of stabilised weights. These must be included in the outcome model.  
 adjustment\_terms formula. User specified terms to include in the outcome model  
 treatment\_terms formula. Estimand defined treatment term  
 followup\_time\_terms formula. Terms to model follow up time within an emulated trial  
 trial\_period\_terms formula. Terms to model start time ("trial\_period") of an emulated trial  
 model\_fitter Model fitter object  
 fitted list. Saves the model objects

---

trial\_example

*Example of longitudinal data for sequential trial emulation*


---

## Description

A dataset containing the treatment, outcomes and other attributes of 503 patients for sequential trial emulation. See vignette("Getting-Started").

## Usage

```
trial_example
```

## Format

A data frame with 48400 rows and 11 variables:

**id** patient identifier

**eligible** eligible for trial start in this period, 1=yes, 0=no

**period** time period

**outcome** indicator for outcome in this period, 1=event occurred, 0=no event

**treatment** indicator for receiving treatment in this period, 1=treatment, 0=no treatment

**catvarA** A categorical variable relating to treatment and the outcome

**catvarB** A categorical variable relating to treatment and the outcome

**catvarC** A categorical variable relating to treatment and the outcome

**nvarA** A numerical variable relating to treatment and the outcome

**nvarB** A numerical variable relating to treatment and the outcome

**nvarC** A numerical variable relating to treatment and the outcome

---

trial\_msm

---

*Fit the marginal structural model for the sequence of emulated trials*


---

## Description

[Stable]

## Usage

```
trial_msm(
  data,
  outcome_cov = ~1,
  estimand_type = c("ITT", "PP", "As-Treated"),
  model_var = NULL,
  first_followup = NA,
  last_followup = NA,
  analysis_weights = c("asis", "unweighted", "p99", "weight_limits"),
  weight_limits = c(0, Inf),
  include_followup_time = ~followup_time + I(followup_time^2),
  include_trial_period = ~trial_period + I(trial_period^2),
  where_case = NA,
  glm_function = c("glm", "parglm"),
  use_sample_weights = TRUE,
  quiet = FALSE,
  ...
)
```

## Arguments

|             |                                                                                                                                                                                                                                                                             |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| data        | A data.frame containing all the required variables in the person-time format, i.e., the 'long' format.                                                                                                                                                                      |
| outcome_cov | A RHS formula with baseline covariates to be adjusted for in the marginal structural model for the emulated trials. Note that if a time-varying covariate is specified in outcome_cov, only its value at each of the trial baselines will be included in the expanded data. |

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| estimand_type         | Specify the estimand for the causal analyses in the sequence of emulated trials. <code>estimand_type = "ITT"</code> will perform intention-to-treat analyses, where treatment switching after trial baselines are ignored. <code>estimand_type = "PP"</code> will perform per-protocol analyses, where individuals' follow-ups are artificially censored and inverse probability of treatment weighting is applied. <code>estimand_type = "As-Treated"</code> will fit a standard marginal structural model for all possible treatment sequences, where individuals' follow-ups are not artificially censored but treatment switching after trial baselines are accounted for by applying inverse probability of treatment weighting. |
| model_var             | Treatment variables to be included in the marginal structural model for the emulated trials. <code>model_var = "assigned_treatment"</code> will create a variable <code>assigned_treatment</code> that is the assigned treatment at the trial baseline, typically used for ITT and per-protocol analyses. <code>model_var = "dose"</code> will create a variable <code>dose</code> that is the cumulative number of treatments received since the trial baseline, typically used in as-treated analyses.                                                                                                                                                                                                                              |
| first_followup        | First follow-up time/visit in the trials to be included in the marginal structural model for the outcome event.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| last_followup         | Last follow-up time/visit in the trials to be included in the marginal structural model for the outcome event.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| analysis_weights      | Choose which type of weights to be used for fitting the marginal structural model for the outcome event. <ul style="list-style-type: none"> <li>• <code>"asis"</code>: use the weights as calculated.</li> <li>• <code>"p99"</code>: use weights truncated at the 1st and 99th percentiles (based on the distribution of weights in the entire sample).</li> <li>• <code>"weight_limits"</code>: use weights truncated at the values specified in <code>weight_limits</code>.</li> <li>• <code>"unweighted"</code>: set all analysis weights to 1, even if treatment weights or censoring weights were calculated.</li> </ul>                                                                                                         |
| weight_limits         | Lower and upper limits to truncate weights, given as <code>c(lower, upper)</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| include_followup_time | The model to include the follow up time/visit of the trial ( <code>followup_time</code> ) in the marginal structural model, specified as a RHS formula.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| include_trial_period  | The model to include the trial period ( <code>trial_period</code> ) in the marginal structural model, specified as a RHS formula.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| where_case            | Define conditions using variables specified in <code>where_var</code> when fitting a marginal structural model for a subgroup of the individuals. For example, if <code>where_var = "age"</code> , <code>where_case = "age &gt;= 30"</code> will only fit the marginal structural model to the subgroup of individuals who are 30 years old or above.                                                                                                                                                                                                                                                                                                                                                                                 |
| glm_function          | Deprecated as <code>parglm</code> is no longer available on CRAN. This option will be ignored and <code>"glm"</code> will be used for model fitting.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| use_sample_weights    | Use case-control sampling weights in addition to inverse probability weights for treatment and censoring. <code>data</code> must contain a column <code>sample_weight</code> . The final weights used in the pooled logistic regression are calculated as <code>weight = weight * sample_weight</code> .                                                                                                                                                                                                                                                                                                                                                                                                                              |

|                    |                                                                                                                                                                                                   |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>quiet</code> | Suppress the printing of progress messages and summaries of the fitted models.                                                                                                                    |
| <code>...</code>   | Additional arguments passed to <code>glm_function</code> . This may be used to specify initial values of parameters or arguments to control. See <a href="#">stats::glm</a> for more information. |

### Details

Apply a weighted pooled logistic regression to fit the marginal structural model for the sequence of emulated trials and calculates the robust covariance matrix of parameter using the sandwich estimator.

The model formula is constructed by combining the arguments `outcome_cov`, `model_var`, `include_followup_time`, and `include_trial_period`.

### Value

Object of class `TE_msm` containing

**model** a `glm` object

**robust** a list containing a summary table of estimated regression coefficients and the robust covariance matrix

**args** a list contain the parameters used to prepare and fit the model

---

|                             |                                                           |
|-----------------------------|-----------------------------------------------------------|
| <code>trial_sequence</code> | <i>Create a sequence of emulated target trials object</i> |
|-----------------------------|-----------------------------------------------------------|

---

### Description

**[Experimental]**

### Usage

```
trial_sequence(estimand, ...)
```

### Arguments

|                       |                                                                                                                                                                                                                      |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>estimand</code> | The name of the estimand for this analysis, either one of "ITT", "PP", "AT" for intention-to-treat, per-protocol, as-treated estimands respectively, or the name of a class extending <a href="#">trial_sequence</a> |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                  |                                            |
|------------------|--------------------------------------------|
| <code>...</code> | Other parameters used when creating object |
|------------------|--------------------------------------------|

### Value

An estimand specific trial sequence object

### Examples

```
trial_sequence("ITT")
```

---

|                      |                             |
|----------------------|-----------------------------|
| trial_sequence-class | <i>Trial Sequence class</i> |
|----------------------|-----------------------------|

---

### Description

Trial Sequence class

### Slots

data te\_data.  
 estimand character. Descriptive name of estimand.  
 expansion te\_expansion  
 outcome\_model te\_outcome\_model.  
 outcome\_data te\_outcome\_data.  
 censor\_weight te\_weight. Object to define weighting to account for informative censoring  
 censor\_weight te\_weight. Object to define weighting to account for informative censoring due to treatment switching

---

|                      |                                                                             |
|----------------------|-----------------------------------------------------------------------------|
| vignette_switch_data | <i>Example of expanded longitudinal data for sequential trial emulation</i> |
|----------------------|-----------------------------------------------------------------------------|

---

### Description

This is the expanded dataset created in the vignette("Getting-Started") known as switch\_data.

### Usage

vignette\_switch\_data

### Format

A data frame with 1939053 rows and 7 variables:

**id** patient identifier  
**trial\_period** trial start time period  
**followup\_time** follow up time within trial  
**outcome** indicator for outcome in this period, 1=event occurred, 0=no event  
**treatment** indicator for receiving treatment in this period, 1=treatment, 0=non-treatment  
**assigned\_treatment** indicator for assigned treatment at baseline of the trial, 1=treatment, 0=non-treatment  
**weight** weights for use with model fitting  
**catvarA** A categorical variable relating to treatment and the outcome

**catvarB** A categorical variable relating to treatment and the outcome

**catvarC** A categorical variable relating to treatment and the outcome

**nvarA** A numerical variable relating to treatment and the outcome

**nvarB** A numerical variable relating to treatment and the outcome

**nvarC** A numerical variable relating to treatment and the outcome

---

weight\_model\_data\_indices

*Data used in weight model fitting*

---

## Description

**[Experimental]**

## Usage

```
weight_model_data_indices(
  object,
  type = c("switch", "censor"),
  model,
  set_col = NULL
)
```

## Arguments

|         |                                                                                                                  |
|---------|------------------------------------------------------------------------------------------------------------------|
| object  | A <a href="#">trial_sequence</a> object                                                                          |
| type    | Select a censoring or switching model                                                                            |
| model   | The model name                                                                                                   |
| set_col | A character string to specifying a new column to contain indicators for observations used in fitting this model. |

## Value

If set\_col is not specified a logical data.table column is returned. Otherwise

## Examples

```
trial_pp <- trial_sequence("PP") |>
  set_data(data_censored) |>
  set_switch_weight_model(
    numerator = ~age,
    denominator = ~ age + x1 + x3,
    model_fitter = stats_glm_logit(tempdir())
  ) |>
  calculate_weights()
ipw_data(trial_pp)
```

```
show_weight_models(trial_pp)

# get logical column for own processing
i <- weight_model_data_indices(trial_pp, "switch", "d0")

# set column in data
weight_model_data_indices(trial_pp, "switch", "d0", set_col = "sw_d0")
weight_model_data_indices(trial_pp, "switch", "d1", set_col = "sw_d1")
ipw_data(trial_pp)
```

# Index

- \* **datasets**
  - data\_censored, [5](#)
  - te\_data\_ex, [39](#)
  - te\_model\_ex, [40](#)
  - trial\_example, [42](#)
  - vignette\_switch\_data, [46](#)
- \* **model\_fitter**
  - parsnip\_model, [19](#)
  - stats\_glm\_logit, [37](#)
  - te\_model\_fitter-class, [41](#)
- \* **save\_to**
  - save\_to\_csv, [26](#)
  - save\_to\_datatable, [27](#)
  - save\_to\_duckdb, [28](#)
  - set\_expansion\_options, [32](#)
- calculate\_weights, [3](#)
- calculate\_weights(), [37](#)
- calculate\_weights, trial\_sequence\_AT-method
  - (calculate\_weights), [3](#)
- calculate\_weights, trial\_sequence\_ITT-method
  - (calculate\_weights), [3](#)
- calculate\_weights, trial\_sequence\_PP-method
  - (calculate\_weights), [3](#)
- case\_control\_sampling\_trials, [4](#), [9](#)
- data\_censored, [5](#)
- data\_preparation, [6](#), [39](#)
- data\_preparation(), [4](#), [15](#)
- expand\_trials, [9](#), [26](#)
- expand\_trials(), [10](#)
- fit\_msm, [10](#)
- fit\_msm, trial\_sequence-method
  - (fit\_msm), [10](#)
- fit\_outcome\_model, [41](#)
- fit\_weights\_model, [11](#), [41](#)
- initiators, [12](#)
- initiators(), [21](#)
- ipw\_data, [16](#)
- ipw\_data, trial\_sequence-method
  - (ipw\_data), [16](#)
- ipw\_data<- (ipw\_data), [16](#)
- ipw\_data<-, trial\_sequence-method
  - (ipw\_data), [16](#)
- load\_expanded\_data, [17](#)
- load\_expanded\_data, trial\_sequence-method
  - (load\_expanded\_data), [17](#)
- outcome\_data, [18](#)
- outcome\_data, trial\_sequence-method
  - (outcome\_data), [18](#)
- outcome\_data<- (outcome\_data), [18](#)
- outcome\_data<-, trial\_sequence-method
  - (outcome\_data), [18](#)
- parsnip\_model, [19](#)
- parsnip\_model(), [38](#), [41](#)
- predict, [41](#)
- predict(predict\_marginal), [20](#)
- predict, trial\_sequence\_ITT-method
  - (predict\_marginal), [20](#)
- predict, trial\_sequence\_PP-method
  - (predict\_marginal), [20](#)
- predict.TE\_msm(predict\_marginal), [20](#)
- predict\_marginal, [20](#)
- print.data.frame, [23](#)
- print.TE\_weight\_summary, [23](#)
- read\_expanded\_data, [24](#)
- read\_expanded\_data, te\_datastore\_datatable-method
  - (read\_expanded\_data), [24](#)
- sample\_expanded\_data, [25](#)
- sample\_expanded\_data, te\_datastore-method
  - (sample\_expanded\_data), [25](#)
- save\_expanded\_data, [26](#), [39](#)
- save\_expanded\_data, te\_datastore\_datatable-method
  - (save\_expanded\_data), [26](#)

save\_to\_csv, 26  
 save\_to\_csv(), 27, 28, 33  
 save\_to\_datatable, 27  
 save\_to\_datatable(), 27, 28, 33  
 save\_to\_duckdb, 28  
 save\_to\_duckdb(), 27, 33  
 set\_censor\_weight\_model, 28  
 set\_censor\_weight\_model, trial\_sequence-method  
     (set\_censor\_weight\_model), 28  
 set\_censor\_weight\_model, trial\_sequence\_AT-method  
     (set\_censor\_weight\_model), 28  
 set\_censor\_weight\_model, trial\_sequence\_ITT-method  
     (set\_censor\_weight\_model), 28  
 set\_censor\_weight\_model, trial\_sequence\_PP-method  
     (set\_censor\_weight\_model), 28  
 set\_data, 30  
 set\_data(), 16  
 set\_data, trial\_sequence\_AT, data.frame-method  
     (set\_data), 30  
 set\_data, trial\_sequence\_ITT, data.frame-method  
     (set\_data), 30  
 set\_data, trial\_sequence\_PP, data.frame-method  
     (set\_data), 30  
 set\_expansion\_options, 26, 32  
 set\_expansion\_options(), 9, 27, 28  
 set\_expansion\_options, trial\_sequence\_ITT-method  
     (set\_expansion\_options), 32  
 set\_expansion\_options, trial\_sequence\_PP-method  
     (set\_expansion\_options), 32  
 set\_outcome\_model, 10, 34  
 set\_outcome\_model(), 10  
 set\_outcome\_model, trial\_sequence-method  
     (set\_outcome\_model), 34  
 set\_outcome\_model, trial\_sequence\_AT-method  
     (set\_outcome\_model), 34  
 set\_outcome\_model, trial\_sequence\_ITT-method  
     (set\_outcome\_model), 34  
 set\_outcome\_model, trial\_sequence\_PP-method  
     (set\_outcome\_model), 34  
 set\_switch\_weight\_model, 35  
 set\_switch\_weight\_model, trial\_sequence-method  
     (set\_switch\_weight\_model), 35  
 set\_switch\_weight\_model, trial\_sequence\_ITT-method  
     (set\_switch\_weight\_model), 35  
 show\_weight\_models, 37  
 split(), 5  
 stats::glm, 8, 15, 37, 45  
 stats\_glm\_logit, 36, 37  
 stats\_glm\_logit(), 20, 30, 41  
 subset(), 4  
 summary.TE\_data\_prep, 38  
 summary.TE\_data\_prep\_dt  
     (summary.TE\_data\_prep), 38  
 summary.TE\_data\_prep\_sep  
     (summary.TE\_data\_prep), 38  
 summary.TE\_msm(summary.TE\_data\_prep),  
     38  
 summary.TE\_robust  
     (summary.TE\_data\_prep), 38  
 te\_data-class, 39  
 te\_data\_ex, 39, 40  
 te\_datastore, 17, 24–26, 33  
 te\_datastore-class, 39  
 te\_datastore\_csv, 27  
 te\_datastore\_duckdb, 28  
 te\_model\_ex, 40, 40  
 te\_model\_fitter, 20, 36, 38  
 te\_model\_fitter-class, 41  
 te\_outcome\_data, 18  
 te\_outcome\_data-class, 41  
 te\_outcome\_fitted-class, 41  
 te\_outcome\_model-class, 42  
 trial\_example, 42  
 trial\_msm, 9, 40, 43  
 trial\_msm(), 5, 15, 21  
 trial\_sequence, 3, 4, 9, 17, 18, 21, 22,  
     31–33, 36, 37, 45, 45, 47  
 trial\_sequence-class, 46  
 trial\_sequence\_AT-class  
     (trial\_sequence-class), 46  
 trial\_sequence\_ITT-class  
     (trial\_sequence-class), 46  
 trial\_sequence\_PP-class  
     (trial\_sequence-class), 46  
 vignette\_switch\_data, 46  
 weight\_model\_data\_indices, 47