

Package ‘dataSDA’

August 20, 2026

Type Package

Title Datasets and Basic Statistics for Symbolic Data Analysis

Version 0.2.7

Date 2026-08-09

Description Provides benchmark datasets and foundational tools for Symbolic Data Analysis (SDA). The package includes functions for constructing symbolic data objects from classical data, converting among different interval-valued data formats, managing interval-valued, histogram-valued, modal-valued, and multi-valued data, and performing basic descriptive statistics. It is designed to support teaching, methodological research, and the development of SDA techniques.

License GPL (>= 2)

Encoding UTF-8

LazyData true

Depends R (>= 4.0.0)

Suggests testthat (>= 2.1.0), knitr, rmarkdown, ggInterval, ggplot2, MAINT.Data, e1071, symbolicDA

VignetteBuilder knitr

Imports magrittr, tidyr, dplyr, RSDA, HistDAWass, methods

NeedsCompilation no

Config/roxygen2/version 8.0.0

Author Po-Wei Chen [aut],
Chun-houh Chen [aut],
Han-Ming Wu [cre]

Maintainer Han-Ming Wu <wuhm@g.nccu.edu.tw>

Repository CRAN

Date/Publication 2026-08-20 11:10:13 UTC

Contents

abalone.iGAP	5
abalone.int	6
acid_rain.int	7
age_cholesterol_weight.int	8
age_pyramids.hist	9
aggregate_to_symbolic	10
airline_flights.hist	12
airline_flights2.modal	14
ARRAY_to_iGAP	15
ARRAY_to_MM	15
ARRAY_to_RSDA	16
bank_rates	17
baseball.int	18
bats.int	19
bird.mix	20
bird_color_taxonomy.hist	21
bird_species.mix	22
bird_species_extended.mix	23
blood.hist	24
blood_pressure.int	25
car.int	26
cardiological.int	27
cars.int	28
car_models.int	29
census.mix	30
check_zero_width_intervals	31
china_climate_month.hist	32
china_climate_season.hist	33
china_temp.int	34
china_temp_monthly.int	35
cholesterol.hist	36
clean_colnames	37
county_income_gender.hist	37
cover_types.hist	38
credit_card.int	39
crime.modal	41
crime2.modal	42
crude_oil_wti.its	43
djia.its	44
ecoli_routes.int	45
employment.int	46
energy_consumption.distr	47
energy_usage.distr	48
environment.mix	49
euro_usd.its	51
exchange_rate_returns.hist	52

face.iGAP	53
finance.int	54
flights_detail.hist	55
french_agriculture.hist	56
freshwater_fish.int	57
fuel_consumption.modal	58
fungi.int	59
genome_abundances.int	60
glucose.hist	61
hardwood.hist	62
hdi_gender.int	63
health_insurance.mix	64
health_insurance2.modal	66
hematocrit.hist	67
hematocrit_hemoglobin.hist	68
hemoglobin.hist	69
hierarchy	70
hierarchy.hist	71
hierarchy.int	72
histogram_stats	73
horses.int	75
hospital.hist	76
household_characteristics.distr	77
ibovespa.its	78
iGAP_to_ARRAY	79
iGAP_to_MM	80
iGAP_to_RSDA	80
interval_distance	81
interval_geometry	83
interval_position	85
interval_robust	86
interval_shape	88
interval_similarity	89
interval_stats	91
interval_uncertainty	92
int_convert_format	94
int_detect_format	95
int_list_conversions	96
iris.int	97
irish_wind.its	98
iris_species.hist	99
joggers.mix	100
judge1.int	101
judge2.int	102
judge3.int	103
lackinfo.int	104
lisbon_air_quality.int	105
loans_by_purpose.int	106

loans_by_risk.int	107
loans_by_risk_quantile.int	108
lung_cancer.hist	109
lynne1.int	110
merval.its	111
MM_to_ARRAY	112
MM_to_iGAP	113
MM_to_RSDA	114
mtcars.mix	114
mushroom.int	115
mushroom.int.mm	116
mushroom_fuzzy.mix	118
nycflights.int	119
occupations.modal	120
occupations2.modal	121
ohtemp.int	122
oils.int	123
ozone.hist	124
petrobras.its	125
polish_cars.mix	126
polish_voivodships.int	128
profession.int	129
prostate.int	130
read_symbolic_csv	131
RSDA_format	132
RSDA_to_ARRAY	133
RSDA_to_iGAP	134
RSDA_to_MM	134
search_data	135
set_variable_format	136
shanghai_stock.its	137
simulated.hist	138
soccer_bivar.int	139
SODAS_to_ARRAY	140
SODAS_to_iGAP	141
SODAS_to_MM	141
sp500.its	142
state_income.hist	143
synthetic_clusters.int	144
teams.int	145
temperature_city.int	146
tennis.int	147
town_services.mix	148
to_all_interval_formats	149
trivial_intervals.int	151
uscrime.int	152
utsnow.int	153
veterinary.int	154

video1.int	155
video2.int	156
video3.int	157
water_flow.int	158
weight_age.hist	159
wine.int	160
world_cup.int	161
write_symbolic_csv	162

Index	164
--------------	------------

abalone.iGAP	<i>Abalone Dataset (iGAP Format)</i>
--------------	--------------------------------------

Description

Interval-valued dataset of 24 units from the UCI Abalone dataset, aggregated by sex and age group. iGAP format (comma-separated interval strings). See [abalone.int](#) for the Min-Max column format.

Usage

```
data(abalone.iGAP)
```

Format

A data frame with 24 observations (e.g., F-10-12, M-4-6) and 7 character columns in iGAP format (comma-separated "min, max" strings):

- Length: Shell length range.
- Diameter: Shell diameter range.
- Height: Shell height range.
- Whole: Whole weight range.
- Shucked: Shucked weight range.
- Viscera: Viscera weight range.
- Shell: Shell weight range.

Row names encode Sex-AgeGroup (e.g., F-10-12 = Female age 10–12).

Metadata

Sample size (n)	24
Variables (p)	7
Subject area	Marine biology
Symbolic format	Interval (iGAP)
Analytical tasks	Clustering, Visualization

Source

Derived from `MAINT.Data::AbaloneIdt`, which aggregates the UCI Abalone microdata by sex and age group. UCI Machine Learning Repository, [doi:10.24432/C55C7W](https://doi.org/10.24432/C55C7W).

References

Nash, W. J., Sellers, T. L., Talbot, S. R., Cawthorn, A. J., and Ford, W. B. (1994). The Population Biology of Abalone (*Haliotis* species) in Tasmania. Sea Fisheries Division, Technical Report No. 48.

UCI Machine Learning Repository. [doi:10.24432/C55C7W](https://doi.org/10.24432/C55C7W).

Examples

```
data(abalone.iGAP)
```

`abalone.int`

Abalone Interval Dataset

Description

Interval-valued dataset of 24 units from the UCI Abalone dataset, aggregated by sex and age group. Min-Max column format (two columns per variable). See [abalone.iGAP](#) for the iGAP format version.

Usage

```
data(abalone.int)
```

Format

A data frame with 24 observations and 14 columns (7 interval variables in `_min/_max` pairs):

- `Length_min`, `Length_max`: Shell length range.
- `Diameter_min`, `Diameter_max`: Shell diameter range.
- `Height_min`, `Height_max`: Shell height range.
- `Whole_min`, `Whole_max`: Whole weight range.
- `Shucked_min`, `Shucked_max`: Shucked weight range.
- `Viscera_min`, `Viscera_max`: Viscera weight range.
- `Shell_min`, `Shell_max`: Shell weight range.

Row names encode Sex-AgeGroup (e.g., F-10-12 = Female age 10–12).

Metadata

Sample size (n)	24
Variables (p)	14
Subject area	Marine biology
Symbolic format	Interval
Analytical tasks	Clustering, Visualization

Source

Derived from MAINT .Data : : AbaloneIdt, which aggregates the UCI Abalone microdata by sex and age group. UCI Machine Learning Repository, [doi:10.24432/C55C7W](https://doi.org/10.24432/C55C7W).

References

Nash, W. J., Sellers, T. L., Talbot, S. R., Cawthorn, A. J., and Ford, W. B. (1994). The Population Biology of Abalone (*Haliotis* species) in Tasmania. Sea Fisheries Division, Technical Report No. 48.

UCI Machine Learning Repository. [doi:10.24432/C55C7W](https://doi.org/10.24432/C55C7W).

Examples

```
data(abalone.int)
```

acid_rain.int

Acid Rain Pollution Indices Interval Dataset

Description

Interval-valued acid rain pollution indices for sulphates and nitrates (kg/hectares) for 2 US states (Massachusetts and New York).

Usage

```
data(acid_rain.int)
```

Format

A data frame with 2 observations and 5 variables in Min-Max format:

- state: State name (character).
- sulphate_l, sulphate_u: Sulphate pollution index range (kg/hectares).
- nitrate_l, nitrate_u: Nitrate pollution index range (kg/hectares).

Metadata

Sample size (n)	2
Variables (p)	5
Subject area	Environment
Symbolic format	Interval
Analytical tasks	Descriptive statistics

Source

Billard and Diday (2006), Table 2.21.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley. Table 2.21.

Examples

```
data(acid_rain.int)
```

```
age_cholesterol_weight.int
```

Age-Cholesterol-Weight Interval Dataset

Description

Interval-valued dataset of 7 age-group observations with cholesterol and weight measurements. Each observation aggregates individuals in a 10-year age band with interval ranges for cholesterol and weight.

Usage

```
data(age_cholesterol_weight.int)
```

Format

A symbolic data frame (symbolic_tbl) with 7 observations and 4 variables:

- Age: Age range (years, interval).
- Cholesterol: Cholesterol level range (mg/dL, interval).
- Weight: Weight range (pounds, interval).
- n: Number of individuals in the age group (numeric).

Metadata

Sample size (n)	7
Variables (p)	4
Subject area	Medical
Symbolic format	Interval
Analytical tasks	Descriptive statistics, Regression

Source

Billard and Diday (2006).

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley.

Examples

```
data(age_cholesterol_weight.int)
```

age_pyramids.hist	<i>World Age Pyramids Histogram-Valued Dataset (2014)</i>
-------------------	---

Description

Histogram-valued dataset of 229 countries with 3 population age pyramid histograms (both sexes, male, female). Each histogram has 21 age bins representing the distribution of the population across age groups.

Usage

```
data(age_pyramids.hist)
```

Format

A data frame with 229 observations (countries) and 3 histogram-valued variables:

- `Both.Sexes.Population`: Histogram of total population by age group.
- `Male.Population`: Histogram of male population by age group.
- `Female.Population`: Histogram of female population by age group.

Row names are country names (e.g., WORLD, Afghanistan, Albania).

Metadata

Sample size (n)	229
Variables (p)	3
Subject area	Demographics
Symbolic format	Histogram
Analytical tasks	Clustering, Descriptive statistics

Source

HistDAWass::Age_Pyramids_2014; the upstream documentation identifies the U.S. Census Bureau as the original source.

References

U.S. Census Bureau (2014). International population estimates and projections by age and sex.

Examples

```
data(age_pyramids.hist)
```

aggregate_to_symbolic *Aggregate Tabular Data to Symbolic Data*

Description

Aggregate tabular numerical data (n by p) into interval-valued or histogram-valued symbolic data (K by p) based on a grouping mechanism.

Usage

```
aggregate_to_symbolic(x, type = "int", group_by = "kmeans",
  stratify_var = NULL, K = 5, interval = "range",
  quantile_probs = c(0.05, 0.95), bins = 10, nK = NULL,
  zero_width = c("keep", "remove", "regenerate", "adjust"), epsilon = 1e-07)
```

Arguments

x	A data.frame with n rows and p columns. May contain non-numeric columns used for grouping or stratification; only numeric columns are aggregated.
type	Output symbolic type: "int" for interval data or "hist" for histogram data.
group_by	Grouping mechanism. One of: "kmeans" Partition the data into K groups using k-means clustering. "hclust" Partition the data into K groups using hierarchical clustering. "resampling" Generate K concepts by randomly sampling nK observations with replacement, repeated K times.

	A column name or column index Use the specified categorical variable to define groups.
stratify_var	Optional column name or index for a stratification variable. When provided, grouping and aggregation are performed independently within each level. Default is NULL.
K	Number of groups for clustering (group_by = "kmeans" or "hclust") or re-sampling (group_by = "resampling"). Ignored when group_by is a variable. Default is 5.
interval	Interval construction method when type = "int": "range" uses min/max; "quantile" uses quantiles given by quantile_probs. Default is "range".
quantile_probs	Numeric vector of length 2 giving the lower and upper quantile probabilities for interval = "quantile". Default is c(0.05, 0.95).
bins	Number of histogram bins when type = "hist". Default is 10.
nK	Number of observations to sample per group when group_by = "resampling". Default is floor(n / K).
zero_width	How to handle zero-width intervals (min == max) produced when type = "int". Such degenerate intervals break downstream tools that divide by interval width (e.g. ggInterval::ggInterval_indexImage()). One of: "keep" (default) Leave the aggregated output unchanged; zero-width intervals are returned as-is and no action is taken. Use check_zero_width_intervals to screen the result. "remove" Drop every concept (row) that contains at least one zero-width interval. "regenerate" Re-run the aggregation (re-clustering or re-sampling) until no zero-width interval remains. Only effective for stochastic group_by ("kmeans", "resampling"); for deterministic grouping (a variable or "hclust") the result cannot change, so an error is raised suggesting another option. "adjust" Add a small amount epsilon to the upper endpoint of each zero-width interval. Ignored when type = "hist".
epsilon	Positive amount added to the upper endpoint of each zero-width interval when zero_width = "adjust". Default is 1e-07.

Details

The function aggregates classical tabular data into symbolic data by:

1. Partitioning observations into groups via group_by (clustering, resampling, or a categorical variable).
2. Within each group, summarizing each numeric variable as an interval (min/max or quantiles) or a histogram.

When stratify_var is provided, grouping and aggregation are performed within each level of the stratification variable. Label values are prefixed by the stratum name (e.g., "setosa.cluster_1").

For type = "hist", bin boundaries are computed from the global data range to ensure comparability across groups.

Non-numeric columns (other than those used for grouping or stratification) are silently excluded from aggregation.

Value

- For type = "int": a `symbolic_tbl` (RSDA format) with a label column followed by `symbolic_interval` columns for each numeric variable (K rows, 1 + p columns).
- For type = "hist": a `Math` object (K rows by p columns of histogram-valued data).

Examples

```
# Group by a categorical variable -> interval data
res1 <- aggregate_to_symbolic(iris, type = "int", group_by = "Species")
res1

# K-means clustering -> interval data
res2 <- aggregate_to_symbolic(iris[, 1:4], type = "int",
                             group_by = "kmeans", K = 3)

# Quantile-based intervals
res3 <- aggregate_to_symbolic(iris[, 1:4], type = "int",
                             group_by = "kmeans", K = 3,
                             interval = "quantile",
                             quantile_probs = c(0.1, 0.9))

# Resampling -> interval data
set.seed(42)
res4 <- aggregate_to_symbolic(iris[, 1:4], type = "int",
                             group_by = "resampling", K = 5, nK = 30)

# Histogram aggregation
res5 <- aggregate_to_symbolic(iris, type = "hist",
                             group_by = "Species", bins = 5)

# Hierarchical clustering -> interval data
res6 <- aggregate_to_symbolic(iris[, 1:4], type = "int",
                             group_by = "hclust", K = 3)

# Stratified aggregation
res7 <- aggregate_to_symbolic(iris, type = "int",
                             group_by = "kmeans", K = 2,
                             stratify_var = "Species")
```

Description

Histogram-valued dataset of 16 airlines flying into JFK Airport. Six variables (Flight Time, Taxi In, Arrival Delay, Taxi Out, Departure Delay, Weather Delay) recorded as frequency distributions. This is the wide (flat table) format; see [airline_flights2.modal](#) for the modal-valued version.

Usage

```
data(airline_flights.hist)
```

Format

A data frame with 16 observations (Airline1–Airline16) and 17 numeric columns representing 6 histogram variables in wide format:

- Flight Time(<120), Flight Time([120, 220]), Flight Time(>220): Flight time distribution (3 bins).
- Taxi In(<4), Taxi In([4, 10]), Taxi In(>10): Taxi-in time distribution (3 bins).
- Arrival Delay(<0), Arrival Delay([0, 60]), Arrival Delay(>60): Arrival delay distribution (3 bins).
- Taxi Out(<16), Taxi Out([16, 30]), Taxi Out(>30): Taxi-out time distribution (3 bins).
- Departure Delay(<0), Departure Delay([0, 60]), Departure Delay(>60): Departure delay distribution (3 bins).
- Weather Delay(No), Weather Delay(Yes): Weather delay distribution (2 bins).

Metadata

Sample size (n)	16
Variables (p)	17
Subject area	Transportation
Symbolic format	Histogram
Analytical tasks	Clustering, Descriptive statistics

Source

Billard and Diday (2006), Table 2.7.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley. Table 2.7.

Examples

```
data(airline_flights.hist)
```

airline_flights2.modal

JFK Airport Airline Flights Modal-Valued Dataset

Description

Modal-valued version of the airline flights dataset. See [airline_flights.hist](#) for the wide-format version.

Usage

```
data(airline_flights2.modal)
```

Format

A symbolic data frame (symbolic_tbl) with 16 observations and 6 modal-valued variables:

- FlightTime: Modal distribution over flight time bins.
- TaxiIn: Modal distribution over taxi-in time bins.
- ArrivalDelay: Modal distribution over arrival delay bins.
- TaxiOut: Modal distribution over taxi-out time bins.
- DepartureDelay: Modal distribution over departure delay bins.
- WeatherDelay: Modal distribution over weather delay bins.

Metadata

Sample size (n)	16
Variables (p)	6
Subject area	Transportation
Symbolic format	Modal
Analytical tasks	Clustering, Descriptive statistics

Source

Billard and Diday (2006), Table 2.7.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley. Table 2.7.

Examples

```
data(airline_flights2.modal)
```

 ARRAY_to_iGAP

ARRAY to iGAP

Description

Convert a 3-dimensional array [n, p, 2] to iGAP format (data.frame with comma-separated interval values).

Usage

```
ARRAY_to_iGAP(data)
```

Arguments

data A numeric array of dimension [n, p, 2] where [, , 1] stores minima and [, , 2] stores maxima.

Value

A data.frame in iGAP format with comma-separated "min,max" values.

Examples

```
x <- array(NA, dim = c(4, 3, 2))
x[, , 1] <- matrix(c(1,2,3,4, 5,6,7,8, 9,10,11,12), nrow = 4)
x[, , 2] <- matrix(c(3,5,6,7, 8,9,10,12, 13,15,16,18), nrow = 4)
dimnames(x) <- list(paste0("obs_", 1:4), c("V1", "V2", "V3"), c("min", "max"))
igap <- ARRAY_to_iGAP(x)
igap
```

 ARRAY_to_MM

ARRAY to MM

Description

Convert a 3-dimensional array [n, p, 2] to MM format (data.frame with paired _min/_max columns).

Usage

```
ARRAY_to_MM(data)
```

Arguments

data A numeric array of dimension [n, p, 2] where [, , 1] stores minima and [, , 2] stores maxima.

Value

A data.frame with 2p columns (paired _min/_max).

Examples

```
x <- array(NA, dim = c(4, 3, 2))
x[, , 1] <- matrix(c(1,2,3,4, 5,6,7,8, 9,10,11,12), nrow = 4)
x[, , 2] <- matrix(c(3,5,6,7, 8,9,10,12, 13,15,16,18), nrow = 4)
dimnames(x) <- list(paste0("obs_", 1:4), c("V1", "V2", "V3"), c("min", "max"))
mm <- ARRAY_to_MM(x)
mm
```

ARRAY_to_RSDA	<i>ARRAY to RSDA</i>
---------------	----------------------

Description

Convert a 3-dimensional array [n, p, 2] to RSDA format (symbolic_tbl with symbolic_interval columns).

Usage

```
ARRAY_to_RSDA(data)
```

Arguments

data	A numeric array of dimension [n, p, 2] where [, , 1] stores minima and [, , 2] stores maxima.
------	---

Value

A symbolic_tbl with p symbolic_interval columns.

Examples

```
x <- array(NA, dim = c(4, 3, 2))
x[, , 1] <- matrix(c(1,2,3,4, 5,6,7,8, 9,10,11,12), nrow = 4)
x[, , 2] <- matrix(c(3,5,6,7, 8,9,10,12, 13,15,16,18), nrow = 4)
dimnames(x) <- list(paste0("obs_", 1:4), c("V1", "V2", "V3"), c("min", "max"))
rsda <- ARRAY_to_RSDA(x)
rsda
```

bank_rates	<i>Bank Interest Rates AR Model Symbolic Dataset</i>
------------	--

Description

Symbolic dataset of autoregressive time series models for 4 banks. Each bank is described by AR model order, parameters, and whether parameters are known.

Usage

`data(bank_rates)`

Format

A data frame with 4 observations (Bank1–Bank4) and 6 variables:

- bank: Bank identifier (character).
- order: AR model order (numeric).
- phi1: First AR parameter (numeric; NA if unknown).
- phi2: Second AR parameter (numeric; NA if order < 2 or unknown).
- phi1_known: Whether phi1 is known (logical).
- phi2_known: Whether phi2 is known (logical; NA if order < 2).

Metadata

Sample size (n)	4
Variables (p)	6
Subject area	Finance
Symbolic format	Symbolic (model-valued)
Analytical tasks	Descriptive statistics

Source

Billard and Diday (2006), Table 2.9.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley. Table 2.9.

Examples

`data(bank_rates)`

`baseball.int`*Baseball Teams Interval Dataset*

Description

Interval-valued data for 19 baseball teams with aggregated player batting statistics and a pattern variable classifying team performance.

Usage

```
data(baseball.int)
```

Format

A symbolic data frame (`symbolic_tbl`) with 19 observations and 3 variables:

- `At_Bats`: Range of at-bats across players (interval).
- `Hits`: Range of hits across players (interval).
- `Pattern`: Team performance pattern code (character).

Metadata

Sample size (n)	19
Variables (p)	3
Subject area	Sports
Symbolic format	Interval
Analytical tasks	Descriptive statistics, Clustering

Source

Billard and Diday (2006).

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley.

Examples

```
data(baseball.int)
```

bats.int	<i>Bat Species Interval Dataset</i>
----------	-------------------------------------

Description

Interval-valued data for 21 bat species described by 4 morphological measurements. Benchmark dataset for matrix visualization.

Usage

```
data(bats.int)
```

Format

A data frame with 21 observations and 9 columns (4 interval variables in _l/_u Min-Max pairs, plus a label):

- species: Bat species name (character).
- head_l, head_u: Head length range (mm).
- tail_l, tail_u: Tail length range (mm).
- height_l, height_u: Ear height range (cm).
- forearm_l, forearm_u: Forearm length range (mm).

Details

Used to demonstrate color coding schemes, the HCT-R2E seriation algorithm, and distance measure comparisons (Gowda-Diday, Hausdorff, City-Block, L1, L2, etc.) for interval data.

Metadata

Sample size (n)	21
Variables (p)	9
Subject area	Zoology
Symbolic format	Interval
Analytical tasks	Clustering, Visualization

Source

The interval-valued bat data analyzed by Kao et al. (2014).

References

Kao, C.-H., Nakano, J., Shieh, S.-H., Tien, Y.-J., Wu, H.-M., Yang, C.-K. and Chen, C.-H. (2014). Exploratory data analysis of interval-valued symbolic data with matrix visualization. *Computational Statistics & Data Analysis*, 79, 14–29. doi:10.1016/j.csda.2014.04.012.

Examples

```
data(bats.int)
```

bird.mix

Bird Species Mixed Symbolic Dataset

Description

Interval-valued morphological measurements for 20 bird specimens. Despite the .mix suffix, this dataset contains only interval-valued variables (density and size).

Usage

```
data(bird.mix)
```

Format

A symbolic data frame (symbolic_tbl) with 20 observations and 2 variables:

- Density: Feather density range (interval).
- Size: Body size range (cm, interval).

Metadata

Sample size (n)	20
Variables (p)	2
Subject area	Zoology
Symbolic format	Interval
Analytical tasks	Descriptive statistics

Source

Billard and Diday (2006), Table 2.5.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley. Table 2.5.

Examples

```
data(bird.mix)
```

`bird_color_taxonomy.hist`*Bird Color Taxonomy Histogram Dataset*

Description

Mixed symbolic dataset of 20 bird observations with histogram-valued feather density and body size, categorical tone, and distribution-valued shade (fuzzy taxonomy). From Tables 6.9 and 6.14 of Billard and Diday (2006).

Usage

```
data(bird_color_taxonomy.hist)
```

Format

A data frame with 20 observations and 4 variables:

- `density`: Histogram-valued feather density (up to 4 bins).
- `size`: Histogram-valued body size (2-bin).
- `tone`: Categorical tone (dark/light).
- `shade`: Distribution-valued shade (purple/red/white/yellow with fuzzy weights).

Metadata

Sample size (n)	20
Variables (p)	4
Subject area	Zoology
Symbolic format	Mixed (histogram, categorical, distribution)
Analytical tasks	Clustering, Descriptive statistics

Source

Billard, L. and Diday, E. (2006), Tables 6.9 and 6.14.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis: Conceptual Statistics and Data Mining*. Wiley, Chichester. Tables 6.9 and 6.14.

Examples

```
data(bird_color_taxonomy.hist)
```

bird_species.mix

*Bird Species Mixed Symbolic Dataset***Description**

Symbolic data for 3 bird species (Swallow, Ostrich, Penguin) with interval-valued size, categorical flying, and categorical migration. Foundational SDA example from 600 individual bird observations.

Usage

```
data(bird_species.mix)
```

Format

A data frame with 3 observations (Swallow, Ostrich, Penguin) and 5 variables:

- species: Species name (character).
- flying: Flying ability (Yes/No, character).
- size_l, size_u: Size range (cm, Min-Max pair).
- migration: Migratory behavior (TRUE/FALSE, logical).

Metadata

Sample size (n)	3
Variables (p)	5
Subject area	Zoology
Symbolic format	Mixed (interval, categorical)
Analytical tasks	Descriptive statistics

Source

Diday and Noirhomme-Fraiture (2008), Table 1.2, p. 6.

References

Diday, E. and Noirhomme-Fraiture, M. (Eds.) (2008). *Symbolic Data Analysis and the SODAS Software*. Wiley. Table 1.2, p.6.

Examples

```
data(bird_species.mix)
```

bird_species_extended.mix

Bird Species Extended Mixed Symbolic Dataset

Description

Three bird species (Geese, Ostrich, Penguin) with interval-valued height, distribution-valued color, and categorical flying/migratory variables.

Usage

```
data(bird_species_extended.mix)
```

Format

A data frame with 3 observations and 6 variables:

- species: Species name (character).
- flying: Flying ability (Yes/No, character).
- height_l: Height lower bound (cm, numeric).
- height_u: Height upper bound (cm, numeric).
- color: Color distribution as weighted set string (e.g., "{ white, 0.3; black, 0.7}").
- migratory: Migratory behavior (Yes/No, character).

Metadata

Sample size (n)	3
Variables (p)	6
Subject area	Zoology
Symbolic format	Mixed (interval, categorical, distribution)
Analytical tasks	Descriptive statistics

Source

Billard and Diday (2006), Table 2.19.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley. Table 2.19.

Examples

```
data(bird_species_extended.mix)
```

blood.hist

*Blood Test Histogram Dataset***Description**

Histogram-valued blood test results for 14 gender-age groups (e.g., Female-20, Male-50). Each observation contains histograms for cholesterol, hemoglobin, and hematocrit, represented as multi-bin distributions.

Usage

```
data(blood.hist)
```

Format

A data frame with 14 observations and 3 histogram-valued variables:

- Cholesterol: Histogram of cholesterol levels (mg/dL).
- Hemoglobin: Histogram of hemoglobin levels (g/dL).
- Hematocrit: Histogram of hematocrit levels (%).

Metadata

Sample size (n)	14
Variables (p)	3
Subject area	Medical
Symbolic format	Histogram
Analytical tasks	Descriptive statistics, Clustering

Source

HistDAWass::BLOOD; Irpino and Verde (2015) analyze the data and attribute them to Billard and Diday (2006).

References

Irpino, A. and Verde, R. (2015). Basic statistics for distributional symbolic variables: a new metric-based approach. *Advances in Data Analysis and Classification*, 9(2), 143–175.

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis: Conceptual Statistics and Data Mining*. Wiley, Chichester.

Examples

```
data(blood.hist)
```

blood_pressure.int	<i>Blood Pressure Interval Dataset</i>
--------------------	--

Description

Interval-valued blood pressure and pulse rate measurements for 15 patient groups.

Usage

```
data(blood_pressure.int)
```

Format

A symbolic data frame (symbolic_tbl) with 15 observations and 3 interval-valued variables:

- Pulse_Rate: Pulse rate range (beats per minute, interval).
- Systolic_Pressure: Systolic blood pressure range (mmHg, interval).
- Diastolic_Pressure: Diastolic blood pressure range (mmHg, interval).

Metadata

Sample size (n)	15
Variables (p)	3
Subject area	Medical
Symbolic format	Interval
Analytical tasks	Descriptive statistics, Regression

Source

Billard and Diday (2006).

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley.

Examples

```
data(blood_pressure.int)
```

car.int

*Car Models Interval Dataset***Description**

Interval-valued data for 8 car brands with price and performance specifications. Each brand aggregates multiple models into interval ranges.

Usage

```
data(car.int)
```

Format

A symbolic data frame (symbolic_tbl) with 8 observations and 5 variables:

- Car: Car brand name (character).
- Price: Price range (thousands of currency units, interval).
- Max_Velocity: Maximum velocity range (km/h, interval).
- Accn_Time: Acceleration time range (seconds 0–100 km/h, interval).
- Cylinder_Capacity: Engine cylinder capacity range (cc, interval).

Metadata

Sample size (n)	8
Variables (p)	5
Subject area	Automotive
Symbolic format	Interval
Analytical tasks	Descriptive statistics, Clustering

Source

Billard and Diday (2006).

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley.

Examples

```
data(car.int)
```

cardiological.int	<i>Cardiological Examination Interval Dataset</i>
-------------------	---

Description

Interval-valued data from cardiological examinations of 44 patients. Each patient is described by 5 interval-valued physiological measurements.

Usage

```
data(cardiological.int)
```

Format

A data frame with 44 observations and 5 interval-valued variables:

- pulse: Pulse rate range (beats per minute).
- systolic: Systolic blood pressure range (mmHg).
- diastolic: Diastolic blood pressure range (mmHg).
- arterial1: First arterial measurement range.
- arterial2: Second arterial measurement range.

Metadata

Sample size (n)	44
Variables (p)	5
Subject area	Medical
Symbolic format	Interval
Analytical tasks	Descriptive statistics, Clustering

Source

Extracted from RSDA::cardiologicalv2; the RSDA documentation attributes the data to Billard and Diday (2006).

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis: Conceptual Statistics and Data Mining*. Wiley, Chichester.

Examples

```
data(cardiological.int)
```

cars.int

*Cars Interval Dataset***Description**

Interval-valued data for 27 car models classified into four classes (Utilitarian, Berlina, Sportive, Luxury), described by Price, EngineCapacity, TopSpeed and Acceleration intervals.

Usage

```
data(cars.int)
```

Format

A symbolic data frame (symbolic_tbl) with 27 observations and 5 variables:

- Price: Price range (interval).
- EngCap: Engine capacity range (cc, interval).
- TopSpeed: Top speed range (km/h, interval).
- Acceleration: Acceleration range (seconds 0–100 km/h, interval).
- class: Car class (Utilitarian, Berlina, Sportive, Luxury; set-valued).

Metadata

Sample size (n)	27
Variables (p)	5
Subject area	Automotive
Symbolic format	Interval
Analytical tasks	Classification

Source

MAINT.Data: :Cars, containing interval specifications for 27 car models in four classes.

References

Duarte Silva, A. P., Brito, P., Filzmoser, P. and Dias, J. G. (2021). MAINT.Data: Modelling and Analysing Interval Data in R. *The R Journal*, 13(2), 336–364. doi:[10.32614/RJ2021074](https://doi.org/10.32614/RJ2021074).

Examples

```
data(cars.int)
```

car_models.int	<i>Italian Car Models Interval Dataset</i>
----------------	--

Description

Interval-valued specifications for 33 Italian car models, classified into 4 categories (Utilitaria, Berlina, Ammiraglia, Sportiva). An extended version of the classic cars interval dataset with 8 interval-valued variables including dimensions.

Usage

```
data(car_models.int)
```

Format

A data frame with 33 observations and 9 variables:

- price: Price range (currency units).
- engine_cc: Engine displacement range (cc).
- top_speed: Top speed range (km/h).
- acceleration: Acceleration range (seconds 0-100 km/h).
- wheelbase: Wheelbase range (cm).
- length: Length range (cm).
- width: Width range (cm).
- height: Height range (cm).
- class: Car category (Utilitaria, Berlina, Ammiraglia, Sportiva).

Metadata

Sample size (n)	33
Variables (p)	9
Subject area	Automotive
Symbolic format	Interval
Analytical tasks	Clustering, Classification

Source

<https://github.com/Natandradesa/Kernel-Clustering-for-Interval-Data>

References

Andrade de Sa, J. N., Ferreira, M. R. P. and de Carvalho, F. A. T. (2025). Kernel clustering with automatic variable weighting for interval data. *Neurocomputing*, 650, 130849. doi:10.1016/j.neucom.2025.130849.

Examples

```
data(car_models.int)
```

census.mix

Census Mixed Symbolic Dataset

Description

Mixed symbolic dataset of 10 census regions combining 6 different symbolic variable types: histograms (age, home value), distributions (gender, tenure), a multi-valued set (fuel), and an interval (income).

Usage

```
data(census.mix)
```

Format

A symbolic data frame (symbolic_tbl) with 10 observations (regions) and 6 variables:

- age: Histogram-valued age distribution (12 age bins).
- home_value: Histogram-valued home value distribution (7 value bins, in \$1000s).
- gender: Distribution over gender (male, female).
- fuel: Multi-valued set of fuel types used.
- tenure: Distribution over housing tenure (owner, renter, vacant).
- income: Interval-valued household income range (\$1000s).

Row names are Region_1 through Region_10.

Metadata

Sample size (n)	10
Variables (p)	6
Subject area	Demographics
Symbolic format	Mixed (interval, histogram, distribution, multi-valued)
Analytical tasks	Clustering

Source

Billard, L. and Diday, E. (2020), Table 7-23.

References

Billard, L. and Diday, E. (2020). *Clustering Methodology for Symbolic Data*. Wiley, Chichester. Table 7-23.

Examples

```
data(census.mix)
```

```
check_zero_width_intervals
```

Check for Zero-Width Intervals

Description

Checks whether interval-valued data contains any zero-width intervals ($\min == \max$). Such degenerate intervals break downstream tools that divide by interval width (e.g. `ggInterval::ggInterval_indexImage()`). The input may be supplied either in MM format (a `data.frame` with paired `_min/_max` columns) or in RSDA format (a `symbolic_tbl` with `symbolic_interval` columns).

Usage

```
check_zero_width_intervals(data, tol = 0, warn = TRUE)
```

Arguments

<code>data</code>	Interval-valued data, in one of two accepted formats: • a <code>data.frame</code> in MM format with paired <code>_min/_max</code> columns, or • a <code>symbolic_tbl</code> (RSDA format) with <code>symbolic_interval</code> columns. Non-interval columns (e.g. <code>set/modal</code> variables) are ignored.
<code>tol</code>	Non-negative numeric tolerance. An interval is flagged when $\text{abs}(\max - \min) \leq \text{tol}$. Defaults to 0 (exact $\min == \max$).
<code>warn</code>	Logical; if TRUE (default) a single warning naming the affected variables is emitted when zero-width intervals are found.

Value

Invisibly, a logical scalar: TRUE if any zero-width interval is present, otherwise FALSE. The returned value carries two attributes: `"flagged"`, a logical $[n, p]$ matrix marking each zero-width cell (rows = concepts, columns = interval variables), and `"variables"`, the names of variables containing at least one zero-width interval.

Examples

```
# MM format (paired _min/_max columns)
data(mushroom.int.mm)
check_zero_width_intervals(mushroom.int.mm)

# RSDA format (symbolic_tbl)
data(mushroom.int)
check_zero_width_intervals(mushroom.int)
```

china_climate_month.hist

Chinese Climate Monthly Histogram Dataset

Description

Histogram-valued monthly climate data for 60 Chinese weather stations. Each station has 14 climate variables measured across 12 months (168 histogram columns total). Histograms are reduced to 10 decile bins from the original HistDAWass distributions.

Usage

```
data(china_climate_month.hist)
```

Format

A data frame with 60 observations (stations) and 168 histogram-valued variables. Variables follow the pattern `variable_Month` (e.g., `mean.temp_Jan`). The 14 climate variables are: mean pressure, mean temperature, mean max/min temperature, total precipitation, sunshine duration, mean cloud amount, mean relative humidity, snow days, dominant wind direction, mean wind speed, dominant wind frequency, extreme max/min temperature.

Metadata

Sample size (n)	60
Variables (p)	168
Subject area	Climate
Symbolic format	Histogram
Analytical tasks	Clustering

Source

Derived from `HistDAWass::China_Month`; the upstream source is the Climate Databases of the People's Republic of China, 1841–1988.

References

Carbon Dioxide Information Analysis Center. *Climate Databases of the People's Republic of China, 1841–1988*. doi:[10.3334/CDIAC/CLI.TR055](https://doi.org/10.3334/CDIAC/CLI.TR055).

Examples

```
data(china_climate_month.hist)
```

china_climate_season.hist

Chinese Climate Seasonal Histogram Dataset

Description

Histogram-valued seasonal climate data for 60 Chinese weather stations. Each station has 14 climate variables measured across 4 seasons (56 histogram columns total). Histograms are reduced to 10 decile bins from the original HistDAWass distributions.

Usage

```
data(china_climate_season.hist)
```

Format

A data frame with 60 observations (stations) and 56 histogram-valued variables. Variables follow the pattern `variable_Season` (e.g., `mean.temp_Spring`). The 14 climate variables are: mean pressure, mean temperature, mean max/min temperature, total precipitation, sunshine duration, mean cloud amount, mean relative humidity, snow days, dominant wind direction, mean wind speed, dominant wind frequency, extreme max/min temperature.

Metadata

Sample size (n)	60
Variables (p)	56
Subject area	Climate
Symbolic format	Histogram
Analytical tasks	Clustering

Source

Derived from `HistDAWass::China_Seas`; the upstream source is the Climate Databases of the People's Republic of China, 1841–1988.

References

Carbon Dioxide Information Analysis Center. *Climate Databases of the People's Republic of China, 1841–1988*. doi:[10.3334/CDIAC/CLI.TR055](https://doi.org/10.3334/CDIAC/CLI.TR055).

Examples

```
data(china_climate_season.hist)
```

china_temp.int	<i>China Meteorological Stations Quarterly Temperature Interval Dataset</i>
----------------	---

Description

Interval-valued temperature data (Celsius) for 60 Chinese meteorological stations observed over the four quarters of years 1974 to 1988. One outlier observation (YinChuan_1982) has been discarded.

Usage

```
data(china_temp.int)
```

Format

A symbolic data frame (symbolic_tbl) with 899 observations and 5 variables:

- Q1: Quarter 1 (Jan–Mar) temperature range (tenths of degrees Celsius, interval).
- Q2: Quarter 2 (Apr–Jun) temperature range (interval).
- Q3: Quarter 3 (Jul–Sep) temperature range (interval).
- Q4: Quarter 4 (Oct–Dec) temperature range (interval).
- GeoReg: Geographic region classification (factor).

Details

Originates from the Long-Term Instrumental Climatic Database of the People's Republic of China. Widely used in the SDA literature for demonstrating standardization, clustering, self-organizing maps, MLE and MANOVA.

Metadata

Sample size (n)	899
Variables (p)	5
Subject area	Climate
Symbolic format	Interval
Analytical tasks	Clustering

Source

MAINT.Data::ChinaTemp, derived from the Long-Term Instrumental Climatic Database of the People's Republic of China.

References

Brito, P. and Duarte Silva, A. P. (2012). Modelling interval data with Normal and Skew-Normal distributions. *Journal of Applied Statistics*, 39(1), 3–20. doi:[10.1080/02664763.2011.575125](https://doi.org/10.1080/02664763.2011.575125).

Examples

```
data(china_temp.int)
```

```
china_temp_monthly.int
```

China Monthly Temperature Intervals (15 Stations)

Description

Interval-valued dataset of monthly temperature ranges for 15 weather stations in China. Each station has 12 monthly temperature intervals (minimum and maximum observed temperatures in degrees Celsius) and an elevation value in meters.

Usage

```
data(china_temp_monthly.int)
```

Format

A symbolic data frame (symbolic_tbl) with 15 observations (weather stations) and 13 variables:

- January, February, March, April, May, June, July, August, September, October, November, December: Interval-valued monthly temperature ranges (degrees Celsius).
- Elevation: Station elevation above sea level (numeric, meters).

Row names are station names (e.g., BoKeTu, Hailaer, LaSa).

Metadata

Sample size (n)	15
Variables (p)	13
Subject area	Climate
Symbolic format	Interval
Analytical tasks	Clustering

Source

Billard, L. and Diday, E. (2020), Table 7-9.

References

Billard, L. and Diday, E. (2020). *Clustering Methodology for Symbolic Data*. Wiley, Chichester. Table 7-9.

Examples

```
data(china_temp_monthly.int)
```

cholesterol.hist

Cholesterol by Gender and Age Histogram-Valued Dataset

Description

Histogram-valued cholesterol distributions for 14 gender-age groups (7 female + 7 male age groups from 20s to 80+). Each observation has a 10-bin histogram of cholesterol levels.

Usage

```
data(cholesterol.hist)
```

Format

A data frame with 14 observations and 3 variables:

- gender: Gender (Female or Male).
- age: Age group (20s, 30s, 40s, 50s, 60s, 70s, 80+).
- cholesterol: Histogram-valued cholesterol distribution.

Metadata

Sample size (n)	14
Variables (p)	3
Subject area	Medical
Symbolic format	Histogram
Analytical tasks	Descriptive statistics

Source

Billard, L. and Diday, E. (2006), Table 4.5.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis: Conceptual Statistics and Data Mining*. Wiley, Chichester. Table 4.5.

Examples

```
data(cholesterol.hist)
```

clean_colnames	<i>clean_colnames</i>
----------------	-----------------------

Description

This function is used to clean up variable names to conform to the RSDA format.

Usage

```
clean_colnames(data)
```

Arguments

data	The conventional data.
------	------------------------

Value

Data after cleaning variable names.

Examples

```
data(mushroom.int.mm)
mushroom.clean <- clean_colnames(data = mushroom.int.mm)
```

county_income_gender.hist	<i>County Income by Gender Histogram-Valued Dataset</i>
---------------------------	---

Description

Histogram-valued dataset of 12 counties with gender-stratified income histograms and sample sizes. Each county has a male income histogram, a female income histogram, and the number of respondents in each group.

Usage

```
data(county_income_gender.hist)
```

Format

A data frame with 12 observations (counties) and 4 variables:

- male_income: Histogram of male household income (4 bins from \$0 to \$100k).
- female_income: Histogram of female household income (4 bins from \$0 to \$100k).
- n_males: Number of male respondents (numeric).
- n_females: Number of female respondents (numeric).

Row names are County_1 through County_12.

Metadata

Sample size (n)	12
Variables (p)	4
Subject area	Economics
Symbolic format	Histogram
Analytical tasks	Clustering, Descriptive statistics

Source

Billard, L. and Diday, E. (2020), Table 6-16.

References

Billard, L. and Diday, E. (2020). *Clustering Methodology for Symbolic Data*. Wiley, Chichester. Table 6-16.

Examples

```
data(county_income_gender.hist)
```

cover_types.hist	<i>Forest Cover Types Histogram-Valued Dataset</i>
------------------	--

Description

Histogram-valued dataset of 7 forest cover types with 4 topographic histogram variables. Each histogram describes the distribution of a terrain feature across locations classified as that cover type.

Usage

```
data(cover_types.hist)
```

Format

A data frame with 7 observations (cover types) and 4 histogram-valued variables:

- elevation: Histogram of elevation values (meters).
- distance_to_water: Histogram of horizontal distance to nearest water source (meters).
- hillshade: Histogram of hillshade index values.
- slope: Histogram of slope values (degrees).

Row names are CoverType_1 through CoverType_7.

Metadata

Sample size (n)	7
Variables (p)	4
Subject area	Forestry
Symbolic format	Histogram
Analytical tasks	Clustering, Classification

Source

Billard, L. and Diday, E. (2020), Table 7-21.

References

Billard, L. and Diday, E. (2020). *Clustering Methodology for Symbolic Data*. Wiley, Chichester. Table 7-21.

Examples

```
data(cover_types.hist)
```

credit_card.int	<i>Credit Card Expenses Interval Dataset</i>
-----------------	--

Description

Interval-valued credit card spending aggregated by person-month. Three individuals' (Jon, Tom, Leigh) monthly expenditures across five categories.

Usage

```
data(credit_card.int)
```

Format

A data frame with 6 observations and 11 columns (5 interval variables in _l/_u Min-Max pairs, plus a label):

- person_month: Person-month identifier (e.g., "Jon - January"; character).
- food_l, food_u: Food expenditure range (USD).
- social_l, social_u: Social expenditure range (USD).
- travel_l, travel_u: Travel expenditure range (USD).
- gas_l, gas_u: Gas expenditure range (USD).
- clothes_l, clothes_u: Clothes expenditure range (USD).

Details

The original classical dataset (Table 2.3) records individual transactions. The symbolic version (Table 2.4) aggregates into interval-valued observations for each person-month combination.

Metadata

Sample size (n)	6
Variables (p)	11
Subject area	Finance
Symbolic format	Interval
Analytical tasks	Descriptive statistics

Source

Billard and Diday (2006), Tables 2.3–2.4.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley. Tables 2.3-2.4.

Examples

```
data(credit_card.int)
```

crime.modal

*Crime Demographics Dataset***Description**

Modal-valued dataset of 15 gangs described by probability distributions over crime type, gender, and age group. This is the wide (flat table) format; see [crime2.modal](#) for the modal-valued version.

Usage

```
data(crime.modal)
```

Format

A data frame with 15 observations (gang1–gang15) and 7 numeric columns representing 3 modal variables in wide format:

- Crime(violent), Crime(non-violent), Crime(none): Distribution over crime types (3 bins).
- Gender(male), Gender(female): Distribution over gender (2 bins).
- Age(<20), Age(>=20): Distribution over age groups (2 bins).

Metadata

Sample size (n)	15
Variables (p)	7
Subject area	Criminology
Symbolic format	Modal
Analytical tasks	Clustering, Descriptive statistics

Source

Billard and Diday (2006).

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley.

Examples

```
data(crime.modal)
```

`crime2.modal`*Crime Demographics Modal-Valued Dataset*

Description

Modal-valued version of the crime demographics dataset. See [crime.modal](#) for the wide-format version.

Usage

```
data(crime2.modal)
```

Format

A symbolic data frame (`symbolic_tbl`) with 15 observations and 3 modal-valued variables:

- Crime: Modal distribution over crime types (violent, non-violent, none).
- Gender: Modal distribution over gender (male, female).
- Age: Modal distribution over age groups (<20, >=20).

Metadata

Sample size (n)	15
Variables (p)	3
Subject area	Criminology
Symbolic format	Modal
Analytical tasks	Clustering, Descriptive statistics

Source

Billard and Diday (2006).

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley.

Examples

```
data(crime2.modal)
```

crude_oil_wti.its

*WTI Crude Oil Futures Daily High/Low Interval Time Series***Description**

Daily high and low prices of WTI (West Texas Intermediate) crude oil futures from January 2, 2003 to December 30, 2011 (2261 trading days). Yang, Han, Hong and Wang (2016) provide a related interval time-series application; this object was independently downloaded from Yahoo Finance.

Usage

```
data(crude_oil_wti.its)
```

Format

A data frame with 2261 observations and 3 variables:

- date: Trading date (Date class).
- low: Daily low price (USD per barrel).
- high: Daily high price (USD per barrel).

Details

WTI crude oil is a benchmark for oil prices in the Americas. This dataset covers a period that includes the 2003 Iraq War, the 2007–2008 oil price spike (reaching nearly USD 150/barrel), the 2008 global financial crisis, and the subsequent recovery. The wide variation in price levels and volatility regimes makes this dataset ideal for evaluating interval time series models under structural breaks.

Metadata

Sample size (n)	2261
Variables (p)	3 (date, low, high)
Subject area	Finance / Commodities
Symbolic format	Interval time series
Analytical tasks	Forecasting, Structural break analysis

Source

Yahoo Finance, continuous WTI crude-oil futures ticker CL=F, January 2, 2003–December 30, 2011. The Yahoo Low and High fields were retained after download via **quantmod**; the original retrieval date was not recorded.

References

Yang, W., Han, A., Hong, Y. and Wang, S. (2016). Analysis of crisis impact on crude oil prices: A new approach with interval time series modelling. *Quantitative Finance*, **16**(12), 1917–1928. doi:10.1080/14697688.2016.1211795.

Examples

```
data(crude_oil_wti.its)
head(crude_oil_wti.its)
plot(crude_oil_wti.its$date, crude_oil_wti.its$high, type = "l",
     col = "red", ylab = "Price (USD/barrel)", xlab = "Date",
     main = "WTI Crude Oil Daily High/Low (2003-2011)")
lines(crude_oil_wti.its$date, crude_oil_wti.its$low, col = "blue")
legend("topleft", c("High", "Low"), col = c("red", "blue"), lty = 1)
```

`djia.its`

Dow Jones Industrial Average Daily High/Low Interval Time Series

Description

Daily high and low prices of the Dow Jones Industrial Average (DJIA) from January 2, 2004 to December 30, 2005 (504 trading days), independently downloaded from Yahoo Finance for use as an interval time-series benchmark.

Usage

```
data(djia.its)
```

Format

A data frame with 504 observations and 3 variables:

- `date`: Trading date (Date class).
- `low`: Daily low price of the DJIA.
- `high`: Daily high price of the DJIA.

Details

The DJIA is a price-weighted index of 30 prominent companies listed on stock exchanges in the United States. Each observation represents a trading day with the daily low and high prices forming an interval. This interval.

Metadata

Sample size (n)	504
Variables (p)	3 (date, low, high)
Subject area	Finance
Symbolic format	Interval time series
Analytical tasks	Forecasting, Time series analysis

Source

Yahoo Finance, ticker ^DJI, January 2, 2004–December 30, 2005. The Yahoo Low and High fields were retained after download via **quantmod**; the original retrieval date was not recorded.

Examples

```
data(djia.its)
head(djia.its)
plot(djia.its$date, djia.its$high, type = "l", col = "red",
      ylab = "Price", xlab = "Date", main = "DJIA Daily High/Low")
lines(djia.its$date, djia.its$low, col = "blue")
legend("topleft", c("High", "Low"), col = c("red", "blue"), lty = 1)
```

ecoli_routes.int	<i>E. coli Transport Routes Interval Dataset</i>
------------------	--

Description

Interval-valued dataset of 9 E. coli transport routes with 5 interval variables representing biochemical pathway measurements.

Usage

```
data(ecoli_routes.int)
```

Format

A symbolic data frame (symbolic_tbl) with 9 observations (transport routes) and 5 interval-valued variables:

- Y1 through Y5: Interval-valued biochemical pathway measurements.

Row names are Route_1 through Route_9.

Metadata

Sample size (n)	9
Variables (p)	5
Subject area	Biology
Symbolic format	Interval
Analytical tasks	Clustering

Source

Billard, L. and Diday, E. (2020), Table 8-10.

References

Billard, L. and Diday, E. (2020). *Clustering Methodology for Symbolic Data*. Wiley, Chichester. Table 8-10.

Examples

```
data(ecoli_routes.int)
```

employment.int	<i>European Employment by Gender and Age Interval Dataset</i>
----------------	---

Description

Interval-valued proportions for 12 sex-age population groups across employment variables (employment type, education, industry sector, occupation, marital status). Used for factorial discriminant analysis.

Usage

```
data(employment.int)
```

Format

A data frame with 12 observations and 20 columns (9 interval variables in _l/_u Min-Max pairs, plus a group label and class):

- group: Sex-age group identifier (character).
- full_time_l, full_time_u: Full-time employment proportion range.
- part_time_l, part_time_u: Part-time employment proportion range.
- primary_studies_l, primary_studies_u: Primary studies proportion range.
- secondary_studies_l, secondary_studies_u: Secondary studies proportion range.
- uni_studies_l, uni_studies_u: University studies proportion range.
- employee_l, employee_u: Employee proportion range.

- manufacturing_l, manufacturing_u: Manufacturing sector proportion range.
- construction_l, construction_u: Construction sector proportion range.
- wholesale_retail_l, wholesale_retail_u: Wholesale/retail proportion range.
- class: Group classification (numeric).

Metadata

Sample size (n)	12
Variables (p)	20
Subject area	Economics
Symbolic format	Interval
Analytical tasks	Discriminant analysis, Classification

Source

Diday and Noirhomme-Fraiture (2008), Table 18.1.

References

Diday, E. and Noirhomme-Fraiture, M. (Eds.) (2008). *Symbolic Data Analysis and the SODAS Software*. Wiley. Table 18.1.

Examples

```
data(employment.int)
```

```
energy_consumption.distr
```

US Energy Consumption Distribution-Valued Dataset

Description

Distribution-valued dataset of energy consumption across US states. Each energy type described by Normal distribution parameters (mean, SD).

Usage

```
data(energy_consumption.distr)
```

Format

A data frame with 5 observations and 3 variables:

- type: Energy type.
- mean: Mean consumption across 50 states.
- sd: Standard deviation.

Details

Five types: Petroleum, Natural Gas, Coal, Hydroelectric, Nuclear Power. Values are rescaled consumption from the US Census Bureau (2004).

Metadata

Sample size (n)	5
Variables (p)	3
Subject area	Energy
Symbolic format	Distribution
Analytical tasks	Descriptive statistics

Source

Billard and Diday (2006), Table 2.8.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley. Table 2.8.

Examples

```
data(energy_consumption.distr)
```

energy_usage.distr	<i>Energy Usage Distribution-Valued Dataset</i>
--------------------	---

Description

Distribution-valued dataset for 10 towns (geographic areas) with categorical probability distributions for fuel type and central heating. Each observation has two distribution-valued variables.

Usage

```
data(energy_usage.distr)
```

Format

A data frame with 10 observations and 2 distribution-valued variables:

- fuel_type: Distribution over fuel types (None, Gas, Oil, Electricity, Coal).
- central_heating: Distribution over central heating (No, Yes).

Row names are Town_1 through Town_10.

Metadata

Sample size (n)	10
Variables (p)	2
Subject area	Energy
Symbolic format	Distribution
Analytical tasks	Descriptive statistics

Source

Billard, L. and Diday, E. (2006), Table 3.7.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis: Conceptual Statistics and Data Mining*. Wiley, Chichester. Table 3.7.

Examples

```
data(energy_usage.distr)
```

environment.mix

EPA Environmental Data Mixed Symbolic Dataset

Description

Mixed symbolic dataset from the US EPA with 14 state-group observations and 17 variables of mixed types: interval-valued environmental measurements and modal-valued (distributional) categorical variables.

Usage

```
data(environment.mix)
```

Format

A symbolic data frame (symbolic_tbl, of class c("symbolic_tbl", "tbl_df", "tbl", "data.frame")) with 14 observations and 17 variables. The first four are modal-valued (symbolic_modal) variables and the remaining thirteen are interval-valued (symbolic_interval) variables. This matches the structure of ggInterval::Environment.

- URBANICITY: Modal-valued urbanicity distribution (modal).
- INCOMELEVEL: Modal-valued income level distribution (modal).
- EDUCATION: Modal-valued education distribution (modal).
- REGIONDEVELOPME: Modal-valued regional development distribution (modal).

- CONTROL: Environmental control index range (interval).
- SATISFY: Satisfaction index range (interval).
- INDIVIDUAL: Individual concern index range (interval).
- WELFARE: Welfare index range (interval).
- HUMAN: Human impact index range (interval).
- POLITICS: Political concern index range (interval).
- BURDEN: Burden index range (interval).
- NOISE: Noise pollution index range (interval).
- NATURE: Nature preservation index range (interval).
- SEASETC: Seas/coastal index range (interval).
- MULTI: Multi-indicator range (interval).
- WATERWASTE: Water/waste index range (interval).
- VEHICLE: Vehicle emissions index range (interval).

Metadata

Sample size (n)	14
Variables (p)	17
Subject area	Environment
Symbolic format	Mixed (interval, modal)
Analytical tasks	Descriptive statistics, Clustering

Source

Extracted from `ggInterval::Environment`. The upstream package documentation does not identify a more original data provider.

References

Jiang, B.-S. and Wu, H.-M. (2026). *ggInterval: Visualizing Interval-Valued Data Using ggplot2*. R package. doi:[10.32614/CRAN.package.ggInterval](https://doi.org/10.32614/CRAN.package.ggInterval).

Examples

```
data(environment.mix)
```

euro_usd.its*Euro/Dollar Exchange Rate Daily High/Low Interval Time Series*

Description

Daily high and low values of the EUR/USD exchange rate from January 1, 2004 to December 30, 2005 (520 trading days). Inspired by the dataset used by Arroyo, Espinola and Mate (2011) for exponential smoothing methods for interval time series.

Usage

```
data(euro_usd.its)
```

Format

A data frame with 520 observations and 3 variables:

- date: Trading date (Date class).
- low: Daily low EUR/USD exchange rate.
- high: Daily high EUR/USD exchange rate.

Details

The EUR/USD exchange rate is the most traded currency pair in the world foreign exchange market. Each observation represents a trading day with the daily low and high exchange rates (USD per EUR) forming an interval. Note: the original study by Arroyo et al. (2011) used the period 2002–2003 (519 trading days); this dataset covers 2004–2005 because Yahoo Finance historical data for this ticker is only available from late 2003 onward.

Metadata

Sample size (n)	520
Variables (p)	3 (date, low, high)
Subject area	Finance / Foreign Exchange
Symbolic format	Interval time series
Analytical tasks	Forecasting, Time series analysis

Source

Yahoo Finance, ticker EURUSD=X, January 1, 2004–December 30, 2005. The Yahoo Low and High fields were retained after download via **quantmod**; the original retrieval date was not recorded.

References

Arroyo, J., Espinola, R. and Mate, C. (2011). Different approaches to forecast interval time series: A comparison in finance. *Computational Economics*, **37**(2), 169–191. doi:10.1007/s10614010-92302.

Examples

```
data(euro_usd.its)
head(euro_usd.its)
plot(euro_usd.its$date, euro_usd.its$high, type = "l", col = "red",
      ylab = "EUR/USD", xlab = "Date",
      main = "EUR/USD Daily High/Low (2004-2005)")
lines(euro_usd.its$date, euro_usd.its$low, col = "blue")
legend("topleft", c("High", "Low"), col = c("red", "blue"), lty = 1)
```

exchange_rate_returns.hist

Exchange Rate Returns Histogram Time Series

Description

Histogram-valued time series of 108 monthly observations of daily dollar/yen exchange-rate returns. Each observation is a histogram distribution of intra-month daily returns.

Usage

```
data(exchange_rate_returns.hist)
```

Format

A data frame with 108 observations and 1 histogram-valued variable:

- returns: Histogram of daily exchange rate returns within each month.

Metadata

Sample size (n)	108
Variables (p)	1
Subject area	Finance
Symbolic format	Histogram
Analytical tasks	Time series, Descriptive statistics

Source

HistDAWass: :RetHTS. The upstream package identifies the series as dollar/yen change-rate returns but does not state the original data provider.

References

Irpino, A. *HistDAWass: Histogram-Valued Data Analysis*. R package. doi:[10.32614/CRAN.package.HistDAWass](https://doi.org/10.32614/CRAN.package.HistDAWass).

Examples

```
data(exchange_rate_returns.hist)
```

<i>face.iGAP</i>	<i>Face Dataset (iGAP Format)</i>
------------------	-----------------------------------

Description

Interval-valued facial measurement data for 27 face images (9 individuals x 3 replications) in iGAP format (comma-separated interval strings). Contains 6 distance measurements between facial landmarks.

Usage

```
data(face.iGAP)
```

Format

A data frame with 27 observations and 6 character columns in iGAP format (comma-separated "min,max" strings):

- AD: Distance AD (facial landmark pair).
- BC: Distance BC (facial landmark pair).
- AH: Distance AH (facial landmark pair).
- DH: Distance DH (facial landmark pair).
- EH: Distance EH (facial landmark pair).
- GH: Distance GH (facial landmark pair).

Row names encode individual and replication (e.g., FRA1, FRA2, FRA3).

Metadata

Sample size (n)	27
Variables (p)	6
Subject area	Biometrics
Symbolic format	Interval (iGAP)
Analytical tasks	Classification, Visualization

Source

Derived from RSDA : : facedata, which is attributed to Leroy et al. (1996), and represented here in iGAP interval-string format.

References

Leroy, B., Chouakria, A., Herlin, I., and Diday, E. (1996). Approche geometrique et classification pour la reconnaissance de visage. In *Reconnaissance des Formes et Intelligence Artificielle (RFIA)*, 548–557.

Examples

```
data(face.iGAP)
```

finance.int

Finance Sector Interval Dataset

Description

Interval-valued data for 14 business sectors described by job-related financial variables (job cost codes, activity codes, budgets). Used for PCA demonstrations.

Usage

```
data(finance.int)
```

Format

A symbolic data frame (symbolic_tbl) with 14 observations and 7 variables:

- Sector: Business sector name (character).
- Job_Cost: Job cost range (currency units, interval).
- Job_Code: Job code range (interval).
- Activity_Code: Activity code range (interval).
- Monthly_Cost: Monthly cost range (currency units, interval).
- Annual_Budget: Annual budget range (currency units, interval).
- n: Number of entities in the sector (numeric).

Metadata

Sample size (n)	14
Variables (p)	7
Subject area	Finance
Symbolic format	Interval
Analytical tasks	PCA

Source

Billard and Diday (2006), Table 5.2.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley. Table 5.2.

Examples

```
data(finance.int)
```

flights_detail.hist	<i>Airline Flights Detailed Histogram-Valued Dataset</i>
---------------------	--

Description

Histogram-valued dataset of 16 airlines with 5 flight performance histograms. Each histogram has 12 bins describing the distribution of a performance metric across flights for that airline.

Usage

```
data(flights_detail.hist)
```

Format

A data frame with 16 observations (airlines) and 5 histogram-valued variables:

- `airtime`: Histogram of air time (minutes).
- `taxi_in`: Histogram of taxi-in time (minutes).
- `arrival_delay`: Histogram of arrival delay (minutes).
- `taxi_out`: Histogram of taxi-out time (minutes).
- `departure_delay`: Histogram of departure delay (minutes).

Row names are `Airline_1` through `Airline_16`.

Metadata

Sample size (n)	16
Variables (p)	5
Subject area	Transportation
Symbolic format	Histogram
Analytical tasks	Clustering

Source

Billard, L. and Diday, E. (2020), Table 5-1.

References

Billard, L. and Diday, E. (2020). *Clustering Methodology for Symbolic Data*. Wiley, Chichester. Table 5-1.

Examples

```
data(flights_detail.hist)
```

```
french_agriculture.hist
```

French Agriculture Histogram-Valued Dataset

Description

Histogram-valued dataset of 22 French regions with 4 economic histogram variables related to agricultural production. Each histogram describes the distribution of farm-level values within a region.

Usage

```
data(french_agriculture.hist)
```

Format

A data frame with 22 observations (French regions) and 4 histogram-valued variables:

- Y_TSC: Histogram of total standard coefficient.
- X_Wheat: Histogram of wheat production.
- X_Pig: Histogram of pig production.
- X_Cmilk: Histogram of cow milk production.

Row names are French region names (e.g., Ile-de-France, Picardie).

Metadata

Sample size (n)	22
Variables (p)	4
Subject area	Agriculture
Symbolic format	Histogram
Analytical tasks	Regression, Clustering

Source

HistDAWass: :Agronomique; provenance follows the source cited in the upstream package documentation.

References

Verde, R., Irpino, A. and Desbois, D. (2014). How to cope with modelling and privacy concerns? A regression model and a visualization tool for aggregated data. Conference of European Statistics Stakeholders, Rome.

Examples

```
data(french_agriculture.hist)
```

freshwater_fish.int	<i>Freshwater Fish Heavy Metal Bioaccumulation Interval Dataset</i>
---------------------	---

Description

Interval-valued dataset of heavy metal concentrations in organs and tissues of 12 freshwater fish species, grouped into 4 feeding categories (Carnivores, Omnivores, Detritivores, Herbivores). Contains 13 interval-valued variables measuring metal concentrations in organs and organ-to-muscle ratios.

Usage

```
data(freshwater_fish.int)
```

Format

A data frame with 12 observations and 14 variables:

- `body_length`: Body length (cm).
- `body_weight`: Body weight (g).
- `muscle`: Metal concentration in muscle tissue.
- `intestine`: Metal concentration in intestine.
- `stomach`: Metal concentration in stomach.
- `gills`: Metal concentration in gills.
- `liver`: Metal concentration in liver.
- `kidney`: Metal concentration in kidney.
- `liver_muscle_ratio`: Liver-to-muscle concentration ratio.
- `kidney_muscle_ratio`: Kidney-to-muscle concentration ratio.
- `gills_muscle_ratio`: Gills-to-muscle concentration ratio.
- `intestine_muscle_ratio`: Intestine-to-muscle concentration ratio.
- `stomach_muscle_ratio`: Stomach-to-muscle concentration ratio.
- `class`: Feeding category (Carnivores, Omnivores, Detritivores, Herbivores).

Metadata

Sample size (n)	12
Variables (p)	14
Subject area	Biology
Symbolic format	Interval
Analytical tasks	Clustering

Source

<https://github.com/Natandradesa/Kernel-Clustering-for-Interval-Data>

References

Andrade de Sa, J. N., Ferreira, M. R. P. and de Carvalho, F. A. T. (2025). Kernel clustering with automatic variable weighting for interval data. *Neurocomputing*, 650, 130849. doi:10.1016/j.neucom.2025.130849.

Examples

```
data(freshwater_fish.int)
```

```
fuel_consumption.modal
```

Fuel Consumption by Region Dataset

Description

Modal-valued dataset describing fuel consumption patterns across 10 regions by proportions of heating fuel types (gas, oil, electricity, other) and per-capita expenditure.

Usage

```
data(fuel_consumption.modal)
```

Format

A symbolic data frame (symbolic_tbl) with 10 observations and 3 variables:

- Region: Region identifier (character).
- Expenditure: Per-capita fuel expenditure (numeric).
- Fuel_Type: Modal distribution over fuel types (gas, oil, electric, other).

Metadata

Sample size (n)	10
Variables (p)	3
Subject area	Energy
Symbolic format	Modal
Analytical tasks	Regression

Source

Billard and Diday (2006), Table 3.7.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley. Table 3.7.

Examples

```
data(fuel_consumption.modal)
```

fungi.int

Fungi Morphological Measurements Interval Dataset

Description

Interval-valued morphological measurements for 55 fungi specimens from 3 genera (Amanita, Agaricus, Boletus). Contains 5 interval-valued variables describing pileus and stipe dimensions and spore characteristics.

Usage

```
data(fungi.int)
```

Format

A data frame with 55 observations and 6 variables:

- pileus_width: Width of the pileus (cap).
- stipe_width: Width of the stipe (stem).
- stipe_thickness: Thickness of the stipe.
- spore_height: Height of the spores.
- spore_width: Width of the spores.
- class: Fungus genus (Amanita, Agaricus, Boletus).

Metadata

Sample size (n)	55
Variables (p)	6
Subject area	Biology
Symbolic format	Interval
Analytical tasks	Clustering

Source

<https://github.com/Natandradesa/Kernel-Clustering-for-Interval-Data>

References

Andrade de Sa, J. N., Ferreira, M. R. P. and de Carvalho, F. A. T. (2025). Kernel clustering with automatic variable weighting for interval data. *Neurocomputing*, 650, 130849. doi:10.1016/j.neucom.2025.130849.

Examples

```
data(fungi.int)
```

genome_abundances.int *Genome Dinucleotide Abundance Intervals*

Description

Interval-valued dataset of dinucleotide relative abundances for 14 genome classes. Each class aggregates multiple genomes; the intervals represent the range of observed abundance values within each class for 10 dinucleotide pairs, plus a count variable.

Usage

```
data(genome_abundances.int)
```

Format

A symbolic data frame (symbolic_tbl) with 14 observations (genome classes) and 11 variables:

- CG: Interval-valued CG dinucleotide relative abundance.
- GC: Interval-valued GC dinucleotide relative abundance.
- TA: Interval-valued TA dinucleotide relative abundance.
- AT: Interval-valued AT dinucleotide relative abundance.
- CC: Interval-valued CC dinucleotide relative abundance.

- AA: Interval-valued AA dinucleotide relative abundance.
- AC: Interval-valued AC dinucleotide relative abundance.
- AG: Interval-valued AG dinucleotide relative abundance.
- CA: Interval-valued CA dinucleotide relative abundance.
- GA: Interval-valued GA dinucleotide relative abundance.
- n: Number of genomes in the class (integer).

Row names are Class_1 through Class_14.

Metadata

Sample size (n)	14
Variables (p)	11
Subject area	Genomics
Symbolic format	Interval
Analytical tasks	Clustering, Descriptive statistics

Source

Billard, L. and Diday, E. (2020), Table 3-16.

References

Billard, L. and Diday, E. (2020). *Clustering Methodology for Symbolic Data*. Wiley, Chichester. Table 3-16.

Examples

```
data(genome_abundances.int)
```

glucose.hist

Blood Glucose Histogram-Valued Dataset

Description

Histogram-valued dataset of 4 regions with a single histogram-valued variable describing the distribution of blood glucose measurements.

Usage

```
data(glucose.hist)
```

Format

A data frame with 4 observations (regions) and 1 histogram-valued variable:

- glucose: Histogram of blood glucose levels.

Row names are Region_1 through Region_4.

Metadata

Sample size (n)	4
Variables (p)	1
Subject area	Medical
Symbolic format	Histogram
Analytical tasks	Descriptive statistics

Source

Billard, L. and Diday, E. (2020), Table 4-14.

References

Billard, L. and Diday, E. (2020). *Clustering Methodology for Symbolic Data*. Wiley, Chichester. Table 4-14.

Examples

```
data(glucose.hist)
```

hardwood.hist	<i>Hardwood Tree Species Histogram-Valued Dataset</i>
---------------	---

Description

Histogram-valued climate data for 5 hardwood tree species in the southeastern United States. Each observation represents a species with 4 histogram-valued climate variables.

Usage

```
data(hardwood.hist)
```

Format

A data frame with 5 observations and 4 histogram-valued variables:

- ANNT: Annual temperature histogram (degrees C).
- JUL7: July temperature histogram (degrees C).
- ANNP: Annual precipitation histogram (mm).
- MITM: Moisture index histogram.

Metadata

Sample size (n)	5
Variables (p)	4
Subject area	Forestry
Symbolic format	Histogram
Analytical tasks	Clustering, Descriptive statistics

Source

Extracted from RSDA: : hardwoodBr i to; the dataset and its distributional principal-component analysis are described by Brito and Dias (2022).

References

Brito, P. and Dias, S. (2022). *Analysis of Distributional Data*. CRC Press.

Examples

```
data(hardwood.hist)
```

hdi_gender.int

Human Development Index and Gender Indicators Interval Dataset

Description

Interval-valued World Bank gender indicators for 183 countries, with ordinal HDI classification. Contains interval ranges for Women, Business and the Law Index Score and proportion of seats held by women in national parliaments.

Usage

```
data(hdi_gender.int)
```

Format

A data frame with 183 observations and 6 variables:

- code: ISO 3166-1 alpha-3 country code.
- country: Country name.
- hdi: Human Development Index value (UNDP).
- women_law_index: Women, Business and the Law Index Score range.
- women_parliament: Proportion of seats held by women in national parliaments range (%).
- hdi_category: Ordered factor with HDI classification (Low < Medium < High < Very High).

Metadata

Sample size (n)	183
Variables (p)	6
Subject area	Socioeconomics
Symbolic format	Interval
Analytical tasks	Classification

Source

<https://github.com/aleixalcacer/OCFIVD>

References

Alcacer, A., Martinez-Garcia, M. and Epifanio, I. (2024). Ordinal classification for interval-valued data and interval-valued functional data. *Expert Systems with Applications*, 238, 122277. doi:10.1016/j.eswa.2023.122277.

Examples

```
data(hdi_gender.int)
```

health_insurance.mix	<i>Health Insurance Mixed Symbolic Dataset</i>
----------------------	--

Description

Classical (microdata) health insurance dataset of 51 individual patient records with 30 variables including demographics, clinical measurements, and diagnostic indicators. This is the raw data underlying the symbolic [health_insurance2.modal](#) dataset.

Usage

```
data(health_insurance.mix)
```

Format

A data frame with 51 observations and 30 variables (Y1–Y30):

- Y1: City (character).
- Y2: Gender (M/F, character).
- Y3: Age (integer).
- Y4: Sex (M/D, character).
- Y5: Marital status (S/M, character).
- Y6: Number of dependents (integer).
- Y7: Parents alive indicator (integer).
- Y8: Number of children (integer).
- Y9: Height (cm, integer).
- Y10: Weight (pounds, integer).
- Y11: Systolic blood pressure (mmHg, integer).
- Y12: Diastolic blood pressure (mmHg, integer).
- Y13: Cholesterol (mg/dL, integer).
- Y14: Cholesterol measure 2 (integer).
- Y15: Additional lab measurement (integer).
- Y16: Ratio measurement (numeric).
- Y17: Lab value (integer).
- Y18: Lab value (integer).
- Y19: Lab value (integer).
- Y20: Lab ratio (numeric).
- Y21: Additional lab value (integer).
- Y22: Additional lab value (integer).
- Y23: Blood chemistry value (numeric).
- Y24: Blood chemistry value (numeric).
- Y25: Blood chemistry value (numeric).
- Y26: Blood chemistry value (numeric).
- Y27: Blood chemistry value (numeric).
- Y28: Diagnostic indicator (Y/N, character).
- Y29: Diagnostic indicator (Y/N, character).
- Y30: Count variable (integer).

Metadata

Sample size (n)	51
Variables (p)	30
Subject area	Medical
Symbolic format	Classical (microdata)
Analytical tasks	Descriptive statistics, Aggregation

Source

Billard and Diday (2006), Tables 2.1–2.2.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley. Tables 2.1-2.2.

Examples

```
data(health_insurance.mix)
```

```
health_insurance2.modal
```

Health Insurance Modal-Valued Dataset

Description

Modal-valued symbolic version of the health insurance dataset, aggregated into 6 disease-type-by-gender groups. See [health_insurance.mix](#) for the underlying microdata.

Usage

```
data(health_insurance2.modal)
```

Format

A symbolic data frame (`symbolic_tbl`) with 6 observations and 6 variables:

- Type Gender: Disease type and gender label (character).
- Age: Modal distribution over age bins.
- Marital Status: Modal distribution over marital status (M, S).
- Parents Alive: Modal distribution over number of parents alive (0, 1, 2).
- Weight: Modal distribution over weight bins (pounds).
- Cholesterol: Modal distribution over cholesterol bins (mg/dL).

Metadata

Sample size (n)	6
Variables (p)	6
Subject area	Medical
Symbolic format	Modal
Analytical tasks	Clustering, Descriptive statistics

Source

Billard and Diday (2006), Table 2.2b.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley. Table 2.2b.

Examples

```
data(health_insurance2.modal)
```

hematocrit.hist

Hematocrit by Gender and Age Histogram-Valued Dataset

Description

Histogram-valued hematocrit distributions for 14 gender-age groups (7 female + 7 male age groups from 20s to 80+). Each observation has a 10-bin histogram of hematocrit percentages.

Usage

```
data(hematocrit.hist)
```

Format

A data frame with 14 observations and 3 variables:

- gender: Gender (Female or Male).
- age: Age group (20s, 30s, 40s, 50s, 60s, 70s, 80+).
- hematocrit: Histogram-valued hematocrit distribution (%).

Metadata

Sample size (n)	14
Variables (p)	3
Subject area	Medical
Symbolic format	Histogram
Analytical tasks	Descriptive statistics

Source

Billard, L. and Diday, E. (2006), Table 4.14.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis: Conceptual Statistics and Data Mining*. Wiley, Chichester. Table 4.14.

Examples

```
data(hematocrit.hist)
```

```
hematocrit_hemoglobin.hist
```

Hematocrit and Hemoglobin Bivariate Histogram-Valued Dataset

Description

Bivariate histogram-valued dataset with 10 observations, each described by a 2-bin hematocrit histogram and a 2-bin hemoglobin histogram. Used for bivariate symbolic regression demonstrations.

Usage

```
data(hematocrit_hemoglobin.hist)
```

Format

A data frame with 10 observations and 2 histogram-valued variables:

- **hematocrit**: Histogram-valued hematocrit distribution (%).
- **hemoglobin**: Histogram-valued hemoglobin distribution (g/dL).

Metadata

Sample size (n)	10
Variables (p)	2
Subject area	Medical
Symbolic format	Histogram
Analytical tasks	Regression

Source

Billard, L. and Diday, E. (2006), Table 6.8.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis: Conceptual Statistics and Data Mining*. Wiley, Chichester. Table 6.8.

Examples

```
data(hematocrit_hemoglobin.hist)
```

hemoglobin.hist	<i>Hemoglobin by Gender and Age Histogram-Valued Dataset</i>
-----------------	--

Description

Histogram-valued hemoglobin distributions for 14 gender-age groups (7 female + 7 male age groups from 20s to 80+). Each observation has a 10-bin histogram of hemoglobin levels (g/dL).

Usage

```
data(hemoglobin.hist)
```

Format

A data frame with 14 observations and 3 variables:

- gender: Gender (Female or Male).
- age: Age group (20s, 30s, 40s, 50s, 60s, 70s, 80+).
- hemoglobin: Histogram-valued hemoglobin distribution (g/dL).

Metadata

Sample size (n)	14
Variables (p)	3
Subject area	Medical
Symbolic format	Histogram
Analytical tasks	Descriptive statistics

Source

Billard, L. and Diday, E. (2006), Table 4.6.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis: Conceptual Statistics and Data Mining*. Wiley, Chichester. Table 4.6.

Examples

```
data(hemoglobin.hist)
```

hierarchy

Hierarchy Dataset

Description

Classical (microdata) dataset of 20 observations illustrating hierarchical categorical structures with a response variable Y and hierarchical predictors X1–X5. See [hierarchy.int](#) for the interval-valued version.

Usage

```
data(hierarchy)
```

Format

A data frame with 20 observations and 6 variables:

- Y: Response variable (numeric).
- X1: Hierarchy level 1 category (a/b/c, character).
- X2: Hierarchy level 2 category (a1/a2, character; NA for non-a).
- X3: Hierarchy level 3 category (a11/a12, character; NA for non-a1).
- X4: Numeric predictor for group b (numeric; NA for non-b).
- X5: Numeric predictor for group c (numeric; NA for non-c).

Metadata

Sample size (n)	20
Variables (p)	6
Subject area	Methodology
Symbolic format	Classical (microdata)
Analytical tasks	Aggregation, Descriptive statistics

Source

Billard and Diday (2006), Table 2.15.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley. Table 2.15.

Examples

```
data(hierarchy)
```

hierarchy.hist	<i>Hierarchical Symbolic Dataset with Mixed Types</i>
----------------	---

Description

Mixed symbolic dataset of 10 observations with hierarchical categorical variables, conditional histogram variables, and an interval-valued variable. From Table 6.20 of Billard and Diday (2006).

Usage

```
data(hierarchy.hist)
```

Format

A symbolic data frame (symbolic_tbl) with 10 observations and 7 variables:

- duration_time: Histogram-valued duration (2-bin).
- hierarchy_1: Categorical hierarchy level 1 (a/b/c).
- hierarchy_2: Categorical hierarchy level 2 (a1/a2), conditional on hierarchy_1 = a.
- hierarchy_3: Categorical hierarchy level 3 (a11/a12), conditional on hierarchy_2 = a1.
- glucose: Histogram-valued glucose (2-bin), conditional.
- pulse_rate: Histogram-valued pulse rate (2-bin), conditional.
- cholesterol: Interval-valued cholesterol level.

Metadata

Sample size (n)	10
Variables (p)	7
Subject area	Methodology
Symbolic format	Mixed (histogram, interval, categorical)
Analytical tasks	Descriptive statistics

Source

Billard, L. and Diday, E. (2006), Table 6.20.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis: Conceptual Statistics and Data Mining*. Wiley, Chichester. Table 6.20.

Examples

```
data(hierarchy.hist)
```

hierarchy.int	<i>Hierarchy Interval Dataset</i>
---------------	-----------------------------------

Description

Interval-valued version of the hierarchy dataset. See [hierarchy](#) for the classical version.

Usage

```
data(hierarchy.int)
```

Format

A symbolic data frame (symbolic_tbl) with 20 observations and 6 variables:

- Y: Response variable range (interval).
- X1: Hierarchy level 1 category (a/b/c, character).
- X2: Hierarchy level 2 category (a1/a2, character; NA for non-a).
- X3: Hierarchy level 3 category (a11/a12, character; NA for non-a1).
- X4: Predictor range for group b (interval; NA for non-b).
- X5: Predictor range for group c (interval; NA for non-c).

Metadata

Sample size (n)	20
Variables (p)	6
Subject area	Methodology
Symbolic format	Interval
Analytical tasks	Descriptive statistics, Regression

Source

Billard and Diday (2006), Table 2.15.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley. Table 2.15.

Examples

```
data(hierarchy.int)
```

histogram_stats	<i>Statistics for Histogram Data</i>
-----------------	--------------------------------------

Description

Functions to compute the mean, variance, covariance, and correlation of histogram-valued data.

Usage

```
hist_mean(x, var_name, method = "BG", ...)
hist_var(x, var_name, method = "BG", ...)
hist_cov(x, var_name1, var_name2, method = "BG", ...)
hist_cor(x, var_name1, var_name2, method = "BG", ...)
```

Arguments

x	histogram-valued data object.
var_name	the variable name or the column location.
method	method to calculate statistics. One of "BG" (Bertrand and Goupil, 2000; default), "BD" (Billard and Diday, 2006), "B" (Billard, 2008), or "L2W" (L2 Wasserstein). All four methods are available for all four functions.
...	additional parameters.
var_name1	the variable name or the column location.
var_name2	the variable name or the column location.

Details

Four functions are provided:

- `hist_mean`: Compute the mean of histogram-valued data.
- `hist_var`: Compute the variance of histogram-valued data.
- `hist_cov`: Compute the covariance between two histogram-valued variables.
- `hist_cor`: Compute the correlation between two histogram-valued variables.

Four methods are supported for all functions:

BG Bertrand and Goupil (2000) method. Uses histogram bin boundaries and probabilities to compute first and second moments.

BD Billard and Diday (2006) method. A signed decomposition using the sign of each bin's mid-point deviation from the overall mean and a quadratic form on the bin boundaries.

B Billard (2008) method. Uses cross-products of deviations of the bin boundaries from the overall mean.

L2W L2 Wasserstein method. Uses optimal-transport (Wasserstein) distances between the quantile functions of the histogram distributions.

For the mean, BG, BD, and B return the same value because they share the same first-order moment definition; only L2W uses a different (quantile-based) mean. For variance, covariance, and correlation, all four methods generally produce different results.

For `hist_cor`, the BG, BD, and B correlations all use the Bertrand-Goupil standard deviation $S(Y)$ in the denominator, following Irpino and Verde (2015, Eqs. 30–32). Only the L2W method uses its own Wasserstein-based standard deviation in the denominator.

Value

A numeric value or vector for `hist_mean` and `hist_var`; a single numeric value for `hist_cov` and `hist_cor`.

Author(s)

Po-Wei Chen, Han-Ming Wu

See Also

`int_mean` `int_var` `int_cov` `int_cor`

Examples

```
library(HistDAWass)
x <- HistDAWass::BLOOD
hist_mean(x, var_name = "Cholesterol", method = "BG")
hist_mean(x, var_name = "Cholesterol", method = "BD")
hist_var(x, var_name = "Cholesterol", method = "BG")
hist_var(x, var_name = "Cholesterol", method = "BD")
hist_cov(x, var_name1 = "Cholesterol", var_name2 = "Hemoglobin", method = "BG")
hist_cor(x, var_name1 = "Cholesterol", var_name2 = "Hemoglobin", method = "BG")
```

horses.int

*Horse Breeds Interval Dataset***Description**

Interval-valued data for 8 horse breeds (CES, CMA, PEN, TES, CEN, LES, PES, PAM) described by 6 variables: minimum/maximum weight, minimum/maximum height, cost of mares, cost of fillies.

Usage

```
data(horses.int)
```

Format

A symbolic data frame (symbolic_tbl) with 8 observations and 7 variables:

- Breed: Horse breed code (CES, CMA, PEN, TES, CEN, LES, PES, PAM; character).
- Minimum_Weight: Minimum weight range (kg, interval).
- Maximum_Weight: Maximum weight range (kg, interval).
- Minimum_Height: Minimum height range (cm, interval).
- Maximum_Height: Maximum height range (cm, interval).
- Mares_Cost: Cost of mares range (currency units, interval).
- Fillies_Cost: Cost of fillies range (currency units, interval).

Details

Extensively used in SDA for demonstrating divisive clustering, distance computation, hierarchy/pyramid construction, and complete objects.

Metadata

Sample size (n)	8
Variables (p)	7
Subject area	Zoology
Symbolic format	Interval
Analytical tasks	Clustering

Source

Billard and Diday (2006), Table 7.14.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley. Table 7.14.

Examples

```
data(horses.int)
```

hospital.hist	<i>Hospital Costs Histogram-Valued Dataset</i>
---------------	--

Description

Histogram-valued cost distributions for 15 hospitals. Each observation is a hospital with a 10-bin histogram of patient costs.

Usage

```
data(hospital.hist)
```

Format

A data frame with 15 observations and 1 histogram-valued variable:

- cost: Histogram-valued cost distribution (currency units).

Row names are H1 through H15.

Metadata

Sample size (n)	15
Variables (p)	1
Subject area	Healthcare
Symbolic format	Histogram
Analytical tasks	Descriptive statistics, Clustering

Source

Billard, L. and Diday, E. (2006), Table 3.12.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis: Conceptual Statistics and Data Mining*. Wiley, Chichester. Table 3.12.

Examples

```
data(hospital.hist)
```

household_characteristics.distr
<i>Household Characteristics Distribution-Valued Dataset</i>

Description

Distribution-valued dataset of 12 counties with 3 categorical probability distribution variables describing household fuel type, number of rooms, and household income brackets.

Usage

```
data(household_characteristics.distr)
```

Format

A data frame with 12 observations (counties) and 3 distribution-valued variables:

- fuel_type: Distribution over fuel types (gas, electric, oil, wood, none).
- rooms: Distribution over room counts ({1,2}, {3,4,5}, {>=6}).
- household_income: Distribution over income brackets (<10, [10,25), [25,50), [50,75), [75,100), [100,150), [150,200), >=200).

Row names are County_1 through County_12.

Metadata

Sample size (n)	12
Variables (p)	3
Subject area	Socioeconomics
Symbolic format	Distribution
Analytical tasks	Clustering, Descriptive statistics

Source

Billard, L. and Diday, E. (2020), Table 6-1.

References

Billard, L. and Diday, E. (2020). *Clustering Methodology for Symbolic Data*. Wiley, Chichester. Table 6-1.

Examples

```
data(household_characteristics.distr)
```

ibovespa.its

IBOVESPA Daily High/Low Interval Time Series

Description

Daily high and low values of the Brazilian IBOVESPA stock market index from January 3, 2000 to December 28, 2012 (3216 trading days). It covers the period studied by Maciel, Ballini and Gomide (2016), but this object was independently downloaded from Yahoo Finance; the article reports Bloomberg as its data source.

Usage

```
data(ibovespa.its)
```

Format

A data frame with 3216 observations and 3 variables:

- date: Trading date (Date class).
- low: Daily low value of the IBOVESPA index.
- high: Daily high value of the IBOVESPA index.

Details

The IBOVESPA (Indice Bovespa) is the benchmark index of the Brazilian stock exchange (B3, formerly BM&FBOVESPA). It tracks the performance of the most actively traded stocks on the Sao Paulo stock exchange. The 13-year span of this dataset covers multiple market regimes including the 2008 global financial crisis, making it suitable for evaluating forecasting models under diverse conditions.

Metadata

Sample size (n)	3216
Variables (p)	3 (date, low, high)
Subject area	Finance
Symbolic format	Interval time series
Analytical tasks	Forecasting, Time series analysis

Source

Yahoo Finance, ticker ^BVSP, January 3, 2000–December 28, 2012. The Yahoo Low and High fields were retained after download via **quantmod**; the original retrieval date was not recorded.

References

Maciel, L., Ballini, R. and Gomide, F. (2016). Evolving granular analytics for interval time series forecasting. *Granular Computing*, **1**(4), 213–224. doi:[10.1007/s4106601600163](https://doi.org/10.1007/s4106601600163).

Examples

```
data(ibovespa.its)
head(ibovespa.its)
plot(ibovespa.its$date, ibovespa.its$high, type = "l", col = "red",
     ylab = "Index Value", xlab = "Date",
     main = "IBOVESPA Daily High/Low (2000-2012)")
lines(ibovespa.its$date, ibovespa.its$low, col = "blue")
legend("topleft", c("High", "Low"), col = c("red", "blue"), lty = 1)
```

iGAP_to_ARRAY	<i>iGAP to ARRAY</i>
---------------	----------------------

Description

Convert iGAP format to a 3-dimensional array [n, p, 2].

Usage

```
iGAP_to_ARRAY(data, location = NULL)
```

Arguments

data	A data.frame in iGAP format.
location	Integer vector specifying which columns contain comma-separated interval values.

Value

A numeric array of dimension [n, p, 2] with dimnames.

Examples

```
data(abalone.iGAP)
arr <- iGAP_to_ARRAY(abalone.iGAP, 1:7)
dim(arr)
```

iGAP_to_MM	<i>iGAP to MM</i>
------------	-------------------

Description

To convert iGAP format to MM format.

Usage

```
iGAP_to_MM(data, location = NULL)
```

Arguments

- data The dataframe with the iGAP format.
- location The location of the symbolic variable in the data.

Value

Return a dataframe with the MM format.

Examples

```
data(abalone.iGAP)
abalone <- iGAP_to_MM(abalone.iGAP, 1:7)
```

iGAP_to_RSDA	<i>iGAP to RSDA</i>
--------------	---------------------

Description

To convert iGAP format interval dataframe to RSDA format (symbolic_tbl).

Usage

```
iGAP_to_RSDA(data, location = NULL)
```

Arguments

- data The dataframe with the iGAP format.
- location The location of the symbolic variable in the data.

Value

Return a symbolic_tbl dataframe with complex-encoded interval columns.

Examples

```
data(abalone.iGAP)
rsda <- iGAP_to_RSDA(abalone.iGAP, 1:7)
```

interval_distance	<i>Distance Measures for Interval Data</i>
-------------------	--

Description

Functions to compute various distance measures between interval-valued observations.

int_dist_all computes all available distance measures at once.

Usage

```
int_dist(x, method = "euclidean", gamma = 0.5, q = 1, p = 2, ...)
```

```
int_dist_matrix(x, method = "euclidean", gamma = 0.5, q = 1, p = 2, ...)
```

```
int_pairwise_dist(x, var_name1, var_name2, method = "euclidean", ...)
```

```
int_dist_all(x, gamma = 0.5, q = 1)
```

Arguments

x	interval-valued data with symbolic_tbl class, or an array of dimension [n, p, 2]
method	distance method: "GD", "IY", "L1", "L2", "CB", "HD", "EHD", "nEHD", "snEHD", "TD", "WD", "euclidean", "hausdorff", "manhattan", "city_block", "minkowski", "wasserstein", "ichino", "de_carvalho"
gamma	parameter for the Ichino-Yaguchi distance, $0 \leq \gamma \leq 0.5$ (default: 0.5)
q	parameter for the Ichino-Yaguchi distance (Minkowski exponent) (default: 1)
p	power parameter for Minkowski distance (default: 2)
...	additional parameters
var_name1	first variable name or column location
var_name2	second variable name or column location

Details

Available distance methods:

- GD: Gowda-Diday distance (Gowda & Diday, 1991)
- IY: Ichino-Yaguchi distance (Ichino, 1988)
- L1: L1 (midpoint Manhattan) distance
- L2: L2 (Euclidean midpoint) distance
- CB: City-Block distance (Souza & de Carvalho, 2004)

- HD: Hausdorff distance (Chavent & Lechevallier, 2002)
- EHD: Euclidean Hausdorff distance
- nEHD: Normalized Euclidean Hausdorff distance
- snEHD: Span Normalized Euclidean Hausdorff distance
- TD: Tran-Duckstein distance (Tran & Duckstein, 2002)
- WD: L2-Wasserstein distance (Verde & Irpino, 2008)
- euclidean: Euclidean distance on interval centers (same as L2)
- hausdorff: Hausdorff distance (same as HD)
- manhattan: Manhattan distance (same as L1)
- city_block: City-block distance (same as CB)
- minkowski: Minkowski distance with parameter p
- wasserstein: Wasserstein distance (same as WD)
- ichino: Ichino-Yaguchi distance (simplified version)
- de_carvalho: De Carvalho distance

Value

A distance matrix (class 'dist') or numeric vector

Author(s)

Han-Ming Wu

References

- Gowda, K. C., & Diday, E. (1991). Symbolic clustering using a new dissimilarity measure. *Pattern Recognition*, 24(6), 567-578.
- Ichino, M. (1988). General metrics for mixed features. *Systems and Computers in Japan*, 19(2), 37-50.
- Chavent, M., & Lechevallier, Y. (2002). Dynamical clustering of interval data. In *Classification, Clustering and Data Analysis* (pp. 53-60). Springer.
- Tran, L., & Duckstein, L. (2002). Comparison of fuzzy numbers using a fuzzy distance measure. *Fuzzy Sets and Systems*, 130, 331-341.
- Verde, R., & Irpino, A. (2008). A new interval data distance based on the Wasserstein metric.
- Kao, C.-H. et al. (2014). Exploratory data analysis of interval-valued symbolic data with matrix visualization. *Computational Statistics & Data Analysis*, 79, 14-29.

See Also

int_dist_matrix int_dist_all int_pairwise_dist

Examples

```
# Using symbolic_tbl format
data(mushroom.int)
d1 <- int_dist(mushroom.int[, 3:4], method = "euclidean")
d2 <- int_dist(mushroom.int[, 3:4], method = "hausdorff")
d3 <- int_dist(mushroom.int[, 3:4], method = "GD")

# Using array format: 4 concepts, 3 variables
x <- array(NA, dim = c(4, 3, 2))
x[, ,1] <- matrix(c(1,2,3,4, 5,6,7,8, 9,10,11,12), nrow=4)
x[, ,2] <- matrix(c(3,5,6,7, 8,9,10,12, 13,15,16,18), nrow=4)
d4 <- int_dist(x, method = "snEHD")
d5 <- int_dist(x, method = "IY", gamma = 0.3)
```

interval_geometry

*Geometric Properties of Interval Data***Description**

Functions to compute geometric characteristics of interval-valued data.

Usage

```
int_width(x, var_name, ...)

int_radius(x, var_name, ...)

int_center(x, var_name, ...)

int_overlap(x, var_name1, var_name2, ...)

int_containment(x, var_name1, var_name2, ...)

int_midrange(x, var_name, ...)
```

Arguments

x	interval-valued data with symbolic_tbl class.
var_name	the variable name or the column location (multiple variables are allowed).
...	additional parameters
var_name1	the first variable name or column location.
var_name2	the second variable name or column location.

Details

These functions compute basic geometric properties:

- `int_width`: Width of each interval ($\text{upper} - \text{lower}$)
- `int_radius`: Radius of each interval ($\text{width} / 2$)
- `int_center`: Center point of each interval ($(\text{lower} + \text{upper}) / 2$)
- `int_overlap`: Overlap measure between two interval variables
- `int_containment`: Check if one interval contains another
- `int_midrange`: Half-range of each interval ($(\text{upper} - \text{lower}) / 2$)

Value

A numeric matrix or value

Author(s)

Han-Ming Wu

See Also

`int_width` `int_radius` `int_center` `int_overlap`

Examples

```
data(mushroom.int)

# Calculate interval widths
int_width(mushroom.int, var_name = "Pileus.Cap.Width")
int_width(mushroom.int, var_name = 2:3)

# Calculate interval radius
int_radius(mushroom.int, var_name = c("Stipe.Length", "Stipe.Thickness"))

# Get interval centers
int_center(mushroom.int, var_name = 2:4)

# Measure overlap between two variables
int_overlap(mushroom.int, "Pileus.Cap.Width", "Stipe.Length")

# Check containment
int_containment(mushroom.int, "Pileus.Cap.Width", "Stipe.Length")

# Calculate midrange
int_midrange(mushroom.int, var_name = 2:3)
```

interval_position	<i>Position and Scale Measures for Interval Data</i>
-------------------	--

Description

Functions to compute position and scale statistics for interval-valued data.

Usage

```
int_median(x, var_name, method = "CM", ...)

int_quantile(x, var_name, probs = c(0.25, 0.5, 0.75), method = "CM", ...)

int_range(x, var_name, method = "CM", ...)

int_iqr(x, var_name, method = "CM", ...)

int_mad(x, var_name, method = "CM", ...)

int_mode(x, var_name, method = "CM", breaks = 30, ...)
```

Arguments

x	interval-valued data with symbolic_tbl class.
var_name	the variable name or the column location (multiple variables are allowed).
method	methods to calculate statistics: CM (default), VM, QM, SE, FV, EJD, GQ, SPT.
...	additional parameters
probs	numeric vector of probabilities with values in [0,1].
breaks	number of histogram breaks for mode estimation (default: 30).

Details

These functions provide position and scale measures:

- `int_median`: Median of interval data
- `int_quantile`: Quantiles of interval data
- `int_range`: Range (max - min) of interval data
- `int_iqr`: Interquartile range (Q3 - Q1)
- `int_mad`: Median absolute deviation
- `int_mode`: Mode of interval data (estimated via histogram)

Value

A numeric matrix or value

Author(s)

Han-Ming Wu

See Also

int_mean int_var int_median int_quantile

Examples

```

data(mushroom.int)

# Calculate median
int_median(mushroom.int, var_name = "Pileus.Cap.Width")
int_median(mushroom.int, var_name = 2:3, method = c("CM", "EJD"))

# Calculate quantiles
int_quantile(mushroom.int, var_name = 2, probs = c(0.25, 0.5, 0.75))

# Calculate interquartile range
int_iqr(mushroom.int, var_name = c("Stipe.Length", "Stipe.Thickness"))

# Calculate range
int_range(mushroom.int, var_name = "Pileus.Cap.Width")

# Calculate MAD
int_mad(mushroom.int, var_name = 2:3, method = "CM")

# Estimate mode
int_mode(mushroom.int, var_name = "Stipe.Length", method = "CM")

```

interval_robust

*Robust Statistics for Interval Data***Description**

Functions to compute robust statistics for interval-valued data.

Usage

```

int_trimmed_mean(x, var_name, trim = 0.1, method = "CM", ...)

int_winsorized_mean(x, var_name, trim = 0.1, method = "CM", ...)

int_trimmed_var(x, var_name, trim = 0.1, method = "CM", ...)

int_winsorized_var(x, var_name, trim = 0.1, method = "CM", ...)

```

Arguments

<code>x</code>	interval-valued data with <code>symbolic_tbl</code> class.
<code>var_name</code>	the variable name or the column location (multiple variables are allowed).
<code>trim</code>	the fraction (0 to 0.5) of observations to be trimmed from each end.
<code>method</code>	methods to calculate statistics: CM (default), VM, QM, SE, FV, EJD, GQ, SPT.
<code>...</code>	additional parameters

Details

These functions provide robust alternatives to standard statistics:

- `int_trimmed_mean`: Mean after trimming extreme values
- `int_winsorized_mean`: Mean after winsorizing extreme values
- `int_trimmed_var`: Variance after trimming extreme values
- `int_winsorized_var`: Variance after winsorizing extreme values

Trimming vs Winsorizing:

- Trimming: Remove extreme values
- Winsorizing: Replace extreme values with less extreme values

Value

A numeric matrix

Author(s)

Han-Ming Wu

See Also

`int_mean` `int_var` `int_trimmed_mean`

Examples

```
data(mushroom.int)

# Trimmed mean (10% from each end)
int_trimmed_mean(mushroom.int, var_name = "Pileus.Cap.Width", trim = 0.1)

# Winsorized mean
int_winsorized_mean(mushroom.int, var_name = 2:3, trim = 0.05, method = "CM")

# Trimmed variance
int_trimmed_var(mushroom.int, var_name = c("Stipe.Length"), trim = 0.1)
```

Description

Functions to compute shape statistics (skewness, kurtosis) for interval-valued data.

Usage

```
int_skewness(x, var_name, method = "CM", ...)
int_kurtosis(x, var_name, method = "CM", ...)
int_symmetry(x, var_name, method = "CM", ...)
int_tailedness(x, var_name, method = "CM", ...)
```

Arguments

x	interval-valued data with symbolic_tbl class.
var_name	the variable name or the column location (multiple variables are allowed).
method	methods to calculate statistics: CM (default), VM, QM, SE, FV, EJD, GQ, SPT.
...	additional parameters

Details

These functions measure distribution shape:

- `int_skewness`: Measure of asymmetry (skewness)
- `int_kurtosis`: Measure of tail heaviness (kurtosis)
- `int_symmetry`: Symmetry coefficient
- `int_tailedness`: Tailedness measure (alias for excess kurtosis)

Skewness interpretation:

- = 0: Symmetric distribution
- > 0: Right-skewed (positive skew)
- < 0: Left-skewed (negative skew)

Kurtosis interpretation (excess kurtosis):

- = 0: Normal distribution (mesokurtic)
- > 0: Heavy tails (leptokurtic)
- < 0: Light tails (platykurtic)

Value

A numeric matrix

Author(s)

Han-Ming Wu

See Also

int_mean int_var int_skewness int_kurtosis

Examples

```
data(mushroom.int)

# Calculate skewness
int_skewness(mushroom.int, var_name = "Pileus.Cap.Width")
int_skewness(mushroom.int, var_name = 2:3, method = c("CM", "EJD"))

# Calculate kurtosis
int_kurtosis(mushroom.int, var_name = c("Stipe.Length", "Stipe.Thickness"))

# Check symmetry
int_symmetry(mushroom.int, var_name = 2:4, method = "CM")

# Check tailedness
int_tailedness(mushroom.int, var_name = "Pileus.Cap.Width", method = "CM")
```

interval_similarity *Similarity Measures for Interval Data*

Description

Functions to compute similarity measures between interval-valued observations.

Usage

```
int_jaccard(x, var_name1, var_name2, ...)

int_dice(x, var_name1, var_name2, ...)

int_cosine(x, var_name1, var_name2, ...)

int_overlap_coefficient(x, var_name1, var_name2, ...)

int_tanimoto(x, var_name1, var_name2, ...)

int_similarity_matrix(x, method = "jaccard", ...)
```

Arguments

<code>x</code>	interval-valued data with <code>symbolic_tbl</code> class.
<code>var_name1</code>	the first variable name or column location.
<code>var_name2</code>	the second variable name or column location.
<code>...</code>	additional parameters
<code>method</code>	similarity method for <code>int_similarity_matrix</code> : "jaccard", "dice", or "overlap".

Details

These functions compute various similarity measures:

- `int_jaccard`: Jaccard similarity coefficient
- `int_dice`: Dice similarity coefficient
- `int_cosine`: Cosine similarity
- `int_overlap_coefficient`: Overlap coefficient
- `int_tanimoto`: Tanimoto coefficient (generalized Jaccard)
- `int_similarity_matrix`: Pairwise similarity matrix across all observations

All similarity measures range from 0 (no similarity) to 1 (perfect similarity).

Value

A numeric matrix or value

Author(s)

Han-Ming Wu

See Also

`int_dist` `int_cor` `int_jaccard`

Examples

```
data(mushroom.int)

# Jaccard similarity
int_jaccard(mushroom.int, "Pileus.Cap.Width", "Stipe.Length")

# Dice coefficient
int_dice(mushroom.int, 2, 3)

# Cosine similarity
int_cosine(mushroom.int,
  var_name1 = c("Pileus.Cap.Width"),
  var_name2 = c("Stipe.Length", "Stipe.Thickness"))

# Overlap coefficient
```

```

int_overlap_coefficient(mushroom.int, 2, 3:4)

# Tanimoto coefficient
int_tanimoto(mushroom.int, "Pileus.Cap.Width", "Stipe.Length")

# Similarity matrix across all observations
int_similarity_matrix(mushroom.int, method = "jaccard")

```

interval_stats	<i>Statistics for Interval Data</i>
----------------	-------------------------------------

Description

Functions to compute the mean, variance, covariance, and correlation of interval-valued data.

Usage

```

int_mean(x, var_name, method = "CM", ...)

int_var(x, var_name, method = "CM", ...)

int_cov(x, var_name1, var_name2, method = "CM", ...)

int_cor(x, var_name1, var_name2, method = "CM", ...)

```

Arguments

x	interval-valued data with <code>symbolic_tbl</code> class.
var_name	the variable name or the column location (multiple variables are allowed).
method	methods to calculate statistics: CM (default), VM, QM, SE, FV, EJD, GQ, SPT.
...	additional parameters
var_name1	the variable name or the column location (multiple variables are allowed).
var_name2	the variable name or the column location (multiple variables are allowed).

Details

Available methods (applicable to all four functions):

- CM: Center Method — uses midpoints $(a + b) / 2$
- VM: Vertices Method — uses all 2^p vertex combinations
- QM: Quantiles Method — uses equally spaced quantile points
- SE: Set Expansion — uses endpoints only (quantiles with $m = 1$)
- FV: Fitted Values — uses linear regression fitted values
- EJD: Empirical Joint Distribution
- GQ: Symbolic Covariance method (Billard and Diday, 2006)
- SPT: Total Sum of Products (Billard, 2008)

Value

A numeric matrix for `int_mean` and `int_var` (methods x variables); a named list of covariance/correlation matrices for `int_cov` and `int_cor` (one matrix per method).

Author(s)

Han-Ming Wu

See Also

`int_mean` `int_var` `int_cov` `int_cor`

Examples

```
data(mushroom.int)
int_mean(mushroom.int, var_name = "Pileus.Cap.Width")
int_mean(mushroom.int, var_name = 2:3)

var_name <- c("Stipe.Length", "Stipe.Thickness")
method <- c("CM", "FV", "EJD")
int_mean(mushroom.int, var_name, method)
int_var(mushroom.int, var_name, method)

var_name1 <- "Pileus.Cap.Width"
var_name2 <- c("Stipe.Length", "Stipe.Thickness")
method <- c("CM", "VM", "EJD", "GQ", "SPT")
int_cov(mushroom.int, var_name1, var_name2, method)
int_cor(mushroom.int, var_name1, var_name2, method)
```

interval_uncertainty *Uncertainty and Variability Measures for Interval Data*

Description

Functions to compute uncertainty and variability measures for interval-valued data.

Usage

```
int_entropy(x, var_name, method = "CM", base = 2, ...)

int_cv(x, var_name, method = "CM", ...)

int_dispersion(x, var_name, method = "CM", ...)

int_imprecision(x, var_name, ...)

int_granularity(x, var_name, ...)
```

```
int_uniformity(x, var_name, ...)
```

```
int_information_content(x, var_name, method = "CM", ...)
```

Arguments

<code>x</code>	interval-valued data with <code>symbolic_tbl</code> class.
<code>var_name</code>	the variable name or the column location (multiple variables are allowed).
<code>method</code>	methods to calculate statistics: CM (default), VM, QM, SE, FV, EJD, GQ, SPT.
<code>base</code>	logarithm base for entropy calculation (default: 2)
<code>...</code>	additional parameters

Details

These functions measure uncertainty and variability:

- `int_entropy`: Shannon entropy (information content)
- `int_cv`: Coefficient of variation ($CV = SD / Mean$)
- `int_dispersion`: General dispersion index
- `int_imprecision`: Imprecision based on interval width
- `int_granularity`: Variability in interval sizes
- `int_uniformity`: Uniformity of interval widths (inverse of granularity)
- `int_information_content`: Normalized entropy ($entropy / \log_2(n)$)

Value

A numeric matrix or value

Author(s)

Han-Ming Wu

See Also

`int_var` `int_entropy` `int_cv`

Examples

```
data(mushroom.int)

# Calculate entropy
int_entropy(mushroom.int, var_name = "Pileus.Cap.Width")

# Coefficient of variation
int_cv(mushroom.int, var_name = c("Stipe.Length", "Stipe.Thickness"), method = c("CM", "EJD"))

# Measure imprecision
int_imprecision(mushroom.int, var_name = c("Stipe.Length", "Stipe.Thickness"))
```

```
# Dispersion index
int_dispersion(mushroom.int, var_name = "Pileus.Cap.Width", method = "CM")

# Check data granularity
int_granularity(mushroom.int, var_name = 2:4)

# Check uniformity
int_uniformity(mushroom.int, var_name = 2:3)

# Information content
int_information_content(mushroom.int, var_name = "Stipe.Length", method = "CM")
```

int_convert_format	<i>Convert Interval Data Format</i>
--------------------	-------------------------------------

Description

Automatically detect the format of interval data and convert it to the target format.

Usage

```
int_convert_format(x, to = "MM", from = NULL, ...)
```

Arguments

x	interval data in one of the supported formats
to	target format: "MM", "iGAP", "RSDA", "ARRAY", "SODAS" (default: "MM")
from	source format (optional): "MM", "iGAP", "RSDA", "ARRAY", "SODAS". If NULL, will auto-detect.
...	additional parameters passed to specific conversion functions

Details

This function provides a unified interface for all interval format conversions. It automatically detects the source format (unless specified) and applies the appropriate conversion function.

Supported conversions:

- RSDA ??? MM, iGAP, ARRAY
- MM ??? iGAP, RSDA, ARRAY
- iGAP ??? MM, RSDA, ARRAY
- ARRAY ??? RSDA, MM, iGAP
- SODAS ??? MM, iGAP, ARRAY

Value

Interval data in the target format

Author(s)

Han-Ming Wu

See Also

```
int_detect_format int_list_conversions RSDA_to_MM RSDA_to_ARRAY MM_to_RSDA MM_to_ARRAY
ARRAY_to_RSDA ARRAY_to_MM ARRAY_to_iGAP iGAP_to_MM iGAP_to_RSDA iGAP_to_ARRAY
MM_to_iGAP
```

Examples

```
# Auto-detect and convert to MM
data(mushroom.int)
data_mm <- int_convert_format(mushroom.int, to = "MM")

# Explicitly specify source format
data(abalone.iGAP)
data_mm <- int_convert_format(abalone.iGAP, from = "iGAP", to = "MM")

# Convert MM to iGAP
data_igap <- int_convert_format(data_mm, to = "iGAP")

# Convert multiple datasets to MM
datasets <- list(mushroom.int, abalone.int, car.int)
mm_datasets <- lapply(datasets, int_convert_format, to = "MM")

# Check what conversions are available
int_list_conversions()
```

int_detect_format	<i>Detect Interval Data Format</i>
-------------------	------------------------------------

Description

Automatically detect the format of interval data.

Usage

```
int_detect_format(x)
```

Arguments

x	interval data in unknown format
---	---------------------------------

Details

Detection rules:

- RSDA: has class "symbolic_tbl" and contains complex columns
- MM: data.frame with paired "_min" and "_max" columns
- iGAP: data.frame with columns containing comma-separated values (e.g., "1.2,3.4")
- ARRAY: a 3-dimensional array with `dim[3] = 2` (min/max slices)
- SODAS: character string ending with ".xml" (file path)
- SDS: alias for SODAS

Value

A character string indicating the detected format: "RSDA", "MM", "iGAP", "ARRAY", "SODAS", or "unknown"

Examples

```
data(mushroom.int)
int_detect_format(mushroom.int) # Should return "RSDA"

data(abalone.iGAP)
int_detect_format(abalone.iGAP) # Should return "iGAP"

# ARRAY format
x <- array(1:24, dim = c(4, 3, 2))
int_detect_format(x) # Should return "ARRAY"
```

int_list_conversions *List Available Format Conversions*

Description

List all available format conversion functions.

Usage

```
int_list_conversions(from = NULL, to = NULL)
```

Arguments

from	source format (optional): "RSDA", "MM", "iGAP", "ARRAY", "SODAS"
to	target format (optional): "RSDA", "MM", "iGAP", "ARRAY", "SODAS"

Value

A data.frame showing available conversions

Examples

```
# List all conversions
int_list_conversions()

# List conversions from RSDA
int_list_conversions(from = "RSDA")

# List conversions to MM
int_list_conversions(to = "MM")
```

iris.int	<i>Iris Species Interval Dataset</i>
----------	--------------------------------------

Description

Interval-valued version of the classic iris dataset, aggregated from Fisher’s iris data into 30 interval observations across 3 species (Setosa, Versicolor, Virginica). Each observation represents a group of flowers with ranges for sepal and petal measurements.

Usage

```
data(iris.int)
```

Format

A data frame with 30 observations and 5 variables:

- sepal_length: Sepal length range (cm).
- sepal_width: Sepal width range (cm).
- petal_length: Petal length range (cm).
- petal_width: Petal width range (cm).
- class: Species (Setosa, Versicolor, Virginica).

Metadata

Sample size (n)	30
Variables (p)	5
Subject area	Botany
Symbolic format	Interval
Analytical tasks	Clustering

Source

<https://github.com/Natandradesa/Kernel-Clustering-for-Interval-Data>

References

Andrade de Sa, J. N., Ferreira, M. R. P. and de Carvalho, F. A. T. (2025). Kernel clustering with automatic variable weighting for interval data. *Neurocomputing*, 650, 130849. doi:[10.1016/j.neucom.2025.130849](https://doi.org/10.1016/j.neucom.2025.130849).

Examples

```
data(iris.int)
```

irish_wind.its

Irish Wind Speed Monthly Interval Time Series

Description

Monthly interval-valued wind speed data at 5 meteorological stations in Ireland from January 1961 to December 1978 (216 months). For each month and station, the interval is defined as [minimum daily average wind speed, maximum daily average wind speed] across all days in that month.

Usage

```
data(irish_wind.its)
```

Format

A data frame with 216 observations and 11 columns (5 interval variables in _l/_u Min-Max pairs, plus a date):

- date: First day of the month (Date class).
- BIR_l, BIR_u: Monthly [min, max] daily wind speed at Birr (knots).
- DUB_l, DUB_u: Monthly [min, max] daily wind speed at Dublin Airport (knots).
- KIL_l, KIL_u: Monthly [min, max] daily wind speed at Kilkenny (knots).
- SHA_l, SHA_u: Monthly [min, max] daily wind speed at Shannon Airport (knots).
- VAL_l, VAL_u: Monthly [min, max] daily wind speed at Valentia Observatory (knots).

Details

The original data contains daily average wind speeds (in knots) at 12 synoptic meteorological stations in the Republic of Ireland, collected by the Irish Meteorological Service. This is the classic Haslett and Raftery (1989) dataset, one of the most widely used benchmarks in spatial statistics. Following the approach of Teles and Brito (2015), the raw daily data is aggregated to monthly intervals for 5 selected stations: Birr (BIR), Dublin Airport (DUB), Kilkenny (KIL), Shannon Airport (SHA), and Valentia Observatory (VAL). Each monthly interval captures the range of daily wind variability within that month.

Metadata

Sample size (n)	216
Variables (p)	11
Subject area	Meteorology
Symbolic format	Interval time series (multivariate)
Analytical tasks	Space-time modelling, Forecasting, Clustering

Source

Derived from the wind dataset in the **gstat** R package (originally from Haslett and Raftery, 1989). Daily data aggregated to monthly intervals.

References

Haslett, J. and Raftery, A. E. (1989). Space-time modelling with long-memory dependence: Assessing Ireland's wind power resource. *Journal of the Royal Statistical Society, Series C (Applied Statistics)*, **38**(1), 1–50.

Teles, P. and Brito, P. (2015). Modeling interval time series with space-time processes. *Communications in Statistics – Theory and Methods*, **44**(17), 3599–3627. doi:[10.1080/03610926.2013.782200](https://doi.org/10.1080/03610926.2013.782200).

Examples

```
data(iris_wind.its)
head(iris_wind.its)
# Plot Valentia Observatory wind speed interval
plot(iris_wind.its$date, iris_wind.its$VAL_u, type = "l", col = "red",
     ylab = "Wind speed (knots)", xlab = "Date",
     main = "Valentia Observatory Monthly Wind Speed Interval")
lines(iris_wind.its$date, iris_wind.its$VAL_l, col = "blue")
legend("topright", c("Max", "Min"), col = c("red", "blue"), lty = 1)
```

iris_species.hist	<i>Iris Species Histogram-Valued Dataset</i>
-------------------	--

Description

Histogram-valued dataset of 3 iris species (Versicolor, Virginica, Setosa) with 4 histogram-valued morphological variables and a species label. Each histogram describes the distribution of measurements within a species.

Usage

```
data(iris_species.hist)
```

Format

- A data frame with 3 observations and 5 variables:
- species: Species name (factor: Versicolor, Virginica, Setosa).
 - sepal_width: Histogram-valued sepal width distribution.
 - sepal_length: Histogram-valued sepal length distribution.
 - petal_width: Histogram-valued petal width distribution.
 - petal_length: Histogram-valued petal length distribution.

Row names are species names.

Metadata

Sample size (n)	3
Variables (p)	5
Subject area	Botany
Symbolic format	Histogram
Analytical tasks	Clustering, Descriptive statistics

Source

Billard, L. and Diday, E. (2020), Table 4-10.

References

Billard, L. and Diday, E. (2020). *Clustering Methodology for Symbolic Data*. Wiley, Chichester. Table 4-10.

Examples

```
data(iris_species.hist)
```

joggers.mix	<i>Joggers Mixed Symbolic Dataset</i>
-------------	---------------------------------------

Description

Mixed symbolic dataset of 10 jogger groups with one interval-valued variable (pulse rate) and one histogram-valued variable (running time distribution).

Usage

```
data(joggers.mix)
```

Format

A symbolic data frame (`symbolic_tbl`) with 10 observations (jogger groups) and 2 variables:

- `pulse_rate`: Interval-valued resting pulse rate range (bpm).
- `running_time`: Histogram-valued distribution of running times (minutes).

Row names are `Group_1` through `Group_10`.

Metadata

Sample size (n)	10
Variables (p)	2
Subject area	Sports
Symbolic format	Mixed (interval, histogram)
Analytical tasks	Clustering

Source

Billard, L. and Diday, E. (2020), Table 2-5.

References

Billard, L. and Diday, E. (2020). *Clustering Methodology for Symbolic Data*. Wiley, Chichester. Table 2-5.

Examples

```
data(joggers.mix)
```

`judge1.int`

Judge 1 Interval-Valued Ratings

Description

Simulated interval-valued agricultural-product grades assigned by Judge 1 for 6 regions on 4 variables, distributed with the GPCSIV package.

Usage

```
data(judge1.int)
```

Format

A symbolic data frame (`symbolic_tbl`) with 6 observations and 4 interval-valued variables (`V1–V4`).

Metadata

Sample size (n)	6
Variables (p)	4
Subject area	Methodology
Symbolic format	Interval
Analytical tasks	PCA

Source

Simulated data distributed as GPCSIV: : Judge1.

References

Makosso-Kallyth, S. (2013). Analysis of m sets of symbolic interval variables. *Revue des Nouvelles Technologies de l'Information*, RNTI-E-25, 97–108.

Examples

```
data(judge1.int)
```

judge2.int

Judge 2 Interval-Valued Ratings

Description

Simulated interval-valued agricultural-product grades assigned by Judge 2 for 6 regions on 4 variables, distributed with the GPCSIV package.

Usage

```
data(judge2.int)
```

Format

A symbolic data frame (symbolic_tbl) with 6 observations and 4 interval-valued variables (V1–V4).

Metadata

Sample size (n)	6
Variables (p)	4
Subject area	Methodology
Symbolic format	Interval
Analytical tasks	PCA

Source

Simulated data distributed as GPCSIV: : Judge2.

References

Makosso-Kallyth, S. (2013). Analysis of m sets of symbolic interval variables. *Revue des Nouvelles Technologies de l'Information*, RNTI-E-25, 97–108.

Examples

```
data(judge2.int)
```

judge3.int

Judge 3 Interval-Valued Ratings

Description

Simulated interval-valued agricultural-product grades assigned by Judge 3 for 6 regions on 4 variables, distributed with the GPCSIV package.

Usage

```
data(judge3.int)
```

Format

A symbolic data frame (symbolic_tbl) with 6 observations and 4 interval-valued variables (V1–V4).

Metadata

Sample size (n)	6
Variables (p)	4
Subject area	Methodology
Symbolic format	Interval
Analytical tasks	PCA

Source

Simulated data distributed as GPCSIV: : Judge3.

References

Makosso-Kallyth, S. (2013). Analysis of m sets of symbolic interval variables. *Revue des Nouvelles Technologies de l'Information*, RNTI-E-25, 97–108.

Examples

```
data(judge3.int)
```

lackinfo.int

Lack of Information Questionnaire Interval Dataset

Description

Interval-valued dataset from a lack-of-information questionnaire. Contains biographical data and responses to 5 items measuring perception of lack of information, collected via an interval-valued Likert scale.

Usage

```
data(lackinfo.int)
```

Format

A data frame with 50 observations and 8 variables:

- `id`: Identification number.
- `sex`: Sex of the respondent (male or female).
- `age`: Respondent's age (in years).
- `item1`: Interval-valued answer to item 1.
- `item2`: Interval-valued answer to item 2.
- `item3`: Interval-valued answer to item 3.
- `item4`: Interval-valued answer to item 4.
- `item5`: Interval-valued answer to item 5.

Details

An educational innovation project was carried out for improving teaching-learning processes at the University of Oviedo (Spain) for the 2020/2021 academic year. A total of 50 students answered an online questionnaire about biographical data (sex and age) and their perception of lack of information by selecting the interval that best represents their level of agreement on a scale bounded between 1 (strongly disagree) and 7 (strongly agree).

The 5 items measuring perception of lack of information are:

- I1: I receive too little information from my classmates.
- I2: It is difficult to receive relevant information from my classmates.
- I3: It is difficult to receive relevant information from the teacher.
- I4: The amount of information I receive from my classmates is very low.
- I5: The amount of information I receive from the teacher is very low.

Metadata

Sample size (n)	50
Variables (p)	8
Subject area	Education
Symbolic format	Interval
Analytical tasks	Descriptive statistics, Regression

Source

IntervalQuestionStat::lackinfo; responses were collected from 50 University of Oviedo students during the 2020/2021 academic year, as documented by the upstream package.

References

Garcia-Garcia, J. (2022). *IntervalQuestionStat: Tools to Deal with Interval-Valued Responses in Questionnaires*. R package. doi:[10.32614/CRAN.package.IntervalQuestionStat](https://doi.org/10.32614/CRAN.package.IntervalQuestionStat).

Examples

```
data(lackinfo.int)
```

```
lisbon_air_quality.int
```

Lisbon Air Quality Daily Interval Dataset

Description

Interval-valued daily air quality data from the Entrecampos monitoring station in Lisbon, Portugal, covering 2019–2021 (1096 days). Each day's pollutant concentration is represented as a [min, max] interval from hourly measurements. Missing days are imputed via linear interpolation.

Usage

```
data(lisbon_air_quality.int)
```

Format

A symbolic data frame (symbolic_tbl) with 1096 observations (daily) and 8 interval-valued pollutant variables:

- so2: Sulphur dioxide (ug/m3).
- pm10: Particulate matter < 10 um (ug/m3).
- o3: Ozone (ug/m3).
- no2: Nitrogen dioxide (ug/m3).

- co: Carbon monoxide (ug/m3).
- pm25: Particulate matter < 2.5 um (ug/m3).
- nox: Nitrogen oxides (ug/m3).
- no: Nitric oxide (ug/m3).

Metadata

Sample size (n)	1096
Variables (p)	8
Subject area	Environment
Symbolic format	Interval
Analytical tasks	Regression, Time series

Source

Hourly measurements from the QualAr Portuguese air-quality monitoring network, operated by the Portuguese Environment Agency, at the Entrecampos station in Lisbon, Portugal. Daily intervals were constructed from hourly measurements as described by Loureiro et al. (2025).

References

Loureiro, C. P., Oliveira, M. R., Brito, P. and Oliveira, L. (2025). Air Quality Data Analysis with Symbolic Principal Components. In *New Frontiers in Statistics and Data Science – SPE2023*, Springer Proceedings in Mathematics and Statistics, 469, 335–348. doi:10.1007/978303168949-9_25.

Examples

```
data(lisbon_air_quality.int)
```

loans_by_purpose.int	<i>Loans by Purpose Interval Dataset</i>
----------------------	--

Description

Interval-valued data for loan characteristics aggregated by their purpose. Original microdata contains 887,383 loan records from Kaggle.

Usage

```
data(loans_by_purpose.int)
```

Format

A data frame with 14 observations and 4 interval-valued variables:

- `ln_inc`: Natural logarithm of self-reported annual income.
- `ln_revolbal`: Natural logarithm of total credit revolving balance.
- `open_acc`: Number of open credit lines.
- `total_acc`: Total number of credit lines.

Metadata

Sample size (n)	14
Variables (p)	4
Subject area	Finance
Symbolic format	Interval
Analytical tasks	Descriptive statistics, Clustering

Source

Derived from `MAINT.Data::LoansbyPurpose_minmaxDt`, which aggregates the Lending Club Loan Data by loan purpose using minima and maxima. The underlying Lending Club Loan Data were distributed through the Kaggle Data Science platform; the original upstream URL is no longer active.

References

Duarte Silva, A. P., Brito, P., Filzmoser, P. and Dias, J. G. (2021). MAINT.Data: Modelling and Analysing Interval Data in R. *The R Journal*, 13(2), 336–364. doi:[10.32614/RJ2021074](https://doi.org/10.32614/RJ2021074).

The underlying loan records were distributed as the Lending Club Loan Data on Kaggle.

Examples

```
data(loans_by_purpose.int)
```

<code>loans_by_risk.int</code>	<i>Lending Club Loans by Risk Level</i>
--------------------------------	---

Description

Interval-valued dataset of 35 Lending Club loan groups classified by risk level (A through G, 5 groups each). Each group is described by 4 interval-valued financial variables.

Usage

```
data(loans_by_risk.int)
```

Format

A symbolic data frame (symbolic_tbl) with 35 observations and 5 variables:

- log_income: Interval-valued log annual income.
- interest_rate: Interval-valued interest rate (%).
- open_accounts: Interval-valued number of open credit accounts.
- total_accounts: Interval-valued total number of credit accounts.
- risk_level: Risk grade factor (A, B, C, D, E, F, G).

Row names are A1–A5, B1–B5, ..., G1–G5.

Metadata

Sample size (n)	35
Variables (p)	5
Subject area	Finance
Symbolic format	Interval
Analytical tasks	Classification, Clustering

Source

Derived from MAINT.Data::LoansbyRiskLvs_minmaxDt, based on the Lending Club Loan Data distributed through the Kaggle Data Science platform; the original upstream URL is no longer active.

References

Duarte Silva, A. P., Brito, P., Filzmoser, P. and Dias, J. G. (2021). MAINT.Data: Modelling and Analysing Interval Data in R. *The R Journal*, 13(2), 336–364. doi:[10.32614/RJ2021074](https://doi.org/10.32614/RJ2021074).

Examples

```
data(loans_by_risk.int)
```

loans_by_risk_quantile.int

Lending Club Loans by Risk Level (Quantile-Based Intervals)

Description

Interval-valued dataset of 35 Lending Club loan groups stratified by risk level (A1–G5). Intervals represent the 10th to 90th percentile range of each financial variable within each risk subgrade.

Usage

```
data(loans_by_risk_quantile.int)
```

Format

A symbolic data frame (symbolic_tbl) with 35 observations and 4 variables:

- `ln-inc`: Interval-valued log income.
- `int-rate`: Interval-valued interest rate.
- `open-acc`: Interval-valued number of open accounts.
- `total-acc`: Interval-valued total accounts.

Metadata

Sample size (n)	35
Variables (p)	4
Subject area	Finance
Symbolic format	Interval
Analytical tasks	Classification, Clustering

Source

Derived from `MAINT.Data: :LoansbyRiskLvs_qnt1Dt`, based on the Lending Club Loan Data distributed through the Kaggle Data Science platform; the original upstream URL is no longer active.

References

Duarte Silva, A. P., Brito, P., Filzmoser, P. and Dias, J. G. (2021). MAINT.Data: Modelling and Analysing Interval Data in R. *The R Journal*, 13(2), 336–364. doi:[10.32614/RJ2021074](https://doi.org/10.32614/RJ2021074).

Examples

```
data(loans_by_risk_quantile.int)
```

<code>lung_cancer.hist</code>	<i>Lung Cancer Treatments by State Histogram-Valued Dataset</i>
-------------------------------	---

Description

Histogram-valued distribution of lung cancer treatment counts for 2 US states (Massachusetts and New York).

Usage

```
data(lung_cancer.hist)
```

Format

A data frame with 2 observations and 2 variables:

- state: State name (character).
- y30: Histogram-valued distribution of treatment counts as a weighted set string (e.g., "{0, 0.77; 1, 0.08; 2, 0.15}").

Metadata

Sample size (n)	2
Variables (p)	2
Subject area	Medical
Symbolic format	Histogram
Analytical tasks	Descriptive statistics

Source

Billard and Diday (2006), Table 2.20.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley. Table 2.20.

Examples

```
data(lung_cancer.hist)
```

lynne1.int	<i>Lynne1 Blood Pressure Interval Dataset</i>
------------	---

Description

Interval-valued dataset of 10 observations with pulse rate, systolic pressure, and diastolic pressure intervals.

Usage

```
data(lynne1.int)
```

Format

A symbolic data frame (symbolic_tbl) with 10 observations and 4 variables:

- concept: Character concept label.
- Pulse Rate: Interval-valued pulse rate (beats/min).
- Systolic Pressure: Interval-valued systolic pressure (mmHg).
- Diastolic Pressure: Interval-valued diastolic pressure (mmHg).

Metadata

Sample size (n)	10
Variables (p)	4
Subject area	Medical
Symbolic format	Interval
Analytical tasks	Descriptive statistics, Regression

Source

RSDA::lynne1.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis: Conceptual Statistics and Data Mining*. Wiley, Chichester.

Original data from the RSDA R package (lynne1 dataset).

Examples

```
data(lynne1.int)
```

merval.its

MERVAL Index Weekly Min/Max Interval Time Series

Description

Weekly minimum and maximum values of the Argentine MERVAL stock market index from January 4, 2016 to September 28, 2020 (248 weeks). Daily data was downloaded and aggregated to weekly intervals. This dataset matches the period used by de Carvalho and Martos (2022).

Usage

```
data(merval.its)
```

Format

A data frame with 248 observations and 3 variables:

- date: Week start date, Monday (Date class).
- low: Weekly minimum of daily low values.
- high: Weekly maximum of daily high values.

Details

The Merval (Mercado de Valores de Buenos Aires) is the main stock market index of the Buenos Aires Stock Exchange. Each observation represents one week, with the weekly low computed as the minimum of daily lows and the weekly high computed as the maximum of daily highs. The date column indicates the Monday (start) of each week. This period covers the Argentine economic crisis and the early COVID-19 pandemic impact.

Metadata

Sample size (n)	248
Variables (p)	3 (date, low, high)
Subject area	Finance
Symbolic format	Interval time series (weekly aggregation)
Analytical tasks	Forecasting, Time series analysis

Source

Yahoo Finance, ticker ^MERY, January 1, 2016–September 30, 2020. Downloaded via **quantmod** and aggregated by week using the minimum daily low and maximum daily high; the original retrieval date was not recorded.

References

de Carvalho, F. A. T. and Martos, G. (2022). Modeling interval trendlines: Symbolic singular spectrum analysis for interval time series. *Journal of Forecasting*, **41**(1), 167–180. doi:10.1002/for.2801.

Examples

```
data(merval.its)
head(merval.its)
plot(merval.its$date, merval.its$high, type = "l", col = "red",
      ylab = "Index Value", xlab = "Date",
      main = "Merval Weekly Min/Max (2016-2020)")
lines(merval.its$date, merval.its$low, col = "blue")
legend("topleft", c("High", "Low"), col = c("red", "blue"), lty = 1)
```

MM_to_ARRAY

MM to ARRAY

Description

Convert MM format (paired _min/_max columns) to a 3-dimensional array [n, p, 2].

Usage

```
MM_to_ARRAY(data)
```

Arguments

`data` A data.frame in MM format with paired `_min` and `_max` columns.

Value

A numeric array of dimension `[n, p, 2]` with dimnames. Non-interval columns are excluded.

Examples

```
data(mushroom.int)
mm <- RSDA_to_MM(mushroom.int, RSDA = FALSE)
arr <- MM_to_ARRAY(mm)
dim(arr)
```

`MM_to_iGAP`*MM to iGAP*

Description

To convert MM format to iGAP format.

Usage

```
MM_to_iGAP(data)
```

Arguments

`data` The dataframe with the MM format.

Value

Return a dataframe with the iGAP format.

Examples

```
data(face.iGAP)
face <- iGAP_to_MM(face.iGAP, 1:6)
MM_to_iGAP(face)
```

MM_to_RSDA	<i>MM to RSDA</i>
------------	-------------------

Description

To convert MM format interval dataframe to RSDA format (symbolic_tbl).

Usage

```
MM_to_RSDA(data)
```

Arguments

data The dataframe with the MM format (paired _min/_max columns).

Value

Return a symbolic_tbl dataframe with complex-encoded interval columns.

Examples

```
data(mushroom.int)
mm <- RSDA_to_MM(mushroom.int, RSDA = FALSE)
rsda <- MM_to_RSDA(mm)
```

mtcars.mix	<i>Motor Trend Cars Mixed Symbolic Dataset</i>
------------	--

Description

Mixed symbolic dataset of 5 car groups from the mtcars data, with 7 interval-valued performance variables and 4 modal-valued categorical variables.

Usage

```
data(mtcars.mix)
```

Format

A symbolic data frame (symbolic_tbl) with 5 observations (car groups) and 11 variables:

- mpg: Interval-valued miles per gallon.
- cyl: Modal-valued number of cylinders.
- disp: Interval-valued displacement (cu.in.).
- hp: Interval-valued horsepower.

- drat: Interval-valued rear axle ratio.
- wt: Interval-valued weight (1000 lbs).
- qsec: Interval-valued quarter-mile time (seconds).
- vs: Modal-valued engine type (V/S).
- am: Modal-valued transmission type (auto/manual).
- gear: Modal-valued number of forward gears.
- carb: Modal-valued number of carburetors.

Metadata

Sample size (n)	5
Variables (p)	11
Subject area	Automotive
Symbolic format	Mixed (interval, modal)
Analytical tasks	Descriptive statistics, Clustering

Source

ggInterval R package (mtcars.i dataset).

References

Henderson, R. and Velleman, P. (1981). Building multiple regression models interactively. *Biometrics*, 37, 391–411.

Original data from the ggInterval R package (mtcars.i dataset).

Examples

```
data(mtcars.mix)
```

mushroom.int	<i>Mushroom Species Interval Dataset</i>
--------------	--

Description

Interval-valued version of the mushroom dataset. See [mushroom.int.mm](#).

Usage

```
data(mushroom.int)
```

Format

A symbolic data frame (symbolic_tbl) with 23 observations and 5 variables:

- Species: Mushroom species name (character).
- Pileus.Cap.Width: Pileus cap width range (cm, interval).
- Stipe.Length: Stipe length range (cm, interval).
- Stipe.Thickness: Stipe thickness range (cm, interval).
- Edibility: Edibility code (U = Unknown, Y = Yes, N = No, T = Toxic; character).

Metadata

Sample size (n)	23
Variables (p)	5
Subject area	Biology
Symbolic format	Interval
Analytical tasks	Clustering, Descriptive statistics

Source

Billard and Diday (2006), Table 3.2.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley. Table 3.2.

Examples

```
data(mushroom.int)
```

mushroom.int.mm

Mushroom Species Dataset (Original Format)

Description

Interval-valued data for 23 mushroom species of the genus *Agaricus* with 3 morphological measurements from the Fungi of California Species.

Usage

```
data(mushroom.int.mm)
```

Format

A data frame with 23 observations and 5 variables:

- Species: Mushroom species name.
- Pileus.Cap.Width: Pileus cap width range (cm).
- Stipe.Length: Stipe length range (cm).
- Stipe.Thickness: Stipe thickness range (cm).
- Edibility: Edibility code (U/Y/N/T).

Details

Classic SDA dataset used for descriptive statistics, histogram construction, and clustering of interval-valued data.

Metadata

Sample size (n)	23
Variables (p)	5
Subject area	Biology
Symbolic format	Interval
Analytical tasks	Clustering, Descriptive statistics

Source

Billard, L. and Diday, E. (2006), Table 3.2.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis: Conceptual Statistics and Data Mining*. Wiley, Chichester. Table 3.2.

Examples

```
data(mushroom.int.mm)
```

mushroom_fuzzy.mix	<i>Mushroom Species Fuzzy/Symbolic Dataset</i>
--------------------	--

Description

Extended mushroom data with fuzzy stipe thickness (Small/Average/Large), numerical stipe length, interval cap size, and categorical cap colour for two Amanita species (4 specimens).

Usage

```
data(mushroom_fuzzy.mix)
```

Format

A data frame with 4 observations (Mushroom1–Mushroom4) and 9 variables:

- specimen: Specimen identifier (character).
- species: Species name (character).
- stipe_thickness: Stipe thickness measurement (numeric, cm).
- fuzzy_small: Fuzzy membership degree for Small (numeric, 0–1).
- fuzzy_average: Fuzzy membership degree for Average (numeric, 0–1).
- fuzzy_large: Fuzzy membership degree for Large (numeric, 0–1).
- stipe_length: Stipe length (numeric, cm).
- cap_size: Cap size as interval string (e.g., "24 +/- 1", character).
- cap_colour: Cap colour (character).

Metadata

Sample size (n)	4
Variables (p)	9
Subject area	Biology
Symbolic format	Fuzzy
Analytical tasks	Descriptive statistics

Source

Diday and Noirhomme-Fraiture (2008), Tables 1.14–1.16.

References

Diday, E. and Noirhomme-Fraiture, M. (Eds.) (2008). *Symbolic Data Analysis and the SODAS Software*. Wiley. Tables 1.14-1.16.

Examples

```
data(mushroom_fuzzy.mix)
```

nycflights.int

New York City Flights Interval Dataset

Description

Interval-valued dataset with 142 units and four interval-valued variables from the nycflights13 package, aggregated by month and carrier.

Usage

```
data(nycflights.int)
```

Format

A symbolic data frame (symbolic_tbl) with 142 observations and 5 variables:

- X: Month-carrier identifier (character).
- dep_delay: Departure delay range (minutes, interval).
- arr_delay: Arrival delay range (minutes, interval).
- air_time: Air time range (minutes, interval).
- distance: Distance range (miles, interval).

Metadata

Sample size (n)	142
Variables (p)	5
Subject area	Transportation
Symbolic format	Interval
Analytical tasks	Regression, Descriptive statistics

Source

Derived from MAINT.Data::FlightsIdt. The upstream object removes incomplete rows from **nycflights13** and aggregates flights by month and carrier using the 0.05 and 0.95 quantiles.

References

Duarte Silva, A. P., Brito, P., Filzmoser, P. and Dias, J. G. (2021). MAINT.Data: Modelling and Analysing Interval Data in R. *The R Journal*, 13(2), 336–364. doi:[10.32614/RJ2021074](https://doi.org/10.32614/RJ2021074).

Examples

```
data(nycflights.int)
```

occupations.modal	<i>Occupation Salaries Dataset</i>
-------------------	------------------------------------

Description

Modal-valued dataset of 9 occupations with gender and salary distributions. This is the wide (flat table) format; see [occupations2.modal](#) for the modal-valued version.

Usage

```
data(occupations.modal)
```

Format

A data frame with 9 observations and 11 columns:

- Occupation: Occupation name (character).
- Gender(M), Gender(F): Proportion male/female (2 bins).
- Salary(1) through Salary(7): Salary distribution across 7 ordered bins (proportions).
- n: Sample size (integer).

Metadata

Sample size (n)	9
Variables (p)	11
Subject area	Sociology
Symbolic format	Modal
Analytical tasks	Descriptive statistics, Clustering

Source

Billard and Diday (2006).

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley.

Examples

```
data(occupations.modal)
```

occupations2.modal	<i>Occupation Salaries Modal-Valued Dataset</i>
--------------------	---

Description

Modal-valued version of the occupation salaries dataset. See [occupations.modal](#) for the wide-format version.

Usage

```
data(occupations2.modal)
```

Format

A symbolic data frame (`symbolic_tbl`) with 9 observations and 4 variables:

- Occupation: Occupation name (character).
- Gender: Modal distribution over gender (Male, Female).
- Salary: Modal distribution over 7 ordered salary bins.
- n: Sample size (numeric).

Metadata

Sample size (n)	9
Variables (p)	4
Subject area	Sociology
Symbolic format	Modal
Analytical tasks	Descriptive statistics, Clustering

Source

Billard and Diday (2006).

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley.

Examples

```
data(occupations2.modal)
```

ohtemp.int	<i>Ohio River Basin 30-Year Trimmed Mean Daily Temperatures Interval Dataset</i>
------------	--

Description

Interval-valued dataset of 30-year trimmed mean daily temperatures for the Ohio river basin. Intervals are defined by the mean daily maximum and minimum temperatures from January 1, 1988 to December 31, 2018.

Usage

`data(ohtemp.int)`

Format

A data frame with 161 rows and 7 variables:

- ID: Global Historical Climatological Network (GHCN) station identifier.
- NAME: GHCN station name.
- STATE: Two-digit state designation.
- LATITUDE: Latitude coordinate position.
- LONGITUDE: Longitude coordinate position.
- ELEVATION: Elevation of the measurement location (meters).
- TEMPERATURE: 30-year mean daily temperature (tenths of degrees Celsius).

Metadata

Sample size (n)	161
Variables (p)	7
Subject area	Climate
Symbolic format	Interval
Analytical tasks	Regression, Spatial analysis

Source

`intkrige::ohtemp`, derived from NOAA Global Historical Climatology Network station records for January 1, 1988–December 31, 2018.

References

Bean, B. (2025). *intkrige: A Numerical Implementation of Interval-Valued Kriging*. R package. [doi:10.32614/CRAN.package.intkrige](https://doi.org/10.32614/CRAN.package.intkrige).

Examples

```
data(ohtemp.int)
```

oils.int

*Oils and Fats Interval Dataset***Description**

Classic benchmark interval-valued data for 8 oils and fats described by 4 physico-chemical properties. Originally from Ichino (1988).

Usage

```
data(oils.int)
```

Format

A data frame with 8 observations and 9 columns (4 interval variables in _l/_u Min-Max pairs, plus a label):

- sample: Oil/fat sample name (character).
- specific_gravity_l, specific_gravity_u: Specific gravity range.
- freezing_point_l, freezing_point_u: Freezing point range (degrees Celsius).
- iodine_value_l, iodine_value_u: Iodine value range.
- saponification_value_l, saponification_value_u: Saponification value range.

Details

The 8 samples are: Linseed oil, Perilla oil, Cottonseed oil, Sesame oil, Camellia oil, Olive oil, Beef tallow, Hog fat. The expected 3-cluster structure is: {Beef tallow, Hog fat}, {Cottonseed, Sesame, Camellia, Olive}, and {Linseed, Perilla}. Widely used for comparing clustering methods and distance measures in symbolic data analysis.

Metadata

Sample size (n)	8
Variables (p)	9
Subject area	Chemistry
Symbolic format	Interval
Analytical tasks	Clustering

Source

Diday and Noirhomme-Fraiture (2008), Table 13.7; also distributed as RSDA::oils.

References

- Ichino, M. (1988). General metrics for mixed features. *Proc. IEEE Conf. Systems, Man, and Cybernetics*, pp. 494-497.
- Diday, E. and Noirhomme-Fraiture, M. (Eds.) (2008). *Symbolic Data Analysis and the SODAS Software*. Wiley. Table 13.7, p.253.

Examples

```
data(oils.int)
```

ozone.hist

Ozone Air Quality Histogram-Valued Dataset

Description

Histogram-valued dataset for 84 U.S. air-quality monitoring stations with 4 weather-related histogram variables. Each histogram has 10 equal-probability (decile) bins.

Usage

```
data(ozone.hist)
```

Format

A data frame with 84 observations (stations) and 4 histogram-valued variables:

- `Ozone.Conc.ppb`: Histogram of ozone concentration (ppb).
- `Temperature.C`: Histogram of temperature (Celsius).
- `Solar.Radiation.WattM2`: Histogram of solar radiation (W/m^2).
- `Wind.Speed.mSec`: Histogram of wind speed (m/s).

Row names are I1 through I84.

Metadata

Sample size (n)	84
Variables (p)	4
Subject area	Environment
Symbolic format	Histogram
Analytical tasks	Regression, Clustering

Source

Derived from HistDAWass::OzoneH, which documents 84 U.S. monitoring stations and identifies EPA CASTNET/metdata as the source. The original 100 quantile bins were reduced to 10 decile bins here.

References

U.S. Environmental Protection Agency. Clean Air Status and Trends Network (CASTNET) ozone and associated meteorological data.

Examples

```
data(ozone.hist)
```

petrobras.its

Petrobras Stock Daily High/Low Interval Time Series

Description

Daily high and low stock prices of Petrobras (ADR traded on NYSE) from January 3, 2005 to December 29, 2006 (503 trading days). Maia, de Carvalho and Ludermir (2008) provide related interval time-series methodology; this object is specifically the independently downloaded NYSE Petrobras ADR.

Usage

```
data(petrobras.its)
```

Format

A data frame with 503 observations and 3 variables:

- date: Trading date (Date class).
- low: Daily low price (USD).
- high: Daily high price (USD).

Details

Petrobras (Petroleo Brasileiro S.A.) is the Brazilian multinational petroleum corporation. The ADR (American Depositary Receipt) is traded on the New York Stock Exchange under ticker PBR. Each observation represents a trading day with the daily low and high prices forming an interval. This was one of the first datasets used to demonstrate interval-valued autoregressive (iAR) models.

Metadata

Sample size (n)	503
Variables (p)	3 (date, low, high)
Subject area	Finance
Symbolic format	Interval time series
Analytical tasks	Forecasting, Time series analysis

Source

Yahoo Finance, NYSE ADR ticker PBR, January 3, 2005–December 29, 2006. The Yahoo Low and High fields were retained after download via **quantmod**; the original retrieval date was not recorded.

References

Maia, A. L. S., de Carvalho, F. A. T. and Ludermir, T. B. (2008). Forecasting models for interval-valued time series. *Neurocomputing*, **71**(16–18), 3344–3352. doi:10.1016/j.neucom.2008.02.022.

Examples

```
data(petrobras.its)
head(petrobras.its)
plot(petrobras.its$date, petrobras.its$high, type = "l", col = "red",
      ylab = "Price (USD)", xlab = "Date",
      main = "Petrobras Daily High/Low (2005-2006)")
lines(petrobras.its$date, petrobras.its$low, col = "blue")
legend("topleft", c("High", "Low"), col = c("red", "blue"), lty = 1)
```

polish_cars.mix	<i>Polish Car Models Mixed Symbolic Dataset</i>
-----------------	---

Description

Mixed symbolic dataset of 30 car models sold in Poland, with 9 interval-valued technical specification variables and 3 multinomial-valued categorical variables.

Usage

```
data(polish_cars.mix)
```

Format

A symbolic data frame (symbolic_tbl) with 30 observations and 12 variables:

- price: Interval-valued price (PLN).
- body: Multinomial body types (e.g., hatchback, sedan, combi).
- wheelbase: Interval-valued wheelbase (mm).
- chassis_length: Interval-valued chassis length (mm).
- chassis_width: Interval-valued chassis width (mm).
- chassis_height: Interval-valued chassis height (mm).
- engine_capacity: Multinomial engine displacement categories (litres).
- engine_power: Interval-valued engine power (HP).
- maximum_speed: Interval-valued maximum speed (km/h).
- acceleration: Interval-valued 0–100 km/h time (seconds).
- fuel_type: Multinomial fuel types (petrol, diesel, LPG).
- fuel_consumption: Interval-valued fuel consumption (L/100km).

Metadata

Sample size (n)	30
Variables (p)	12
Subject area	Automotive
Symbolic format	Mixed (interval, multinomial)
Analytical tasks	Clustering, Descriptive statistics

Source

symbolicDA::cars; the upstream documentation states that the data were collected from authorized Polish car-dealer websites for the Polish market in 2010.

References

Dudek, A., Pelka, M., Wilk, J. and Walesiak, M. *symbolicDA: Analysis of Symbolic Data*. R package. doi:10.32614/CRAN.package.symbolicDA.

Examples

```
data(polish_cars.mix)
```

polish_voivodships.int

Polish Voivodships Socio-Economic Intervals

Description

Interval-valued dataset of 18 Polish voivodships (administrative regions) with 9 socio-economic interval variables describing demographic and economic characteristics at the county (powiat) level.

Usage

```
data(polish_voivodships.int)
```

Format

A symbolic data frame (symbolic_tbl) with 18 observations (voivodships) and 9 interval-valued variables:

- V1 through V9: Interval-valued socio-economic indicators aggregated across counties within each voivodship.

Row names are voivodship names (e.g., Dolnoslaskie, Lubelskie).

Metadata

Sample size (n)	18
Variables (p)	9
Subject area	Socioeconomics
Symbolic format	Interval
Analytical tasks	Clustering

Source

clusterSim::data_symbolic_interval_polish_voivodships. The data were aggregated by voivodship from the Polish Central Statistical Office Local Data Bank for 2016.

References

Walesiak, M. and Dudek, A. (2020). The choice of variable normalization method in cluster analysis. In K. S. Soliman (Ed.), *Education Excellence and Innovation Management: A 2025 Vision to Sustain Economic Development During Global Challenges*, 325–340.

Examples

```
data(polish_voivodships.int)
```

profession.int	<i>Profession Work Salary Time Interval Dataset</i>
----------------	---

Description

Interval-valued data for 15 profession entries classified by work type (White Collar / Blue Collar). Each entry describes a specific profession with salary and working duration ranges.

Usage

```
data(profession.int)
```

Format

A symbolic data frame (symbolic_tbl) with 15 observations and 4 variables:

- Type_of_Work: Work category (White Collar or Blue Collar, character).
- Profession: Profession name (character).
- Salary: Salary range (currency units, interval).
- Duration: Working duration range (hours per week, interval).

Metadata

Sample size (n)	15
Variables (p)	4
Subject area	Sociology
Symbolic format	Interval
Analytical tasks	Descriptive statistics, Classification

Source

Billard and Diday (2006).

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley.

Examples

```
data(profession.int)
```

prostate.int

*Prostate Cancer Clinical Interval Dataset***Description**

Interval-valued clinical measurements for 97 prostate cancer patients (training and test sets combined). Contains 9 interval-valued variables from log-transformed cancer volume, weight, age, and other clinical predictors.

Usage

```
data(prostate.int)
```

Format

A data frame with 97 observations and 9 interval-valued variables:

- lcavol: Log cancer volume range.
- lweight: Log prostate weight range.
- age: Patient age range.
- lbph: Log benign prostatic hyperplasia amount range.
- svi: Seminal vesicle invasion range.
- lcp: Log capsular penetration range.
- gleason: Gleason score range.
- pgg45: Percentage Gleason scores 4 or 5 range.
- lpsa: Log prostate specific antigen range.

Metadata

Sample size (n)	97
Variables (p)	9
Subject area	Medical
Symbolic format	Interval
Analytical tasks	Regression

Source

Extracted from RSDA package (int_prost_train, int_prost_test).

References

Stamey, T. et al. (1989). Prostate specific antigen in the diagnosis and treatment of adenocarcinoma of the prostate. II. Radical prostatectomy treated patients. *J. Urology*, 141(5), 1076-1083.

Examples

```
data(prostate.int)
```

read_symbolic_csv	<i>Read a Symbolic Data CSV File</i>
-------------------	--------------------------------------

Description

Reads an external CSV file containing symbolic data, automatically detects whether the data is interval-valued (min/max pairs or comma-separated), histogram-valued, modal-valued, or another symbolic type, and returns an appropriate R object.

Usage

```
read_symbolic_csv(
  file,
  sep = ",",
  header = TRUE,
  row.names = NULL,
  stringsAsFactors = FALSE,
  na.strings = c("", "NA"),
  symbolic_type = NULL,
  ...
)
```

Arguments

file	Path to the CSV file to read.
sep	Field separator character. Default ",".
header	Logical; does the first row contain column names? Default TRUE.
row.names	Column number or character string giving row names. Passed to read.table . Default NULL (automatic).
stringsAsFactors	Logical; should character columns be converted to factors? Default FALSE.
na.strings	Character vector of strings to interpret as NA. Default c("", "NA").
symbolic_type	Optional character string to override automatic type detection. One of "interval", "histogram", "modal", or "other". When NULL (the default) the type is detected automatically.
...	Additional arguments passed to read.table .

Details

The detection heuristic works as follows:

1. **Interval (MM)**: If the file contains paired `_min/_max` columns the data is returned as-is (MM format).
2. **Interval (iGAP)**: If one or more character columns contain comma-separated numeric pairs (e.g., "1.2, 3.4") they are expanded into `_min/_max` column pairs and the result is returned in MM format.
3. **Histogram / Modal**: If columns follow a `VarName(bin)` naming pattern (e.g., `Crime(violent)`) and the proportions within each variable group sum to approximately 1, the data is classified as histogram or modal. It is returned as a plain `data.frame`.
4. **Other**: If none of the above patterns match, the data is returned as a plain `data.frame`.

Value

A `data.frame`. Interval data is returned in MM format (paired `_min/_max` columns). All other symbolic types are returned as plain data frames.

See Also

[write_symbolic_csv](#), [int_detect_format](#), [int_convert_format](#)

Examples

```
# Write then read back an interval dataset
data(mushroom.int.mm)
tmp <- tempfile(fileext = ".csv")
write_symbolic_csv(mushroom.int.mm, tmp)
df <- read_symbolic_csv(tmp)
head(df)

# Write then read back a histogram dataset
data(airline_flights.hist)
tmp2 <- tempfile(fileext = ".csv")
write_symbolic_csv(airline_flights.hist, tmp2)
df2 <- read_symbolic_csv(tmp2)
head(df2)
```

RSDA_format

RSDA Format

Description

This function changes the format of the data to conform to RSDA format.

Usage

```
RSDA_format(data, sym_type1 = NULL, location = NULL, sym_type2 = NULL, var = NULL)
```

Arguments

data	A conventional data.
sym_type1	The labels I means an interval variable and \$\$ means set variable.
location	The location of the sym_type in the data.
sym_type2	The labels I means an interval variable and \$\$ means set variable.
var	The name of the symbolic variable in the data.

Value

Return a dataframe with a label added to the previous column of symbolic variable.

Examples

```
data("mushroom.int.mm")
mushroom.set <- set_variable_format(data = mushroom.int.mm, location = 8, var = "Species")
mushroom.tmp <- RSDA_format(data = mushroom.set, sym_type1 = c("I", "S"),
                             location = c(25, 31), sym_type2 = c("S", "I", "I"),
                             var = c("Species", "Stipe.Length_min", "Stipe.Thickness_min"))
```

RSDA_to_ARRAY	<i>RSDA to ARRAY</i>
---------------	----------------------

Description

Convert RSDA format (symbolic_tbl) to a 3-dimensional array [n, p, 2] where slice [, , 1] contains the minima and slice [, , 2] contains the maxima.

Usage

```
RSDA_to_ARRAY(data)
```

Arguments

data	A symbolic_tbl with interval columns.
------	---------------------------------------

Value

A numeric array of dimension [n, p, 2] with dimnames. Only interval (symbolic_interval) columns are included.

Examples

```
data(mushroom.int)
arr <- RSDA_to_ARRAY(mushroom.int)
dim(arr) # [23, 3, 2]
```

RSDA_to_iGAP	<i>RSDA to iGAP</i>
--------------	---------------------

Description

To convert RSDA format interval dataframe to iGAP format.

Usage

```
RSDA_to_iGAP(data)
```

Arguments

data The RSDA format with interval dataframe.

Value

Return a dataframe with the iGAP format.

Examples

```
data(mushroom.int)
RSDA_to_iGAP(mushroom.int)
```

RSDA_to_MM	<i>RSDA to MM</i>
------------	-------------------

Description

To convert RSDA format interval dataframe to MM format.

Usage

```
RSDA_to_MM(data, RSDA = TRUE)
```

Arguments

data The RSDA format with interval dataframe.
RSDA Whether to load the RSDA package.

Value

Return a dataframe with the MM format.

Examples

```
data(mushroom.int)
RSDA_to_MM(mushroom.int, RSDA = FALSE)
```

search_data

*Search Datasets***Description**

Search and filter the dataSDA dataset catalog by metadata criteria including sample size, number of variables, subject area, symbolic format, analytical tasks, keywords, and book reference.

Usage

```
search_data(...)
```

Arguments

...

Filter expressions. Each argument is a comparison expression evaluated against the dataset metadata. Supported columns:

n Sample size (numeric). Operators: ==, >, <, >=, <=.

p Number of variables (numeric). Operators: ==, >, <, >=, <=.

subject Subject area (character). Case-insensitive partial match with ==. Areas: Agriculture, Automotive, Biology, Biometrics, Botany, Chemistry, Climate, Criminology, Demographics, Digital media, Economics, Education, Energy, Engineering, Environment, Finance, Food science, Forestry, Genomics, Healthcare, Marine biology, Medical, Methodology, Public services, Socioeconomics, Sociology, Sports, Transportation, Zoology.

type Symbolic format (character). Exact match with ==. Types correspond to the dataset name suffix: "int" (interval), "hist" (histogram), "mix" (mixed), "distr" (distribution), "its" (interval time series), "modal" (modal), "iGAP" (interval in iGAP format).

task Analytical tasks (character). Case-insensitive partial match with ==. Tasks: Clustering, Classification, Regression, PCA, Descriptive statistics, Discriminant analysis, Visualization, Spatial analysis, Time series, Aggregation.

tag Keywords (character). Case-insensitive partial match with ==. Use tag == "all" to list all datasets.

book Book reference short name (character). Case-insensitive partial match with ==. Available books: SDA_2006 (Billard & Diday, 2006), CMD_2020 (Billard & Diday, 2020), SODAS_2008 (Diday & Noirhomme-Fraiture, 2008).

Details

For character columns (subject, type, task, tag, book), the == operator performs a case-insensitive substring match (using grepl). The type column uses short suffix-based labels that match the dataset name suffix (e.g., type == "int" matches all .int datasets).

For numeric columns (n, p), standard comparison operators are used with exact semantics.

When no arguments are provided, or when tag == "all" is used, all datasets are returned.

Value

A data frame with one row per matching dataset and the following columns: name, n, p, subject, type, task, tag, book.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis: Conceptual Statistics and Data Mining*. Wiley, Chichester.

Billard, L. and Diday, E. (2020). *Clustering Methodology for Symbolic Data*. Wiley.

Diday, E. and Noirhomme-Fraiture, M. (Eds.) (2008). *Symbolic Data Analysis and the SODAS Software*. Wiley.

Examples

```
# List all datasets
search_data()

# Filter by symbolic format (suffix-based)
search_data(type == "hist")

# Filter by analytical task and size
search_data(task == "Regression", n > 10)

# Filter by book reference
search_data(book == "SDA_2006")

# Combine multiple filters
search_data(type == "int", task == "Clustering", subject == "Biology")

# Filter by size range
search_data(n >= 20, n <= 100, p < 10)
```

set_variable_format	<i>Set Variable Format</i>
---------------------	----------------------------

Description

This function changes the format of the set variables in the data to conform to the RSDA format.

Usage

```
set_variable_format(data, location = NULL, var = NULL)
```

Arguments

data	A conventional data.
location	The location of the set variable in the data.
var	The name of the set variable in the data.

Value

Return a dataframe in which a set variable is converted to one-hot encoding.

Examples

```
data("mushroom.int.mm")
mushroom.set <- set_variable_format(data = mushroom.int.mm, location = 8, var = "Species")
```

shanghai_stock.its	<i>Shanghai Stock Exchange Composite Index Daily High/Low Interval Time Series</i>
--------------------	--

Description

Daily high and low values of the Shanghai Stock Exchange Composite Index (SSE Composite) from January 2, 2019 to December 30, 2022 (970 trading days). Yang, Zhang and Wang (2026) provide a related interval autoregressive application; this object was independently downloaded from Yahoo Finance.

Usage

```
data(shanghai_stock.its)
```

Format

A data frame with 970 observations and 3 variables:

- date: Trading date (Date class).
- low: Daily low value of the SSE Composite Index.
- high: Daily high value of the SSE Composite Index.

Details

The SSE Composite Index is the most commonly used indicator to reflect the performance of the Shanghai Stock Exchange. It tracks all stocks (A-shares and B-shares) listed on the exchange. This dataset covers a period that includes the COVID-19 pandemic and its market impacts, providing a rich testbed for evaluating interval forecasting models under extreme volatility.

Metadata

Sample size (n)	970
Variables (p)	3 (date, low, high)
Subject area	Finance
Symbolic format	Interval time series
Analytical tasks	Forecasting, Time series analysis

Source

Yahoo Finance, ticker 000001.SS, January 2, 2019–December 30, 2022. The Yahoo Low and High fields were retained after download via **quantmod**; the original retrieval date was not recorded.

References

Yang, K., Zhang, G. and Wang, D. (2026). On smooth transition interval autoregressive models. *Journal of Business & Economic Statistics*, **44**(2), 613–625. doi:10.1080/07350015.2025.2546455.

Examples

```
data(shanghai_stock.its)
head(shanghai_stock.its)
plot(shanghai_stock.its$date, shanghai_stock.its$high, type = "l",
      col = "red", ylab = "Index Value", xlab = "Date",
      main = "Shanghai Composite Daily High/Low (2019-2022)")
lines(shanghai_stock.its$date, shanghai_stock.its$low, col = "blue")
legend("topleft", c("High", "Low"), col = c("red", "blue"), lty = 1)
```

simulated.hist	<i>Simulated Histogram-Valued Dataset</i>
----------------	---

Description

Small simulated histogram-valued dataset of 5 observations with 2 histogram-valued variables. Useful for testing and demonstrating histogram-valued statistical methods.

Usage

```
data(simulated.hist)
```

Format

A data frame with 5 observations and 2 histogram-valued variables:

- Y1: Histogram-valued variable 1.
- Y2: Histogram-valued variable 2.

Row names are Obs_1 through Obs_5.

Metadata

Sample size (n)	5
Variables (p)	2
Subject area	Methodology
Symbolic format	Histogram
Analytical tasks	Clustering

Source

Billard, L. and Diday, E. (2020), Table 7-26.

References

Billard, L. and Diday, E. (2020). *Clustering Methodology for Symbolic Data*. Wiley, Chichester. Table 7-26.

Examples

```
data(simulated.hist)
```

soccer_bivar.int	<i>French Soccer Championship Bivariate Interval Dataset</i>
------------------	--

Description

Interval-valued data for 20 teams from the French premier soccer championship. Contains ranges of Weight (response), Height and Age (explanatory variables).

Usage

```
data(soccer_bivar.int)
```

Format

A data frame with 20 rows and 3 interval-valued variables:

- y: Weight (response variable, kg).
- t1: Height (explanatory variable, cm).
- t2: Age (explanatory variable, years).

Metadata

Sample size (n)	20
Variables (p)	3
Subject area	Sports
Symbolic format	Interval
Analytical tasks	Regression

Source

French soccer interval data distributed with the **iRegression** package and analyzed by Lima Neto et al. (2011).

References

Lima Neto, E. A., Cordeiro, G. and De Carvalho, F.A.T. (2011). Bivariate symbolic regression models for interval-valued variables. *Journal of Statistical Computation and Simulation*, 81, 1727–1744. doi:[10.1080/00949655.2010.500470](https://doi.org/10.1080/00949655.2010.500470).

Examples

```
data(soccer_bivar.int)
```

SODAS_to_ARRAY

SODAS to ARRAY

Description

Convert SODAS format (XML file) to a 3-dimensional array [n, p, 2].

Usage

```
SODAS_to_ARRAY(XMLPath)
```

Arguments

XMLPath Disk path where the SODAS *.XML file is.

Value

A numeric array of dimension [n, p, 2] with dimnames.

Examples

```
## Not run:  
arr <- SODAS_to_ARRAY("C:/Users/user/AppData/abalone.xml")  
  
## End(Not run)
```

SODAS_to_iGAP	<i>SODAS to iGAP</i>
---------------	----------------------

Description

To convert SODAS format interval dataframe to the iGAP format.

Usage

SODAS_to_iGAP(XMLPath)

Arguments

XMLPath Disk path where the SODAS *.XML file is.

Value

Return a dataframe with the iGAP format.

Examples

```
## Not run:
# Read from a SODAS XML file:
abalone <- SODAS_to_iGAP("C:/Users/user/AppData/abalone.xml")

## End(Not run)
```

SODAS_to_MM	<i>SODAS to MM</i>
-------------	--------------------

Description

To convert SODAS format interval dataframe to the MM format.

Usage

SODAS_to_MM(XMLPath)

Arguments

XMLPath Disk path where the SODAS *.XML file is.

Value

Return a dataframe with the MM format.

Examples

```
## Not run:
# Read from a SODAS XML file:
abalone <- SODAS_to_MM("C:/Users/user/AppData/abalone.xml")

## End(Not run)
```

sp500.its

S&P 500 Daily High/Low Interval Time Series

Description

Daily high and low prices of the S&P 500 index from January 2, 2004 to December 30, 2005 (504 trading days). The independently downloaded Yahoo Finance series is provided as a benchmark for interval time-series forecasting; it is not the same sample as Arroyo, Gonzalez-Rivera and Mate (2011).

Usage

```
data(sp500.its)
```

Format

A data frame with 504 observations and 3 variables:

- date: Trading date (Date class).
- low: Daily low price of the S&P 500 index.
- high: Daily high price of the S&P 500 index.

Details

The S&P 500 is a market-capitalization-weighted index of 500 leading publicly traded companies in the United States. Each observation represents a trading day with the daily low and high prices forming an interval. This dataset has been widely used to evaluate interval-valued autoregressive models, exponential smoothing methods for intervals, and center-and-range forecasting approaches.

Metadata

Sample size (n)	504
Variables (p)	3 (date, low, high)
Subject area	Finance
Symbolic format	Interval time series
Analytical tasks	Forecasting, Time series analysis

Source

Yahoo Finance, ticker ^GSPC, January 2, 2004–December 30, 2005. The Yahoo Low and High fields were retained after download via **quantmod**; the original retrieval date was not recorded.

References

Arroyo, J., Gonzalez-Rivera, G. and Mate, C. (2011). Forecasting with interval and histogram data: Some financial applications. In *Handbook of Empirical Economics and Finance*, pp. 247–280. Chapman and Hall/CRC.

Examples

```
data(sp500.its)
head(sp500.its)
plot(sp500.its$date, sp500.its$high, type = "l", col = "red",
      ylab = "Price", xlab = "Date", main = "S&P 500 Daily High/Low")
lines(sp500.its$date, sp500.its$low, col = "blue")
legend("topleft", c("High", "Low"), col = c("red", "blue"), lty = 1)
```

state_income.hist	<i>State Income Histogram-Valued Dataset</i>
-------------------	--

Description

Histogram-valued dataset of 6 US states with 4 income distribution histograms. Each histogram describes the distribution of household income within a state.

Usage

```
data(state_income.hist)
```

Format

A data frame with 6 observations (states) and 4 histogram-valued variables:

- Y1 through Y4: Histogram-valued income distribution variables.

Row names are State_1 through State_6.

Metadata

Sample size (n)	6
Variables (p)	4
Subject area	Economics
Symbolic format	Histogram
Analytical tasks	Clustering

Source

Billard, L. and Diday, E. (2020), Table 7-18.

References

Billard, L. and Diday, E. (2020). *Clustering Methodology for Symbolic Data*. Wiley, Chichester. Table 7-18.

Examples

```
data(state_income.hist)
```

synthetic_clusters.int
<i>Synthetic Interval Clusters Dataset</i>

Description

Synthetic interval-valued dataset with 125 observations in 5 groups of 25 each, described by 6 interval-valued variables and a cluster label. Designed for benchmarking interval data clustering algorithms.

Usage

```
data(synthetic_clusters.int)
```

Format

A symbolic data frame (symbolic_tbl) with 125 observations and 7 variables:

- V1 through V6: Six interval-valued variables.
- class: Cluster membership (1–5, set-valued).

Metadata

Sample size (n)	125
Variables (p)	7
Subject area	Methodology
Symbolic format	Interval
Analytical tasks	Clustering

Source

Artificial benchmark data from symbolicDA::data_symbolic.

References

Dudek, A., Pelka, M., Wilk, J. and Walesiak, M. *symbolicDA: Analysis of Symbolic Data*. R package. doi:10.32614/CRAN.package.symbolicDA.

Examples

```
data(synthetic_clusters.int)
```

teams.int	<i>Pickup League Teams Interval Dataset</i>
-----------	---

Description

Interval-valued data for 5 teams in a local pickup league, classified by season performance. Each team is described by ranges of player age, weight, and speed.

Usage

```
data(teams.int)
```

Format

A data frame with 5 observations and 7 columns (3 interval variables in _l/_u Min-Max pairs, plus a label):

- team_type: Performance category (Very Good, Good, Average, Fair, Poor).
- age_l, age_u: Player age range (years).
- weight_l, weight_u: Player weight range (pounds).
- speed_l, speed_u: Speed range – time to run 100 yards (seconds).

Details

The symbolic results are more informative than classical midpoint analyses: the Very Good team has homogeneous players, whereas the Poor team has players varying widely in age, weight, and speed. Used for symbolic principal component analysis.

Metadata

Sample size (n)	5
Variables (p)	7
Subject area	Sports
Symbolic format	Interval
Analytical tasks	PCA

Source

Billard and Diday (2006), Table 2.24, p. 63.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley. Table 2.24, p.63.

Examples

```
data(teams.int)
```

temperature_city.int	<i>World Cities Monthly Temperature Interval Dataset</i>
----------------------	--

Description

Interval-valued monthly temperatures for major cities worldwide. Benchmark dataset for comparing distance measures (Hausdorff, L2, Wasserstein) in dynamic clustering algorithms.

Usage

```
data(temperature_city.int)
```

Format

A data frame with 6 observations and 13 columns (6 monthly interval variables in _l/_u Min-Max pairs, plus a label). Only January through June are included:

- city: City name (character).
- jan_l, jan_u: January temperature range (degrees Celsius).
- feb_l, feb_u: February temperature range.
- mar_l, mar_u: March temperature range.
- apr_l, apr_u: April temperature range.
- may_l, may_u: May temperature range.
- jun_l, jun_u: June temperature range.

Details

Expert partition into 4 classes: Class 1 (tropical/warm), Class 2 (temperate European and Asian), Class 3 (Mauritius), Class 4 (Tehran).

Metadata

Sample size (n)	6
Variables (p)	13
Subject area	Climate
Symbolic format	Interval
Analytical tasks	Clustering

Source

Interval-valued city-temperature data analyzed by Verde and Irpino (2008).

References

Verde, R. and Irpino, A. (2008). A new interval data distance based on the Wasserstein metric. *Proc. COMPSTAT 2008*, pp. 705–712. doi:[10.1007/9783540782469_83](https://doi.org/10.1007/9783540782469_83).

Examples

```
data(temperature_city.int)
```

tennis.int

Tennis Court Types Interval Dataset

Description

Interval-valued data for tennis players aggregated by court type (Hard, Grass, Indoor, Clay) with weight, height, and racket tension.

Usage

```
data(tennis.int)
```

Format

A data frame with 4 observations and 7 columns (3 interval variables in `_l/_u` Min-Max pairs, plus a label):

- `court_type`: Type of court (Hard, Grass, Indoor, Clay).
- `player_weight_l`, `player_weight_u`: Player weight range (kg).
- `player_height_l`, `player_height_u`: Player height range (m).
- `racket_tension_l`, `racket_tension_u`: Racket tension range.

Details

Clustering on weight and height separates grass courts from the rest (decision rule: Weight ≤ 74.75 kg). When all three variables are used, clustering separates by racket tension instead.

Metadata

Sample size (n)	4
Variables (p)	7
Subject area	Sports
Symbolic format	Interval
Analytical tasks	Clustering

Source

Billard and Diday (2006), Table 2.25, p. 64.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley. Table 2.25, p.64.

Examples

```
data(tennis.int)
```

town_services.mix	<i>Town Services Concatenated Mixed Symbolic Dataset</i>
-------------------	--

Description

Symbolic data for 3 towns (Paris, Lyon, Toulouse) combining school and hospital databases. Contains interval-valued, multi-valued, and modal-valued variables.

Usage

```
data(town_services.mix)
```

Format

A data frame with 3 observations (Paris, Lyon, Toulouse) and 8 columns:

- town: Town name (character).
- no_pupils_l, no_pupils_u: Number of pupils range (Min-Max pair).
- type: School type (modal, character).
- level: Coded level (multi-valued, character).
- no_beds_l, no_beds_u: Number of beds range (Min-Max pair).
- specialty: Specialty code (multi-valued, character).

Metadata

Sample size (n)	3
Variables (p)	8
Subject area	Public services
Symbolic format	Mixed (interval, modal, multi-valued)
Analytical tasks	Descriptive statistics

Source

Diday and Noirhomme-Fraiture (2008), Table 1.21, p. 19.

References

Diday, E. and Noirhomme-Fraiture, M. (Eds.) (2008). *Symbolic Data Analysis and the SODAS Software*. Wiley. Table 1.21, p.19.

Examples

```
data(town_services.mix)
```

to_all_interval_formats
<i>Convert Interval Data to All Supported Formats</i>

Description

Convert interval data from any recognized format to all six supported interval data formats and return the results as a named list. This is useful for inspecting and comparing how the same interval data is represented across different formats.

Usage

```
to_all_interval_formats(x, ...)
```

Arguments

x	Interval data in one of the supported formats: "RSDA", "MM", "iGAP", "ARRAY", "SODAS", or "SDS".
...	Additional arguments passed to conversion functions (e.g., location for iGAP input).

Details

Six interval data formats are supported in this package. Each format stores the same information – lower and upper bounds for every variable of every observation – but differs in its structure and origin:

RSDA A `symbolic_tbl` object (class `c("symbolic_tbl", "tbl_df", "tbl", "data.frame")`) where each interval variable is a complex column (`symbolic_interval`): `Re()` gives the minimum and `Im()` gives the maximum. This is the native format of the **RSDA** package (Billard & Diday, 2006; Rodriguez, 2024).

MM (Min-Max) A plain `data.frame` where each interval variable is represented by two numeric columns named `<var>_min` and `<var>_max`. This is a widely used general-purpose representation.

iGAP A `data.frame` where each interval variable is stored as a character column with comma-separated values "min,max". This is the format used by the **iGAP** software (Correia, 2009).

ARRAY A three-dimensional numeric array of size `[n, p, 2]`. The first slice `[, , 1]` contains all minima and the second slice `[, , 2]` contains all maxima. Dimnames encode observation labels, variable names, and `c("min", "max")`. This format is convenient for matrix-based computations.

SODAS An XML file on disk produced by the SODAS software (Diday & Noirhomme, 2008). In R, SODAS data is referenced by its file path and read via `RSDA::SODAS.to.RSDA()`. Since SODAS is a file-based format, it cannot be generated from in-memory data.

SDS An alias for SODAS. Both refer to the same XML-based format.

Value

A named list with six slots:

RSDA A `symbolic_tbl` with complex-encoded `symbolic_interval` columns.

MM A `data.frame` with paired `_min/_max` columns.

iGAP A `data.frame` with comma-separated "min,max" character values.

ARRAY A three-dimensional numeric array of dimension `[n, p, 2]` where `[, , 1]` stores minima and `[, , 2]` stores maxima.

SODAS `NULL` unless the input is a SODAS XML file path, in which case it stores the original path.

SDS `NULL` unless the input is a SODAS/SDS XML file path (alias for SODAS).

Author(s)

Han-Ming Wu

References

- Billard, L. and Diday, E. (2006). *Symbolic Data Analysis: Conceptual Statistics and Data Mining*. Wiley.
- Rodriguez, O. (2024). *RSDA: R to Symbolic Data Analysis*. R package, <https://CRAN.R-project.org/package=RSDA>.

Correia, M. (2009). *Interval GARCH and Aggregation of Predictions*.

Diday, E. and Noirhomme-Fraiture, M. (2008). *Symbolic Data Analysis and the SODAS Software*. Wiley.

See Also

[int_detect_format](#), [int_convert_format](#), [int_list_conversions](#)

Examples

```
data(car.int)
result <- to_all_interval_formats(car.int)
names(result)

# RSDA format (symbolic_tbl)
result$RSDA

# MM format (data.frame with _min/_max columns)
head(result$MM)

# iGAP format (data.frame with comma-separated values)
head(result$iGAP)

# ARRAY format (3D array)
dim(result$ARRAY)
result$ARRAY[1:3, , 1] # minima
result$ARRAY[1:3, , 2] # maxima

# SODAS/SDS slots are NULL (file-based format)
result$SODAS
result$SDS
```

trivial_intervals.int *Trivial and Non-Trivial Intervals Example Dataset*

Description

Simple 5x3 example illustrating different interval types: full intervals (hyperrectangles), degenerate intervals (lines), and trivial intervals (points). Used for vertices PCA demonstration.

Usage

```
data(trivial_intervals.int)
```

Format

A data frame with 5 observations (w1–w5) and 6 columns (3 interval variables in _l/_u Min-Max pairs):

- y1_l, y1_u: First interval variable.
- y2_l, y2_u: Second interval variable.
- y3_l, y3_u: Third interval variable.

Metadata

Sample size (n)	5
Variables (p)	6
Subject area	Methodology
Symbolic format	Interval
Analytical tasks	PCA

Source

Billard and Diday (2006), Table 5.1, p. 146.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley. Table 5.1, p.146.

Examples

```
data(trivial_intervals.int)
```

uscrime.int

US Crime Statistics Interval Dataset

Description

Interval-valued crime statistics for 46 US states, containing 102 interval-valued variables covering various crime types and rates. Originally from the RSDA package.

Usage

```
data(uscrime.int)
```

Format

A symbolic data frame (symbolic_tbl) with 46 observations and 102 interval-valued variables. Key variables include:

- fold: Cross-validation fold assignment.
- population: Population range.
- householdsize: Household size range.

- racepctblack, racePctWhite, racePctAsian, racePctHisp: Race percentage ranges.
- medIncome, medFamInc, perCapInc: Income ranges.
- PctUnemployed, PctEmploy: Employment percentage ranges.
- ViolentCrimesPerPop: Violent crimes per population range.

Plus 90 additional interval-valued socio-economic and demographic variables.

Metadata

Sample size (n)	46
Variables (p)	102
Subject area	Criminology
Symbolic format	Interval
Analytical tasks	Regression, Clustering

Source

Extracted from RSDA::uscrime_intv2.

References

Rodriguez, O. (2013). A generalization of Centre and Range method for fitting a linear regression model to symbolic interval data. In the proceedings of the 14th Conference of the International Federation of Classification Societies (IFCS 2013).

Examples

```
data(uscrime.int)
```

utsnow.int

Utah Snow Load Interval Dataset

Description

Interval-valued ground snow load data from 415 weather stations in Utah and surrounding states. Each observation is a station with a 50-year ground snow load interval (lower and upper bounds of the prediction interval in kPa) plus the point estimate, geographic coordinates, and elevation.

Usage

```
data(utsnow.int)
```

Format

A symbolic data frame (symbolic_tbl) with 415 observations and 5 variables:

- snow_load: Interval-valued 50-year ground snow load (kPa).
- point_estimate: Numeric point estimate (kPa).
- latitude: Numeric latitude (degrees).
- longitude: Numeric longitude (degrees).
- elevation: Numeric elevation (meters).

Metadata

Sample size (n)	415
Variables (p)	5
Subject area	Climate
Symbolic format	Interval
Analytical tasks	Regression, Spatial analysis

Source

intridge::utsnow; the upstream documentation identifies the 415 locations as data from the 2018 Utah Snow Load Study.

References

Bean, B., Sun, Y. and Maguire, M. (2022). Interval-valued kriging for geostatistical mapping with imprecise inputs. *International Journal of Approximate Reasoning*, 140, 31–51. doi:10.1016/j.ijar.2021.10.003.

Bean, B., Maguire, M. and Sun, Y. (2018). *Utah Snow Load Study*.

Examples

```
data(utsnow.int)
```

veterinary.int	<i>Veterinary Interval Dataset</i>
----------------	------------------------------------

Description

Interval-valued veterinary dataset of 10 animal specimens described by height and weight ranges. Includes male and female specimens of horses, bears, foxes, cats, and dogs.

Usage

```
data(veterinary.int)
```

Format

A symbolic data frame (`symbolic_tbl`) with 10 observations and 3 variables:

- **Animal:** Animal type and sex label (e.g., HorseM, BearF; character).
- **Height:** Height range (cm, interval).
- **Weight:** Weight range (kg, interval).

Metadata

Sample size (n)	10
Variables (p)	3
Subject area	Zoology
Symbolic format	Interval
Analytical tasks	Descriptive statistics, Clustering

Source

Distributed as `RSDA::VeterinaryData`; the RSDA documentation attributes the data to Billard and Diday (2006).

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis*. Wiley.

Examples

```
data(veterinary.int)
```

video1.int	<i>Video Platform User Engagement Intervals (Dataset 1)</i>
------------	---

Description

Simulated interval-valued engagement metrics for 10 user groups on a video platform. Variables represent ranges of visit, watch, like, comment, and share counts.

Usage

```
data(video1.int)
```

Format

A symbolic data frame (`symbolic_tbl`) with 10 observations and 5 interval-valued variables (V1–V5): number of visits, watches, likes, comments, and shares.

Metadata

Sample size (n)	10
Variables (p)	5
Subject area	Digital media
Symbolic format	Interval
Analytical tasks	PCA

Source

Simulated data distributed as GPCIV::video1.

References

Makosso-Kallyth, S. (2013). Analysis of m sets of symbolic interval variables. *Revue des Nouvelles Technologies de l'Information*, RNTI-E-25, 97–108.

Examples

```
data(video1.int)
```

video2.int	<i>Video Platform User Engagement Intervals (Dataset 2)</i>
------------	---

Description

Simulated interval-valued engagement metrics for 10 user groups on a video platform. Variables represent ranges of visit, watch, like, comment, and share counts.

Usage

```
data(video2.int)
```

Format

A symbolic data frame (symbolic_tbl) with 10 observations and 5 interval-valued variables (V1–V5): number of visits, watches, likes, comments, and shares.

Metadata

Sample size (n)	10
Variables (p)	5
Subject area	Digital media
Symbolic format	Interval
Analytical tasks	PCA

Source

Simulated data distributed as GPCSIV::video2.

References

Makosso-Kallyth, S. (2013). Analysis of m sets of symbolic interval variables. *Revue des Nouvelles Technologies de l'Information*, RNTI-E-25, 97–108.

Examples

```
data(video2.int)
```

video3.int	<i>Video Platform User Engagement Intervals (Dataset 3)</i>
------------	---

Description

Simulated interval-valued engagement metrics for 10 user groups on a video platform. Variables represent ranges of visit, watch, like, comment, and share counts.

Usage

```
data(video3.int)
```

Format

A symbolic data frame (symbolic_tbl) with 10 observations and 5 interval-valued variables (V1–V5): number of visits, watches, likes, comments, and shares.

Metadata

Sample size (n)	10
Variables (p)	5
Subject area	Digital media
Symbolic format	Interval
Analytical tasks	PCA

Source

Simulated data distributed as GPCSIV::video3.

References

Makosso-Kallyth, S. (2013). Analysis of m sets of symbolic interval variables. *Revue des Nouvelles Technologies de l'Information*, RNTI-E-25, 97–108.

Examples

```
data(video3.int)
```

water_flow.int	Water Flow Sensor Readings Interval Dataset
----------------	---

Description

Large interval-valued dataset of water flow sensor readings with 316 observations and 47 interval-valued feature variables (IF1-IF48, excluding IF17), classified into 2 groups. Used as a benchmark for interval data clustering with high-dimensional features.

Usage

```
data(water_flow.int)
```

Format

A data frame with 316 observations and 48 variables:

- if1 through if48 (excluding if17): 47 interval-valued sensor feature measurements.
- class: Group label (1 or 2).

Metadata

Sample size (n)	316
Variables (p)	48
Subject area	Engineering
Symbolic format	Interval
Analytical tasks	Clustering

Source

<https://github.com/Natandradesa/Kernel-Clustering-for-Interval-Data>

References

Andrade de Sa, J. N., Ferreira, M. R. P. and de Carvalho, F. A. T. (2025). Kernel clustering with automatic variable weighting for interval data. *Neurocomputing*, 650, 130849. doi:10.1016/j.neucom.2025.130849.

Examples

```
data(water_flow.int)
```

weight_age.hist*Weight by Age Group Histogram-Valued Dataset*

Description

Histogram-valued weight distributions for 7 age groups (20s through 80s). Each observation represents an age decade with a 7-bin histogram of weight values (pounds).

Usage

```
data(weight_age.hist)
```

Format

A data frame with 7 observations and 1 histogram-valued variable:

- weight: Histogram-valued weight distribution (pounds).

Row names indicate age groups (20s, 30s, 40s, 50s, 60s, 70s, 80s).

Metadata

Sample size (n)	7
Variables (p)	1
Subject area	Medical
Symbolic format	Histogram
Analytical tasks	Descriptive statistics

Source

Billard, L. and Diday, E. (2006), Table 3.10.

References

Billard, L. and Diday, E. (2006). *Symbolic Data Analysis: Conceptual Statistics and Data Mining*. Wiley, Chichester. Table 3.10.

Examples

```
data(weight_age.hist)
```

wine.int

*Wine Chemical Properties Interval Dataset***Description**

Interval-valued chemical and physical properties of 33 wine samples classified into 2 groups. Contains 9 interval-valued measurement variables. Used as a benchmark for interval data clustering algorithms.

Usage

```
data(wine.int)
```

Format

A data frame with 33 observations and 10 variables:

- V1 through V9: Nine interval-valued chemical/physical property measurements.
- class: Wine group (1 or 2).

Metadata

Sample size (n)	33
Variables (p)	10
Subject area	Food science
Symbolic format	Interval
Analytical tasks	Clustering

Source

<https://github.com/Natandradesa/Kernel-Clustering-for-Interval-Data>

References

Andrade de Sa, J. N., Ferreira, M. R. P. and de Carvalho, F. A. T. (2025). Kernel clustering with automatic variable weighting for interval data. *Neurocomputing*, 650, 130849. doi:10.1016/j.neucom.2025.130849.

Examples

```
data(wine.int)
```

world_cup.int	<i>World Cup Soccer Teams Interval Dataset</i>
---------------	--

Description

Interval-valued data for soccer teams grouped by World Cup qualification status (yes/no). Includes age, weight, height ranges and the covariance between weight and height.

Usage

```
data(world_cup.int)
```

Format

A data frame with 2 observations and 8 variables:

- world_cup: Qualification status (yes/no, character).
- age_l, age_u: Player age range (years).
- weight_l, weight_u: Player weight range (kg).
- height_l, height_u: Player height range (meters).
- cov_weight_height: Covariance between weight and height (numeric).

Metadata

Sample size (n)	2
Variables (p)	8
Subject area	Sports
Symbolic format	Interval
Analytical tasks	Descriptive statistics

Source

Diday and Noirhomme-Fraiture (2008), Table 1.9, p. 13.

References

Diday, E. and Noirhomme-Fraiture, M. (Eds.) (2008). *Symbolic Data Analysis and the SODAS Software*. Wiley. Table 1.9, p.13.

Examples

```
data(world_cup.int)
```

write_symbolic_csv	<i>Write Symbolic Data to a CSV File</i>
--------------------	--

Description

Writes a symbolic data object (interval, histogram, modal, or any data frame) to a CSV file. Interval data stored in RSDA format (symbolic_tbl with complex columns) is automatically converted to MM format (paired _min/_max columns) before writing.

Usage

```
write_symbolic_csv(
  x,
  file,
  sep = ",",
  row.names = TRUE,
  na = "NA",
  quote = TRUE,
  ...
)
```

Arguments

x	A data.frame, symbolic_tbl, or other tabular object containing symbolic data.
file	Path to the output CSV file.
sep	Field separator character. Default ",".
row.names	Logical or character. If TRUE (the default), row names are written as the first column.
na	Character string to use for missing values. Default "NA".
quote	Logical; should character and factor columns be quoted? Default TRUE.
...	Additional arguments passed to write.table .

Details

write_symbolic_csv handles every tabular symbolic type stored in **dataSDA**:

- **Interval (RSDA)**: symbolic_tbl objects with complex interval columns are converted to MM format before writing.
- **Interval (MM)**: Data frames with _min/_max columns are written directly.
- **Histogram / Modal / Other**: Plain data frames are written directly.

The output is a standard CSV that can be read back with [read_symbolic_csv](#).

Value

Invisibly returns the data frame that was written (after any conversion).

See Also

[read_symbolic_csv](#)

Examples

```
# Interval data (RSDA symbolic_tbl)
data(mushroom.int)
tmp <- tempfile(fileext = ".csv")
write_symbolic_csv(mushroom.int, tmp)
cat(readLines(tmp, n = 3), sep = "\n")

# Histogram data
data(airline_flights.hist)
tmp2 <- tempfile(fileext = ".csv")
write_symbolic_csv(airline_flights.hist, tmp2)
cat(readLines(tmp2, n = 3), sep = "\n")
```

Index

* PCA

finance.int, 54
teams.int, 145
trivial_intervals.int, 151

* agriculture

french_agriculture.hist, 56

* biology

ecoli_routes.int, 45

* categorical

bird_species.mix, 22
bird_species_extended.mix, 23

* classification

cars.int, 28

* climate

china_temp_monthly.int, 35

* clustering

bats.int, 19
car_models.int, 29
china_temp.int, 34
freshwater_fish.int, 57
fungi.int, 59
horses.int, 75
iris.int, 97
oils.int, 123
synthetic_clusters.int, 144
temperature_city.int, 146
tennis.int, 147
water_flow.int, 158
wine.int, 160

* commodities

crude_oil_wti.its, 43

* crime

uscrime.int, 152

* datasets

abalone.iGAP, 5
abalone.int, 6
acid_rain.int, 7
age_cholesterol_weight.int, 8
age_pyramids.hist, 9

airline_flights.hist, 12

airline_flights2.modal, 14

bank_rates, 17

baseball.int, 18

bats.int, 19

bird.mix, 20

bird_color_taxonomy.hist, 21

bird_species.mix, 22

bird_species_extended.mix, 23

blood.hist, 24

blood_pressure.int, 25

car.int, 26

car_models.int, 29

cardiological.int, 27

cars.int, 28

census.mix, 30

china_climate_month.hist, 32

china_climate_season.hist, 33

china_temp.int, 34

china_temp_monthly.int, 35

cholesterol.hist, 36

county_income_gender.hist, 37

cover_types.hist, 38

credit_card.int, 39

crime.modal, 41

crime2.modal, 42

crude_oil_wti.its, 43

djia.its, 44

ecoli_routes.int, 45

employment.int, 46

energy_consumption.distr, 47

energy_usage.distr, 48

environment.mix, 49

euro_usd.its, 51

exchange_rate_returns.hist, 52

face.iGAP, 53

finance.int, 54

flights_detail.hist, 55

french_agriculture.hist, 56

- freshwater_fish.int, 57
- fuel_consumption.modal, 58
- fungi.int, 59
- genome_abundances.int, 60
- glucose.hist, 61
- hardwood.hist, 62
- hdi_gender.int, 63
- health_insurance.mix, 64
- health_insurance2.modal, 66
- hematocrit.hist, 67
- hematocrit_hemoglobin.hist, 68
- hemoglobin.hist, 69
- hierarchy, 70
- hierarchy.hist, 71
- hierarchy.int, 72
- horses.int, 75
- hospital.hist, 76
- household_characteristics.distr, 77
- ibovespa.its, 78
- iris.int, 97
- iris_species.hist, 99
- irish_wind.its, 98
- joggers.mix, 100
- judge1.int, 101
- judge2.int, 102
- judge3.int, 103
- lackinfo.int, 104
- lisbon_air_quality.int, 105
- loans_by_purpose.int, 106
- loans_by_risk.int, 107
- loans_by_risk_quantile.int, 108
- lung_cancer.hist, 109
- lynne1.int, 110
- merval.its, 111
- mtcars.mix, 114
- mushroom.int, 115
- mushroom.int.mm, 116
- mushroom_fuzzy.mix, 118
- nycflights.int, 119
- occupations.modal, 120
- occupations2.modal, 121
- ohtemp.int, 122
- oils.int, 123
- ozone.hist, 124
- petrobras.its, 125
- polish_cars.mix, 126
- polish_voivodships.int, 128
- profession.int, 129
- prostate.int, 130
- shanghai_stock.its, 137
- simulated.hist, 138
- soccer_bivar.int, 139
- sp500.its, 142
- state_income.hist, 143
- synthetic_clusters.int, 144
- teams.int, 145
- temperature_city.int, 146
- tennis.int, 147
- town_services.mix, 148
- trivial_intervals.int, 151
- uscrime.int, 152
- utsnow.int, 153
- veterinary.int, 154
- video1.int, 155
- video2.int, 156
- video3.int, 157
- water_flow.int, 158
- weight_age.hist, 159
- wine.int, 160
- world_cup.int, 161
- * demographics**
 - age_pyramids.hist, 9
- * discriminant**
 - employment.int, 46
- * distance**
 - temperature_city.int, 146
- * distribution**
 - bird_color_taxonomy.hist, 21
 - census.mix, 30
 - energy_consumption.distr, 47
 - energy_usage.distr, 48
 - household_characteristics.distr, 77
- * economics**
 - french_agriculture.hist, 56
- * environment**
 - ozone.hist, 124
- * exchange**
 - euro_usd.its, 51
- * finance**
 - crude_oil_wti.its, 43
 - djia.its, 44
 - euro_usd.its, 51
 - ibovespa.its, 78
 - loans_by_risk.int, 107

- merval.its, 111
- petrobras.its, 125
- shanghai_stock.its, 137
- sp500.its, 142
- * **flights**
 - flights_detail.hist, 55
- * **forestry**
 - cover_types.hist, 38
- * **fuzzy**
 - mushroom_fuzzy.mix, 118
- * **gender**
 - county_income_gender.hist, 37
- * **genomics**
 - genome_abundances.int, 60
- * **hierarchical**
 - hierarchy, 70
- * **histogram**
 - age_pyramids.hist, 9
 - airline_flights.hist, 12
 - bird_color_taxonomy.hist, 21
 - bird_species_extended.mix, 23
 - blood.hist, 24
 - census.mix, 30
 - china_climate_month.hist, 32
 - china_climate_season.hist, 33
 - cholesterol.hist, 36
 - county_income_gender.hist, 37
 - cover_types.hist, 38
 - exchange_rate_returns.hist, 52
 - flights_detail.hist, 55
 - french_agriculture.hist, 56
 - glucose.hist, 61
 - hardwood.hist, 62
 - hematocrit.hist, 67
 - hematocrit_hemoglobin.hist, 68
 - hemoglobin.hist, 69
 - hierarchy.hist, 71
 - hospital.hist, 76
 - iris_species.hist, 99
 - joggers.mix, 100
 - lung_cancer.hist, 109
 - ozone.hist, 124
 - simulated.hist, 138
 - state_income.hist, 143
 - weight_age.hist, 159
- * **household**
 - household_characteristics.distr, 77

- * **iGAP**
 - abalone.iGAP, 5
 - face.iGAP, 53
- * **income**
 - county_income_gender.hist, 37
 - state_income.hist, 143
- * **interval**
 - abalone.iGAP, 5
 - abalone.int, 6
 - acid_rain.int, 7
 - age_cholesterol_weight.int, 8
 - baseball.int, 18
 - bats.int, 19
 - bird.mix, 20
 - bird_species.mix, 22
 - bird_species_extended.mix, 23
 - blood_pressure.int, 25
 - car.int, 26
 - car_models.int, 29
 - cardiological.int, 27
 - cars.int, 28
 - census.mix, 30
 - china_temp.int, 34
 - china_temp_monthly.int, 35
 - credit_card.int, 39
 - crude_oil_wti.its, 43
 - djia.its, 44
 - ecoli_routes.int, 45
 - employment.int, 46
 - environment.mix, 49
 - euro_usd.its, 51
 - face.iGAP, 53
 - finance.int, 54
 - freshwater_fish.int, 57
 - fungi.int, 59
 - genome_abundances.int, 60
 - hdi_gender.int, 63
 - hierarchy.hist, 71
 - hierarchy.int, 72
 - horses.int, 75
 - ibovespa.its, 78
 - iris.int, 97
 - irish_wind.its, 98
 - joggers.mix, 100
 - judge1.int, 101
 - judge2.int, 102
 - judge3.int, 103
 - lackinfo.int, 104

- lisbon_air_quality.int, 105
- loans_by_purpose.int, 106
- loans_by_risk.int, 107
- loans_by_risk_quantile.int, 108
- lynne1.int, 110
- merval.its, 111
- mtcars.mix, 114
- mushroom.int, 115
- mushroom.int.mm, 116
- nycflights.int, 119
- ohtemp.int, 122
- oils.int, 123
- petrobras.its, 125
- polish_cars.mix, 126
- polish_voivodships.int, 128
- profession.int, 129
- prostate.int, 130
- shanghai_stock.its, 137
- soccer_bivar.int, 139
- sp500.its, 142
- synthetic_clusters.int, 144
- teams.int, 145
- temperature_city.int, 146
- tennis.int, 147
- town_services.mix, 148
- trivial_intervals.int, 151
- uscrime.int, 152
- utsnow.int, 153
- veterinary.int, 154
- video1.int, 155
- video2.int, 156
- video3.int, 157
- water_flow.int, 158
- wine.int, 160
- world_cup.int, 161
- * **iris**
 - iris_species.hist, 99
- * **medical**
 - cholesterol.hist, 36
 - glucose.hist, 61
 - hematocrit.hist, 67
 - hematocrit_hemoglobin.hist, 68
 - hemoglobin.hist, 69
 - prostate.int, 130
- * **meteorology**
 - irish_wind.its, 98
- * **mixed**
 - bird_color_taxonomy.hist, 21
 - bird_species.mix, 22
 - bird_species_extended.mix, 23
 - census.mix, 30
 - environment.mix, 49
 - health_insurance.mix, 64
 - hierarchy.hist, 71
 - joggers.mix, 100
 - mtcars.mix, 114
 - polish_cars.mix, 126
 - town_services.mix, 148
- * **modal**
 - airline_flights2.modal, 14
 - crime.modal, 41
 - crime2.modal, 42
 - environment.mix, 49
 - fuel_consumption.modal, 58
 - health_insurance2.modal, 66
 - mtcars.mix, 114
 - occupations.modal, 120
 - occupations2.modal, 121
 - town_services.mix, 148
- * **model**
 - bank_rates, 17
- * **multi-valued**
 - town_services.mix, 148
- * **multinomial**
 - polish_cars.mix, 126
- * **ordinal**
 - hdi_gender.int, 63
- * **regression**
 - fuel_consumption.modal, 58
 - hematocrit_hemoglobin.hist, 68
 - soccer_bivar.int, 139
- * **simulated**
 - simulated.hist, 138
- * **socioeconomic**
 - polish_voivodships.int, 128
- * **spatial**
 - irish_wind.its, 98
- * **symbolic**
 - bank_rates, 17
 - health_insurance.mix, 64
 - mushroom_fuzzy.mix, 118
- * **synthetic**
 - synthetic_clusters.int, 144
- * **temperature**
 - china_temp_monthly.int, 35
- * **timeseries**

- crude_oil_wti.its, 43
- djia.its, 44
- euro_usd.its, 51
- ibovespa.its, 78
- irish_wind.its, 98
- merval.its, 111
- petrobras.its, 125
- shanghai_stock.its, 137
- sp500.its, 142
- * **visualization**
 - bats.int, 19
- * **weather**
 - ozone.hist, 124
- abalone.iGAP, 5, 6
- abalone.int, 5, 6
- acid_rain.int, 7
- age_cholesterol_weight.int, 8
- age_pyramids.hist, 9
- aggregate_to_symbolic, 10
- airline_flights.hist, 12, 14
- airline_flights2.modal, 13, 14
- ARRAY_to_iGAP, 15
- ARRAY_to_MM, 15
- ARRAY_to_RSDA, 16
- bank_rates, 17
- baseball.int, 18
- bats.int, 19
- bird.mix, 20
- bird_color_taxonomy.hist, 21
- bird_species.mix, 22
- bird_species_extended.mix, 23
- blood.hist, 24
- blood_pressure.int, 25
- car.int, 26
- car_models.int, 29
- cardiological.int, 27
- cars.int, 28
- census.mix, 30
- check_zero_width_intervals, 11, 31
- china_climate_month.hist, 32
- china_climate_season.hist, 33
- china_temp.int, 34
- china_temp_monthly.int, 35
- cholesterol.hist, 36
- clean_colnames, 37
- county_income_gender.hist, 37
- cover_types.hist, 38
- credit_card.int, 39
- crime.modal, 41, 42
- crime2.modal, 41, 42
- crude_oil_wti.its, 43
- djia.its, 44
- ecoli_routes.int, 45
- employment.int, 46
- energy_consumption.distr, 47
- energy_usage.distr, 48
- environment.mix, 49
- euro_usd.its, 51
- exchange_rate_returns.hist, 52
- face.iGAP, 53
- finance.int, 54
- flights_detail.hist, 55
- french_agriculture.hist, 56
- freshwater_fish.int, 57
- fuel_consumption.modal, 58
- fungi.int, 59
- genome_abundances.int, 60
- glucose.hist, 61
- hardwood.hist, 62
- hdi_gender.int, 63
- health_insurance.mix, 64, 66
- health_insurance2.modal, 64, 66
- hematocrit.hist, 67
- hematocrit_hemoglobin.hist, 68
- hemoglobin.hist, 69
- hierarchy, 70, 72
- hierarchy.hist, 71
- hierarchy.int, 70, 72
- hist_cor(histogram_stats), 73
- hist_cov(histogram_stats), 73
- hist_mean(histogram_stats), 73
- hist_var(histogram_stats), 73
- histogram_stats, 73
- horses.int, 75
- hospital.hist, 76
- household_characteristics.distr, 77
- ibovespa.its, 78
- iGAP_to_ARRAY, 79
- iGAP_to_MM, 80
- iGAP_to_RSDA, 80

- `int_center` (`interval_geometry`), 83
- `int_containment` (`interval_geometry`), 83
- `int_convert_format`, 94, 132, 151
- `int_cor` (`interval_stats`), 91
- `int_cosine` (`interval_similarity`), 89
- `int_cov` (`interval_stats`), 91
- `int_cv` (`interval_uncertainty`), 92
- `int_detect_format`, 95, 132, 151
- `int_dice` (`interval_similarity`), 89
- `int_dispersion` (`interval_uncertainty`), 92
- `int_dist` (`interval_distance`), 81
- `int_dist_all` (`interval_distance`), 81
- `int_dist_matrix` (`interval_distance`), 81
- `int_entropy` (`interval_uncertainty`), 92
- `int_granularity` (`interval_uncertainty`), 92
- `int_imprecision` (`interval_uncertainty`), 92
- `int_information_content` (`interval_uncertainty`), 92
- `int_iqr` (`interval_position`), 85
- `int_jaccard` (`interval_similarity`), 89
- `int_kurtosis` (`interval_shape`), 88
- `int_list_conversions`, 96, 151
- `int_mad` (`interval_position`), 85
- `int_mean` (`interval_stats`), 91
- `int_median` (`interval_position`), 85
- `int_midrange` (`interval_geometry`), 83
- `int_mode` (`interval_position`), 85
- `int_overlap` (`interval_geometry`), 83
- `int_overlap_coefficient` (`interval_similarity`), 89
- `int_pairwise_dist` (`interval_distance`), 81
- `int_quantile` (`interval_position`), 85
- `int_radius` (`interval_geometry`), 83
- `int_range` (`interval_position`), 85
- `int_similarity_matrix` (`interval_similarity`), 89
- `int_skewness` (`interval_shape`), 88
- `int_symmetry` (`interval_shape`), 88
- `int_tailedness` (`interval_shape`), 88
- `int_tanimoto` (`interval_similarity`), 89
- `int_trimmed_mean` (`interval_robust`), 86
- `int_trimmed_var` (`interval_robust`), 86
- `int_uniformity` (`interval_uncertainty`), 92
- `int_var` (`interval_stats`), 91
- `int_width` (`interval_geometry`), 83
- `int_winsorized_mean` (`interval_robust`), 86
- `int_winsorized_var` (`interval_robust`), 86
- `interval_distance`, 81
- `interval_geometry`, 83
- `interval_position`, 85
- `interval_robust`, 86
- `interval_shape`, 88
- `interval_similarity`, 89
- `interval_stats`, 91
- `interval_uncertainty`, 92
- `iris.int`, 97
- `iris_species.hist`, 99
- `irish_wind.its`, 98
- `joggers.mix`, 100
- `judge1.int`, 101
- `judge2.int`, 102
- `judge3.int`, 103
- `lackinfo.int`, 104
- `lisbon_air_quality.int`, 105
- `loans_by_purpose.int`, 106
- `loans_by_risk.int`, 107
- `loans_by_risk_quantile.int`, 108
- `lung_cancer.hist`, 109
- `lynne1.int`, 110
- `Math`, 12
- `merval.its`, 111
- `MM_to_ARRAY`, 112
- `MM_to_iGAP`, 113
- `MM_to_RSDA`, 114
- `mtcars.mix`, 114
- `mushroom.int`, 115
- `mushroom.int.mm`, 115, 116
- `mushroom_fuzzy.mix`, 118
- `nycflights.int`, 119
- `occupations.modal`, 120, 121
- `occupations2.modal`, 120, 121
- `ohtemp.int`, 122
- `oils.int`, 123
- `ozone.hist`, 124
- `petrobras.its`, 125
- `polish_cars.mix`, 126

polish_voivodships.int, [128](#)
profession.int, [129](#)
prostate.int, [130](#)

read.table, [131](#)
read_symbolic_csv, [131](#), [162](#), [163](#)
RSDA_format, [132](#)
RSDA_to_ARRAY, [133](#)
RSDA_to_iGAP, [134](#)
RSDA_to_MM, [134](#)

search_data, [135](#)
set_variable_format, [136](#)
shanghai_stock.its, [137](#)
simulated.hist, [138](#)
soccer_bivar.int, [139](#)
SODAS_to_ARRAY, [140](#)
SODAS_to_iGAP, [141](#)
SODAS_to_MM, [141](#)
sp500.its, [142](#)
state_income.hist, [143](#)
synthetic_clusters.int, [144](#)

teams.int, [145](#)
temperature_city.int, [146](#)
tennis.int, [147](#)
to_all_interval_formats, [149](#)
town_services.mix, [148](#)
trivial_intervals.int, [151](#)

uscrime.int, [152](#)
utsnow.int, [153](#)

veterinary.int, [154](#)
video1.int, [155](#)
video2.int, [156](#)
video3.int, [157](#)

water_flow.int, [158](#)
weight_age.hist, [159](#)
wine.int, [160](#)
world_cup.int, [161](#)
write.table, [162](#)
write_symbolic_csv, [132](#), [162](#)