

Package ‘evalHTE’

September 7, 2026

Title Evaluating Heterogeneous Treatment Effects

Version 0.2.0

Description Provides various statistical methods for evaluating heterogeneous treatment effects (HTE) in randomized experiments. The package includes tools to estimate uniform confidence bands for estimation of the group average treatment effect sorted by generic machine learning algorithms (GATES). It also provides the tools to identify a subgroup of individuals who are likely to benefit from a treatment the most “exceptional responders” or those who are harmed by it. Detailed reference in Imai and Li (2023) <[doi:10.48550/arXiv.2310.07973](https://doi.org/10.48550/arXiv.2310.07973)>.

License MIT + file LICENSE

Depends R (>= 3.5.0), dplyr (>= 1.0.10)

Imports cli, evalITR (>= 1.1.0), ggplot2, ggthemes, rlang, zoo, furrr, ggdist, scales, tidyr, stats, purrr, caret

Encoding UTF-8

RoxygenNote 7.3.3

Suggests testthat (>= 3.0.0), knitr, rmarkdown, future, grf, magrittr, tibble

VignetteBuilder knitr

NeedsCompilation no

Author Michael Lingzhi Li [aut, cre],
Kosuke Imai [aut],
Jialu Li [ctb]

Maintainer Michael Lingzhi Li <mili@hbs.edu>

Repository CRAN

Date/Publication 2026-09-07 08:30:02 UTC

Contents

compute_qoi	2
compute_qoi_user	2
consist.test	3

consistcv.test	4
estimate_hte	5
evaluate_hte	6
GATE	7
GATEcv	8
het.test	9
hetcv.test	10
plot.hte	11
plot_CI	11
plot_CI.hte	12
print.summary.hte	12
print.summary.test_hte	13
summary.hte	13
summary.test_hte	14
test_itr	15
URATE	15
Index	17

compute_qoi	<i>Compute Quantities of Interest (GATE, GATEcv, URATE)</i>
-------------	---

Description

Compute Quantities of Interest (GATE, GATEcv, URATE)

Usage

compute_qoi(fit_obj, algorithms)

Arguments

- fit_obj An output object of estimate_itr function from the evalITR package.
- algorithms Machine learning algorithms

compute_qoi_user	<i>Compute Quantities of Interest (GATE, GATEcv, URATE) with user defined functions</i>
------------------	---

Description

Compute Quantities of Interest (GATE, GATEcv, URATE) with user defined functions

Usage

compute_qoi_user(user_hte, Tcv, Ycv, data, ngates, ...)

Arguments

user_hte	A user-defined function to estimate heterogeneous treatment effects (HTE). The function should take the data as input and return an unit-level continuous score for treatment assignment. We assume those that have score less than 0 should not have treatment. The default is NULL, which means the heterogeneous treatment effects will be estimated from by the package.
Tcv	A vector of the unit-level binary treatment.
Ycv	A vector of the unit-level continuous outcome.
data	A data frame containing the variables of interest.
ngates	The number of gates to be used in the GATE function.
...	Additional arguments to be passed to the user-defined function.

consist.test	<i>The Consistency Test for Grouped Average Treatment Effects (GATEs) in Randomized Experiments</i>
--------------	---

Description

Tests whether treatment effects are nondecreasing across score groups.

Usage

```
consist.test(D, tau, Y, ngates = 5, nsim = 10000, centered = TRUE)
```

Arguments

D	Binary treatment indicator (0 or 1).
tau	Continuous score vector.
Y	Outcome vector.
ngates	Number of groups (at least 2).
nsim	Number of Monte Carlo draws (at least 2).
centered	Whether to center outcomes before estimation.

Details

Uses `consist.test` for inference.

Value

A list with test statistic `stat` and p-value `pval`.

Author(s)

Michael Lingzhi Li, Technology and Operations Management, Harvard Business School <mili@hbs.edu>, <https://www.michaellz.com/>;

References

Imai and Li (2022). “Statistical Inference for Heterogeneous Treatment Effects Discovered by Generic Machine Learning in Randomized Experiments”,

Examples

```
D = c(1,0,1,0,1,0,1,0)
tau = c(0,0.1,0.2,0.3,0.4,0.5,0.6,0.7)
Y = c(4,5,0,2,4,1,-4,3)
consisttestlist <- consist.test(D, tau, Y, ngates=2)
consisttestlist$stat
consisttestlist$pval
```

consistcv.test	<i>The Consistency Test for Grouped Average Treatment Effects (GATEs) under Cross Validation in Randomized Experiments</i>
----------------	--

Description

Tests whether treatment effects are nondecreasing across cross-validated score groups.

Usage

```
consistcv.test(D, tau, Y, ind, ngates = 5, nsim = 10000, centered = TRUE)
```

Arguments

D	Binary treatment indicator (0 or 1).
tau	A matrix of scores with one column per fold. Column i contains predictions for all observations from a model trained without fold i.
Y	Outcome vector.
ind	Integer validation-fold labels starting at 1.
ngates	Number of groups (at least 2).
nsim	Number of Monte Carlo draws (at least 2).
centered	Whether to center outcomes before estimation.

Details

Uses [consistcv.test](#) for inference.

Value

A list with test statistic stat and p-value pval.

Author(s)

Michael Lingzhi Li, Technology and Operations Management, Harvard Business School <mili@hbs.edu>, <https://www.michaellz.com/>;

References

Imai and Li (2022). “Statistical Inference for Heterogeneous Treatment Effects Discovered by Generic Machine Learning in Randomized Experiments”,

Examples

```
D = c(1,0,1,0,1,0,1,0)
tau = matrix(c(0,0.1,0.2,0.3,0.4,0.5,0.6,0.7,-0.5,-0.3,-0.1,0.1,0.3,0.5,0.7,0.9),nrow = 8, ncol = 2)
Y = c(4,5,0,2,4,1,-4,3)
ind = c(rep(1,4),rep(2,4))
consisttestlist <- consistcv.test(D,tau,Y,ind,ngates=2)
consisttestlist$stat
consisttestlist$pval
```

estimate_hte

Evaluate Heterogeneous Treatment Effects

Description

Evaluate Heterogeneous Treatment Effects

Usage

```
estimate_hte(
  treatment,
  form,
  data,
  algorithms,
  n_folds = 5,
  split_ratio = 0,
  ngates = 5,
  preProcess = NULL,
  weights = NULL,
  trControl = caret::trainControl(method = "none"),
  tuneGrid = NULL,
  tuneLength = ifelse(trControl$method == "none", 1, 3),
  user_model = NULL,
  SL_library = NULL,
  meta_learner = "slearner",
  ...
)
```

Arguments

treatment	Treatment variable
form	a formula object that takes the form $y \sim D + x_1 + x_2 + \dots$
data	A data frame that contains the outcome y and the treatment D .
algorithms	List of machine learning algorithms to be used.
n_folds	Number of cross-validation folds. Default is 5.
split_ratio	Split ratio between train and test set under sample splitting. Default is 0.
ngates	The number of groups to separate the data into. The groups are determined by τ . Default is 5.
preProcess	caret parameter
weights	caret parameter
trControl	caret parameter
tuneGrid	caret parameter
tuneLength	caret parameter
user_model	A user-defined function to estimate heterogeneous treatment effects.
SL_library	A list of machine learning algorithms to be used in the super learner.
meta_learner	The type of meta-learner to use (e.g., "slearner", "tlearner"). Default is "slearner".
...	Additional arguments passed to <code>caret::train</code> .

Value

An object of hte class

evaluate_hte	<i>Evaluate Heterogeneous Treatment Effects</i>
--------------	---

Description

Evaluate Heterogeneous Treatment Effects

Usage

```
evaluate_hte(fit, ...)
```

Arguments

fit	Fitted model. Usually an output from <code>estimate_hte</code> .
...	Additional arguments passed to the function.

Value

An object of hte class

GATE	<i>Estimation of the Grouped Average Treatment Effects (GATEs) in Randomized Experiments</i>
------	--

Description

Estimates grouped average treatment effects from a continuous score.

Usage

```
GATE(D, tau, Y, ngates = 5, centered = FALSE)
```

Arguments

D	Binary treatment indicator (0 or 1).
tau	Continuous score vector.
Y	Outcome vector.
ngates	Number of groups (at least 2).
centered	Whether to center outcomes before estimation.

Details

Uses [GATE](#) for inference.

Value

A list with group estimates gate and standard errors sd, ordered by increasing score.

Author(s)

Michael Lingzhi Li, Technology and Operations Management, Harvard Business School <mili@hbs.edu>, <https://www.michaellz.com/>;

References

Imai and Li (2022). “Statistical Inference for Heterogeneous Treatment Effects Discovered by Generic Machine Learning in Randomized Experiments”,

Examples

```
D = c(1,0,1,0,1,0,1,0)
tau = c(0,0.1,0.2,0.3,0.4,0.5,0.6,0.7)
Y = c(4,5,0,2,4,1,-4,3)
gatelist <- GATE(D,tau,Y,ngates=2)
gatelist$gate
gatelist$sd
```

GATEcv	<i>Estimation of the Grouped Average Treatment Effects (GATEs) in Randomized Experiments Under Cross Validation</i>
--------	---

Description

Estimates grouped average treatment effects from cross-validated scores.

Usage

```
GATEcv(D, tau, Y, ind, ngates = 5, centered = FALSE)
```

Arguments

D	Binary treatment indicator (0 or 1).
tau	A matrix of scores with one column per fold. Column i contains predictions for all observations from a model trained without fold i.
Y	Outcome vector.
ind	Integer validation-fold labels starting at 1.
ngates	Number of groups (at least 2).
centered	Whether to center outcomes before estimation.

Details

Uses [GATEcv](#) for inference.

Value

A list with group estimates gate and standard errors sd, ordered by increasing score.

Author(s)

Michael Lingzhi Li, Technology and Operations Management, Harvard Business School <mili@hbs.edu>, <https://www.michaellz.com/>;

References

Imai and Li (2022). “Statistical Inference for Heterogeneous Treatment Effects Discovered by Generic Machine Learning in Randomized Experiments”,

Examples

```
D = c(1,0,1,0,1,0,1,0)
tau = matrix(c(0,0.1,0.2,0.3,0.4,0.5,0.6,0.7,-0.5,-0.3,-0.1,0.1,0.3,0.5,0.7,0.9),nrow = 8, ncol = 2)
Y = c(4,5,0,2,4,1,-4,3)
ind = c(rep(1,4),rep(2,4))
gatelist <- GATEcv(D, tau, Y, ind, ngates = 2)
gatelist$gate
gatelist$sd
```

het.test	<i>The Heterogeneity Test for Grouped Average Treatment Effects (GATEs) in Randomized Experiments</i>
----------	---

Description

Tests whether treatment effects are equal across score groups.

Usage

```
het.test(D, tau, Y, ngates = 5, centered = TRUE)
```

Arguments

D	Binary treatment indicator (0 or 1).
tau	Continuous score vector.
Y	Outcome vector.
ngates	Number of groups (at least 2).
centered	Whether to center outcomes before estimation.

Details

Uses [het.test](#) for inference.

Value

A list with test statistic `stat` and p-value `pval`.

Author(s)

Michael Lingzhi Li, Technology and Operations Management, Harvard Business School <mili@hbs.edu>, <https://www.michaellz.com/>;

References

Imai and Li (2022). “Statistical Inference for Heterogeneous Treatment Effects Discovered by Generic Machine Learning in Randomized Experiments”,

Examples

```
D = c(1,0,1,0,1,0,1,0)
tau = c(0,0.1,0.2,0.3,0.4,0.5,0.6,0.7)
Y = c(4,5,0,2,4,1,-4,3)
hettestlist <- het.test(D,tau,Y,ngates=2)
hettestlist$stat
hettestlist$pval
```

hetcv.test	<i>The Heterogeneity Test for Grouped Average Treatment Effects (GATEs) under Cross Validation in Randomized Experiments</i>
------------	--

Description

Tests whether treatment effects are equal across cross-validated score groups.

Usage

```
hetcv.test(D, tau, Y, ind, ngates = 5, centered = TRUE)
```

Arguments

D	Binary treatment indicator (0 or 1).
tau	A matrix of scores with one column per fold. Column i contains predictions for all observations from a model trained without fold i.
Y	Outcome vector.
ind	Integer validation-fold labels starting at 1.
ngates	Number of groups (at least 2).
centered	Whether to center outcomes before estimation.

Details

Uses [hetcv.test](#) for inference.

Value

A list with test statistic stat and p-value pval.

Author(s)

Michael Lingzhi Li, Technology and Operations Management, Harvard Business School <mili@hbs.edu>, <https://www.michaellz.com/>;

References

Imai and Li (2022). “Statistical Inference for Heterogeneous Treatment Effects Discovered by Generic Machine Learning in Randomized Experiments”,

Examples

```

D = c(1,0,1,0,1,0,1,0)
tau = matrix(c(0,0.1,0.2,0.3,0.4,0.5,0.6,0.7,-0.5,-0.3,-0.1,0.1,0.3,0.5,0.7,0.9),nrow = 8, ncol = 2)
Y = c(4,5,0,2,4,1,-4,3)
ind = c(rep(1,4),rep(2,4))
hettestlist <- hetcv.test(D,tau,Y,ind,ngates=2)
hettestlist$stat
hettestlist$pval

```

plot.hte	<i>Plot the GATE estimate</i>
----------	-------------------------------

Description

Plot the GATE estimate

Usage

```

## S3 method for class 'hte'
plot(x, ...)

```

Arguments

x	An table object. This is typically an output of evaluate_hte() function.
...	Further arguments passed to the function.

Value

A plot of ggplot2 object.

plot_CI	<i>Plot Confidence Intervals</i>
---------	----------------------------------

Description

A generic function to plot uniform and pointwise confidence intervals for HTE objects.

Usage

```
plot_CI(x, ...)
```

Arguments

x	An object for which a plot is desired.
...	Further arguments passed to methods.

Value

A ggplot2 object displaying uniform and pointwise confidence intervals for heterogeneous treatment effects.

plot_CI.hte	<i>Plot the uniform confidence interval</i>
-------------	---

Description

Plot the uniform confidence interval

Usage

```
## S3 method for class 'hte'
plot_CI(x, alpha = 0.05, ...)
```

Arguments

x	An object of evaluate_hte() class. This is typically an output of evaluate_hte() function.
alpha	Significance level. Default is 0.05.
...	Further arguments passed to the function.

Value

A plot of ggplot2 object.

print.summary.hte	<i>Print</i>
-------------------	--------------

Description

Print

Usage

```
## S3 method for class 'summary.hte'
print(x, ...)
```

Arguments

x	An object of summary.hte class. This is typically an output of summary.hte() function.
...	Other parameters. Currently not supported.

Value

No return value, called for side effects (prints summary tables to console).

```
print.summary.test_hte
```

Print

Description

Print

Usage

```
## S3 method for class 'summary.test_hte'
print(x, ...)
```

Arguments

x	An object of <code>summary.test_hte</code> class. This is typically an output of <code>summary.test_hte()</code> function.
...	Other parameters.

Value

No return value, called for side effects (prints test results to console).

```
summary.hte
```

Summarize Heterogeneity and Consistency Tests

Description

Summarize Heterogeneity and Consistency Tests

Usage

```
## S3 method for class 'hte'
summary(object, ...)
```

Arguments

object	An object of <code>evaluate_hte</code> class (typically an output of <code>evaluate_hte()</code> function).
...	Other parameters.

Value

An object of class `summary.hte`, which is a list containing:

GATE A tibble with group average treatment effect estimates, including columns: `group`, `algorithm`, `estimate`, `std.deviation`, `lower`, `upper`, `z.score`, and `p.value`.

URATE A tibble with uplift rate estimates for exceptional responders, including columns: `algorithm`, `estimate`, `std.deviation`, `conf.low.uniform`, `z.score`, and `p.value`. Returns `NULL` when cross-validation is used.

<code>summary.test_hte</code>	<i>Summarize Heterogeneity and Consistency Tests</i>
-------------------------------	--

Description

Summarize Heterogeneity and Consistency Tests

Usage

```
## S3 method for class 'test_hte'
summary(object, ...)
```

Arguments

<code>object</code>	An object of <code>test_hte</code> class (typically an output of <code>test_hte()</code> function).
<code>...</code>	Other parameters.

Value

An object of class `summary.test_hte`, which is a list containing:

Consistency A tibble with consistency test results, including columns: `algorithm`, `statistic`, and `p.value` (for sample splitting).

Heterogeneity A tibble with heterogeneity test results, including columns: `algorithm`, `statistic`, and `p.value` (for sample splitting).

Consistency_cv A tibble with consistency test results for cross-validation.

Heterogeneity_cv A tibble with heterogeneity test results for cross-validation.

Note: The output contains either the first two or last two elements depending on whether cross-validation was used.

test_itr	<i>Conduct hypothesis tests</i>
----------	---------------------------------

Description

Conduct hypothesis tests

Usage

```
test_itr(model, nsim = 1000, centered = TRUE, ...)
```

Arguments

model	Fitted model. Usually an output from <code>evaluate_hte</code> .
nsim	Number of Monte Carlo simulations used to simulate the null distributions. Default is 1000.
centered	Whether to center outcomes before testing.
...	Further arguments passed to the function.

Value

An object of `test_itr` class

URATE	<i>This function use individualized treatment rule to identify exceptional responders. The details of the methods for this design are given in Imai and Li (2023).</i>
-------	--

Description

This function use individualized treatment rule to identify exceptional responders. The details of the methods for this design are given in Imai and Li (2023).

Usage

```
URATE(D, tau, Y)
```

Arguments

D	A vector of the unit-level binary treatment receipt variable for each sample.
tau	A vector of the unit-level continuous score. Conditional Average Treatment Effect is one possible measure.
Y	A vector of the outcome variable of interest for each sample.

Value

A list that contains the following items:

rate	The estimated vector of URATE of length Y.
sd	The estimated vector of standard deviation of URATE.

Author(s)

Michael Lingzhi Li, Technology and Operations Management, Harvard Business School <mili@hbs.edu>, <https://www.michaellz.com/>;

References

Imai and Li (2022). “Statistical Inference for Heterogeneous Treatment Effects Discovered by Generic Machine Learning in Randomized Experiments”,

Examples

```
D <- c(1, 0, 1, 0, 1, 0, 1, 0)
tau <- c(0, 0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7)
Y <- c(4, 5, 0, 2, 4, 1, -4, 3)
ratelist <- URATE(D, tau, Y)
ratelist$rate
ratelist$sd
```

Index

* **band**

URATE, [15](#)

* **evaluation**

consist.test, [3](#)

consistcv.test, [4](#)

GATE, [7](#)

GATEcv, [8](#)

het.test, [9](#)

hetcv.test, [10](#)

* **uniform**

URATE, [15](#)

compute_qoi, [2](#)

compute_qoi_user, [2](#)

consist.test, [3](#), [3](#)

consistcv.test, [4](#), [4](#)

estimate_hte, [5](#)

evaluate_hte, [6](#)

GATE, [7](#), [7](#)

GATEcv, [8](#), [8](#)

het.test, [9](#), [9](#)

hetcv.test, [10](#), [10](#)

plot.hte, [11](#)

plot_CI, [11](#)

plot_CI.hte, [12](#)

print.summary.hte, [12](#)

print.summary.test_hte, [13](#)

summary.hte, [13](#)

summary.test_hte, [14](#)

test_itr, [15](#)

URATE, [15](#)