

Package ‘ggspatial’

September 15, 2026

Type Package

Title Spatial Data Framework for ggplot2

Version 1.1.11

Maintainer Dewey Dunnington <dewey@fishandwhistle.net>

Description Spatial data plus the power of the ggplot2 framework means easier mapping when input data are already in the form of spatial objects.

License GPL-3

Depends R (>= 2.10)

Imports sf, ggplot2 (>= 3.0.0), rosm (>= 0.3.2), abind, methods, tibble, scales, tidyr, rlang, grid, glue

Suggests prettymapr, knitr, rmarkdown, sp, raster, terra, testthat (>= 3.0.0), dplyr, withr, ggrepel, stars, covr, vdiff, lwgeom

URL <https://paleolimbot.github.io/ggspatial/>,
<https://github.com/paleolimbot/ggspatial>

BugReports <https://github.com/paleolimbot/ggspatial/issues>

Encoding UTF-8

Config/testthat/edition 3

Config/roxygen2/version 8.0.0

NeedsCompilation no

Author Dewey Dunnington [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-9415-4582>>),
Brent Thorne [ctb] (ORCID: <<https://orcid.org/0000-0002-1099-3857>>),
Diego Hernangómez [ctb] (ORCID:
<<https://orcid.org/0000-0001-8457-4658>>)

Repository CRAN

Date/Publication 2026-09-14 22:10:02 UTC

Contents

annotation_map_tile	2
annotation_north_arrow	3
annotation_scale	5
annotation_spatial_hline	6
df_spatial	8
fixed_plot_aspect	9
geom_polypath	10
geom_spatial_rect	11
geom_spatial_segment	12
layer_spatial	14
layer_spatial.bbox	16
layer_spatial.Raster	17
layer_spatial.SpatRaster	18
layer_spatial.stars	19
load_longlake_data	21
north_arrow_orienteering	22
stat_spatial_identity	23
xy_transform	25
Index	26

annotation_map_tile	<i>Add background OSM tiles</i>
---------------------	---------------------------------

Description

Uses `rosm::osm.image()` to add background tiles. If you are publishing a map using these tiles, make sure to use the proper attribution (e.g., "Copyright OpenStreetMap contributors" when using an OpenStreetMap-based tile set).

Usage

```
annotation_map_tile(  
  type = "osm",  
  zoom = NULL,  
  zoomin = -2,  
  forcedownload = FALSE,  
  cachedir = NULL,  
  progress = c("text", "none"),  
  quiet = TRUE,  
  interpolate = TRUE,  
  data = NULL,  
  mapping = NULL,  
  alpha = 1,  
  api_key = NULL  
)
```

GeomMapTile

Arguments

type	The map type (one of that returned by rosm::osm.types)
zoom	The zoom level (overrides zoomin)
zoomin	Delta on default zoom. The default value is designed to download fewer tiles than you probably want. Use -1 or 0 to increase the resolution.
forcedownload	Re-download cached tiles?
cachedir	Specify cache directory
progress	Use progress = "none" to suppress progress and zoom output
quiet	Use quiet = FALSE to see which URLs are downloaded
interpolate	Passed to grid::rasterGrob()
data, mapping	Specify data and mapping to use this geom with facets
alpha	Use to make this layer semi-transparent
api_key	API key used for CARTO map types. If NULL, rosm uses the CARTO_API_KEY environment variable.

Value

A ggplot2 layer

Examples

```
library(ggplot2)
load_longlake_data(which = "longlake_waterdf")

ggplot() +
  annotation_map_tile(zoom = 13, cachedir = system.file("rosm.cache", package = "ggspatial")) +
  geom_sf(data = longlake_waterdf, fill = NA, col = "grey50")
```

annotation_north_arrow

Spatial-aware north arrow

Description

Spatial-aware north arrow

Usage

```
annotation_north_arrow(
  mapping = NULL,
  data = NULL,
  ...,
  height = unit(1.5, "cm"),
  width = unit(1.5, "cm"),
  pad_x = unit(0.25, "cm"),
  pad_y = unit(0.25, "cm"),
  rotation = NULL,
  style = north_arrow_orienteering
)
```

GeomNorthArrow

Arguments

mapping, data, ...	See Aesthetics
height, width	Height and width of north arrow
pad_x, pad_y	Padding between north arrow and edge of frame
rotation	Override the rotation of the north arrow (degrees counterclockwise)
style	A grob or callable that produces a grob that will be drawn as the north arrow. See north_arrow_orienteering for options.

Value

A ggplot2 layer

Aesthetics

The following can be used as parameters or aesthetics. Using them as aesthetics is useful when facets are used to display multiple panels, and a different (or missing) scale bar is required in different panels. Otherwise, just pass them as arguments to `annotation_north_arrow()`.

- `which_north`: "grid" results in a north arrow always pointing up; "true" always points to the north pole from whichever corner of the map the north arrow is in.
- `location`: Where to put the scale bar ("tl" for top left, etc.)

Examples

```
cities <- data.frame(
  x = c(-63.58595, 116.41214),
  y = c(44.64862, 40.19063),
  city = c("Halifax", "Beijing")
)

ggplot(cities) +
```

```

geom_spatial_point(aes(x, y), crs = 4326) +
annotation_north_arrow(which_north = "true") +
coord_sf(crs = 3995)

ggplot(cities) +
  geom_spatial_point(aes(x, y), crs = 4326) +
  annotation_north_arrow(which_north = "grid") +
  coord_sf(crs = 3995)

```

annotation_scale	<i>Spatial-aware scalebar annotation</i>
------------------	--

Description

Spatial-aware scalebar annotation

Usage

```

annotation_scale(
  mapping = NULL,
  data = NULL,
  ...,
  plot_unit = NULL,
  bar_cols = c("black", "white"),
  line_width = 1,
  height = unit(0.25, "cm"),
  pad_x = unit(0.25, "cm"),
  pad_y = unit(0.25, "cm"),
  text_pad = unit(0.15, "cm"),
  text_cex = 0.7,
  text_face = NULL,
  text_family = "",
  tick_height = 0.6
)

```

GeomScaleBar

Arguments

mapping, data, ...	See Aesthetics
plot_unit	For non-coord_sf applications, specify the unit for x and y coordinates. Must be one of km, m, cm, mi, ft, or in.
bar_cols	Colours to use for the bars
line_width	Line width for scale bar
height	Height of scale bar

pad_x, pad_y Distance between scale bar and edge of panel
 text_pad, text_cex, text_face, text_family
 Parameters for label
 tick_height Height of ticks relative to height of scale bar

Value

A ggplot2 layer.

Aesthetics

The following can be used as parameters or aesthetics. Using them as aesthetics is useful when facets are used to display multiple panels, and a different (or missing) scale bar is required in different panels. Otherwise, just pass them as arguments to `annotation_scale`.

- `width_hint`: The (suggested) proportion of the plot area which the scalebar should occupy.
- `unit_category`: Use "metric" or "imperial" units.
- `style`: One of "bar" or "ticks"
- `location`: Where to put the scale bar ("tl" for top left, etc.)
- `line_col` and `text_col`: Line and text colour, respectively

Examples

```
cities <- data.frame(
  x = c(-63.58595, 116.41214),
  y = c(44.64862, 40.19063),
  city = c("Halifax", "Beijing")
)

ggplot(cities) +
  geom_spatial_point(aes(x, y), crs = 4326) +
  annotation_scale() +
  coord_sf(crs = 3995)
```

annotation_spatial_hline

Projected horizontal and vertical lines

Description

Projected horizontal and vertical lines

Usage

```
annotation_spatial_hline(
  mapping = NULL,
  data = NULL,
  stat = "identity",
  ...,
  intercept = waiver(),
  limits = NULL,
  detail = 100,
  crs = NULL,
  na.rm = FALSE,
  show.legend = NA
)
```

```
annotation_spatial_vline(
  mapping = NULL,
  data = NULL,
  stat = "identity",
  ...,
  intercept = waiver(),
  limits = NULL,
  detail = 100,
  crs = NULL,
  na.rm = FALSE,
  show.legend = NA
)
```

```
GeomSpatialXline
```

Arguments

mapping	An aesthetic mapping created with <code>ggplot2::aes()</code> .
data	A data frame or other object, coerced to a data.frame by <code>ggplot2::fortify()</code> .
stat	Statistical transformation to use on this layer. See <code>ggplot2::layer()</code> .
...	Passed to the combined stat/geom as parameters or fixed aesthetics.
intercept	The x or y value that should be constant in the given crs. Can also be passed as an aesthetic through data and mapping.
limits	Use NULL to guess the minimum and maximum x or y value in the non-constant dimension, or specify a vector of length 2 to specify manually.
detail	The number of points that should be used when converting the line into segments.
crs	The crs of the x and y aesthetics, or NULL to use default lon/lat crs (with a message).
na.rm	Should missing aesthetic values be removed?
show.legend	Should the legend be shown?

Examples

```
cities <- data.frame(
  x = c(-63.58595, 116.41214, 0),
  y = c(44.64862, 40.19063, 89.9),
  city = c("Halifax", "Beijing", "North Pole")
)

p <- ggplot(cities, aes(x, y, label = city)) +
  geom_spatial_point(crs = 4326) +
  # view of the north pole
  coord_sf(crs = 3995)

p +
  # longitude lines
  annotation_spatial_vline(
    intercept = seq(-180, 180, by = 10),
    crs = 4326
  ) +
  # latitude lines
  annotation_spatial_hline(
    intercept = seq(0, 90, by = 10),
    crs = 4326
  )
```

df_spatial

Create a ggplot-friendly data frame from a spatial object

Description

Create a ggplot-friendly data frame from a spatial object

Usage

```
df_spatial(x, ...)
```

Arguments

x	A spatial object
...	Passed to specific methods

Value

A tibble with coordinates as x and y, features as feature_id, and parts as part_id.

Examples

```
load_longlake_data(which = c("longlake_osm", "longlake_depthdf"))
df_spatial(longlake_osm)
df_spatial(longlake_depthdf)
df_spatial(as(longlake_depthdf, "Spatial"))
```

fixed_plot_aspect	<i>Enforce a plot aspect ratio</i>
-------------------	------------------------------------

Description

When using a fixed-aspect coordinate system, `fixed_plot_aspect()` expands either the width or height of the plot to ensure that the output has dimensions that make sense. This is a useful workaround for getting reasonable-shaped plots when using `ggplot2::coord_sf()` or `ggplot2::coord_fixed()` when the data happen to be aligned vertically or horizontally.

Usage

```
fixed_plot_aspect(ratio = 1)
```

Arguments

ratio	The desired aspect ratio (width / height)
-------	---

Value

A `ggplot2::layer()` that can be added to a `ggplot2::ggplot()`.

Examples

```
library(ggplot2)
df <- data.frame(x = 0:5, y = seq(0, 10, length.out = 6))
ggplot(df, aes(x, y)) +
  geom_point() +
  fixed_plot_aspect(ratio = 1) +
  coord_fixed()
```

geom_polypath

Polygons with holes in ggplot2

Description

This geometry used to plot polygons with holes in ggplot2 at the more correctly than [geom_polygon](#); however, in recent R and ggplot2 versions this is no longer needed.

Usage

```
geom_polypath(
  mapping = NULL,
  data = NULL,
  stat = "identity",
  position = "identity",
  na.rm = FALSE,
  show.legend = NA,
  inherit.aes = TRUE,
  rule = "winding",
  ...
)
```

Arguments

mapping	An aesthetic mapping, created with aes . The aesthetic will mostly likely need to contain a group mapping.
data	A data.frame containing the coordinates to plot.
stat	A statistic to apply (most likely "identity")
position	A position to apply (most likely "identity")
na.rm	Should missing coordinate be removed?
show.legend	Should a legend be shown for mapped aesthetics?
inherit.aes	Should aesthetics be inherited?
rule	A fill rule to apply. One of "winding" or "evenodd".
...	Passed to the geom and/or stat.

Value

A ggplot2 layer

Examples

```
library(ggplot2)
load_longlake_data(which = "longlake_waterdf")
ggplot(df_spatial(longlake_waterdf), aes(x, y, group = piece_id)) +
  geom_polypath()
```

geom_spatial_rect	<i>Projected rectangular regions</i>
-------------------	--------------------------------------

Description

If you need to plot a `sf::st_bbox()`, use `layer_spatial()` instead. While the implementation is slightly different, these functions are intended to behave identically to `ggplot2::geom_rect()` and `ggplot2::geom_tile()`.

Usage

```
geom_spatial_rect(
  mapping = NULL,
  data = NULL,
  ...,
  crs = NULL,
  detail = 30,
  linejoin = "mitre",
  na.rm = FALSE,
  show.legend = NA,
  inherit.aes = TRUE
)
```

```
geom_spatial_tile(
  mapping = NULL,
  data = NULL,
  ...,
  crs = NULL,
  detail = 30,
  linejoin = "mitre",
  na.rm = FALSE,
  show.legend = NA,
  inherit.aes = TRUE
)
```

StatSpatialRect

StatSpatialTile

Arguments

mapping	An aesthetic mapping created with <code>ggplot2::aes()</code> .
data	A data frame or other object, coerced to a data.frame by <code>ggplot2::fortify()</code> .
...	Passed to the combined stat/geom as parameters or fixed aesthetics.
crs	The crs of the x and y aesthetics, or NULL to use default lon/lat crs (with a message).

detail	Passed to <code>sf::st_segmentize()</code> : the number of line segments per quadrant of the bounding box. Increase this number for a smoother projected bounding box.
linejoin	How corners should be joined
na.rm	Should missing aesthetic values be removed?
show.legend, inherit.aes	See <code>ggplot2::layer()</code> .

Examples

```
library(ggplot2)
tile_df <- expand.grid(
  x = seq(-140, -52, by = 20),
  y = seq(40, 70, by = 10)
)

ggplot(tile_df, aes(x, y)) +
  geom_spatial_tile(crs = 4326) +
  coord_sf(crs = 3979)

# the same plot using geom_spatial_rect()
ggplot(
  tile_df,
  aes(xmin = x - 10, xmax = x + 10, ymin = y - 5, ymax = y + 5)
) +
  geom_spatial_rect(crs = 4326) +
  coord_sf(crs = 3979)
```

geom_spatial_segment *Spatial line segments*

Description

While the implementation is slightly different, this function is intended to behave identically to `ggplot2::geom_segment()`. Use `great_circle = FALSE` and `detail = NULL` if you wish ignore the fact that the earth is round.

Usage

```
geom_spatial_segment(
  mapping = NULL,
  data = NULL,
  ...,
  crs = NULL,
  detail = waiver(),
  great_circle = TRUE,
  wrap_dateline = TRUE,
  arrow = NULL,
```

```

    lineend = "butt",
    linejoin = "round",
    na.rm = FALSE,
    show.legend = NA,
    inherit.aes = TRUE
  )

```

```
StatSpatialSegment
```

Arguments

mapping	An aesthetic mapping created with <code>ggplot2::aes()</code> .
data	A data frame or other object, coerced to a data.frame by <code>ggplot2::fortify()</code> .
...	Passed to the combined stat/geom as parameters or fixed aesthetics.
crs	The crs of the x and y aesthetics, or NULL to use default lon/lat crs (with a message).
detail	Passed to <code>sf::st_segmentize()</code> : the number of line segments per quadrant of the bounding box. Increase this number for a smoother projected bounding box.
great_circle	If TRUE, use <code>lwgeom::st_geod_segmentize()</code> to connect the (x, y) and (xend, yend) with the shortest possible great circle along the earth.
wrap_dateline	When using <code>great_circle = TRUE</code> , using <code>wrap_dateline = TRUE</code> splits the great circle along the dateline. You may want to pass FALSE here if using <code>arrow</code> and a projection that wraps the dateline.
arrow	An arrow specification as a call to <code>grid::arrow()</code> .
lineend	See <code>ggplot2::geom_segment()</code> .
linejoin	How corners should be joined
na.rm	Should missing aesthetic values be removed?
show.legend, inherit.aes	See <code>ggplot2::layer()</code> .

Examples

```

library(ggplot2)

# visualize flights from
# Halifax -> Anchorage -> Berlin -> Halifax
cities <- data.frame(
  lon = c(-63.58595, 116.41214, 13.50, -149.75),
  lat = c(44.64862, 40.19063, 52.51, 61.20),
  city = c("Halifax", "Beijing", "Berlin", "Anchorage"),
  city_to = c("Anchorage", "Beijing", "Berlin", "Halifax")
)

cities$lon_end <- cities$lon[c(4, 3, 1, 2)]
cities$lat_end <- cities$lat[c(4, 3, 1, 2)]

p <- ggplot(cities, aes(lon, lat, xend = lon_end, yend = lat_end)) +

```

```

geom_spatial_point(crs = 4326)

# by default, geom_spatial_segment() connects points
# using the shortest distance along the face of the earth
# wrapping at the date line
p +
  geom_spatial_segment(crs = 4326) +
  coord_sf(crs = 3857)

# to let the projection handle the dateline,
# use `wrap_dateline = FALSE` (most useful for
# when using `arrow`)
p +
  geom_spatial_segment(
    wrap_dateline = FALSE,
    arrow = grid::arrow(),
    crs = 4326
  ) +
  coord_sf(crs = 3995)

# to ignore the roundness of the earth, use
# `great_circle = FALSE`
p +
  geom_spatial_segment(
    great_circle = FALSE,
    arrow = grid::arrow(),
    crs = 4326
  ) +
  coord_sf(crs = 3995)

```

layer_spatial

Turn a spatial object into a ggplot2 layer

Description

See also [layer_spatial.Raster\(\)](#), [layer_spatial.stars\(\)](#), [layer_spatial.SpatRaster\(\)](#) and [layer_spatial.bbox\(\)](#) for implementations for other types of spatial objects.

Usage

```

layer_spatial(data, mapping, ...)

annotation_spatial(data, mapping, ...)

## Default S3 method:
layer_spatial(
  data,
  mapping = aes(),

```

```

    inherit.aes = FALSE,
    sf_params = list(),
    ...
  )

## Default S3 method:
annotation_spatial(
  data,
  mapping = aes(),
  inherit.aes = FALSE,
  sf_params = list(),
  ...
)

shadow_spatial(data, ...)

## Default S3 method:
shadow_spatial(data, ...)

```

Arguments

<code>data</code>	An object that can be coerced to an sf object using st_as_sf .
<code>mapping</code>	A mapping, created using aes .
<code>...</code>	Passed to geom_sf
<code>inherit.aes</code>	Inherit aesthetics from <code>ggplot()</code> ?
<code>sf_params</code>	Passed to st_as_sf .

Value

A `ggplot2` [layer](#).

Examples

```

library(ggplot2)
load_longlake_data(
  which = c(
    "longlake_roadsdf",
    "longlake_depthdf",
    "longlake_depth_raster"
  ),
  raster_format = "terra"
)

ggplot() +

# annotation_spatial() layers don't train the scales, so data stays central
annotation_spatial(longlake_roadsdf, size = 2, col = "black") +
annotation_spatial(longlake_roadsdf, size = 1.6, col = "white") +

```

```
# raster layers train scales and get projected automatically
layer_spatial(longlake_depth_raster, aes(alpha = after_stat(band1)), fill = "darkblue") +
  scale_alpha_continuous(na.value = 0) +

# layer_spatial() layers train the scales
layer_spatial(longlake_depthdf, aes(col = DEPTH_M)) +

# spatial-aware automagic scale bar
annotation_scale(location = "tl") +

# spatial-aware automagic north arrow
annotation_north_arrow(location = "br", which_north = "true")
```

layer_spatial.bbox	<i>Add a bounding box to a map</i>
--------------------	------------------------------------

Description

To include a bounding box without drawing it, use [shadow_spatial\(\)](#) on the original object.

Usage

```
## S3 method for class 'bbox'
layer_spatial(data, mapping = aes(), ..., detail = 30)

## S3 method for class 'bbox'
annotation_spatial(data, mapping = aes(), ..., detail = 30)

## S3 method for class 'bbox'
shadow_spatial(data, ..., detail = 30)
```

Arguments

data	A bounding box generated by sf::st_bbox()
mapping	A mapping, created using aes .
...	Passed to geom_sf
detail	Passed to sf::st_segmentize() : the number of line segments per quadrant of the bounding box. Increase this number for a smoother projected bounding box.

Examples

```
library(ggplot2)
load_longlake_data(which = c("longlake_waterdf", "longlake_depthdf"))
ggplot() +
  layer_spatial(sf::st_bbox(longlake_waterdf)) +
  layer_spatial(longlake_depthdf)
```

```
# use shadow_spatial() to include the geographic area of an object
# without drawing it
ggplot() +
  shadow_spatial(longlake_waterdf) +
  layer_spatial(longlake_depthdf)
```

layer_spatial.Raster *Spatial ggplot2 layer for raster objects*

Description

This is intended for use with RGB(A) rasters (e.g., georeferenced imagery or photos). To work with bands as if they were columns, use `df_spatial()` and `ggplot2::geom_raster()`.

Usage

```
## S3 method for class 'Raster'
layer_spatial(
  data,
  mapping = NULL,
  interpolate = NULL,
  is_annotation = FALSE,
  lazy = FALSE,
  dpi = 150,
  ...
)

## S3 method for class 'Raster'
annotation_spatial(data, mapping = NULL, interpolate = NULL, ...)
```

StatSpatialRaster

StatSpatialRasterAnnotation

StatSpatialRasterDf

GeomSpatialRaster

Arguments

data	A Raster object
mapping	Currently, only RGB or RGBA rasters are supported. In the future, one may be able to map specific bands to the fill and alpha aesthetics.
interpolate	Interpolate resampling for rendered raster image

is_annotation	Lets raster exist without modifying scales
lazy	Delay projection and resample of raster until the plot is being rendered
dpi	if lazy = TRUE, the dpi to which the raster should be resampled
...	Passed to other methods

Value

A ggplot2 layer

Examples

```
library(ggplot2)
load_longlake_data(which = c("longlake_osm", "longlake_depth_raster"))
ggplot() + layer_spatial(longlake_osm)
ggplot() + layer_spatial(longlake_depth_raster) + scale_fill_continuous(na.value = NA)
```

layer_spatial.SpatRaster

Spatial ggplot2 layer for SpatRaster objects

Description

This is intended for use with RGB(A) rasters (e.g., georeferenced imagery or photos). To work with bands as if they were columns, use `df_spatial()` and `ggplot2::geom_raster()`.

Usage

```
## S3 method for class 'SpatRaster'
layer_spatial(
  data,
  mapping = NULL,
  interpolate = NULL,
  is_annotation = FALSE,
  lazy = FALSE,
  dpi = 150,
  ...
)

## S3 method for class 'SpatRaster'
annotation_spatial(data, mapping = NULL, interpolate = NULL, ...)
```

StatSpatRaster

StatSpatRasterAnnotation

StatSpatRasterDf

GeomSpatRaster

Arguments

data	A SpatRaster object created with <code>terra::rast()</code> .
mapping	Currently, only RGB or RGBA rasters are supported. In the future, one may be able to map specific bands to the fill and alpha aesthetics.
interpolate	Interpolate resampling for rendered raster image
is_annotation	Lets raster exist without modifying scales
lazy	Delay projection and resample of raster until the plot is being rendered
dpi	if lazy = TRUE, the dpi to which the raster should be resampled
...	Passed to other methods

Value

A ggplot2 layer

Examples

```
library(ggplot2)
load_longlake_data(
  which = c(
    "longlake_osm",
    "longlake_depth_raster"
  ),
  raster_format = "terra"
)
ggplot() +
  layer_spatial(longlake_osm)

ggplot() +
  layer_spatial(longlake_depth_raster) +
  scale_fill_continuous(
    na.value = NA,
    type = "viridis"
  )
```

layer_spatial.stars *Spatial ggplot2 layer for stars objects*

Description

This is intended for use with RGB(A) rasters (e.g., georeferenced imagery or photos). To work with bands as if they were columns, use `df_spatial()` and `ggplot2::geom_raster()`.

Usage

```
## S3 method for class 'stars'
layer_spatial(
  data,
  mapping = NULL,
  interpolate = NULL,
  is_annotation = FALSE,
  lazy = FALSE,
  dpi = 150,
  options = character(),
  ...
)

## S3 method for class 'stars'
annotation_spatial(data, mapping = NULL, interpolate = NULL, ...)

StatSpatialStars

StatSpatialStarsAnnotation

StatSpatialStarsDf

GeomSpatialStars
```

Arguments

<code>data</code>	A stars object
<code>mapping</code>	Currently, only RGB or RGBA rasters are supported. In the future, one may be able to map specific bands to the fill and alpha aesthetics.
<code>interpolate</code>	Interpolate resampling for rendered raster image
<code>is_annotation</code>	Lets raster exist without modifying scales
<code>lazy</code>	Delay projection and resample of raster until the plot is being rendered
<code>dpi</code>	if lazy = TRUE, the dpi to which the raster should be resampled
<code>options</code>	GDAL options for warping/resampling (see st_warp)
<code>...</code>	Passed to other methods

Value

A ggplot2 layer

Examples

```
library(ggplot2)
load_longlake_data(
  which = c(
    "longlake_osm",
```

```

      "longlake_depth_raster"
    ),
    raster_format = "stars"
  )
  ggplot() +
    layer_spatial(longlake_osm)

  ggplot() +
    layer_spatial(longlake_depth_raster) +
    scale_fill_continuous(
      na.value = NA,
      type = "viridis"
    )

```

load_longlake_data	<i>Load longlake test data</i>
--------------------	--------------------------------

Description

Load longlake test data

Usage

```

load_longlake_data(
  env = parent.frame(),
  vector_format = c("sf", "sp"),
  raster_format = c("terra", "stars", "stars_proxy", "raster"),
  which = NULL
)

```

Arguments

env	The environment in which to assign the objects
vector_format, raster_format	The format in which objects should be loaded
which	An optional subset of objects to be loaded

Source

The Nova Scotia Topographic Database (<https://geonova.novascotia.ca/>) and Open Street Map (<https://www.openstreetmap.org/>).

Examples

```
load_longlake_data(which = "longlake_waterdf")
```

`north_arrow_orienteering`*North arrow styles*

Description

North arrow styles

Usage

```
north_arrow_orienteering(  
    line_width = 1,  
    line_col = "black",  
    fill = c("white", "black"),  
    text_col = "black",  
    text_family = "",  
    text_face = NULL,  
    text_size = 10,  
    text_angle = 0  
)  
  
north_arrow_fancy_orienteering(  
    line_width = 1,  
    line_col = "black",  
    fill = c("white", "black"),  
    text_col = "black",  
    text_family = "",  
    text_face = NULL,  
    text_size = 10,  
    text_angle = 0  
)  
  
north_arrow_minimal(  
    line_width = 1,  
    line_col = "black",  
    fill = "black",  
    text_col = "black",  
    text_family = "",  
    text_face = NULL,  
    text_size = 10  
)  
  
north_arrow_nautical(  
    line_width = 1,  
    line_col = "black",  
    fill = c("black", "white"),  
    text_size = 10,
```

```
text_face = NULL,  
text_family = "",  
text_col = "black",  
text_angle = 0  
)
```

Arguments

line_width, line_col, fill

Parameters customizing the appearance of the north arrow

text_col, text_family, text_face, text_size, text_angle

Parameters customizing the text of the north arrow

Value

A Grob with npc coordinates (more or less) 0 to 1

Examples

```
grid::grid.newpage()  
grid::grid.draw(north_arrow_orienteering())  
  
grid::grid.newpage()  
grid::grid.draw(north_arrow_fancy_orienteering())  
  
grid::grid.newpage()  
grid::grid.draw(north_arrow_minimal())  
  
grid::grid.newpage()  
grid::grid.draw(north_arrow_nautical())
```

stat_spatial_identity *Spatial-aware ggplot2 layers*

Description

These layers are much like their counterparts, [stat_identity](#), [geom_point](#), [geom_path](#), and [geom_polygon](#), except they have a `crs` argument that ensures they are projected when using [coord_sf](#). Stats are applied to the x and y coordinates that have been transformed.

Usage

```
stat_spatial_identity(  
  mapping = NULL,  
  data = NULL,  
  crs = NULL,  
  geom = "point",
```

```

    position = "identity",
    ...,
    show.legend = NA,
    inherit.aes = TRUE
  )

geom_spatial_point(mapping = NULL, data = NULL, crs = NULL, ...)

geom_spatial_path(mapping = NULL, data = NULL, crs = NULL, ...)

geom_spatial_polygon(mapping = NULL, data = NULL, crs = NULL, ...)

geom_spatial_text(mapping = NULL, data = NULL, crs = NULL, ...)

geom_spatial_label(mapping = NULL, data = NULL, crs = NULL, ...)

geom_spatial_text_repel(mapping = NULL, data = NULL, crs = NULL, ...)

geom_spatial_label_repel(mapping = NULL, data = NULL, crs = NULL, ...)

```

Arguments

mapping	An aesthetic mapping created with ggplot2::aes() .
data	A data frame or other object, coerced to a data.frame by ggplot2::fortify() .
crs	The crs of the x and y aesthetics, or NULL to use default lon/lat crs (with a message).
geom	The geometry to use.
position	The position to use.
...	Passed to the combined stat/geom as parameters or fixed aesthetics.
show.legend, inherit.aes	See ggplot2::layer() .

Value

A [ggplot2::layer\(\)](#).

Examples

```

cities <- data.frame(
  x = c(-63.58595, 116.41214, 0),
  y = c(44.64862, 40.19063, 89.9),
  city = c("Halifax", "Beijing", "North Pole")
)

library(ggrepel)
ggplot(cities, aes(x, y)) +
  geom_spatial_point(crs = 4326) +
  stat_spatial_identity(aes(label = city), geom = "label_repel") +

```

```
coord_sf(crs = 3857)
```

xy_transform	<i>Coordinate transform</i>
--------------	-----------------------------

Description

Coordinate transform, propotating non-finite cases.

Usage

```
xy_transform(x, y, from = 4326, to = 4326, na.rm = FALSE)
```

Arguments

x	The x coordinate
y	The y coordinate
from	From CRS
to	To CRS
na.rm	Warn for non-finite cases?

Value

A data.frame with x and y components.

Examples

```
xy_transform(c(1, 2, 3), c(1, 2, 3), to = 3857)
xy_transform(c(1, 2, 3), c(NA, NA, NA), to = 3857)
xy_transform(c(1, 2, 3), c(NA, 2, 3), to = 3857)
xy_transform(c(1, 2, 3), c(1, 2, NA), to = 3857)
```

Index

aes, [10](#), [15](#), [16](#)
annotation_map_tile, [2](#)
annotation_north_arrow, [3](#)
annotation_scale, [5](#)
annotation_spatial(layer_spatial), [14](#)
annotation_spatial.bbox
 (layer_spatial.bbox), [16](#)
annotation_spatial.Raster
 (layer_spatial.Raster), [17](#)
annotation_spatial.SpatRaster
 (layer_spatial.SpatRaster), [18](#)
annotation_spatial.stars
 (layer_spatial.stars), [19](#)
annotation_spatial_hline, [6](#)
annotation_spatial_vline
 (annotation_spatial_hline), [6](#)

coord_sf, [23](#)

df_spatial, [8](#)
df_spatial(), [17–19](#)

fixed_plot_aspect, [9](#)
fixed_plot_aspect(), [9](#)

geom_path, [23](#)
geom_point, [23](#)
geom_polygon, [10](#), [23](#)
geom_polypath, [10](#)
geom_sf, [15](#), [16](#)
geom_spatial_label
 (stat_spatial_identity), [23](#)
geom_spatial_label_repel
 (stat_spatial_identity), [23](#)
geom_spatial_path
 (stat_spatial_identity), [23](#)
geom_spatial_point
 (stat_spatial_identity), [23](#)
geom_spatial_polygon
 (stat_spatial_identity), [23](#)

geom_spatial_rect, [11](#)
geom_spatial_segment, [12](#)
geom_spatial_text
 (stat_spatial_identity), [23](#)
geom_spatial_text_repel
 (stat_spatial_identity), [23](#)
geom_spatial_tile(geom_spatial_rect),
 [11](#)
GeomMapTile(annotation_map_tile), [2](#)
GeomNorthArrow
 (annotation_north_arrow), [3](#)
GeomScaleBar(annotation_scale), [5](#)
GeomSpatialRaster
 (layer_spatial.Raster), [17](#)
GeomSpatialStars(layer_spatial.stars),
 [19](#)
GeomSpatialXline
 (annotation_spatial_hline), [6](#)
GeomSpatRaster
 (layer_spatial.SpatRaster), [18](#)
ggplot2::aes(), [7](#), [11](#), [13](#), [24](#)
ggplot2::coord_fixed(), [9](#)
ggplot2::coord_sf(), [9](#)
ggplot2::fortify(), [7](#), [11](#), [13](#), [24](#)
ggplot2::geom_raster(), [17–19](#)
ggplot2::geom_rect(), [11](#)
ggplot2::geom_segment(), [12](#), [13](#)
ggplot2::geom_tile(), [11](#)
ggplot2::ggplot(), [9](#)
ggplot2::layer(), [7](#), [9](#), [12](#), [13](#), [24](#)
grid::arrow(), [13](#)
grid::rasterGrob(), [3](#)

layer, [15](#)
layer_spatial, [14](#)
layer_spatial(), [11](#)
layer_spatial.bbox, [16](#)
layer_spatial.bbox(), [14](#)
layer_spatial.Raster, [17](#)
layer_spatial.Raster(), [14](#)

- layer_spatial.SpatRaster, [18](#)
- layer_spatial.SpatRaster(), [14](#)
- layer_spatial.stars, [19](#)
- layer_spatial.stars(), [14](#)
- load_longlake_data, [21](#)
- lwgeom::st_geod_segmentize(), [13](#)

- north_arrow_fancy_orienteering
 - (north_arrow_orienteering), [22](#)
- north_arrow_minimal
 - (north_arrow_orienteering), [22](#)
- north_arrow_nautical
 - (north_arrow_orienteering), [22](#)
- north_arrow_orienteering, [4](#), [22](#)

- rosm::osm.image(), [2](#)
- rosm::osm.types, [3](#)

- sf::st_bbox(), [11](#), [16](#)
- sf::st_segmentize(), [12](#), [13](#), [16](#)
- shadow_spatial(layer_spatial), [14](#)
- shadow_spatial(), [16](#)
- shadow_spatial.bbox
 - (layer_spatial.bbox), [16](#)
- st_as_sf, [15](#)
- st_warp, [20](#)
- stat_identity, [23](#)
- stat_spatial_identity, [23](#)
- StatSpatialRaster
 - (layer_spatial.Raster), [17](#)
- StatSpatialRasterAnnotation
 - (layer_spatial.Raster), [17](#)
- StatSpatialRasterDf
 - (layer_spatial.Raster), [17](#)
- StatSpatialRect (geom_spatial_rect), [11](#)
- StatSpatialSegment
 - (geom_spatial_segment), [12](#)
- StatSpatialStars (layer_spatial.stars), [19](#)
- StatSpatialStarsAnnotation
 - (layer_spatial.stars), [19](#)
- StatSpatialStarsDf
 - (layer_spatial.stars), [19](#)
- StatSpatialTile (geom_spatial_rect), [11](#)
- StatSpatRaster
 - (layer_spatial.SpatRaster), [18](#)
- StatSpatRasterAnnotation
 - (layer_spatial.SpatRaster), [18](#)
- StatSpatRasterDf
 - (layer_spatial.SpatRaster), [18](#)
- terra::rast(), [19](#)
- xy_transform, [25](#)