

Package ‘ggwidth’

September 11, 2026

Title Publication-Quality 'ggplot2' Geom Width

Version 0.2.0

Description Width helper functions for publication-quality 'ggplot2' visualisation. These functions make it easier to create geoms such as bars that have a consistent width appearance across plots.

License MIT + file LICENSE

URL <https://github.com/davidhodge931/ggwidth>,
<https://davidhodge931.github.io/ggwidth/>

BugReports <https://github.com/davidhodge931/ggwidth/issues>

Depends R (>= 4.1.0)

Imports ggplot2 (>= 4.0.0), grid, rlang

Suggests dplyr, forcats, patchwork, testthat (>= 3.0.0), tibble, withr

Encoding UTF-8

Language en-GB

Config/testthat/edition 3

Config/roxygen2/version 8.1.0

NeedsCompilation no

Author David Hodge [aut, cre, cph] (ORCID:
<<https://orcid.org/0000-0002-3868-7501>>)

Maintainer David Hodge <davidhodge931@gmail.com>

Repository CRAN

Date/Publication 2026-09-10 23:40:02 UTC

Contents

get_width	2
update_equiwidth	3
Index	4

get_width	<i>Standardise ggplot2 geom width</i>
-----------	---------------------------------------

Description

Standardise the width in ggplot2 geoms so that widths appear visually consistent across plots with different numbers of categories, panel dimensions, and orientations.

This can be used in geoms such as `ggplot2::geom_bar()`, `ggplot2::geom_col()`, `ggplot2::geom_boxplot()`, and `ggplot2::geom_errorbar()`.

The relevant panel dimension must be an absolute physical unit (for example `grid::unit(..., "mm")`), either supplied directly or set in the current theme. Relative units are not supported.

Usage

```
get_width(
  ...,
  n = NULL,
  n_dodge = NULL,
  orientation = c("x", "y"),
  value = NULL,
  panel_widths = NULL,
  panel_heights = NULL
)
```

Arguments

...	Must be empty. Forces all other arguments to be named and allows trailing commas.
n	Number of categories in the orientation aesthetic (that is, "x" or "y"). For faceted plots, use the maximum n across facets.
n_dodge	Number of dodge categories. Intended for use with <code>position_dodge(preserve = "single")</code> .
orientation	Orientation: "x" for vertical geoms, "y" for horizontal geoms.
value	Numeric scaling factor controlling apparent width. A value of 1 is the default. Increase to make a wider appearance; decrease to make a thinner appearance. If NULL, uses the value set by <code>update_equiwidth()</code> , falling back to 1.
panel_widths	A <code>grid::unit</code> object specifying panel widths. If NULL, uses the value from the current theme.
panel_heights	A <code>grid::unit</code> object specifying panel heights. If NULL, uses the value from the current theme.

Value

A single numeric width suitable for the width argument of geoms such as `ggplot2::geom_bar()` or `ggplot2::geom_col()`.

update_equiwidth	<i>Update the global equiwidth</i>
------------------	------------------------------------

Description

Update a global default for the value argument used by [get_width\(\)](#).

Usage

```
update_equiwidth(value = 1)
```

Arguments

value	A single positive finite numeric value.
-------	---

Value

The previous option value, invisibly.

Index

`get_width`, [2](#)
`get_width()`, [3](#)
`ggplot2::geom_bar()`, [2](#)
`ggplot2::geom_boxplot()`, [2](#)
`ggplot2::geom_col()`, [2](#)
`ggplot2::geom_errorbar()`, [2](#)

`update_equiwidth`, [3](#)
`update_equiwidth()`, [2](#)