

Package ‘leaflet.extras2’

September 16, 2026

Type Package

Title Extra Functionality for 'leaflet' Package

Version 1.3.4

Description

Several 'leaflet' plugins are integrated, which are available as extension to the 'leaflet' package.

License GPL-3 | file LICENSE

Encoding UTF-8

LazyData true

Depends R (>= 3.5.0), leaflet (>= 2.0.0)

Imports htmltools, magrittr, utils

Suggests jsonlite, shiny, sf, yyjsonr, sp, testthat (>= 3.1.7),
fontawesome, htmlwidgets, xfun, covr, curl

URL <https://trafficonese.github.io/leaflet.extras2/>,
<https://github.com/trafficonese/leaflet.extras2>

BugReports <https://github.com/trafficonese/leaflet.extras2/issues>

Config/roxygen2/version 8.1.0

NeedsCompilation no

Author Gatscha Sebastian [aut, cre],
Ricardo Rodrigo Basa [ctb],
Jeffrey O Hanson [ctb] (ORCID: <<https://orcid.org/0000-0002-4716-6134>>)

Maintainer Gatscha Sebastian <sebastian_gatscha@gmx.at>

Repository CRAN

Date/Publication 2026-09-16 12:40:02 UTC

Contents

addAntpath	4
addArrowhead	6
addBuildings	8

addClusterCharts	10
addContextmenu	13
addDivicon	14
addEasyprint	17
addGeosearch	18
addGIBS	19
addHeightgraph	20
addHexbin	22
addHistory	24
addItemContextmenu	25
addLabelgun	26
addLayerGroupConditional	27
addLeafletsync	28
addLeafletsyncDependency	29
addMapkeyMarkers	30
addMovingMarker	32
addOpenweatherCurrent	34
addOpenweatherTiles	35
addPlayback	37
addProtobuf	39
addReachability	41
addSidebar	42
addSidebyside	43
addSpinner	45
addTangram	46
addTimeslider	48
addVectorgrid	50
addVelocity	52
addWMS	53
antpathOptions	55
arrowheadOptions	56
clearAntpath	58
clearArrowhead	58
clearConditionalLayers	59
clearFuture	59
clearHexbin	60
clearHistory	60
clearVectorgrid	61
closeSidebar	61
clusterchartOptions	62
context_mapmenuItems	63
context_markermenuItems	64
context_menuItem	64
disableContextmenu	65
easyprintMap	66
easyprintOptions	67
enableContextmenu	69
geosearchOptions	69

geosearchProvider	71
gibs_layers	71
goBackHistory	72
goForwardHistory	72
heightgraphOptions	73
hexbinOptions	74
hideContextmenu	75
hideHexbin	76
historyOptions	76
insertItemContextmenu	78
isSynced	79
LayerGroupCollision	79
leafletSyncOptions	81
makeMapkeyIcon	82
mapkeyIconList	83
mapkeyIcons	84
mapmenuItems	85
markermenuItems	86
menuItem	86
movingMarkerOptions	87
openSidebar	88
openweatherCurrentOptions	88
openweatherOptions	89
playbackOptions	90
reachabilityOptions	91
removeallItemsContextmenu	92
removeAntpath	93
removeArrowhead	93
removeConditionalLayer	94
removeEasyprint	94
removeGeosearch	95
removeItemContextmenu	95
removePlayback	96
removeReachability	96
removeSidebar	97
removeSidebyside	97
removeTimeslider	98
removeVectorgrid	98
removeVelocity	99
setBuildingData	99
setBuildingStyle	100
setDate	101
setDisabledContextmenu	101
setOptionsVelocity	102
setTransparent	103
setWMSParams	103
showContextmenu	104
showHexbin	105

sidebar_pane	106
sidebar_tabs	107
spinWhile	108
startMoving	109
timesliderOptions	110
to_jsonformat	111
to_ms	112
unsync	112
updateBuildingTime	113
updateHexbin	113
vectorStyling	114
velocityOptions	115
[.leaflet_mapkey_icon_set	116

Index 117

addAntpath	<i>Add Antpath Lines</i>
------------	--------------------------

Description

Can be used almost exactly like addPolylines but instead of pathOptions you can use [antpathOptions](#) to adapt the Antpath behaviour. See [leaflet-ant-path](#) for further details.

Usage

```
addAntpath(
  map,
  lng = NULL,
  lat = NULL,
  layerId = NULL,
  group = NULL,
  stroke = TRUE,
  color = "#03F",
  weight = 5,
  opacity = 0.5,
  fill = FALSE,
  fillColor = color,
  fillOpacity = 0.2,
  dashArray = NULL,
  smoothFactor = 1,
  noClip = FALSE,
  popup = NULL,
  popupOptions = NULL,
  label = NULL,
  labelOptions = NULL,
  options = antpathOptions(),
  highlightOptions = NULL,
```

```

    data = getMapData(map)
  )

```

Arguments

map	a map widget object created from leaflet()
lng	a numeric vector of longitudes, or a one-sided formula of the form <code>~x</code> where <code>x</code> is a variable in data; by default (if not explicitly provided), it will be automatically inferred from data by looking for a column named <code>lng</code> , <code>long</code> , or <code>longitude</code> (case-insensitively)
lat	a vector of latitudes or a formula (similar to the <code>lng</code> argument; the names <code>lat</code> and <code>latitude</code> are used when guessing the latitude column from data)
layerId	the layer id
group	the name of the group the newly created layers should belong to (for clearGroup() and addLayersControl() purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g., markers and polygons) can share the same group name.
stroke	whether to draw stroke along the path (e.g., the borders of polygons or circles)
color	stroke color
weight	stroke width in pixels
opacity	stroke opacity (or layer opacity for tile layers)
fill	whether to fill the path with color (e.g., filling on polygons or circles)
fillColor	fill color
fillOpacity	fill opacity
dashArray	a string that defines the stroke dash pattern
smoothFactor	how much to simplify the polyline on each zoom level (more means better performance and less accurate representation)
noClip	whether to disable polyline clipping
popup	a character vector of the HTML content for the popups (you are recommended to escape the text using htmltools::htmlEscape() for security reasons)
popupOptions	A Vector of popupOptions() to provide popups
label	a character vector of the HTML content for the labels
labelOptions	A Vector of labelOptions() to provide label options for each label. Default NULL
options	A named list of options. See antpathOptions
highlightOptions	Options for highlighting the shape on mouse over.
data	the data object from which the argument values are derived; by default, it is the data object provided to leaflet() initially, but can be overridden

Value

A modified leaflet map, with an 'ant-path' animated polyline

Note

Unlike [addPolylines](#), antpath layers are not registered as "shape". In Shiny the mouse events therefore use the antpath category instead of shape:

1. A click updates `input$MAPID_antpath_click`
2. A mouseover updates `input$MAPID_antpath_mouseover`
3. A mouseout updates `input$MAPID_antpath_mouseout`

References

<https://github.com/rubenspgcavalcante/leaflet-ant-path>

See Also

Other Antpath Functions: [antpathOptions\(\)](#), [clearAntpath\(\)](#), [removeAntpath\(\)](#)

Examples

```
library(leaflet)
leaflet() %>%
  addAntpath(data = atlStorms2005)
```

addArrowhead

Add Lines with an arrowhead

Description

Can be used almost exactly like `addPolylines` but instead of `pathOptions` you can use [arrowheadOptions](#). See [leaflet-arrowheads](#) for further details.

Usage

```
addArrowhead(
  map,
  lng = NULL,
  lat = NULL,
  layerId = NULL,
  group = NULL,
  stroke = TRUE,
  color = "#03F",
  weight = 5,
  opacity = 0.5,
  fill = FALSE,
  fillColor = color,
  fillOpacity = 0.2,
  dashArray = NULL,
  smoothFactor = 1,
```

```

    noClip = FALSE,
    popup = NULL,
    popupOptions = NULL,
    label = NULL,
    labelOptions = NULL,
    options = arrowheadOptions(),
    highlightOptions = NULL,
    data = getMapData(map)
)

```

Arguments

map	a map widget object created from leaflet()
lng	a numeric vector of longitudes, or a one-sided formula of the form <code>~x</code> where <code>x</code> is a variable in data; by default (if not explicitly provided), it will be automatically inferred from data by looking for a column named <code>lng</code> , <code>long</code> , or <code>longitude</code> (case-insensitively)
lat	a vector of latitudes or a formula (similar to the <code>lng</code> argument; the names <code>lat</code> and <code>latitude</code> are used when guessing the latitude column from data)
layerId	the layer id
group	the name of the group the newly created layers should belong to (for clearGroup() and addLayersControl() purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g., markers and polygons) can share the same group name.
stroke	whether to draw stroke along the path (e.g., the borders of polygons or circles)
color	stroke color
weight	stroke width in pixels
opacity	stroke opacity (or layer opacity for tile layers)
fill	whether to fill the path with color (e.g., filling on polygons or circles)
fillColor	fill color
fillOpacity	fill opacity
dashArray	a string that defines the stroke dash pattern
smoothFactor	how much to simplify the polyline on each zoom level (more means better performance and less accurate representation)
noClip	whether to disable polyline clipping
popup	a character vector of the HTML content for the popups (you are recommended to escape the text using htmltools::htmlEscape() for security reasons)
popupOptions	A Vector of popupOptions() to provide popups
label	a character vector of the HTML content for the labels
labelOptions	A Vector of labelOptions() to provide label options for each label. Default NULL
options	A named list of options. See arrowheadOptions

highlightOptions	Options for highlighting the shape on mouse over.
data	the data object from which the argument values are derived; by default, it is the data object provided to leaflet() initially, but can be overridden

Details

It is possible to style the lines and the arrowheads separately; put styling specifications for the lines inside `addArrowhead` and the specifications for the arrowheads inside `arrowheadOptions`. A `dashArray` provided for the lines will also apply to the arrowheads, but the latter can be overruled by specifying a separate `dashArray` for the arrowheads inside `arrowheadOptions`.

Value

A modified leaflet map with a polyline with arrowheads

References

<https://github.com/slutske22/leaflet-arrowheads>

See Also

Other Arrowhead Functions: `arrowheadOptions()`, `clearArrowhead()`, `removeArrowhead()`

Examples

```
library(leaflet)
leaflet() %>%
  addArrowhead(data = at1Storms2005)
```

addBuildings

Add OSM-Buildings to a Leaflet Map

Description

This function adds 2.5D buildings to a Leaflet map using the OSM Buildings plugin.

Usage

```
addBuildings(
  map,
  buildingURL = "https://{s}.data.osmbuildings.org/0.2/59fcc2e8/tile/{z}/{x}/{y}.json",
  group = NULL,
  eachFn = NULL,
  clickFn = NULL,
  data = NULL
)
```

Arguments

map	A map widget object created from leaflet .
buildingURL	The URL template for the building data. Default is the OSM Buildings tile server: "https://{s}.data.osmbuildings.org/0.2/59fcc2e8/tile/{z}/{x}/{y}.json".
group	The name of the group the buildings will be added to.
eachFn	A JavaScript function (using JS) that will be called for each building feature. Use this to apply custom logic to each feature.
clickFn	A JavaScript function (using JS) that will be called when a building is clicked. Use this to handle click events on buildings.
data	A GeoJSON object containing Polygon features representing the buildings. The properties of these polygons can include attributes like height, color, roofColor, and others as specified in the OSM Buildings documentation.

Details

The 'data' parameter allows you to provide custom building data as a GeoJSON object. The following properties can be used within the GeoJSON:

- **height**
- **minHeight**
- **color/wallColor**
- **material**
- **roofColor**
- **roofMaterial**
- **shape**
- **roofShape**
- **roofHeight**

See the OSM Wiki: [Simple_3D_Buildings](#)

See Also

<https://github.com/kekscom/osmbuildings/> for more details on the OSM Buildings plugin and available properties.

Other OSM-Buildings Plugin: [setBuildingData\(\)](#), [setBuildingStyle\(\)](#), [updateBuildingTime\(\)](#)

Examples

```
library(leaflet)
library(leaflet.extras2)

leaflet() %>%
  addProviderTiles("CartoDB") %>%
  addBuildings(group = "Buildings") %>%
  addLayersControl(overlayGroups = "Buildings") %>%
  setView(lng = 13.4, lat = 52.51, zoom = 15)
```

addClusterCharts	<i>addClusterCharts</i>
------------------	-------------------------

Description

Clusters markers on a Leaflet map and visualizes them using customizable charts, such as pie or bar charts, showing counts by category. When using the "custom" type, a pie chart is rendered with aggregated data, employing methods like sum, min, max, mean, or median.

Usage

```
addClusterCharts(
  map,
  layerId = NULL,
  group = NULL,
  type = c("pie", "bar", "horizontal", "custom"),
  aggregation = c("sum", "min", "max", "mean", "median"),
  valueField = NULL,
  options = clusterchartOptions(),
  icon = NULL,
  html = NULL,
  popup = NULL,
  popupOptions = NULL,
  label = NULL,
  labelOptions = NULL,
  clusterOptions = NULL,
  clusterId = NULL,
  categoryField,
  categoryMap,
  popupFields = NULL,
  popupLabels = NULL,
  markerOptions = NULL,
  legendOptions = list(title = "", position = "topright"),
  data = getMapData(map)
)
```

Arguments

map	a map widget object created from <code>leaflet()</code>
layerId	the layer id
group	the name of the group the newly created layers should belong to (for <code>clearGroup()</code> and <code>addLayersControl()</code> purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g., markers and polygons) can share the same group name.
type	The type of chart to use for clusters: "pie", "bar", "horizontal", or "custom".

aggregation	Aggregation method for "custom" charts (e.g., sum, min, max, mean, median).
valueField	Column name with values to aggregate for "custom" charts.
options	Additional options for cluster charts (see clusterchartOptions).
icon	An icon or set of icons to include, created with <code>makeIcon</code> or <code>iconList</code> .
html	The column name containing the HTML content to include in the markers.
popup	The column name used to retrieve feature properties for the popup.
popupOptions	A Vector of popupOptions() to provide popups
label	a character vector of the HTML content for the labels
labelOptions	A Vector of labelOptions() to provide label options for each label. Default NULL
clusterOptions	if not NULL, markers will be clustered using Leaflet.markercluster ; you can use markerClusterOptions() to specify marker cluster options
clusterId	the id for the marker cluster layer
categoryField	Column name for categorizing charts.
categoryMap	A data.frame mapping categories to chart properties (e.g., label, color, icons, stroke).
popupFields	A string or vector of strings indicating the column names to include in popups.
popupLabels	A string or vector of strings indicating the labels for the popup fields.
markerOptions	Additional options for markers (see markerOptions::markerOptions()).
legendOptions	A list of options for the legend, including the title and position.
data	the data object from which the argument values are derived; by default, it is the data object provided to <code>leaflet()</code> initially, but can be overridden

Details

The 'clusterCharts' use Leaflet's 'L.DivIcon', allowing you to fully customize the styling of individual markers and clusters using CSS. Each individual marker within a cluster is assigned the CSS class 'clustermarker', while the entire cluster is assigned the class 'clustermarker-cluster'. You can modify the appearance of these elements by targeting these classes in your custom CSS.

See Also

Other clusterCharts: [clusterchartOptions\(\)](#)

Examples

```
# Example usage:
library(sf)
library(leaflet)
library(leaflet.extras2)

data <- sf::st_as_sf(breweries91)
categories <- c("Schwer", "Mäßig", "Leicht", "kein Schaden")
data$category <- sample(categories, size = nrow(data), replace = TRUE)
```

```

## Pie Chart
leaflet() %>%
  addProviderTiles("CartoDB.Positron") %>%
  leaflet::addLayersControl(overlayGroups = "clustermarkers") %>%
  addClusterCharts(
    data = data,
    categoryField = "category",
    categoryMap = data.frame(
      labels = categories,
      colors = c("#F88", "#FA0", "#FF3", "#BFB"),
      strokes = "gray"
    ),
    group = "clustermarkers",
    popupFields = c("brewery", "address", "zipcode", "category"),
    popupLabels = c("Brauerei", "Adresse", "PLZ", "Art"),
    label = "brewery"
  )

## Bar Chart
leaflet() %>%
  addProviderTiles("CartoDB.Positron") %>%
  leaflet::addLayersControl(overlayGroups = "clustermarkers") %>%
  addClusterCharts(
    data = data,
    type = "bar",
    categoryField = "category",
    categoryMap = data.frame(
      labels = categories,
      colors = c("#F88", "#FA0", "#FF3", "#BFB"),
      strokes = "gray"
    ),
    group = "clustermarkers",
    popupFields = c("brewery", "address", "zipcode", "category"),
    popupLabels = c("Brauerei", "Adresse", "PLZ", "Art"),
    label = "brewery"
  )

## Custom Pie Chart with "mean" aggregation on column "value"
data <- sf::st_as_sf(breweries91)
categories <- c("Schwer", "Mäßig", "Leicht", "kein Schaden")
data$category <- sample(categories, size = nrow(data), replace = TRUE)
data$value <- round(runif(nrow(data), 0, 100), 0)

leaflet() %>%
  addProviderTiles("CartoDB.Positron") %>%
  leaflet::addLayersControl(overlayGroups = "clustermarkers") %>%
  addClusterCharts(
    data = data,
    type = "custom",
    valueField = "value",
    aggregation = "mean",
    categoryField = "category",
    categoryMap = data.frame(

```

```

      labels = categories,
      colors = c("#F88", "#FA0", "#FF3", "#BFB"),
      strokes = "gray"
    ),
    options = clusterchartOptions(rmax = 50, digits = 0, innerRadius = 20),
    group = "clustermarkers",
    popupFields = c("brewery", "address", "zipcode", "category", "value"),
    popupLabels = c("Brauerei", "Adresse", "PLZ", "Art", "Value"),
    label = "brewery"
  )

## For Shiny examples, please run:
# runApp(system.file("examples/clusterCharts_app.R", package = "leaflet.extras2"))
# runApp(system.file("examples/clustercharts_sum.R", package = "leaflet.extras2"))

```

addContextmenu

Add contextmenu Plugin

Description

Add a contextmenu to the map or markers/vector layers.

Usage

```
addContextmenu(map)
```

Arguments

`map` a map widget object created from [leaflet](#)

Details

This function is only used to include the required JavaScript and CSS bindings and to set up some Shiny event handlers.

Contextmenu initialization: The contextmenu for

- the **map** must be defined in [leafletOptions](#).
- the **markers/vector layers** must be defined in [markerOptions](#) or [pathOptions](#).

Contextmenu selection: When a contextmenu is selected, a Shiny input with the ID "MAPID_contextmenu_select" is set ('MAPID' refers to the map's id).

If the selected contextmenu item is triggered from:

- the **map**, the returned list contains the text of the item.
- the **markers**, the returned list also contains the layerId, group, lat, lng and label.
- the **vector layers**, the returned list also contains the layerId, group and label.

Value

A leaflet map object

References

<https://github.com/aratcliffe/Leaflet.contextmenu>

See Also

Other Contextmenu Functions: [addItemContextmenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextmenu\(\)](#), [enableContextmenu\(\)](#), [hideContextmenu\(\)](#), [insertItemContextmenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextmenu\(\)](#), [removeallItemsContextmenu\(\)](#), [setDisabledContextmenu\(\)](#), [showContextmenu\(\)](#)

Examples

```
library(leaflet)
leaflet(options = leafletOptions(
  contextmenu = TRUE,
  contextmenuWidth = 200,
  contextmenuItems =
    context_mapmenuItems(
      context_menuItem("Zoom Out", "function(e) {this.zoomOut()}", disabled = FALSE),
      "-",
      context_menuItem("Zoom In", "function(e) {this.zoomIn()}")
    )
)) %>%
  addTiles(group = "base") %>%
  addContextmenu() %>%
  addMarkers(
    data = breweries91, label = ~brewery,
    layerId = ~founded, group = "marker",
    options = markerOptions(
      contextmenu = TRUE,
      contextmenuWidth = 200,
      contextmenuItems =
        context_markermenuItems(
          context_menuItem(
            text = "Show Marker Coords",
            callback = "function(e) {alert(e.latlng);}",
            index = 1
          )
        )
      )
  )
)
```

Description

Adds customizable DivIcon markers to a Leaflet map. The function can accept either spatial data (lines or points) in the form of a Simple Feature (sf) object or numeric vectors for latitude and longitude coordinates. It allows for the application of custom HTML content and CSS classes to each marker, providing high flexibility in marker design.

Usage

```
addDivicon(
  map,
  lng = NULL,
  lat = NULL,
  layerId = NULL,
  group = NULL,
  popup = NULL,
  popupOptions = NULL,
  label = NULL,
  labelOptions = NULL,
  className = NULL,
  html = NULL,
  options = markerOptions(),
  clusterOptions = NULL,
  clusterId = NULL,
  divOptions = list(),
  data = getMapData(map)
)
```

Arguments

map	the map to add awesome Markers to.
lng	a numeric vector of longitudes, or a one-sided formula of the form <code>~x</code> where <code>x</code> is a variable in <code>data</code> ; by default (if not explicitly provided), it will be automatically inferred from <code>data</code> by looking for a column named <code>lng</code> , <code>long</code> , or <code>longitude</code> (case-insensitively)
lat	a vector of latitudes or a formula (similar to the <code>lng</code> argument; the names <code>lat</code> and <code>latitude</code> are used when guessing the latitude column from <code>data</code>)
layerId	the layer id
group	the name of the group the newly created layers should belong to (for <code>clearGroup()</code> and <code>addLayersControl()</code> purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g., markers and polygons) can share the same group name.
popup	a character vector of the HTML content for the popups (you are recommended to escape the text using <code>htmltools::htmlEscape()</code> for security reasons)
popupOptions	A Vector of <code>popupOptions()</code> to provide popups
label	a character vector of the HTML content for the labels

labelOptions	A Vector of <code>labelOptions()</code> to provide label options for each label. Default NULL
className	A single CSS class or a vector of CSS classes.
html	A single HTML string or a vector of HTML strings.
options	a list of extra options for tile layers, popups, paths (circles, rectangles, polygons, ...), or other map elements
clusterOptions	if not NULL, markers will be clustered using <code>Leaflet.markercluster</code> ; you can use <code>markerClusterOptions()</code> to specify marker cluster options
clusterId	the id for the marker cluster layer
divOptions	A list of extra options for Leaflet DivIcon.
data	the data object from which the argument values are derived; by default, it is the data object provided to <code>leaflet()</code> initially, but can be overridden

Value

The modified Leaflet map object.

Examples

```
library(sf)
library(leaflet)
library(leaflet.extras2)

# Sample data
df <- sf::st_as_sf(atlStorms2005)
df <- suppressWarnings(st_cast(df, "POINT"))
df <- df[sample(1:nrow(df), 50, replace = FALSE), ]
df$classes <- sample(x = c("myclass1", "myclass2", "myclass3"), nrow(df), replace = TRUE)
df$ID <- paste0("ID_", 1:nrow(df))

leaflet() %>%
  addTiles() %>%
  addDivicon(
    data = df,
    html = ~ paste0(
      '<div class="custom-html">',
      '<div class="title">', Name, "</div>",
      '<div class="subtitle">MaxWind: ', MaxWind, "</div>",
      "</div>"
    ),
    label = ~Name,
    layerId = ~ID,
    group = "Divicons",
    popup = ~ paste(
      "ID: ", ID, "<br>",
      "Name: ", Name, "<br>",
      "MaxWind:", MaxWind, "<br>",
      "MinPress:", MinPress
    ),
  ),
```

```
    options = markerOptions(draggable = TRUE)
  )
```

`addEasyprint`*Add easyPrint Plugin*

Description

Add a control, which allows to print or export a map as .PNG.

Usage

```
addEasyprint(map, options = easyprintOptions())
```

Arguments

<code>map</code>	a map widget object created from leaflet
<code>options</code>	A named list of options. See easyprintOptions

Value

A leaflet map object

References

<https://github.com/rowanwins/leaflet-easyPrint>

See Also

Other EasyPrint Functions: [easyprintMap\(\)](#), [easyprintOptions\(\)](#), [removeEasyprint\(\)](#)

Examples

```
library(leaflet)
leaflet() %>%
  addTiles() %>%
  addEasyprint(options = easyprintOptions(
    title = "Print map",
    position = "bottomleft",
    exportOnly = TRUE
  ))

## Custom pixel size (e.g. high-res PNG in a Quarto/HTML document):
leaflet() %>%
  addTiles() %>%
  addEasyprint(options = easyprintOptions(
    title = "Save map to PNG",
    exportOnly = TRUE,
    filename = "map",
```

```

    tileWait = 1000,
    sizeModes = list(
      "CurrentSize",
      list(scale = 3, name = "3x current view")
    )
  ))

```

addGeosearch

Add a GeoSearch control to a Leaflet map

Description

Adds a geocoding search widget to a leaflet map using the leaflet-geosearch plugin. Supports multiple providers such as OpenStreetMap, Esri, Google, HERE, etc.

Usage

```
addGeosearch(map, provider = geosearchProvider(), options = geosearchOptions())
```

Arguments

map	a map widget
provider	A provider list object created with e.g. geosearchProvider
options	A list of control options created with geosearchOptions .

Value

the new map object

Shiny value

When used inside a Shiny application, addGeosearch() will also register two reactive inputs that return the most recent geosearch results:

- `input$<mapId>_geosearch_result` Updated when a search result is selected (from the `geosearch/showlocation` event). Returns a list with `lat`, `lng`, `label`, `bounds`, and other properties provided by the geocoder.
- `input$<mapId>_geosearch_dragend` Updated when the marker placed by the `geosearch` control is dragged to a new location (from the `geosearch/marker/dragend` event). Returns the same structure as above.

Both values are NULL if no result is available.

References

<https://github.com/smeijer/leaflet-geosearch>

See Also

Other Geosearch Functions: [geosearchOptions\(\)](#), [removeGeosearch\(\)](#)

Examples

```
library(leaflet)
library(leaflet.extras2)

leaflet() %>%
  addTiles() %>%
  addGeosearch()
```

addGIBS

*Add GIBS Layers***Description**

A leaflet plugin for NASA EOSDIS GIBS imagery integration. 154 products are available. The date can be set dynamically for multi-temporal products. No-data pixels of MODIS Multiband Imagery can be made transparent.

Usage

```
addGIBS(
  map,
  layers = NULL,
  group = NULL,
  dates = NULL,
  opacity = 0.5,
  transparent = TRUE
)
```

Arguments

map	a map widget object created from leaflet()
layers	A character vector of GIBS-layers. See gibs_layers
group	the name of the group the newly created layers should belong to (for clearGroup() and addLayersControl() purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g., markers and polygons) can share the same group name.
dates	Date object. If multiple layers are added, you can add a Date vector of the same length
opacity	Numeric value determining the opacity. If multiple layers are added, you can add a numeric vector of the same length
transparent	Should the layer be transparent. If multiple layers are added, you can add a boolean vector of the same length

Value

the new map object

References

<https://github.com/aparshin/leaflet-GIBS>

See Also

Other GIBS Functions: [setDate\(\)](#), [setTransparent\(\)](#)

Examples

```
library(leaflet)
library(leaflet.extras2)

layers <- gibs_layers$title[c(35, 128, 185)]

leaflet() %>%
  addTiles() %>%
  setView(9, 50, 4) %>%
  addGIBS(
    layers = layers,
    dates = Sys.Date() - 1,
    group = layers
  ) %>%
  addLayersControl(overlayGroups = layers)
```

addHeightgraph

Add a Heightgraph layer

Description

Visualize height information and road attributes of linestring segments. The linestrings must be a Simple Feature LINESTRING Z and are transformed to GeoJSON. The function therefore inherits arguments from [addGeoJSON](#).

Usage

```
addHeightgraph(
  map,
  data = NULL,
  columns = NULL,
  layerId = NULL,
  group = NULL,
  color = "#03F",
  weight = 5,
  opacity = 0.5,
```

```

    dashArray = NULL,
    smoothFactor = 1,
    noClip = FALSE,
    pathOpts = leaflet::pathOptions(),
    options = heightgraphOptions()
  )

```

Arguments

map	a map widget object created from leaflet()
data	A Simple Feature LINESTRING with Z dimension.
columns	A character vector of the columns you want to include in the heightgraph control
layerId	the layer id
group	the name of the group the newly created layers should belong to (for clearGroup() and addLayersControl() purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g., markers and polygons) can share the same group name.
color	stroke color
weight	stroke width in pixels
opacity	stroke opacity (or layer opacity for tile layers)
dashArray	a string that defines the stroke dash pattern
smoothFactor	how much to simplify the polyline on each zoom level (more means better performance and less accurate representation)
noClip	whether to disable polyline clipping
pathOpts	List of further options for the path. See pathOptions
options	List of further plugin options. See heightgraphOptions

Value

the new map object

Note

When used in Shiny, 3 events update a certain Shiny Input:

1. A click updates `input$MAPID_heightgraph_click`
2. A mouseover updates `input$MAPID_heightgraph_mouseover`
3. A mouseout updates `input$MAPID_heightgraph_mouseout`

If you want to explicitly remove the Heightgraph control, please use [removeControl](#) with the `layerId = "hg_control"`.

References

<https://github.com/GIScience/Leaflet.Heightgraph>

See Also

Other Heightgraph Functions: [heightgraphOptions\(\)](#)

Examples

```
library(leaflet)
library(leaflet.extras2)
library(sf)

data <- st_cast(st_as_sf(leaflet::atlStorms2005[4, ]), "LINESTRING")
data <- st_transform(data, 4326)
data <- data.frame(st_coordinates(data))
data$elev <- round(runif(nrow(data), 10, 500), 2)
data$L1 <- NULL
L1 <- round(seq.int(1, 4, length.out = nrow(data)))
data <- st_as_sf(st_sfc(lapply(split(data, L1), function(x) {
  st_linestring(as.matrix(x))
})))
data$steepness <- 1:nrow(data)
data$suitability <- nrow(data):1
data$popup <- apply(data, 1, function(x) {
  sprintf("Steepness: %s<br>Suitability: %s", x$steepness, x$suitability)
})

leaflet() %>%
  addTiles(group = "base") %>%
  addHeightgraph(
    color = "red", columns = c("steepness", "suitability"),
    opacity = 1, data = data, group = "heightgraph",
    options = heightgraphOptions(width = 400)
  )
```

addHexbin

Add a Hexbin layer

Description

Create dynamic hexbin-based heatmaps on Leaflet maps. This plugin leverages the data-binding power of d3 to allow you to dynamically update the data and visualize the transitions.

Usage

```
addHexbin(
  map,
  lng = NULL,
  lat = NULL,
  radius = 20,
  layerId = NULL,
  group = NULL,
```

```
    opacity = 0.5,  
    options = hexbinOptions(),  
    data = getMapData(map)  
  )
```

Arguments

map	a map widget object created from leaflet()
lng	a numeric vector of longitudes, or a one-sided formula of the form ~x where x is a variable in data; by default (if not explicitly provided), it will be automatically inferred from data by looking for a column named lng, long, or longitude (case-insensitively)
lat	a vector of latitudes or a formula (similar to the lng argument; the names lat and latitude are used when guessing the latitude column from data)
radius	Radius of the hexbin layer
layerId	the layer id
group	the name of the group the newly created layers should belong to (for clearGroup() and addLayersControl() purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g., markers and polygons) can share the same group name.
opacity	Opacity of the hexbin layer
options	List of further options. See hexbinOptions
data	the data object from which the argument values are derived; by default, it is the data object provided to leaflet() initially, but can be overridden

Value

the new map object

Note

Currently doesn't respect layerId nor group.

References

<https://github.com/bluehalo/leaflet-d3#hexbins-api>

See Also

Other Hexbin-D3 Functions: [clearHexbin\(\)](#), [hexbinOptions\(\)](#), [hideHexbin\(\)](#), [showHexbin\(\)](#), [updateHexbin\(\)](#)

Examples

```
library(leaflet)
library(leaflet.extras2)

n <- 1000
df <- data.frame(
  lat = rnorm(n, 42.0285, .01),
  lng = rnorm(n, -93.65, .01)
)

leaflet() %>%
  addTiles() %>%
  addHexbin(
    lng = df$lng, lat = df$lat,
    options = hexbinOptions(
      colorRange = c("red", "yellow", "blue"),
      radiusRange = c(10, 20)
    )
  )
```

addHistory

*Add History Plugin***Description**

The plugin enables tracking of map movements in a history similar to a web browser. By default, it is a simple pair of buttons – back and forward.

Usage

```
addHistory(map, layerId = NULL, options = historyOptions())
```

Arguments

map	a map widget object created from leaflet
layerId	the control id
options	A named list of options. See historyOptions

Value

the new map object

References

<https://github.com/cscott530/leaflet-history>

See Also

Other History Functions: [clearFuture\(\)](#), [clearHistory\(\)](#), [goBackHistory\(\)](#), [goForwardHistory\(\)](#), [historyOptions\(\)](#)

Examples

```
library(leaflet)
leaflet() %>%
  addTiles() %>%
  addHistory()
```

addItemContextmenu	<i>addItemContextmenu</i>
--------------------	---------------------------

Description

Add a new contextmenu menu item

Usage

```
addItemContextmenu(map, option)
```

Arguments

map	a map widget object created from leaflet
option	new menu item to add

Value

A leaflet map object

See Also

Other Contextmenu Functions: [addContextmenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextmenu\(\)](#), [enableContextmenu\(\)](#), [hideContextmenu\(\)](#), [insertItemContextmenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextmenu\(\)](#), [removeallItemsContextmenu\(\)](#), [setDisabledContextmenu\(\)](#), [showContextmenu\(\)](#)

addLabelgun

Add addLabelgun Plugin

Description

The plugin allows to avoid cluttering in marker labels and gives priority to labels of your choice (with higher weight).

Usage

```
addLabelgun(map, group = NULL, weight = NULL, entries = NULL)
```

Arguments

map	A map widget object created from leaflet
group	The group name of the layer/s for which label collisions are to be avoided. To see the effects of this plugin the labelOptions of the markers must be configured with either permanent = TRUE or noHide = TRUE.
weight	An optional weight for markers. If a vector is given, the length should match the number of all markers in the corresponding groups. If a numeric value is specified, it is used for each marker and thus no prioritization of the labels takes place. In all other cases a random integer is calculated.
entries	A numeric value, a higher value relates to faster insertion and slower search, and vice versa. The default is 10

Value

A leaflet map object

Note

It is important to invoke the function after the markers have been added to the map. Otherwise nothing will happen.

References

<https://github.com/Geovation/labelgun>

Examples

```
library(leaflet)
library(leaflet.extras2)

leaflet() %>%
  addTiles() %>%
  addMarkers(
    data = breweries91,
```

```

    label = ~brewery,
    group = "markers",
    labelOptions = labelOptions(permanent = TRUE)
  ) %>%
  addLabelgun("markers", 1)

```

```

addLayerGroupConditional
      addLayerGroupConditional

```

Description

addLayerGroupConditional

Usage

```
addLayerGroupConditional(map, groups = NULL, conditions = NULL)
```

Arguments

- | | |
|------------|--|
| map | A map widget object created from leaflet . |
| groups | A character vector of layer group names already added to the map. These layer groups will be conditionally displayed based on the specified conditions. |
| conditions | <p>A named list of conditions for displaying layer groups. Each list element should have:</p> <ul style="list-style-type: none"> • A <i>name</i>: a JavaScript function as string that defines the condition. • A <i>value</i>: the layer group name(s) from the <code>layers</code> parameter to be shown when the condition evaluates to TRUE. |

Example:

```

conditions = list(
  "(zoomLevel) => zoomLevel < 4" = "group1",
  "(zoomLevel) => zoomLevel >= 4 && zoomLevel < 6" = "group2",
  "(zoomLevel) => zoomLevel >= 6" = c("group3", "group4")
)

```

See Also

<https://github.com/Solfisk/Leaflet.LayerGroup.Conditional> for more details about the plugin.

Other LayerGroupConditional Plugin: [clearConditionalLayers\(\)](#), [removeConditionalLayer\(\)](#)

Examples

```

library(leaflet)
library(sf)
library(leaflet.extras2)

breweries91 <- st_as_sf(breweries91)
lines <- st_as_sf(atlStorms2005)
polys <- st_as_sf(leaflet::gadmCHE)
groups <- c("atlStorms", "breweries", "gadmCHE")

leaflet() %>%
  addTiles() %>%
  # leafem::addMouseCoordinates() %>%
  addPolylines(data = lines, label = ~Name, group = groups[1]) %>%
  addCircleMarkers(data = breweries91, label = ~brewery, group = groups[2]) %>%
  addPolygons(data = polys, label = ~NAME_1, group = groups[3]) %>%
  addLayerGroupConditional(
    groups = groups,
    conditions = list(
      "(zoomLevel) => zoomLevel < 4" = groups[1],
      "(zoomLevel) => zoomLevel >= 4 & zoomLevel < 6 " = groups[2],
      "(zoomLevel) => zoomLevel >= 6 " = groups[3]
    )
  ) %>%
  hideGroup(groups) %>%
  addLayersControl(
    overlayGroups = groups,
    options = layersControlOptions(collapsed = FALSE)
  )

```

addLeafletsync

Synchronize multiple Leaflet map

Description

The plugin allows you to synchronize and unsynchronize multiple leaflet maps in a Shiny application. You can pass additional options to [leafletsyncOptions](#). For more information see [Leaflet.Sync](#)

Usage

```

addLeafletsync(
  map,
  ids = NULL,
  synclist = "all",
  options = leafletsyncOptions()
)

```

Arguments

map	the map
ids	the map ids to be synced. If you use a synclist, you may leave it NULL. The unique names and values of synclist will be used.
synclist	The synchronization list. The default is 'all', which creates a list of all possible combinations of ids. For a more detailed control, a named list can be passed in this form <code>list(m1 = c("m2", "m3"), m2 = c("m1", "m3"), m3 = c("m1", "m2"))</code> , where the names and values represent map-ids. The names of the lists serve as a basis and the list values are the maps to be kept in sync with the basemap.
options	A named list of options. See leafletsyncOptions . If you want to add different options to multiple maps, you can wrap the options in a named list, with the names being the map-ids. See the example in <code>./inst/examples/offset_continuous.R</code>

Value

A modified leaflet map

Note

If you synchronize multiple maps, a map may not yet be initialized and therefore cannot be used. Make sure to use `addLeafletsync` after all maps have been rendered.

References

<https://github.com/jieter/Leaflet.Sync>

See Also

Other leafletsync Functions: [addLeafletsyncDependency\(\)](#), [isSynced\(\)](#), [leafletsyncOptions\(\)](#), [unsync\(\)](#)

addLeafletsyncDependency

Add the Leaflet Sync JS dependencies

Description

Sometimes it makes sense to include the Leaflet Sync dependencies already before synchronizing maps. For example, if you want to use the 'L.Sync.offsetHelper'. See the example in `./inst/examples/offsetHelper.R`

Usage

```
addLeafletsyncDependency(map)
```

Arguments

map	the map
-----	---------

Value

A modified leaflet map

See Also

Other leafletsync Functions: [addLeafletsync\(\)](#), [isSynced\(\)](#), [leafletsyncOptions\(\)](#), [unsync\(\)](#)

addMapkeyMarkers	<i>Add Mapkey Markers</i>
------------------	---------------------------

Description

Add Mapkey Markers

Usage

```
addMapkeyMarkers(
  map,
  lng = NULL,
  lat = NULL,
  layerId = NULL,
  group = NULL,
  icon = NULL,
  popup = NULL,
  popupOptions = NULL,
  label = NULL,
  labelOptions = NULL,
  options = leaflet::markerOptions(),
  clusterOptions = NULL,
  clusterId = NULL,
  data = leaflet::getMapData(map)
)
```

Arguments

map	the map to add mapkey Markers to.
lng	a numeric vector of longitudes, or a one-sided formula of the form <code>~x</code> where <code>x</code> is a variable in data; by default (if not explicitly provided), it will be automatically inferred from data by looking for a column named <code>lng</code> , <code>long</code> , or <code>longitude</code> (case-insensitively)
lat	a vector of latitudes or a formula (similar to the <code>lng</code> argument; the names <code>lat</code> and <code>latitude</code> are used when guessing the latitude column from data)
layerId	the layer id

group	the name of the group the newly created layers should belong to (for <code>clearGroup()</code> and <code>addLayersControl()</code> purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g., markers and polygons) can share the same group name.
icon	the icon(s) for markers;
popup	a character vector of the HTML content for the popups (you are recommended to escape the text using <code>htmltools::htmlEscape()</code> for security reasons)
popupOptions	A Vector of <code>popupOptions()</code> to provide popups
label	a character vector of the HTML content for the labels
labelOptions	A Vector of <code>labelOptions()</code> to provide label options for each label. Default NULL
options	a list of extra options for markers. See <code>markerOptions</code>
clusterOptions	if not NULL, markers will be clustered using <code>Leaflet.markercluster</code> ; you can use <code>markerClusterOptions()</code> to specify marker cluster options
clusterId	the id for the marker cluster layer
data	the data object from which the argument values are derived; by default, it is the data object provided to <code>leaflet()</code> initially, but can be overridden

Value

the new map object

References

<https://github.com/mapshakers/leaflet-mapkey-icon>

See Also

Other Mapkey Functions: `[.leaflet_mapkey_icon_set(), makeMapkeyIcon(), mapkeyIconList(), mapkeyIcons()]`

Examples

```
library(leaflet)

leaflet() %>%
  addTiles() %>%
  addMapkeyMarkers(
    data = breweries91,
    icon = makeMapkeyIcon(
      icon = "mapkey",
      iconSize = 30,
      boxShadow = FALSE,
      background = "transparent"
    ),
    group = "mapkey",
    label = ~state, popup = ~village
  )
```

addMovingMarker	<i>Add Moving Markers</i>
-----------------	---------------------------

Description

The function expects either line or point data as spatial data or as Simple Feature. Alternatively, coordinates can also be passed as numeric vectors.

Usage

```
addMovingMarker(
  map,
  lng = NULL,
  lat = NULL,
  layerId = NULL,
  group = NULL,
  duration = 2000,
  icon = NULL,
  popup = NULL,
  popupOptions = NULL,
  label = NULL,
  labelOptions = NULL,
  movingOptions = movingMarkerOptions(),
  options = leaflet::markerOptions(),
  data = leaflet::getMapData(map)
)
```

Arguments

map	the map to add moving markers
lng	a numeric vector of longitudes, or a one-sided formula of the form <code>~x</code> where <code>x</code> is a variable in data; by default (if not explicitly provided), it will be automatically inferred from data by looking for a column named <code>lng</code> , <code>long</code> , or <code>longitude</code> (case-insensitively)
lat	a vector of latitudes or a formula (similar to the <code>lng</code> argument; the names <code>lat</code> and <code>latitude</code> are used when guessing the latitude column from data)
layerId	In order to be able to address the moving markings individually, a <code>layerId</code> is required. If none is specified, one is created that is derived from the current timestamp.
group	the name of the group the newly created layers should belong to (for clearGroup() and addLayersControl() purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g., markers and polygons) can share the same group name.
duration	Duration in milliseconds per line segment between 2 points. Can be a vector or a single number. Default is 1000

icon	the icon(s) for markers;
popup	a character vector of the HTML content for the popups (you are recommended to escape the text using <code>htmltools::htmlEscape()</code> for security reasons)
popupOptions	A Vector of <code>popupOptions()</code> to provide popups
label	a character vector of the HTML content for the labels
labelOptions	A Vector of <code>labelOptions()</code> to provide label options for each label. Default NULL
movingOptions	a list of extra options for moving markers. See <code>movingMarkerOptions</code>
options	a list of extra options for markers. See <code>markerOptions</code>
data	the data object from which the argument values are derived; by default, it is the data object provided to <code>leaflet()</code> initially, but can be overridden

Value

the new map object

References

<https://github.com/ewoken/Leaflet.MovingMarker>

See Also

Other MovingMarker Functions: `movingMarkerOptions()`, `startMoving()`

Examples

```
library(sf)
library(leaflet)
library(leaflet.extras2)

crds <- data.frame(structure(
  c(
    -67.5, -68.5, -69.6, -70.5, -71.3, -72.2, -72.7,
    -72.9, -73, -72.4, -70.8, 15.8, 16.5, 17.3, 17.8, 18.3, 18.6,
    19.8, 21.6, 23.5, 25.1, 27.9, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1
  ),
  dim = c(11L, 3L), dimnames = list(NULL, c("X", "Y", "L1"))
))
df <- st_sf(st_sfc(st_linestring(as.matrix(crds), dim = "XYZ"), crs = 4326))
st_geometry(df) <- "geometry"
df <- st_zm(df)

leaflet() %>%
  addTiles() %>%
  addPolylines(data = df) %>%
  addMovingMarker(
    data = df,
    movingOptions = movingMarkerOptions(autostart = TRUE, loop = TRUE),
    label = "I am a pirate!",
```

```

    popup = "Arrr"
  )

```

addOpenweatherCurrent *Add current OpenWeatherMap Marker*

Description

Add current OpenWeatherMap Marker

Usage

```

addOpenweatherCurrent(
  map,
  apikey = NULL,
  group = NULL,
  layerId = NULL,
  options = openweatherCurrentOptions()
)

```

Arguments

map	a map widget object created from leaflet()
apikey	a valid Openweathermap-API key.
group	the name of the group the newly created layers should belong to (for clearGroup() and addLayersControl() purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g., markers and polygons) can share the same group name.
layerId	the layer id
options	List of further options. See openweatherCurrentOptions

Value

the new map object

Note

The current weather icons will appear beginning with zoom level 9 and if used in Shiny, a click on an icon will update a Shiny input at `input$MAPID_owm_click`.

References

<https://github.com/trafficonese/leaflet-openweathermap>

See Also

Other Openweathermap Functions: [addOpenweatherTiles\(\)](#), [openweatherCurrentOptions\(\)](#), [openweatherOptions\(\)](#)

Examples

```
## Not run:
library(leaflet)
library(leaflet.extras2)

Sys.setenv("OPENWEATHERMAP" = "Your_API_Key")

leaflet() %>%
  addTiles() %>%
  setView(9, 50, 9) %>%
  addOpenweatherCurrent(options = openweatherCurrentOptions(
    lang = "en", popup = TRUE
  ))

## End(Not run)
```

addOpenweatherTiles	<i>Add OpenWeatherMap Tiles</i>
---------------------	---------------------------------

Description

Add OpenWeatherMap Tiles

Usage

```
addOpenweatherTiles(
  map,
  apikey = NULL,
  layers = NULL,
  group = NULL,
  layerId = NULL,
  opacity = 0.5,
  options = openweatherOptions()
)
```

Arguments

map	a map widget object created from leaflet()
apikey	a valid OpenWeatherMap-API key.
layers	character vector of layers you wish to add to the map. The following layers are currently possible <code>c("clouds", "cloudsClassic", "precipitation", "precipitationClassic", "rain", "rainClassic", "snow", "pressure", "pressureContour", "temperature", "wind")</code> .

group	the name of the group the newly created layers should belong to (for <code>clearGroup()</code> and <code>addLayersControl()</code> purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g., markers and polygons) can share the same group name.
layerId	the layer id
opacity	opacity of the layer
options	List of further options. See openweatherOptions

Value

the new map object

Note

Out of the box a legend image is only available for Pressure, Precipitation Classic, Clouds Classic, Rain Classic, Snow, Temperature and Wind Speed. Please add your own images if you need some more.

References

<https://github.com/trafficonese/leaflet-openweathermap>

See Also

Other Openweathermap Functions: [addOpenweatherCurrent\(\)](#), [openweatherCurrentOptions\(\)](#), [openweatherOptions\(\)](#)

Examples

```
## Not run:
library(leaflet)
library(leaflet.extras2)

Sys.setenv("OPENWEATHERMAP" = "Your_API_Key")

leaflet() %>%
  addTiles() %>%
  setView(9, 50, 6) %>%
  addOpenweatherTiles(layers = "wind")

## End(Not run)
```

addPlayback	<i>Add Playback to Leaflet</i>
-------------	--------------------------------

Description

The **LeafletPlayback plugin** provides the ability to replay GPS Points in the form of POINT Simple Features. Rather than simply animating a marker along a polyline, the speed of the animation is synchronized to a clock. The playback functionality is similar to a video player; you can start and stop playback or change the playback speed.

Usage

```
addPlayback(
  map,
  data,
  time = "time",
  icon = NULL,
  pathOpts = pathOptions(),
  popup = NULL,
  label = NULL,
  popupOptions = NULL,
  labelOptions = NULL,
  options = playbackOptions(),
  name = NULL
)
```

Arguments

map	a map widget
data	data must be a POINT Simple Feature or a list of POINT Simple Feature's with a time column.
time	The column name of the time column. Default is "time".
icon	an icon which can be created with makeIcon
pathOpts	style the CircleMarkers with pathOptions
popup	A formula with the column names for the popup content
label	A formula with the column names for the label content
popupOptions	A Vector of popupOptions() to provide popups
labelOptions	A Vector of labelOptions() to provide label options for each label. Default NULL
options	List of additional options. See playbackOptions
name	A formula with the column names for the feature name

Value

the new map object

Note

If used in Shiny, you can listen to 2 events

- 'map-ID'+"_pb_mouseover"
- 'map-ID'+"_pb_click"

References

<https://github.com/hallahan/LeafletPlayback>

See Also

Other Playback Functions: [playbackOptions\(\)](#), [removePlayback\(\)](#)

Examples

```
library(leaflet)
library(leaflet.extras2)
library(sf)

## Single Elements
data <- sf::st_as_sf(leaflet::atlStorms2005[1, ])
data <- st_cast(data, "POINT")
data$time <- as.POSIXct(
  seq.POSIXt(Sys.time() - 1000, Sys.time(), length.out = nrow(data))
)
data$label <- as.character(data$time)

leaflet() %>%
  addTiles() %>%
  addPlayback(
    data = data, label = ~label,
    popup = ~ sprintf(
      "I am a popup for <b>%s</b> and <b>%s</b>",
      Name, label
    ),
    popupOptions = popupOptions(offset = c(0, -35)),
    options = playbackOptions(
      radius = 3,
      tickLen = 36000,
      speed = 50,
      maxInterpolationTime = 1000
    ),
    pathOpts = pathOptions(weight = 5)
  )

## Multiple Elements
data <- sf::st_as_sf(leaflet::atlStorms2005[1:5, ])
data$Name <- as.character(data$Name)
data <- st_cast(data, "POINT")
data$time <- unlist(lapply(rle(data$Name)$lengths, function(x) {
```

```

    seq.POSIXt(as.POSIXct(Sys.Date() - 2), as.POSIXct(Sys.Date())), length.out = x)
  )))
data$time <- as.POSIXct(data$time, origin = "1970-01-01")
data$label <- paste0("Time: ", data$time)
data$popup <- sprintf(
  "<h3>Customized Popup</h3><b>Name</b>: %s<br><b>Time</b>: %s",
  data$Name, data$time
)
data <- split(data, f = data$Name)

leaflet() %>%
  addTiles() %>%
  addPlayback(
    data = data,
    popup = ~popup,
    label = ~label,
    popupOptions = popupOptions(offset = c(0, -35)),
    labelOptions = labelOptions(noHide = TRUE),
    options = playbackOptions(
      radius = 3,
      tickLen = 1000000,
      speed = 5000,
      maxInterpolationTime = 10000,
      transitionpopup = FALSE,
      transitionlabel = FALSE,
      playCommand = "Let's go",
      stopCommand = "Stop it!",
      color = c(
        "red", "green", "blue",
        "orange", "yellow"
      )
    ),
    pathOpts = pathOptions(weight = 5)
  )

```

addProtobuf

Add protobuf vector tiles

Description

Loads remote Mapbox Vector Tiles (.pbf / .mvt) with `L.vectorGrid.protobuf`. Style each vector-tile layer by name via [vectorStyling](#) (OpenMapTiles / Mapbox / Nextzen names).

Usage

```

addProtobuf(
  map,
  urlTemplate,
  attribution = NULL,
  layerId = NULL,

```

```

    group = NULL,
    key = NULL,
    interactive = TRUE,
    options = leaflet::tileOptions(),
    popup = NULL,
    label = NULL,
    styling = vectorStyling(),
    data = getMapData(map)
  )

```

Arguments

map	a map widget object created from leaflet()
urlTemplate	Tile URL with {z}, {x}, {y}. Use {key} together with key for API tokens.
attribution	the attribution text of the tile layer (HTML)
layerId	the layer id
group	the name of the group the newly created layers should belong to (for clearGroup() and addLayersControl() purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g., markers and polygons) can share the same group name.
key	Optional API key substituted into {key} in the URL.
interactive	Whether the layer fires mouse events. Default TRUE.
options	a list of extra options for tile layers, popups, paths (circles, rectangles, polygons, ...), or other map elements
popup	Name of a feature property shown in a popup on click.
label	Name of a feature property shown as a tooltip on hover.
styling	Named list of path styles, one per vector-tile layer name. See vectorStyling .
data	the data object from which the argument values are derived; by default, it is the data object provided to leaflet() initially, but can be overridden

Details

In Shiny a click updates `input$MAPID_vectorgrid_pbf_click`.

Value

the new map object

References

<https://github.com/Leaflet/Leaflet.VectorGrid>

See Also

Other Vectorgrid Functions: [addVectorgrid\(\)](#), [clearVectorgrid\(\)](#), [removeVectorgrid\(\)](#), [vectorStyling\(\)](#)

Examples

```
## Not run:
leaflet() %>%
  addTiles() %>%
  addProtobuf(
    urlTemplate = "https://vector.openstreetmap.org/shortbread_v1/{z}/{x}/{y}.mvt",
    layerId = "osm",
    attribution = "OpenStreetMap"
  )

## End(Not run)
```

addReachability	<i>Add Isochrones to Leaflet</i>
-----------------	----------------------------------

Description

A leaflet plugin which shows areas of reachability based on time or distance for different modes of travel using the openrouteservice isochrones API. Based on the [leaflet.reachability plugin](#)

Usage

```
addReachability(map, apikey = NULL, options = reachabilityOptions())
```

Arguments

map	a map widget
apikey	a valid Openrouteservice API-key. Can be obtained from Openrouteservice
options	A list of further options. See reachabilityOptions

Value

the new map object

Note

When used in Shiny, 3 events update a certain shiny Input:

1. reachability:displayed updates input\$MAPID_reachability_displayed
2. reachability:delete updates input\$MAPID_reachability_delete
3. reachability:error updates input\$MAPID_reachability_error

References

<https://github.com/traffordDataLab/leaflet.reachability>

See Also

Other Reachability Functions: [reachabilityOptions\(\)](#), [removeReachability\(\)](#)

Examples

```
## Not run:
library(leaflet)
library(leaflet.extras2)

Sys.setenv("OPRS" = "Your_API_Key")

leaflet() %>%
  addTiles() %>%
  setView(8, 50, 10) %>%
  addReachability()

## End(Not run)
```

addSidebar

Add a Sidebar Leaflet Control

Description

The sidebar HTML must be created with [sidebar_tabs](#) and [sidebar_pane](#) before [leafletOutput](#) is called.

Usage

```
addSidebar(map, id = "sidebar", options = list(position = "left"), ns = NULL)
```

Arguments

map	A leaflet map widget
id	Id of the sidebar-div. Must match with the id of sidebar_tabs
options	A named list with the only option position, which should be either left or right.
ns	The namespace function, if used in Shiny modules.

Value

the new map object

References

<https://github.com/Turbo87/sidebar-v2>

See Also

Other Sidebar Functions: [closeSidebar\(\)](#), [openSidebar\(\)](#), [removeSidebar\(\)](#), [sidebar_pane\(\)](#), [sidebar_tabs\(\)](#)

Examples

```
## Not run:
library(shiny)

# run example app showing a single sidebar
runApp(paste0(
  system.file("examples", package = "leaflet.extras2"),
  "/sidebar_app.R"
))

# run example app showing two sidebars
runApp(paste0(
  system.file("examples", package = "leaflet.extras2"),
  "/multi_sidebar_app.R"
))

## End(Not run)
```

addSidebyside

Add Side by Side View

Description

A Leaflet control to add a split screen to compare two map overlays. The plugin works with Panes, see the example.

Usage

```
addSidebyside(
  map,
  layerId = NULL,
  leftId = NULL,
  rightId = NULL,
  options = list/thumbSize = 42, padding = 0)
)
```

Arguments

map	a map widget
layerId	the layer id, needed for removeSidebyside
leftId	the layerId of the Tile layer that should be visible on the left side
rightId	the layerId of the Tile layer that should be visible on the right side
options	A list of options. Currently only thumbSize and padding can be changed.

Value

the new map object

Note

It is currently not working correctly if the baseGroups are defined in [addLayersControl](#).

References

<https://github.com/digidem/leaflet-side-by-side>

See Also

Other Sidebyside Functions: [removeSidebyside\(\)](#)

Examples

```
library(leaflet)
library(leaflet.extras2)

leaflet(quakes) %>%
  addMapPane("left", zIndex = 0) %>%
  addMapPane("right", zIndex = 0) %>%
  addTiles(
    group = "base", layerId = "baseid",
    options = pathOptions(pane = "right")
  ) %>%
  addProviderTiles(providers$CartoDB.DarkMatter,
    group = "carto", layerId = "cartoid",
    options = pathOptions(pane = "left")
  ) %>%
  addCircleMarkers(
    data = breweries91[1:15, ], color = "blue", group = "blue",
    options = pathOptions(pane = "left")
  ) %>%
  addCircleMarkers(data = breweries91[15:20, ], color = "yellow", group = "yellow") %>%
  addCircleMarkers(
    data = breweries91[15:30, ], color = "red", group = "red",
    options = pathOptions(pane = "right")
  ) %>%
  addLayersControl(overlayGroups = c("blue", "red", "yellow")) %>%
  addSidebyside(
    layerId = "sidecontrols",
    rightId = "baseid",
    leftId = "cartoid"
  )
```

addSpinner	<i>Add Spin Plugin</i>
------------	------------------------

Description

Adds an animated loading spinning over the map.

Usage

```
addSpinner(map)

startSpinner(map, options = NULL)

stopSpinner(map)
```

Arguments

map	A map widget object created from leaflet
options	Spin.js options. Named list. See http://spin.js.org

Value

A leaflet map object

Shiny

`startSpinner()` and `stopSpinner()` in the same [leaflet](#) or [leafletProxy](#) chain are sent to the browser together. Use [spinWhile](#) (or start the spinner, then run the work after `session$onFlushed`).

References

<https://github.com/makinacorporus/Leaflet.Spin>
<https://github.com/fgnass/spin.js>

See Also

Other Spinner Functions: [spinWhile\(\)](#)

Examples

```
library(leaflet)

leaflet(data = quakes) %>%
  addTiles() %>%
  addSpinner() %>%
  startSpinner(options = list("lines" = 7, "length" = 20)) %>%
  addMarkers(~long, ~lat, popup = ~ as.character(mag), label = ~ as.character(mag)) %>%
  stopSpinner()
```

```
## Not run:
library(shiny)
shinyApp(
  ui = fluidPage(
    actionButton("go", "Load markers"),
    leafletOutput("leaf")
  ),
  server = function(input, output, session) {
    output$leaf <- renderLeaflet({
      leaflet() %>%
        addTiles() %>%
        addSpinner()
    })
    observeEvent(input$go, {
      spinWhile("leaf",
        {
          Sys.sleep(2)
          leafletProxy("leaf") %>%
            addMarkers(data = quakes, ~long, ~lat)
        },
        options = list(lines = 7, length = 20)
      )
    })
  }
)

## End(Not run)
```

addTangram

Adds a Tangram layer to a Leaflet map in a Shiny App.

Description

Adds a Tangram layer to a Leaflet map in a Shiny App.

Usage

```
addTangram(map, scene = NULL, layerId = NULL, group = NULL, options = NULL)
```

Arguments

map	a map widget object created from leaflet()
scene	Path to a required .yaml or .zip file. If the file is within the /www folder of a Shiny-App, only the filename must be given, otherwise the full path is needed. See the Tangram repository or the Tangram docs for further information on how to edit such a .yaml file.
layerId	the layer id

group	the name of the group the newly created layers should belong to (for <code>clearGroup()</code> and <code>addLayersControl()</code> purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g., markers and polygons) can share the same group name.
options	A list of further options. See the app in the <code>examples/tangram</code> folder or the docs for further information.

Value

the new map object

Note

Only works correctly in a Shiny-App environment.

References

<https://github.com/tangrams/tangram>

Examples

```
## Not run:
library(shiny)
library(leaflet)
library(leaflet.extras2)

## In the /www folder of a ShinyApp. Must contain the Nextzen API-key
scene <- "scene.yaml"

ui <- fluidPage(leafletOutput("map"))

server <- function(input, output, session) {
  output$map <- renderLeaflet({
    leaflet() %>%
      addTiles(group = "base") %>%
      addTangram(scene = scene, group = "tangram") %>%
      addCircleMarkers(data = breweries91, group = "brews") %>%
      setView(11, 49.4, 14) %>%
      addLayersControl(
        baseGroups = c("tangram", "base"),
        overlayGroups = c("brews")
      )
  })
}

shinyApp(ui, server)

## End(Not run)
```

addTimeslider

Add Time Slider to Leaflet

Description

The **LeafletSlider plugin** enables you to dynamically add and remove Markers/Lines on a map by using a JQuery UI slider.

Usage

```
addTimeslider(
  map,
  data,
  radius = 10,
  stroke = TRUE,
  color = "#03F",
  weight = 5,
  opacity = 0.5,
  fill = TRUE,
  fillColor = color,
  fillOpacity = 0.2,
  dashArray = NULL,
  popup = NULL,
  popupOptions = NULL,
  label = NULL,
  labelOptions = NULL,
  ordertime = TRUE,
  options = timesliderOptions()
)
```

Arguments

map	a map widget
data	data must be a Simple Feature collection of type POINT or LINESTRING with a column of class Date or POSIXct.
radius	a numeric vector of radii for the circles; it can also be a one-sided formula, in which case the radius values are derived from the data (units in meters for circles, and pixels for circle markers)
stroke	whether to draw stroke along the path (e.g., the borders of polygons or circles)
color	stroke color
weight	stroke width in pixels
opacity	stroke opacity (or layer opacity for tile layers)
fill	whether to fill the path with color (e.g., filling on polygons or circles)
fillColor	fill color

fillOpacity	fill opacity
dashArray	a string that defines the stroke dash pattern
popup	a character vector of the HTML content for the popups (you are recommended to escape the text using <code>htmltools::htmlEscape()</code> for security reasons)
popupOptions	A Vector of <code>popupOptions()</code> to provide popups
label	a character vector of the HTML content for the labels
labelOptions	A Vector of <code>labelOptions()</code> to provide label options for each label. Default NULL
ordertime	boolean value indicating whether to order the data by the time column. The slider will adopt the order of the timestamps. The default is TRUE.
options	List of additional options. See <code>timesliderOptions</code>

Value

the new map object

References

<https://github.com/dwilhelm89/LeafletSlider>

See Also

Other Timeslider Functions: `removeTimeslider()`, `timesliderOptions()`

Examples

```
library(leaflet)
library(leaflet.extras2)
library(sf)

data <- sf::st_as_sf(leaflet::atlStorms2005[1, ])
data <- st_cast(data, "POINT")
data$time <- as.POSIXct(
  seq.POSIXt(Sys.time() - 1000, Sys.time(), length.out = nrow(data))
)

leaflet() %>%
  addTiles() %>%
  addTimeslider(
    data = data,
    options = timesliderOptions(
      position = "topright",
      timeAttribute = "time",
      range = TRUE
    )
  ) %>%
  setView(-72, 22, 4)
```

addVectorgrid

Add sliced GeoJSON / TopoJSON as a VectorGrid

Description

Displays large polygon/line datasets as tiled vector features using [Leaflet.VectorGrid](#) (`L.vectorGrid.slicer`). This is more efficient than [addPolygons](#) for big GeoJSON.

Usage

```
addVectorgrid(
  map,
  data,
  layerId = NULL,
  group = NULL,
  featureId = NULL,
  popup = NULL,
  stroke = TRUE,
  color = "#03F",
  weight = 5,
  opacity = 0.5,
  fill = TRUE,
  fillColor = color,
  fillOpacity = 0.2,
  dashArray = NULL,
  options = pathOptions(),
  interactive = TRUE
)
```

Arguments

map	a map widget object created from leaflet()
data	An sf / Spatial object, a GeoJSON object, or a URL returning GeoJSON / TopoJSON.
layerId	the layer id
group	the name of the group the newly created layers should belong to (for clearGroup() and addLayersControl() purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g., markers and polygons) can share the same group name.
featureId	Formula or vector of unique feature ids (used for highlight and the Shiny click id). A formula passed as layerId is treated as featureId.
popup	Formula, column name or character vector with HTML for the click popup.
stroke	whether to draw stroke along the path (e.g., the borders of polygons or circles)
color	stroke color

weight	stroke width in pixels
opacity	stroke opacity (or layer opacity for tile layers)
fill	whether to fill the path with color (e.g., filling on polygons or circles)
fillColor	fill color
fillOpacity	fill opacity
dashArray	a string that defines the stroke dash pattern
options	a list of extra options for tile layers, popups, paths (circles, rectangles, polygons, ...), or other map elements
interactive	Whether the layer fires mouse events. Default TRUE.

Details

In Shiny a click updates input\$MAPID_vectorgrid_click with id, group, lat, lng and properties.

Value

the new map object

References

<https://github.com/Leaflet/Leaflet.VectorGrid>

See Also

Other Vectorgrid Functions: [addProtobuf\(\)](#), [clearVectorgrid\(\)](#), [removeVectorgrid\(\)](#), [vectorStyling\(\)](#)

Examples

```
## Not run:
library(leaflet)
library(sf)

nc <- st_read(system.file("shape/nc.shp", package = "sf"), quiet = TRUE)
leaflet() %>%
  addTiles() %>%
  addVectorgrid(
    data = nc,
    layerId = "nc",
    featureId = ~NAME,
    popup = ~NAME,
    color = "black",
    fillColor = "#4daf4a",
    weight = 1
  )

## End(Not run)
```

`addVelocity`*Add Velocity Animation*

Description

Add velocity animated data to leaflet. Based on the [leaflet-velocity plugin](#)

Usage

```
addVelocity(  
  map,  
  layerId = NULL,  
  group = NULL,  
  content = NULL,  
  options = velocityOptions()  
)
```

Arguments

<code>map</code>	a map widget object created from leaflet()
<code>layerId</code>	the layer id
<code>group</code>	the name of the group the newly created layers should belong to (for clearGroup() and addLayersControl() purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g., markers and polygons) can share the same group name.
<code>content</code>	the path or URL to a JSON file representing the velocity data or a data.frame which can be transformed to such a JSON file. Please see the demo files for some example data.
<code>options</code>	List of further options. See velocityOptions

Value

the new map object

References

<https://github.com/onaci/leaflet-velocity>

See Also

Other Velocity Functions: [removeVelocity\(\)](#), [setOptionsVelocity\(\)](#), [velocityOptions\(\)](#)

Examples

```
## Not run:
library(leaflet)
library(leaflet.extras2)
content <- "https://raw.githubusercontent.com/onaci/leaflet-velocity/master/demo/water-gbr.json"
leaflet() %>%
  addTiles(group = "base") %>%
  setView(145, -20, 4) %>%
  addVelocity(content = content, group = "velo", layerId = "veloid") %>%
  addLayersControl(baseGroups = "base", overlayGroups = "velo")

## End(Not run)
```

addWMS

Add Queryable WMS Layer

Description

A Leaflet plugin for working with Web Map services, providing: single-tile/untiled/nontiled layers, shared WMS sources, and **GetFeatureInfo**-powered identify.

You can also use **CQL-Filters** by appending a string to the 'baseUrl'.

Something like 'http://server/wms?qql_filter=attribute=value'

Usage

```
addWMS(
  map,
  baseUrl,
  layerId = NULL,
  group = NULL,
  options = WMSTileOptions(),
  attribution = NULL,
  layers = NULL,
  popupOptions = NULL,
  checkempty = FALSE,
  headers = NULL,
  data = getMapData(map)
)
```

Arguments

map	a map widget object created from <code>leaflet()</code>
baseUrl	a base URL of the WMS service
layerId	the layer id

group	the name of the group the newly created layers should belong to (for <code>clearGroup()</code> and <code>addLayersControl()</code> purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g., markers and polygons) can share the same group name.
options	a list of extra options for tile layers, popups, paths (circles, rectangles, polygons, ...), or other map elements
attribution	the attribution text of the tile layer (HTML)
layers	comma-separated list of WMS layers to show
popupOptions	List of popup options. See <code>popupOptions</code> . Default is NULL.
checkempty	Should the returned HTML-content be checked for emptiness? If the HTML-body is empty no popup is opened. Default is FALSE
headers	Optional HTTP headers for authenticated WMS requests, as a named character vector (<code>c(Authorization = "Bearer <token>")</code>) or a list of <code>list(header = "Authorization", value = "Bearer <token>")</code> .
data	the data object from which the argument values are derived; by default, it is the data object provided to <code>leaflet()</code> initially, but can be overridden

Value

the new map object

Note

The WMS attribution is shown only while the layer (or its group) is visible, matching `addWMSTiles`. `GetFeatureInfo` requests accept HTTP redirects (e.g. 301) and upgrade `http://` WMS URLs to `https://` on HTTPS pages so popups still work behind a reverse proxy. To change WMS request parameters such as time in Shiny, keep the map in `renderLeaflet()` and call `setWMSParams` on a `leafletProxy` instead of recreating the whole map. Custom headers (Basic/Bearer) are sent for tiles, the single-image overlay and `GetFeatureInfo`. The WMS server must allow CORS for those header names. Tokens travel in the browser; do not use them for secrets that must stay on the server.

References

<https://github.com/heigeo/leaflet.wms>

See Also

Other WMS Functions: `setWMSParams()`

Examples

```
library(leaflet)
library(leaflet.extras2)

leaflet() %>%
  addTiles(group = "base") %>%
  setView(9, 50, 5) %>%
```

```

addWMS(
  baseUrl = "https://maps.dwd.de/geoserver/dwd/wms",
  layers = "dwd:BRD_1km_winddaten_10m",
  popupOptions = popupOptions(maxWidth = 600),
  checkempty = TRUE,
  options = WMSTileOptions(
    transparent = TRUE,
    format = "image/png",
    info_format = "text/html"
  )
)

```

antpathOptions

Antpath Options

Description

Additional list of options for 'ant-path' animated polylines.

Usage

```

antpathOptions(
  delay = 400,
  paused = FALSE,
  reverse = FALSE,
  hardwareAccelerated = FALSE,
  dashArray = c(10, 20),
  pulseColor = "#ffffff",
  lineCap = NULL,
  lineJoin = NULL,
  interactive = TRUE,
  pointerEvents = NULL,
  className = "",
  ...
)

```

Arguments

delay	Add a delay to the animation flux. Default is 400
paused	Should the animation be paused. Default is FALSE
reverse	Defines if the flow follows the path order or not. Default is FALSE
hardwareAccelerated	Makes the animation run with hardware acceleration. Default is FALSE
dashArray	The size of the animated dashes. Default is c(10, 20)
pulseColor	Adds a color to the dashed flux. Default is #ffffff
lineCap	a string that defines shape to be used at the end of the stroke.

lineJoin	a string that defines shape to be used at the corners of the stroke.
interactive	whether the element emits mouse events
pointerEvents	sets the pointer-events attribute on the path if SVG backend is used
className	a CSS class name set on an element
...	extra options passed to underlying JavaScript object constructor.

Value

A list of options for addAntpath animated polylines

See Also

Other Antpath Functions: [addAntpath\(\)](#), [clearAntpath\(\)](#), [removeAntpath\(\)](#)

arrowheadOptions	<i>Arrowhead Options</i>
------------------	--------------------------

Description

Additional list of options for polylines with arrowheads. You can also pass options inherited from [L.Path](#)

Usage

```
arrowheadOptions(
  yawn = 60,
  size = "15%",
  frequency = "allvertices",
  proportionalToTotal = FALSE,
  offsets = NULL,
  perArrowheadOptions = NULL,
  ...
)
```

Arguments

yawn	Defines the width of the opening of the arrowhead, given in degrees. The larger the angle, the wider the arrowhead.
size	Determines the size of the arrowhead. Accepts three types of values: • A string with the suffix 'm', i.e. '500m' will set the size of the arrowhead to that number of meters. • A string with the suffix '%', i.e. '15%' will render arrows whose size is that percentage of the size of the parent polyline. If the polyline has multiple segments, it will take the percent of the average size of the segments.

	• A string the suffix 'px', i.e. '20px' will render an arrowhead whose size stays at a constant pixel value, regardless of zoom level. Will look strange at low zoom levels or for smaller parent vectors. Ideal for larger parent vectors and at higher zoom levels.
frequency	How many arrowheads are rendered on a polyline. • 'allvertices' renders an arrowhead on each vertex. • 'endonly' renders only one at the end. • A numeric value renders that number of arrowheads evenly spaced along the polyline. • A string with suffix 'm', i.e. '100m' will render arrowheads spaced evenly along the polyline with roughly that many meters between each one. • A string with suffix 'px', i.e. '30px' will render arrowheads spaced evenly with roughly that many pixels between each, regardless of zoom level.
proportionalToTotal	Only relevant when size is given as a percent. Useful when frequency is set to 'endonly'. Will render the arrowheads with a size proportional to the entire length of the multi-segmented polyline, rather than proportional to the average length of all the segments.
offsets	Enables the developer to have the arrowheads start or end at some offset from the start and/or end of the polyline. This option can be a list with 'start' and 'end' names. The values must be strings defining the size of the offset in either meters or pixels, i.e. <code>list('start' = '100m', 'end' = '15px')</code>.
perArrowheadOptions	Enables the developer to customize arrowheads on a one-by-one basis. Must be in the form of a function of <code>i</code>, which is the index of the arrowhead as it is rendered in the loop through all arrowheads. Must return an options object. Cannot account for frequency or proportionalToTotal from within the perArrowheadOptions callback. See the example for details.
...	Additional options for arrowheads, inherited from L.Path

Value

A list of options for addArrowhead polylines

References

<https://github.com/slutske22/leaflet-arrowheads#options>

See Also

Other Arrowhead Functions: [addArrowhead\(\)](#), [clearArrowhead\(\)](#), [removeArrowhead\(\)](#)

clearAntpath	<i>clearAntpath</i>
--------------	---------------------

Description

Clear all Antpaths

Usage

```
clearAntpath(map)
```

Arguments

map	a map widget object, possibly created from leaflet() but more likely from leafletProxy()
-----	--

Value

the new map object

See Also

Other Antpath Functions: [addAntpath\(\)](#), [antpathOptions\(\)](#), [removeAntpath\(\)](#)

clearArrowhead	<i>Remove arrowheads from Lines by group</i>
----------------	--

Description

Remove arrowheads from Lines by group

Usage

```
clearArrowhead(map, group)
```

Arguments

map	the map
group	A group name

Value

A modified leaflet map

See Also

Other Arrowhead Functions: [addArrowhead\(\)](#), [arrowheadOptions\(\)](#), [removeArrowhead\(\)](#)

clearConditionalLayers	<i>clearConditionalLayers</i>
------------------------	-------------------------------

Description

clearConditionalLayers

Usage

clearConditionalLayers(map)

Arguments

map	A map widget object created from leaflet .
-----	--

See Also

Other LayerGroupConditional Plugin: [addLayerGroupConditional\(\)](#), [removeConditionalLayer\(\)](#)

clearFuture	<i>clearFuture</i>
-------------	--------------------

Description

Resets the stack of future items.

Usage

clearFuture(map)

Arguments

map	a map widget object created from leafletProxy
-----	---

Value

the new map object

References

<https://github.com/cscott530/leaflet-history>

See Also

Other History Functions: [addHistory\(\)](#), [clearHistory\(\)](#), [goBackHistory\(\)](#), [goForwardHistory\(\)](#), [historyOptions\(\)](#)

`clearHexbin`*clearHexbin*

Description

Clears the data of the hexbinLayer.

Usage

```
clearHexbin(map)
```

Arguments

map	The map widget
-----	----------------

Value

the new map object

See Also

Other Hexbin-D3 Functions: [addHexbin\(\)](#), [hexbinOptions\(\)](#), [hideHexbin\(\)](#), [showHexbin\(\)](#), [updateHexbin\(\)](#)

`clearHistory`*clearHistory*

Description

Resets the stack of history items.

Usage

```
clearHistory(map)
```

Arguments

map	a map widget object created from leafletProxy
-----	---

Value

the new map object

References

<https://github.com/cscott530/leaflet-history>

See Also

Other History Functions: [addHistory\(\)](#), [clearFuture\(\)](#), [goBackHistory\(\)](#), [goForwardHistory\(\)](#), [historyOptions\(\)](#)

clearVectorgrid	<i>Clear all VectorGrid layers</i>
-----------------	------------------------------------

Description

Clear all VectorGrid layers

Usage

```
clearVectorgrid(map)
```

Arguments

map	a map widget object, possibly created from leaflet() but more likely from leafletProxy()
-----	--

Value

the new map object

See Also

Other Vectorgrid Functions: [addProtobuf\(\)](#), [addVectorgrid\(\)](#), [removeVectorgrid\(\)](#), [vectorStyling\(\)](#)

closeSidebar	<i>Close the Sidebar</i>
--------------	--------------------------

Description

Close the Sidebar

Usage

```
closeSidebar(map, sidebar_id = NULL)
```

Arguments

map	A leaflet map widget
sidebar_id	The id of the sidebar (per sidebar_tabs). Defaults to NULL such that the first sidebar is used.

Value

the new map object

See Also

Other Sidebar Functions: [addSidebar\(\)](#), [openSidebar\(\)](#), [removeSidebar\(\)](#), [sidebar_pane\(\)](#), [sidebar_tabs\(\)](#)

clusterchartOptions	<i>clusterchartOptions</i>
---------------------	----------------------------

Description

Adds options for clusterCharts

Usage

```
clusterchartOptions(  
  rmax = 30,  
  size = c(20, 20),  
  width = 40,  
  height = 50,  
  strokeWidth = 1,  
  innerRadius = 10,  
  labelBackground = FALSE,  
  labelFill = "white",  
  labelStroke = "black",  
  labelColor = "black",  
  labelOpacity = 0.9,  
  digits = 2,  
  sortTitlebyCount = TRUE  
)
```

Arguments

rmax	The maximum radius of the clusters.
size	The size of the cluster markers.
width	The width of the bar-charts.
height	The height of the bar-charts.
strokeWidth	The stroke width of the chart.
innerRadius	The inner radius of pie-charts.
labelBackground	Should the label have a background? Default is 'FALSE'
labelFill	The label background color. Default is 'white'

labelStroke	The label stroke color. Default is 'black'
labelColor	The label color. Default is 'black'
labelOpacity	The label color. Default is '0.9'
digits	The amount of digits. Default is '2'
sortTitlebyCount	Should the svg-title be sorted by count or by the categories.

See Also

Other clusterCharts: [addClusterCharts\(\)](#)

context_mapmenuItems	<i>context_mapmenuItems</i>
----------------------	-----------------------------

Description

context_mapmenuItems

Usage

context_mapmenuItems(...)

Arguments

... contextmenu item/s

Value

A list of context_menuItem for the map

See Also

Other Contextmenu Functions: [addContextmenu\(\)](#), [addItemContextmenu\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextmenu\(\)](#), [enableContextmenu\(\)](#), [hideContextmenu\(\)](#), [insertItemContextmenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextmenu\(\)](#), [removeallItemsContextmenu\(\)](#), [setDisabledContextmenu\(\)](#), [showContextmenu\(\)](#)

context_markermenuItems	<i>context_markermenuItems</i>
-------------------------	--------------------------------

Description

context_markermenuItems

Usage

context_markermenuItems(...)

Arguments

...	contextmenu item/s
-----	--------------------

Value

A list of context_menuItem for markers

See Also

Other Contextmenu Functions: [addContextmenu\(\)](#), [addItemContextmenu\(\)](#), [context_mapmenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextmenu\(\)](#), [enableContextmenu\(\)](#), [hideContextmenu\(\)](#), [insertItemContextmenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextmenu\(\)](#), [removeallItemsContextmenu\(\)](#), [setDisabledContextmenu\(\)](#), [showContextmenu\(\)](#)

context_menuItem	<i>context_menuItem</i>
------------------	-------------------------

Description

context_menuItem

Usage

context_menuItem(text, callback = NULL, ...)

Arguments

text	The label to use for the menu item
callback	A callback function to be invoked when the menu item is clicked. The callback is passed an object with properties identifying the location the menu was opened at: latlng, layerPoint and containerPoint. The callback-function must be valid JavaScript and will be wrapped in JS .
...	For further options please visit https://github.com/aratcliffe/Leaflet.contextmenu

Value

A contextmenu item list

See Also

Other Contextmenu Functions: [addContextmenu\(\)](#), [addItemContextmenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [disableContextmenu\(\)](#), [enableContextmenu\(\)](#), [hideContextmenu\(\)](#), [insertItemContextmenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextmenu\(\)](#), [removeallItemsContextmenu\(\)](#), [setDisabledContextmenu\(\)](#), [showContextmenu\(\)](#)

disableContextmenu	<i>disableContextmenu</i>
--------------------	---------------------------

Description

Disable the contextmenu

Usage

```
disableContextmenu(map)
```

Arguments

map	a map widget object created from leaflet
-----	--

Value

A leaflet map object

See Also

Other Contextmenu Functions: [addContextmenu\(\)](#), [addItemContextmenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [enableContextmenu\(\)](#), [hideContextmenu\(\)](#), [insertItemContextmenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextmenu\(\)](#), [removeallItemsContextmenu\(\)](#), [setDisabledContextmenu\(\)](#), [showContextmenu\(\)](#)

easyprintMap	<i>easyprintMap</i>
--------------	---------------------

Description

Print or export a map programmatically (e.g. in a Shiny environment).

Usage

```
easyprintMap(map, sizeModes = "A4Portrait", filename = "map")
```

Arguments

map	the map widget
sizeModes	Must match one of the given sizeMode names in easyprintOptions . The options are: CurrentSize, A4Portrait or A4Landscape. If you want to print the map with a Custom sizeMode you need to pass the Custom className. Default is A4Portrait
filename	Name of the file if exportOnly option is TRUE.

Value

A leaflet map object

See Also

Other EasyPrint Functions: [addEasyprint\(\)](#), [easyprintOptions\(\)](#), [removeEasyprint\(\)](#)

Examples

```
## Only run examples in interactive R sessions
if (interactive()) {
  library(shiny)
  library(leaflet)
  library(leaflet.extras2)

  ui <- fluidPage(
    leafletOutput("map"),
    selectInput("scene", "Select Scene", choices = c("CurrentSize", "A4Landscape", "A4Portrait")),
    actionButton("print", "Print Map")
  )

  server <- function(input, output, session) {
    output$map <- renderLeaflet({
      input$print
      leaflet() %>%
        addTiles() %>%
        setView(10, 50, 9) %>%
    })
  }
}
```

```

      addEasyprint(options = easyprintOptions(
        exportOnly = TRUE
      ))
    })
    observeEvent(input$print, {
      leafletProxy("map") %>%
        easyprintMap(sizeModes = input$scene)
    })
  }

  shinyApp(ui, server)
}

```

easyprintOptions	<i>easyprintOptions</i>
------------------	-------------------------

Description

Create a list of further options for the easyprint plugin.

Usage

```

easyprintOptions(
  title = "Print map",
  position = "topleft",
  sizeModes = list("A4Portrait", "A4Landscape", "CurrentSize"),
  defaultSizeTitles = NULL,
  exportOnly = FALSE,
  tileLayer = NULL,
  tileWait = 500,
  filename = "map",
  hidden = FALSE,
  hideControlContainer = TRUE,
  hideClasses = NULL,
  customWindowTitle = NULL,
  spinnerBgColor = "#0DC5C1",
  customSpinnerClass = "epLoader"
)

```

Arguments

title	Sets the text which appears as the tooltip of the print/export button
position	Positions the print button
sizeModes	Either a character vector with one of the following options: CurrentSize, A4Portrait, A4Landscape. Custom pixel sizes can be mixed in as lists with width and height (and optionally name / className): list("CurrentSize", list(width = 3000, height = 1800, name = "High res")). CurrentSize exports at the

current map widget size (often low resolution in Quarto/HTML documents). `list(scale = 3)` captures the current view at 3x pixel resolution without changing zoom or tile labels (best for presentations). A custom width/height resizes the map before export. By default `keepView = TRUE`: the same bounds are kept by zooming in, so OSM/tile labels get smaller. Use `keepView = FALSE` to keep the zoom level and show a larger area, like A4. A custom `className` and CSS `background-image` are optional; see `./inst/examples/easyprint.R` and `./inst/examples/easyprint_app.R`.

<code>defaultSizeTitles</code>	Button tooltips for the default page sizes
<code>exportOnly</code>	If set to <code>TRUE</code> the map is exported to a .png file
<code>tileLayer</code>	The group name of one tile layer that you can wait for to draw (helpful when resizing to a custom size)
<code>tileWait</code>	How long to wait for the tiles to draw (helpful when resizing). Custom sizes always wait at least this long so tiles can reload.
<code>filename</code>	Name of the file if <code>exportOnly</code> option is <code>TRUE</code>
<code>hidden</code>	Set to <code>TRUE</code> if you don't want to display the toolbar. Instead you can create your own buttons or fire print events programmatically.
<code>hideControlContainer</code>	Hides the leaflet controls like the zoom buttons and the attribution on the print out
<code>hideClasses</code>	Use a character vector or list of CSS-classes to hide on the output image.
<code>customWindowTitle</code>	A title for the print window which will get added to the printed paper
<code>spinnerBgColor</code>	A valid css colour for the spinner background color
<code>customSpinnerClass</code>	A class for a custom css spinner to use while waiting for the print.

Value

A list of options for the 'easyprint' control

References

<https://github.com/rowanwins/leaflet-easyPrint>

See Also

Other EasyPrint Functions: [addEasyprint\(\)](#), [easyprintMap\(\)](#), [removeEasyprint\(\)](#)

enableContextmenu	<i>enableContextmenu</i>
-------------------	--------------------------

Description

Enable the contextmenu

Usage

```
enableContextmenu(map)
```

Arguments

map	a map widget object created from leaflet
-----	--

Value

A leaflet map object

See Also

Other Contextmenu Functions: [addContextmenu\(\)](#), [addItemContextmenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextmenu\(\)](#), [hideContextmenu\(\)](#), [insertItemContextmenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextmenu\(\)](#), [removeallItemsContextmenu\(\)](#), [setDisabledContextmenu\(\)](#), [showContextmenu\(\)](#)

geosearchOptions	<i>geosearchOptions</i>
------------------	-------------------------

Description

Add extra options. For a full list please visit the [plugin repository](#) or see the [source code](#)

Usage

```
geosearchOptions(  
  style = c("button", "bar"),  
  resetButton = "x",  
  notFoundMessage = "Nothing found",  
  autoComplete = TRUE,  
  autoCompleteDelay = 250,  
  showMarker = TRUE,  
  showPopup = FALSE,  
  maxMarkers = 1,  
  retainZoomLevel = FALSE,  
  animateZoom = TRUE,
```

```

    autoClose = FALSE,
    searchLabel = "Enter address",
    keepResult = FALSE,
    updateMap = TRUE,
    ...
)

```

Arguments

<code>style</code>	Character. UI style, one of "bar" or "button".
<code>resetButton</code>	Icon or Character for the reset button.
<code>notFoundMessage</code>	Message shown if no result is found.
<code>autoComplete</code>	Logical. Enable autocomplete suggestions.
<code>autoCompleteDelay</code>	Delay in ms before suggestions appear.
<code>showMarker</code>	Logical. Show marker for result location.
<code>showPopup</code>	Logical. Show popup on result location.
<code>maxMarkers</code>	Max number of markers shown.
<code>retainZoomLevel</code>	Logical.
<code>animateZoom</code>	Logical.
<code>autoClose</code>	Logical. Close results after selection.
<code>searchLabel</code>	Placeholder text.
<code>keepResult</code>	Logical. Keep last result shown.
<code>updateMap</code>	Logical. Pan/zoom map on result.
<code>...</code>	Further arguments passed to 'addGeosearch'

Value

A list of options for addGeosearch

See Also

Other Geosearch Functions: [addGeosearch\(\)](#), [removeGeosearch\(\)](#)

geosearchProvider	<i>Provider for GeoSearch</i>
-------------------	-------------------------------

Description

Provider for GeoSearch

Usage

```
geosearchProvider(  
  type = c("OSM", "Bing", "Esri", "GeocodeEarth", "Google", "Here", "LocationIQ",  
    "OpenCage", "Pelias", "Geoapify", "AMap", "GeoApiFr"),  
  options = list()  
)
```

Arguments

type	The provider name
options	Optional named list of options and parameters

Value

A list describing the provider config

gibs_layers	<i>The available GIBS layers with attributes</i>
-------------	--

Description

The available GIBS layers with attributes

Usage

```
gibs_layers
```

Format

An object of class `data.frame` with 276 rows and 4 columns.

`goBackHistory`*goBackHistory*

Description

If possible, will go to previous map extent. Pushes current extent to the "future" stack.

Usage

```
goBackHistory(map)
```

Arguments

map a map widget object created from [leafletProxy](#)

Value

the new map object

References

<https://github.com/cscott530/leaflet-history>

See Also

Other History Functions: [addHistory\(\)](#), [clearFuture\(\)](#), [clearHistory\(\)](#), [goForwardHistory\(\)](#), [historyOptions\(\)](#)

`goForwardHistory`*goForwardHistory*

Description

If possible, will go to next map extent. Pushes current extent to the "back" stack.

Usage

```
goForwardHistory(map)
```

Arguments

map a map widget object created from [leafletProxy](#)

Value

the new map object

References

<https://github.com/cscott530/leaflet-history>

See Also

Other History Functions: [addHistory\(\)](#), [clearFuture\(\)](#), [clearHistory\(\)](#), [goBackHistory\(\)](#), [historyOptions\(\)](#)

heightgraphOptions *heightgraphOptions*

Description

Customize the heightgraph with the following additional options.

Usage

```
heightgraphOptions(
  position = c("bottomright", "topleft", "topright", "bottomleft"),
  width = 800,
  height = 200,
  margins = list(top = 10, right = 30, bottom = 55, left = 50),
  expand = TRUE,
  expandCallback = NULL,
  mappings = NULL,
  highlightStyle = list(color = "red"),
  translation = NULL,
  xTicks = 3,
  yTicks = 3
)
```

Arguments

position	position of control: "topleft", "topright", "bottomleft", or "bottomright". Default is bottomright.
width	The width of the expanded heightgraph display in pixels. Default is 800.
height	The height of the expanded heightgraph display in pixels. Default is 200.
margins	The margins define the distance between the border of the heightgraph and the actual graph inside. You are able to specify margins for top, right, bottom and left in pixels. Default is <code>list(top = 10, right = 30, bottom = 55, left = 50)</code> .
expand	Boolean value that defines if the heightgraph should be expanded on creation. Default is 200.
expandCallback	Function to be called if the heightgraph is expanded or reduced. The state of the heightgraph is passed as an argument. It is TRUE when expanded and FALSE when reduced. Default is NULL.

mappings	You may add a mappings object to customize the colors and labels in the height graph. Without adding custom mappings the segments and labels within the graph will be displayed in random colors. Each key of the object must correspond to the summary key in properties within the FeatureCollection. Default is NULL.
highlightStyle	You can customize the highlight style when using the horizontal line to find parts of the route above an elevation value. Use any Leaflet Path options as value of the highlightStyle parameter. Default is <code>list(color = "red")</code> .
translation	You can change the labels of the heightgraph info field by passing translations for distance, elevation, segment_length, type and legend. Default is NULL.
xTicks	Specify the tick frequency in the x axis of the graph. Corresponds approximately to 2 to the power of value ticks. Default is 3.
yTicks	Specify the tick frequency in the y axis of the graph. Corresponds approximately to 2 to the power of value ticks. Default is 3.

Value

A list of further options for `addHeightgraph`

See Also

Other Heightgraph Functions: [addHeightgraph\(\)](#)

hexbinOptions

hexbinOptions

Description

A list of options for customizing the appearance/behavior of the hexbin layer.

Usage

```
hexbinOptions(
  duration = 200,
  colorScaleExtent = NULL,
  radiusScaleExtent = NULL,
  colorRange = c("#f7fbff", "#08306b"),
  radiusRange = c(5, 15),
  pointerEvents = "all",
  resizetoCount = FALSE,
  tooltip = "Count "
)
```

Arguments

duration	Transition duration for the hexbin layer
colorScaleExtent	extent of the color scale for the hexbin layer. This is used to override the derived extent of the color values and is specified as a vector of the form c(min= numeric, max= numeric). Can be a numeric vector or a custom JS array, like (JS("[40, undefined]"))
radiusScaleExtent	This is the same exact configuration option as colorScaleExtent, only applied to the radius extent.
colorRange	Sets the range of the color scale used to fill the hexbins on the layer.
radiusRange	Sets the range of the radius scale used to size the hexbins on the layer.
pointerEvents	This value is passed directly to an element-level css style for pointer-events. You should only modify this config option if you want to change the mouse event behavior on hexbins. This will modify when the events are propagated based on the visibility state and/or part of the hexbin being hovered.
resizetoCount	Resizes the hexbin to the count. Default is FALSE. If set to TRUE it will resize based on the amount of underlying elements. You can also pass a custom JS function.
tooltip	Should tooltips be displayed? If set to TRUE, it will show the amount of underlying elements. If a string is given, it will append the string before the count. To disable tooltips, please pass NULL or FALSE. You can also pass a custom JS function.

Value

A list of hexbin-specific options

See Also

Other Hexbin-D3 Functions: [addHexbin\(\)](#), [clearHexbin\(\)](#), [hideHexbin\(\)](#), [showHexbin\(\)](#), [updateHexbin\(\)](#)

hideContextmenu

hideContextmenu

Description

Hide the contextmenu

Usage

```
hideContextmenu(map)
```

Arguments

map	a map widget object created from leaflet
-----	--

Value

A leaflet map object

See Also

Other Contextmenu Functions: [addContextmenu\(\)](#), [addItemContextmenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextmenu\(\)](#), [enableContextmenu\(\)](#), [insertItemContextmenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextmenu\(\)](#), [removeallItemsContextmenu\(\)](#), [setDisabledContextmenu\(\)](#), [showContextmenu\(\)](#)

hideHexbin	<i>hideHexbin</i>
------------	-------------------

Description

Hide the hexbinLayer.

Usage

hideHexbin(map)

Arguments

map	The map widget
-----	----------------

Value

the new map object

See Also

Other Hexbin-D3 Functions: [addHexbin\(\)](#), [clearHexbin\(\)](#), [hexbinOptions\(\)](#), [showHexbin\(\)](#), [updateHexbin\(\)](#)

historyOptions	<i>History Options</i>
----------------	------------------------

Description

History Options

Usage

```

historyOptions(
  position = c("topright", "topleft", "bottomleft", "bottomright"),
  maxMovesToSave = 10,
  backImage = "fa fa-caret-left",
  forwardImage = "fa fa-caret-right",
  backText = "",
  forwardText = "",
  backTooltip = "Go to Previous Extent",
  forwardTooltip = "Go to Next Extent",
  backImageBeforeText = TRUE,
  forwardImageBeforeText = FALSE,
  orientation = c("horizontal", "vertical"),
  shouldSaveMoveInHistory = NULL
)

```

Arguments

position	Set the position of the History control. Default is topright.
maxMovesToSave	Number of moves in the history to save before clearing out the oldest. Default value is 10, use 0 or a negative number to make unlimited.
backImage	The class for the 'back' button icon. Default is "fa fa-caret-left".
forwardImage	The class for the 'forward' button icon. Default is "fa fa-caret-right".
backText	The text in the buttons. Default is "".
forwardText	The text in the buttons. Default is "".
backTooltip	Tooltip content. Default is "Go to Previous Extent".
forwardTooltip	Tooltip content. Default is "Go to Next Extent".
backImageBeforeText	When both text and image are present, whether to show the image first or the text first (left to right). Default is TRUE
forwardImageBeforeText	When both text and image are present, whether to show the image first or the text first (left to right). Default is FALSE
orientation	Whether to position the buttons on top of one another or side-by-side. Default is horizontal
shouldSaveMoveInHistory	A JS callback you can provide that gets called with every move. return false to not save a move.

Value

A list of further options for addHistory

References

<https://github.com/cscott530/leaflet-history>

See Also

Other History Functions: [addHistory\(\)](#), [clearFuture\(\)](#), [clearHistory\(\)](#), [goBackHistory\(\)](#), [goForwardHistory\(\)](#)

Examples

```
library(leaflet)
leaflet() %>%
  addTiles() %>%
  addHistory(options = historyOptions(
    position = "bottomright",
    maxMovesToSave = 20,
    backText = "Go back",
    forwardText = "Go forward",
    orientation = "vertical"
  ))
```

insertItemContextmenu *insertItemContextmenu*

Description

Insert a new contextmenu menu item at a specific index

Usage

```
insertItemContextmenu(map, option, index)
```

Arguments

map	a map widget object created from leaflet
option	new menu item to add
index	Index of the contextmenu. (NOTE: Since the index is passed to JavaScript, it is zero-based)

Value

A leaflet map object

See Also

Other Contextmenu Functions: [addContextmenu\(\)](#), [addItemContextmenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextmenu\(\)](#), [enableContextmenu\(\)](#), [hideContextmenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextmenu\(\)](#), [removeallItemsContextmenu\(\)](#), [setDisabledContextmenu\(\)](#), [showContextmenu\(\)](#)

isSynced	<i>Is a map synchronized?</i>
----------	-------------------------------

Description

Is a map synchronized with any or a specific map? Invoking this method sets a Shiny input that returns TRUE when the map is synchronized with another map. If syncwith is set, TRUE is returned if the map is synchronized exactly with that other map.

Usage

```
isSynced(map, id = NULL, syncwith = NULL)
```

Arguments

map	the map
id	The map id
syncwith	Is the map synchronized with one of these maps?

Details

The Siny input name is combined of the map-id and "_synced". For a map with id map1 the input can be retrieved with input\$map1_synced.

Value

A map

See Also

Other leafletsync Functions: [addLeafletsync\(\)](#), [addLeafletsyncDependency\(\)](#), [leafletsyncOptions\(\)](#), [unsync\(\)](#)

LayerGroupCollision	<i>Add LayerGroup Collision Plugin</i>
---------------------	--

Description

Integrates the LayerGroup Collision plugin into a Leaflet map, which hides overlapping markers and only displays the first added marker in a collision group. Markers must be static; dynamic changes, dragging, and deletions are not supported. The function transforms spatial data into GeoJSON format and uses 'L.DivIcon', allowing you to pass HTML content and CSS classes to style the markers.

Usage

```
addLayerGroupCollision(
  map,
  group = NULL,
  className = NULL,
  html = NULL,
  margin = 5,
  data = getMapData(map)
)
```

Arguments

map	the map to add awesome Markers to.
group	the name of the group. It needs to be single string.
className	A single CSS class or a vector of CSS classes.
html	A single HTML string or a vector of HTML strings.
margin	defines the margin between markers, in pixels
data	the data object from which the argument values are derived; by default, it is the data object provided to <code>leaflet()</code> initially, but can be overridden

Value

A leaflet map object with the LayerGroup Collision plugin added.

References

<https://github.com/MazeMap/Leaflet.LayerGroup.Collision>

Examples

```
library(leaflet)
library(sf)
library(leaflet.extras2)

df <- sf::st_as_sf(atlStorms2005)
df <- suppressWarnings(st_cast(df, "POINT"))
df$classes <- sample(x = 1:5, nrow(df), replace = TRUE)

leaflet() %>%
  addProviderTiles("CartoDB.Positron") %>%
  leaflet::addLayersControl(overlayGroups = c("Labels")) %>%
  addPolylines(data = sf::st_as_sf(atlStorms2005), label = ~Name) %>%
  addLayerGroupCollision(
    data = df, margin = 40,
    html = ~ paste0(
      '<div style="width: max-content; background-color: #cbc0c04f" class="custom-html">',
      '<div class="title">', Name, "</div>",
      '<div class="subtitle">MaxWind: ', MaxWind, "</div>",
      "</div>"
    )
  )
```

```

    ),
    className = ~ paste0("my-label my-label-", classes),
    group = "Labels"
  )

```

leafletSyncOptions *leafletSync Options*

Description

Additional list of options.

Usage

```

leafletSyncOptions(
  noInitialSync = FALSE,
  syncCursor = TRUE,
  offsetFn = JS("function (center, zoom, refMap, tgtMap) { return center; }")
)

```

Arguments

noInitialSync	Setting to TRUE disables initial synchronization of the maps. The default is FALSE.
syncCursor	The default TRUE adds a circle marker on the synced map.
offsetFn	A JavaScript-function to compute an offset for the center.

Value

A list of options for addLeafletSync

See Also

Other leafletSync Functions: [addLeafletSync\(\)](#), [addLeafletSyncDependency\(\)](#), [isSynced\(\)](#), [unsync\(\)](#)

makeMapkeyIcon

*Make Mapkey Icon***Description**

Make Mapkey Icon

Usage

```
makeMapkeyIcon(
  icon = "mapkey",
  color = "#ff0000",
  iconSize = 12,
  background = "#1F7499",
  borderRadius = "100%",
  hoverScale = 1.4,
  hoverEffect = TRUE,
  additionalCSS = NULL,
  hoverCSS = NULL,
  htmlCode = NULL,
  boxShadow = TRUE
)
```

Arguments

icon	ID of the mapkey Icon you want to use.
color	Any CSS color (e.g. 'red', 'rgba(20,160,90,0.5)', '#686868', ...)
iconSize	Size of Icon in Pixels. Default is 12
background	Any CSS color or false for no background
borderRadius	Any number (for circle size/2, for square 0.001)
hoverScale	Any real number (best result in range 1 - 2, use 1 for no effect)
hoverEffect	Switch on/off effect on hover
additionalCSS	CSS code (e.g. "border:4px solid #aa3838;")
hoverCSS	CSS code (e.g. "background-color:#992b00 !important; color:#99defc !important;")
htmlCode	e.g. ''.
boxShadow	Should a shadow be visible

Value

A list of mapkey-icon data that can be passed to the argument icon

References

<https://github.com/mapshakers/leaflet-mapkey-icon>

See Also

Other Mapkey Functions: [[.leaflet_mapkey_icon_set\(\)](#), [addMapkeyMarkers\(\)](#), [mapkeyIconList\(\)](#), [mapkeyIcons\(\)](#)]

Examples

```
makeMapkeyIcon(  
  icon = "traffic_signal",  
  color = "#0000ff",  
  iconSize = 12,  
  boxShadow = FALSE,  
  background = "transparent"  
)
```

mapkeyIconList	<i>Make Mapkey-icon set</i>
----------------	-----------------------------

Description

Make Mapkey-icon set

Usage

```
mapkeyIconList(...)
```

Arguments

... icons created from [makeMapkeyIcon\(\)](#)

Value

A list of class "leaflet_mapkey_icon_set"

References

<https://github.com/mapshakers/leaflet-mapkey-icon>

See Also

Other Mapkey Functions: [[.leaflet_mapkey_icon_set\(\)](#), [addMapkeyMarkers\(\)](#), [makeMapkeyIcon\(\)](#), [mapkeyIcons\(\)](#)]

Examples

```
iconSet <- mapkeyIconList(  
  red = makeMapkeyIcon(color = "#ff0000"),  
  blue = makeMapkeyIcon(color = "#0000ff")  
)  
iconSet[c("red", "blue")]
```

mapkeyIcons

Create a list of Mapkey icon data

Description

An icon can be represented as a list of the form `list(color, iconSize, ...)`. This function is vectorized over its arguments to create a list of icon data. Shorter argument values will be re-cycled. NULL values for these arguments will be ignored.

Usage

```
mapkeyIcons(
  icon = "mapkey",
  color = "#ff0000",
  iconSize = 12,
  background = "#1F7499",
  borderRadius = "100%",
  hoverScale = 1.4,
  hoverEffect = TRUE,
  hoverCSS = NULL,
  additionalCSS = NULL,
  htmlCode = NULL,
  boxShadow = TRUE
)
```

Arguments

icon	ID of the mapkey Icon you want to use.
color	Any CSS color (e.g. 'red', 'rgba(20,160,90,0.5)', '#686868', ...)
iconSize	Size of Icon in Pixels. Default is 12
background	Any CSS color or false for no background
borderRadius	Any number (for circle size/2, for square 0.001)
hoverScale	Any real number (best result in range 1 - 2, use 1 for no effect)
hoverEffect	Switch on/off effect on hover
hoverCSS	CSS code (e.g. "background-color:#992b00 !important; color:#99defc !important;")
additionalCSS	CSS code (e.g. "border:4px solid #aa3838;")
htmlCode	e.g. ''
boxShadow	Should a shadow be visible

Value

A list of mapkey-icon data that can be passed to the argument icon

References

<https://github.com/mapshakers/leaflet-mapkey-icon>

See Also

Other Mapkey Functions: [\[.leaflet_mapkey_icon_set\(\)\]](#), [addMapkeyMarkers\(\)](#), [makeMapkeyIcon\(\)](#), [mapkeyIconList\(\)](#)

Examples

```
## Not run:
library(leaflet)
leaflet() %>%
  addMapkeyMarkers(
    data = breweries91,
    icon = mapkeyIcons(
      color = "red",
      borderRadius = 0,
      iconSize = 25
    )
  )

## End(Not run)
```

mapmenuItems

mapmenuItems

Description

mapmenuItems

Usage

```
mapmenuItems(...)
```

Arguments

... contextmenu item/s

Value

A list of menuItem for the map

See Also

Other Contextmenu Functions: [addContextmenu\(\)](#), [addItemContextmenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextmenu\(\)](#), [enableContextmenu\(\)](#), [hideContextmenu\(\)](#), [insertItemContextmenu\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextmenu\(\)](#), [removeallItemsContextmenu\(\)](#), [setDisabledContextmenu\(\)](#), [showContextmenu\(\)](#)

markermenuItems	<i>markermenuItems</i>
-----------------	------------------------

Description

markermenuItems

Usage

markermenuItems(...)

Arguments

... contextmenu item/s

Value

A list of menuItem for markers

See Also

Other Contextmenu Functions: [addContextmenu\(\)](#), [addItemContextmenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextmenu\(\)](#), [enableContextmenu\(\)](#), [hideContextmenu\(\)](#), [insertItemContextmenu\(\)](#), [mapmenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextmenu\(\)](#), [removeallItemsContextmenu\(\)](#), [setDisabledContextmenu\(\)](#), [showContextmenu\(\)](#)

menuItem	<i>menuItem</i>
----------	-----------------

Description

menuItem

Usage

menuItem(text, callback = NULL, ...)

Arguments

text	The label to use for the menu item
callback	A callback function to be invoked when the menu item is clicked. The callback is passed an object with properties identifying the location the menu was opened at: latlng, layerPoint and containerPoint. The callback-function must be valid JavaScript and will be wrapped in JS.
...	For further options please visit https://github.com/araticliffe/Leaflet.contextmenu

Value

A contextmenu item list

See Also

Other Contextmenu Functions: [addContextmenu\(\)](#), [addItemContextmenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextmenu\(\)](#), [enableContextmenu\(\)](#), [hideContextmenu\(\)](#), [insertItemContextmenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [removeItemContextmenu\(\)](#), [removeallItemsContextmenu\(\)](#), [setDisabledContextmenu\(\)](#), [showContextmenu\(\)](#)

movingMarkerOptions	<i>Set options for Moving Markers</i>
---------------------	---------------------------------------

Description

Set options for Moving Markers

Usage

```
movingMarkerOptions({autostart = FALSE, loop = FALSE, pauseOnZoom = FALSE})
```

Arguments

autostart	If TRUE the marker will start automatically after it is added to map. Default is FALSE
loop	if TRUE the marker will start automatically at the beginning of the polyline when the it arrives at the end. Default is FALSE
pauseOnZoom	Pause the marker while zooming. While this improves the animation, it is not recommended because the animation time is lost and the marker will not appear at the correct time at the next station. Default is FALSE

Value

A list of extra options for moving markers

References

<https://github.com/ewoken/Leaflet.MovingMarker>

See Also

Other MovingMarker Functions: [addMovingMarker\(\)](#), [startMoving\(\)](#)

openSidebar	<i>Open the Sidebar by ID</i>
-------------	-------------------------------

Description

Open the Sidebar by ID

Usage

```
openSidebar(map, id, sidebar_id = NULL, ns = NULL)
```

Arguments

map	A leaflet map widget
id	The id of the sidebar_pane to open.
sidebar_id	The id of the sidebar (per sidebar_tabs). Defaults to NULL such that the first sidebar is used.
ns	The namespace function, if used in Shiny modules.

Value

the new map object

See Also

Other Sidebar Functions: [addSidebar\(\)](#), [closeSidebar\(\)](#), [removeSidebar\(\)](#), [sidebar_pane\(\)](#), [sidebar_tabs\(\)](#)

openweatherCurrentOptions	<i>openweatherCurrentOptions</i>
---------------------------	----------------------------------

Description

openweatherCurrentOptions

Usage

```
openweatherCurrentOptions(
  lang = "en",
  minZoom = 7,
  interval = 10,
  imageLoadingUrl = paste0(openweatherDependency()[[1]]$name, "-",
    openweatherDependency()[[1]]$version, "/owmloading.gif"),
  ...
)
```

Arguments

lang	'en', 'de', 'ru', 'fr', 'es', 'ca'. Language of popup texts. Note: not every translation is finished yet.
minZoom	Number (7). Minimal zoom level for fetching city data. Use smaller values only at your own risk.
interval	Number (10). Time in minutes to reload city data. Please do not use less than 10 minutes.
imageLoadingUrl	URL of the loading image.
...	Further options passed to L.OWM.current. See the full list of options

Value

A list of options for addOpenweatherCurrent

See Also

Other Openweathermap Functions: [addOpenweatherCurrent\(\)](#), [addOpenweatherTiles\(\)](#), [openweatherOptions\(\)](#)

openweatherOptions	<i>OpenWeatherMap Options</i>
--------------------	-------------------------------

Description

OpenWeatherMap Options

Usage

```
openweatherOptions(
  showLegend = TRUE,
  legendImagePath = NULL,
  legendPosition = c("bottomleft", "bottomright", "topleft", "topright")
)
```

Arguments

showLegend	If TRUE and option legendImagePath is set there will be a legend image on the map
legendImagePath	A URL (is set to a default image for some layers, null for others, see below). URL or relative path to an image which is a legend to this layer
legendPosition	Position of the legend images on the map. Must be one of 'bottomleft', 'bottomright', 'topleft', 'topright'

Value

A list of options for addOpenweatherTiles

See Also

Other Openweathermap Functions: [addOpenweatherCurrent\(\)](#), [addOpenweatherTiles\(\)](#), [openweatherCurrentOptions](#)

playbackOptions	<i>playbackOptions</i>
-----------------	------------------------

Description

A list of options for [addPlayback](#). For a full list please visit the [plugin repository](#).

Usage

```
playbackOptions(
  color = "blue",
  radius = 5,
  tickLen = 250,
  speed = 50,
  maxInterpolationTime = 5 * 60 * 1000,
  tracksLayer = TRUE,
  playControl = TRUE,
  dateControl = TRUE,
  sliderControl = TRUE,
  orientIcons = FALSE,
  staleTime = 60 * 60 * 1000,
  transitionpopup = TRUE,
  transitionlabel = TRUE,
  ...
)
```

Arguments

color	colors of the CircleMarkers.
radius	a numeric value for the radius of the CircleMarkers.
tickLen	Set tick length in milliseconds. Increasing this value, may improve performance, at the cost of animation smoothness. Default is 250
speed	Set float multiplier for default animation speed. Default is 50
maxInterpolationTime	Set max interpolation time in milliseconds. Default is 5*60*1000 (5 minutes).
tracksLayer	Set TRUE if you want to show layer control on the map. Default is TRUE
playControl	Set TRUE if play button is needed. Default is TRUE
dateControl	Set TRUE if date label is needed. Default is TRUE
sliderControl	Set TRUE if slider control is needed. Default is TRUE
orientIcons	Set TRUE if you want icons to orient themselves on each tick based on the bearing towards their next location. Default: FALSE

staleTime	Set time before a track is considered stale and faded out. Default is 60*60*1000 (1 hour)
transitionpopup	Should the position of the popup move smoothly, like the marker icon? Default: TRUE
transitionlabel	Should the position of the label move smoothly, like the marker icon? Default: TRUE
...	Further arguments passed to 'L.Playback'

Value

A list of options for addPlayback

References

<https://github.com/hallahan/LeafletPlayback>

See Also

Other Playback Functions: [addPlayback\(\)](#), [removePlayback\(\)](#)

reachabilityOptions	<i>reachabilityOptions</i>
---------------------	----------------------------

Description

Add extra options. For a full list please visit the [plugin repository](#).

Usage

```
reachabilityOptions(
  collapsed = TRUE,
  pane = "overlayPane",
  position = "topleft",
  ...
)
```

Arguments

collapsed	Should the control widget start in a collapsed mode. Default is TRUE
pane	Leaflet pane to add the isolines GeoJSON to. Default is overlayPane
position	Leaflet control pane position. Default is topleft
...	Further arguments passed to 'L.Control.Reachability'

Value

A list of options for addReachability

References

<https://github.com/traffordDataLab/leaflet.reachability>

See Also

Other Reachability Functions: [addReachability\(\)](#), [removeReachability\(\)](#)

removeallItemsContextmenu

removeallItemsContextmenu

Description

Remove all contextmenu items from the map.

Usage

```
removeallItemsContextmenu(map)
```

Arguments

map a map widget object created from [leaflet](#)

Value

A leaflet map object

See Also

Other Contextmenu Functions: [addContextmenu\(\)](#), [addItemContextmenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextmenu\(\)](#), [enableContextmenu\(\)](#), [hideContextmenu\(\)](#), [insertItemContextmenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextmenu\(\)](#), [setDisabledContextmenu\(\)](#), [showContextmenu\(\)](#)

removeAntpath	<i>removeAntpath</i>
---------------	----------------------

Description

Remove one or more Antpaths from a map, identified by layerId.

Usage

```
removeAntpath(map, layerId = NULL)
```

Arguments

map	a map widget object, possibly created from leaflet() but more likely from leafletProxy()
layerId	character vector; the layer id(s) of the item to remove

Value

the new map object

See Also

Other Antpath Functions: [addAntpath\(\)](#), [antpathOptions\(\)](#), [clearAntpath\(\)](#)

removeArrowhead	<i>Remove arrowheads from Lines by layerId</i>
-----------------	--

Description

Remove arrowheads from Lines by layerId

Usage

```
removeArrowhead(map, layerId)
```

Arguments

map	the map
layerId	A single layerId or a vector of layerId's

Value

A modified leaflet map

See Also

Other Arrowhead Functions: [addArrowhead\(\)](#), [arrowheadOptions\(\)](#), [clearArrowhead\(\)](#)

```
removeConditionalLayer
    removeConditionalLayer
```

Description

removeConditionalLayer

Usage

```
removeConditionalLayer(map, groups)
```

Arguments

map	A map widget object created from leaflet .
groups	A character vector of layer group names already added to the map. These layer groups will be conditionally displayed based on the specified conditions.

See Also

Other LayerGroupConditional Plugin: [addLayerGroupConditional\(\)](#), [clearConditionalLayers\(\)](#)

```
removeEasyprint    removeEasyprint
```

Description

Removes the easyprint control from the map.

Usage

```
removeEasyprint(map)
```

Arguments

map	the map widget
-----	----------------

Value

A leaflet map object

See Also

Other EasyPrint Functions: [addEasyprint\(\)](#), [easyprintMap\(\)](#), [easyprintOptions\(\)](#)

removeGeosearch	<i>removeGeosearch</i>
-----------------	------------------------

Description

Remove the geosearch

Usage

removeGeosearch(map)

Arguments

map the map widget.

Value

the new map object

See Also

Other Geosearch Functions: [addGeosearch\(\)](#), [geosearchOptions\(\)](#)

removeItemContextmenu	<i>removeItemContextmenu</i>
-----------------------	------------------------------

Description

Remove a contextmenu item by index.

Usage

removeItemContextmenu(map, index)

Arguments

map a map widget object created from [leaflet](#)
index Index of the contextmenu. (NOTE: Since the index is passed to JavaScript, it is zero-based)

Value

A leaflet map object

See Also

Other Contextmenu Functions: [addContextmenu\(\)](#), [addItemContextmenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextmenu\(\)](#), [enableContextmenu\(\)](#), [hideContextmenu\(\)](#), [insertItemContextmenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeallItemsContextmenu\(\)](#), [setDisabledContextmenu\(\)](#), [showContextmenu\(\)](#)

removePlayback	<i>removePlayback</i>
----------------	-----------------------

Description

Remove the Playback controls and markers.

Usage

removePlayback(map)

Arguments

map the map widget

Value

the new map object

See Also

Other Playback Functions: [addPlayback\(\)](#), [playbackOptions\(\)](#)

removeReachability	<i>removeReachability</i>
--------------------	---------------------------

Description

Remove the reachability controls.

Usage

removeReachability(map)

Arguments

map the map widget.

Value

the new map object

See Also

Other Reachability Functions: [addReachability\(\)](#), [reachabilityOptions\(\)](#)

removeSidebar	<i>Remove the Sidebar</i>
---------------	---------------------------

Description

Remove the Sidebar

Usage

```
removeSidebar(map, sidebar_id = NULL)
```

Arguments

map	A leaflet map widget
sidebar_id	The id of the sidebar (per sidebar_tabs). Defaults to NULL such that the first sidebar is removed.

Value

the new map object

See Also

Other Sidebar Functions: [addSidebar\(\)](#), [closeSidebar\(\)](#), [openSidebar\(\)](#), [sidebar_pane\(\)](#), [sidebar_tabs\(\)](#)

removeSidebyside	<i>removeSidebyside</i>
------------------	-------------------------

Description

removeSidebyside

Usage

```
removeSidebyside(map, layerId = NULL)
```

Arguments

map	a map widget
layerId	the layer id of the addSidebyside layer

Value

the new map object

See Also

Other Sidebyside Functions: [addSidebyside\(\)](#)

<code>removeTimeslider</code>	<i>removeTimeslider</i>
-------------------------------	-------------------------

Description

Remove the Timeslider controls and markers.

Usage

```
removeTimeslider(map)
```

Arguments

<code>map</code>	the map widget
------------------	----------------

Value

the new map object

See Also

Other Timeslider Functions: [addTimeslider\(\)](#), [timesliderOptions\(\)](#)

<code>removeVectorgrid</code>	<i>Remove a VectorGrid layer</i>
-------------------------------	----------------------------------

Description

Remove a VectorGrid layer

Usage

```
removeVectorgrid(map, layerId)
```

Arguments

<code>map</code>	a map widget object, possibly created from leaflet() but more likely from leafletProxy()
<code>layerId</code>	character vector; the layer id(s) of the item to remove

Value

the new map object

See Also

Other Vectorgrid Functions: [addProtobuf\(\)](#), [addVectorgrid\(\)](#), [clearVectorgrid\(\)](#), [vectorStyling\(\)](#)

removeVelocity	<i>removeVelocity</i>
----------------	-----------------------

Description

removeVelocity

Usage

removeVelocity(map, group)

Arguments

map	the map widget
group	the group to remove

Value

the new map object

See Also

Other Velocity Functions: [addVelocity\(\)](#), [setOptionsVelocity\(\)](#), [velocityOptions\(\)](#)

setBuildingData	<i>Update the OSM-Buildings Data</i>
-----------------	--------------------------------------

Description

Update the OSM-Buildings Data

Usage

setBuildingData(map, data)

Arguments

map	A map widget object created from leaflet .
data	A GeoJSON object containing Polygon features representing the buildings. The properties of these polygons can include attributes like height, color, roofColor, and others as specified in the OSM Buildings documentation.

See Also

Other OSM-Buildings Plugin: [addBuildings\(\)](#), [setBuildingStyle\(\)](#), [updateBuildingTime\(\)](#)

setBuildingStyle	<i>Update the OSM-Buildings Style</i>
------------------	---------------------------------------

Description

Update the OSM-Buildings Style

Usage

```
setBuildingStyle(
  map,
  style = list(color = "#ffcc00", wallColor = "#ffcc00", roofColor = "orange", shadows =
    TRUE)
)
```

Arguments

map	A map widget object created from leaflet .
style	A named list of styles

See Also

Other OSM-Buildings Plugin: [addBuildings\(\)](#), [setBuildingData\(\)](#), [updateBuildingTime\(\)](#)

Examples

```
library(leaflet)
library(leaflet.extras2)

style <- list(color = "#0000ff", wallColor = "gray", roofColor = "orange", shadows = TRUE)
leaflet() %>%
  addTiles() %>%
  addBuildings() %>%
  setBuildingStyle(style) %>%
  setView(13.40, 52.51836, 15)
```

setDate	<i>Set Date for GIBS Layers</i>
---------	---------------------------------

Description

Set a new date for multi-temporal layers.

Usage

```
setDate(map, layers = NULL, dates = NULL)
```

Arguments

map	a map widget object created from leaflet()
layers	A character vector of GIBS-layers. See gibs_layers
dates	Date object. If multiple layers are added, you can add a Date vector of the same length

Value

the new map object

See Also

Other GIBS Functions: [addGIBS\(\)](#), [setTransparent\(\)](#)

setDisabledContextmenu	<i>setDisabledContextmenu</i>
------------------------	-------------------------------

Description

Enable/Disable a contextmenu item by index.

Usage

```
setDisabledContextmenu(map, index, disabled = TRUE)
```

Arguments

map	a map widget object created from leaflet
index	Index of the contextmenu. (NOTE: Since the index is passed to JavaScript, it is zero-based)
disabled	Set to TRUE to disable the element and FALSE to enable it. Default is TRUE

Value

A leaflet map object

See Also

Other Contextmenu Functions: [addContextmenu\(\)](#), [addItemContextmenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextmenu\(\)](#), [enableContextmenu\(\)](#), [hideContextmenu\(\)](#), [insertItemContextmenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextmenu\(\)](#), [removeallItemsContextmenu\(\)](#), [showContextmenu\(\)](#)

setOptionsVelocity	<i>setOptionsVelocity</i>
--------------------	---------------------------

Description

setOptionsVelocity

Usage

```
setOptionsVelocity(map, layerId, options)
```

Arguments

map	the map widget
layerId	the layer id
options	see velocityOptions

Value

the new map object

See Also

Other Velocity Functions: [addVelocity\(\)](#), [removeVelocity\(\)](#), [velocityOptions\(\)](#)

setTransparent	<i>Set Transparency for GIBS Layers</i>
----------------	---

Description

Change the transparency for no-data pixels.

Usage

```
setTransparent(map, layers = NULL, transparent = TRUE)
```

Arguments

map	a map widget object created from leaflet()
layers	A character vector of GIBS-layers. See gibs_layers
transparent	Should the layer be transparent. If multiple layers are added, you can add a boolean vector of the same length

Value

the new map object

See Also

Other GIBS Functions: [addGIBS\(\)](#), [setDate\(\)](#)

setWMSParams	<i>Update WMS request parameters</i>
--------------	--------------------------------------

Description

Change WMS parameters such as time, styles or cql_filter on an existing layer without rebuilding the map. In Shiny, call this on [leafletProxy](#).

Usage

```
setWMSParams(map, layerId = NULL, group = NULL, ...)
```

Arguments

map	a map widget object created from leaflet()
layerId	the layer id
group	the name of the group the newly created layers should belong to (for clearGroup() and addLayersControl() purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g., markers and polygons) can share the same group name.
...	Named WMS request parameters to set, for example time = "2022-11-10T21:00:00Z".

Value

the new map object

See Also

Other WMS Functions: [addWMS\(\)](#)

Examples

```
library(leaflet)
library(leaflet.extras2)

leaflet() %>%
  addTiles() %>%
  addWMS(
    baseUrl = "https://gibs.earthdata.nasa.gov/wms/epsg3857/best/wms.cgi",
    layers = "MODIS_Terra_CorrectedReflectance_TrueColor",
    layerId = "modis",
    options = WMSTileOptions(format = "image/jpeg", time = "2022-11-10")
  ) %>%
  setWMSParams(layerId = "modis", time = "2022-11-11")
```

showContextmenu

showContextmenu

Description

Open the contextmenu at certain lat/lng-coordinates

Usage

```
showContextmenu(map, lat = NULL, lng = NULL, data = leaflet::getMapData(map))
```

Arguments

map	a map widget object created from leaflet()
lat	a vector of latitudes or a formula (similar to the lng argument; the names lat and latitude are used when guessing the latitude column from data)
lng	a numeric vector of longitudes, or a one-sided formula of the form ~x where x is a variable in data; by default (if not explicitly provided), it will be automatically inferred from data by looking for a column named lng, long, or longitude (case-insensitively)
data	the data object from which the argument values are derived; by default, it is the data object provided to leaflet() initially, but can be overridden

Value

A leaflet map object

See Also

Other Contextmenu Functions: [addContextmenu\(\)](#), [addItemContextmenu\(\)](#), [context_mapmenuItems\(\)](#), [context_markermenuItems\(\)](#), [context_menuItem\(\)](#), [disableContextmenu\(\)](#), [enableContextmenu\(\)](#), [hideContextmenu\(\)](#), [insertItemContextmenu\(\)](#), [mapmenuItems\(\)](#), [markermenuItems\(\)](#), [menuItem\(\)](#), [removeItemContextmenu\(\)](#), [removeallItemsContextmenu\(\)](#), [setDisabledContextmenu\(\)](#)

showHexbin

showHexbin

Description

Show the hexbinLayer.

Usage

```
showHexbin(map)
```

Arguments

map	The map widget
-----	----------------

Value

the new map object

See Also

Other Hexbin-D3 Functions: [addHexbin\(\)](#), [clearHexbin\(\)](#), [hexbinOptions\(\)](#), [hideHexbin\(\)](#), [updateHexbin\(\)](#)

sidebar_pane*Create a Sidebar Pane*

Description

Create a Sidebar Pane

Usage

```
sidebar_pane(  
  title = "Sidebar Title",  
  id = NULL,  
  icon = icon("caret-right"),  
  ...  
)
```

Arguments

title	A title for the sidebar panel
id	An id for the sidebar panel
icon	An icon for the sidebar panel
...	List of elements to include in the panel

Value

A shiny.tag with sidebar-specific HTML classes

References

<https://github.com/Turbo87/sidebar-v2>, <https://github.com/Turbo87/sidebar-v2/blob/master/doc/usage.md>

See Also

Other Sidebar Functions: [addSidebar\(\)](#), [closeSidebar\(\)](#), [openSidebar\(\)](#), [removeSidebar\(\)](#), [sidebar_tabs\(\)](#)

Examples

```
## Not run:  
library(shiny)  
sidebar_pane(id = "id", icon = icon("cars"), tags$div())  
  
## End(Not run)
```

`sidebar_tabs`*Create a Sidebar*

Description

Create a Sidebar

Usage

```
sidebar_tabs(id = "sidebar", iconList = NULL, ...)
```

Arguments

<code>id</code>	The id of the sidebar, which must match the id of <code>addSidebar</code> . Default is "sidebar"
<code>iconList</code>	A list of icons to be shown, when the sidebar is collapsed. The list is required and must match the amount of <code>sidebar_pane</code> .
<code>...</code>	The individual <code>sidebar_pane</code> 's.

Value

A `shiny.tag` with individual sidebar panes

References

<https://github.com/Turbo87/sidebar-v2>, <https://github.com/Turbo87/sidebar-v2/blob/master/doc/usage.md>

See Also

Other Sidebar Functions: `addSidebar()`, `closeSidebar()`, `openSidebar()`, `removeSidebar()`, `sidebar_pane()`

Examples

```
## Not run:
library(shiny)

# run example app showing a single sidebar
runApp(paste0(
  system.file("examples", package = "leaflet.extras2"),
  "/sidebar_app.R"
))

# run example app showing two sidebars
runApp(paste0(
  system.file("examples", package = "leaflet.extras2"),
  "/multi_sidebar_app.R"
```

```

))

## End(Not run)

```

spinWhile

Run work while a map spinner is visible (Shiny)

Description

Starts the spinner, waits until the browser has painted it (and Shiny has flushed that update), then evaluates `expr` and always stops the spinner.

Usage

```

spinWhile(
  mapId,
  expr,
  options = NULL,
  session = shiny::getDefaultReactiveDomain()
)

```

Arguments

<code>mapId</code>	The outputId of the leafletOutput.
<code>expr</code>	Expression to evaluate after the spinner is shown.
<code>options</code>	Passed to startSpinner .
<code>session</code>	The Shiny session; default is the current domain.

Value

The Shiny session (invisible).

See Also

Other Spinner Functions: [addSpinner\(\)](#)

Examples

```

## Not run:
observeEvent(input$go, {
  spinWhile("leaf", {
    Sys.sleep(2)
    leafletProxy("leaf") %>% addMarkers(data = quakes, ~long, ~lat)
  })
})

## End(Not run)

```

startMoving	<i>Interact with the moving markers</i>
-------------	---

Description

The marker begins its path or resumes if it is paused.

Usage

```
startMoving(map, layerId = NULL)

stopMoving(map, layerId = NULL)

pauseMoving(map, layerId = NULL)

resumeMoving(map, layerId = NULL)

addLatLngMoving(map, layerId = NULL, latlng, duration)

moveToMoving(map, layerId = NULL, latlng, duration)

addStationMoving(map, layerId = NULL, pointIndex, duration)
```

Arguments

map	The leafletProxy object
layerId	You can pass a string or a vector of strings for the moving markers that you want to address. If none is specified, the action will be applied to all moving markers.
latlng	Coordinates as list (e.g.: <code>list(33, -67)</code> or <code>list(lng=-65, lat=33)</code>)
duration	Duration in milliseconds
pointIndex	Index of a certain point

Value

the new map object

Functions

- `stopMoving()`: Manually stops the marker, if you call `start` after, the marker starts again the polyline at the beginning.
- `pauseMoving()`: Pauses the marker
- `resumeMoving()`: The marker resumes its animation
- `addLatLngMoving()`: Adds a point to the polyline. Useful, if we have to set the path one by one.

- `moveToMoving()`: Stop the current animation and make the marker move to `latlng` in duration `ms`.
- `addStationMoving()`: The marker will stop at the `pointIndex` point of the polyline for duration milliseconds. You can't add a station at the first or last point of the polyline.

References

<https://github.com/ewoken/Leaflet.MovingMarker>

See Also

Other `MovingMarker` Functions: `addMovingMarker()`, `movingMarkerOptions()`

<code>timesliderOptions</code>	<i>timesliderOptions</i>
--------------------------------	--------------------------

Description

A list of options for `addTimeslider`.

Usage

```
timesliderOptions(  
  position = c("topright", "bottomleft", "bottomright", "topleft"),  
  timeAttribute = "time",  
  isEpoch = FALSE,  
  startTimeIdx = 0,  
  timeStrLength = 19,  
  maxValue = -1,  
  minValue = 0,  
  showAllOnStart = FALSE,  
  range = FALSE,  
  follow = FALSE,  
  alwaysShowDate = FALSE,  
  rezoom = NULL,  
  sameDate = FALSE  
)
```

Arguments

<code>position</code>	position of control: "topleft", "topright", "bottomleft", or "bottomright". Default is topright.
<code>timeAttribute</code>	The column name of the time property. Default is "time"
<code>isEpoch</code>	whether the time attribute is seconds elapsed from epoch. Default is FALSE
<code>startTimeIdx</code>	where to start looking for a timestring Default is 0

timeStrLength	the size of yyyy-mm-dd hh:mm:ss - if milliseconds are present this will be larger. Default is 19
maxValue	Set the maximum value of the slider. Default is -1
minValue	Set the minimum value of the slider. Default is 0
showAllOnStart	Specify whether all markers should be initially visible. Default is FALSE
range	To use a range-slider, set to TRUE. Default is FALSE Default is FALSE
follow	To display only the markers at the specific timestamp specified by the slider. Specify a value of 1 (or true) to display only a single data point at a time, and a value of null (or false) to display the current marker and all previous markers. The range property overrides the follow property. Default is FALSE
alwaysShowDate	Should the Date always be visible. Default is FALSE
rezoom	Use the rezoom property to ensure the markers being displayed remain in view. Default is NULL
sameDate	Show only data with the current selected time. Default is FALSE

Value

A list of options for addTimeslider

References

<https://github.com/dwilhelm89/LeafletSlider>

See Also

Other Timeslider Functions: [addTimeslider\(\)](#), [removeTimeslider\(\)](#)

to_jsonformat	<i>to_jsonformat Transform object to JSON expected format</i>
---------------	---

Description

to_jsonformat Transform object to JSON expected format

Usage

```
to_jsonformat(data, time, popup = NULL, label = NULL, name = NULL)
```

Arguments

data	The data
time	Name of the time column.
popup	Name of the popup column.
label	Name of the label column.
name	Name of the name column.

Value

A list that is transformed to the expected JSON format

to_ms	<i>to_ms Change POSIX or Date to milliseconds</i>
-------	---

Description

to_ms Change POSIX or Date to milliseconds

Usage

```
to_ms(data, time)
```

Arguments

data	The data
time	Name of the time column.

Value

A data.frame with the time column in milliseconds

unsync	<i>Removes synchronization.</i>
--------	---------------------------------

Description

Removes the synchronization of multiple maps from a specific map.

Usage

```
unsync(map, id = NULL, unsyncids = NULL)
```

Arguments

map	the map
id	The map id from which to unsynchronize the maps in unsyncids
unsyncids	Unsyncronize the maps with the following IDs

Value

A map

See Also

Other leafletsync Functions: [addLeafletsync\(\)](#), [addLeafletsyncDependency\(\)](#), [isSynced\(\)](#), [leafletsyncOptions\(\)](#)

updateBuildingTime	<i>Update the Shadows OSM-Buildings with a POSIXct timestamp</i>
--------------------	--

Description

Update the Shadows OSM-Buildings with a POSIXct timestamp

Usage

updateBuildingTime(map, time)

Arguments

- map A map widget object created from [leaflet](#).
- time a timestamp that can be converted to POSIXct

See Also

Other OSM-Buildings Plugin: [addBuildings\(\)](#), [setBuildingData\(\)](#), [setBuildingStyle\(\)](#)

Examples

```
library(leaflet)
library(leaflet.extras2)

leaflet() %>%
  addTiles() %>%
  addBuildings() %>%
  updateBuildingTime(as.POSIXct("2024-09-01 19:00:00 CET")) %>%
  setView(13.40, 52.51836, 15)
```

updateHexbin	<i>updateHexbin</i>
--------------	---------------------

Description

Dynamically change the data and/or the colorRange.

Usage

updateHexbin(map, data = NULL, lng = NULL, lat = NULL, colorRange = NULL)

Arguments

map	a map widget object created from leaflet()
data	the data object from which the argument values are derived; by default, it is the data object provided to leaflet() initially, but can be overridden
lng	a numeric vector of longitudes, or a one-sided formula of the form <code>~x</code> where <code>x</code> is a variable in <code>data</code> ; by default (if not explicitly provided), it will be automatically inferred from <code>data</code> by looking for a column named <code>lng</code> , <code>long</code> , or <code>longitude</code> (case-insensitively)
lat	a vector of latitudes or a formula (similar to the <code>lng</code> argument; the names <code>lat</code> and <code>latitude</code> are used when guessing the latitude column from <code>data</code>)
colorRange	The range of the color scale used to fill the hexbins

Value

the new map object

See Also

Other Hexbin-D3 Functions: [addHexbin\(\)](#), [clearHexbin\(\)](#), [hexbinOptions\(\)](#), [hideHexbin\(\)](#), [showHexbin\(\)](#)

vectorStyling

Default styles for OSM-based vector tiles

Description

Layer-name styles for Mapbox, Nextzen, MapTiler / OpenMapTiles and similar protobuf tiles. Override individual entries before passing to [addProtobuf](#).

Usage

```
vectorStyling()
```

Value

A named list of path options.

References

<https://github.com/Leaflet/Leaflet.VectorGrid>

See Also

Other Vectorgrid Functions: [addProtobuf\(\)](#), [addVectorgrid\(\)](#), [clearVectorgrid\(\)](#), [removeVectorgrid\(\)](#)

velocityOptions	<i>velocityOptions</i>
-----------------	------------------------

Description

Define further options for the velocity layer.

Usage

```
velocityOptions(  
  speedUnit = c("m/s", "k/h", "kt"),  
  minVelocity = 0,  
  maxVelocity = 10,  
  velocityScale = 0.005,  
  colorScale = NULL,  
  ...  
)
```

Arguments

speedUnit	Could be 'm/s' for meter per second, 'k/h' for kilometer per hour or 'kt' for knots
minVelocity	velocity at which particle intensity is minimum
maxVelocity	velocity at which particle intensity is maximum
velocityScale	scale for wind velocity
colorScale	A vector of hex colors or an RGB matrix
...	Further arguments passed to the Velocity layer and Windy.js. For more information, please visit leaflet-velocity plugin

Value

A list of further options for addVelocity

See Also

Other Velocity Functions: [addVelocity\(\)](#), [removeVelocity\(\)](#), [setOptionsVelocity\(\)](#)

```
[.leaflet_mapkey_icon_set  
  leaflet_mapkey_icon_set]
```

Description

leaflet_mapkey_icon_set

Usage

```
## S3 method for class 'leaflet_mapkey_icon_set'  
x[i]
```

Arguments

x	icons
i	offset

See Also

Other Mapkey Functions: [addMapkeyMarkers\(\)](#), [makeMapkeyIcon\(\)](#), [mapkeyIconList\(\)](#), [mapkeyIcons\(\)](#)

Index

* Antpath Functions

- addAntpath, [4](#)
- antpathOptions, [55](#)
- clearAntpath, [58](#)
- removeAntpath, [93](#)

* Arrowhead Functions

- addArrowhead, [6](#)
- arrowheadOptions, [56](#)
- clearArrowhead, [58](#)
- removeArrowhead, [93](#)

* Contextmenu Functions

- addContextmenu, [13](#)
- addItemContextmenu, [25](#)
- context_mapmenuItems, [63](#)
- context_markermenuItems, [64](#)
- context_menuItem, [64](#)
- disableContextmenu, [65](#)
- enableContextmenu, [69](#)
- hideContextmenu, [75](#)
- insertItemContextmenu, [78](#)
- mapmenuItems, [85](#)
- markermenuItems, [86](#)
- menuItem, [86](#)
- removeallItemsContextmenu, [92](#)
- removeItemContextmenu, [95](#)
- setDisabledContextmenu, [101](#)
- showContextmenu, [104](#)

* DivIcon Functions

- addDivicon, [14](#)

* EasyPrint Functions

- addEasyprint, [17](#)
- easyprintMap, [66](#)
- easyprintOptions, [67](#)
- removeEasyprint, [94](#)

* GIBS Functions

- addGIBS, [19](#)
- setDate, [101](#)
- setTransparent, [103](#)

* Geosearch Functions

- addGeosearch, [18](#)
- geosearchOptions, [69](#)
- removeGeosearch, [95](#)

* Heightgraph Functions

- addHeightgraph, [20](#)
- heightgraphOptions, [73](#)

* Hexbin-D3 Functions

- addHexbin, [22](#)
- clearHexbin, [60](#)
- hexbinOptions, [74](#)
- hideHexbin, [76](#)
- showHexbin, [105](#)
- updateHexbin, [113](#)

* History Functions

- addHistory, [24](#)
- clearFuture, [59](#)
- clearHistory, [60](#)
- goBackHistory, [72](#)
- goForwardHistory, [72](#)
- historyOptions, [76](#)

* LayerGroupConditional Plugin

- addLayerGroupConditional, [27](#)
- clearConditionalLayers, [59](#)
- removeConditionalLayer, [94](#)

* Mapkey Functions

- [.leaflet_mapkey_icon_set, [116](#)
- addMapkeyMarkers, [30](#)
- makeMapkeyIcon, [82](#)
- mapkeyIconList, [83](#)
- mapkeyIcons, [84](#)

* MovingMarker Functions

- addMovingMarker, [32](#)
- movingMarkerOptions, [87](#)
- startMoving, [109](#)

* OSM-Buildings Plugin

- addBuildings, [8](#)
- setBuildingData, [99](#)
- setBuildingStyle, [100](#)
- updateBuildingTime, [113](#)

- * **Openweathermap Functions**
 - addOpenweatherCurrent, [34](#)
 - addOpenweatherTiles, [35](#)
 - openweatherCurrentOptions, [88](#)
 - openweatherOptions, [89](#)
- * **Playback Functions**
 - addPlayback, [37](#)
 - playbackOptions, [90](#)
 - removePlayback, [96](#)
- * **Reachability Functions**
 - addReachability, [41](#)
 - reachabilityOptions, [91](#)
 - removeReachability, [96](#)
- * **Sidebar Functions**
 - addSidebar, [42](#)
 - closeSidebar, [61](#)
 - openSidebar, [88](#)
 - removeSidebar, [97](#)
 - sidebar_pane, [106](#)
 - sidebar_tabs, [107](#)
- * **Sidebyside Functions**
 - addSidebyside, [43](#)
 - removeSidebyside, [97](#)
- * **Spinner Functions**
 - addSpinner, [45](#)
 - spinWhile, [108](#)
- * **Tangram Functions**
 - addTangram, [46](#)
- * **Timeslider Functions**
 - addTimeslider, [48](#)
 - removeTimeslider, [98](#)
 - timesliderOptions, [110](#)
- * **Vectorgrid Functions**
 - addProtobuf, [39](#)
 - addVectorgrid, [50](#)
 - clearVectorgrid, [61](#)
 - removeVectorgrid, [98](#)
 - vectorStyling, [114](#)
- * **Velocity Functions**
 - addVelocity, [52](#)
 - removeVelocity, [99](#)
 - setOptionsVelocity, [102](#)
 - velocityOptions, [115](#)
- * **WMS Functions**
 - addWMS, [53](#)
 - setWMSParams, [103](#)
- * **clusterCharts**
 - addClusterCharts, [10](#)
 - clusterchartOptions, [62](#)
- * **datasets**
 - gibs_layers, [71](#)
- * **leafletSync Functions**
 - addLeafletsync, [28](#)
 - addLeafletsyncDependency, [29](#)
 - isSynced, [79](#)
 - leafletSyncOptions, [81](#)
 - unsync, [112](#)
- [.leaflet_mapkey_icon_set, [116](#)
- [.leaflet_mapkey_icon_set(), [31](#), [83](#), [85](#)
- addAntpath, [4](#)
- addAntpath(), [56](#), [58](#), [93](#)
- addArrowhead, [6](#), [8](#)
- addArrowhead(), [57](#), [58](#), [93](#)
- addBuildings, [8](#)
- addBuildings(), [100](#), [113](#)
- addClusterCharts, [10](#)
- addClusterCharts(), [63](#)
- addContextmenu, [13](#)
- addContextmenu(), [25](#), [63–65](#), [69](#), [76](#), [78](#), [85–87](#), [92](#), [96](#), [102](#), [105](#)
- addDivicon, [14](#)
- addEasyprint, [17](#)
- addEasyprint(), [66](#), [68](#), [94](#)
- addGeoJSON, [20](#)
- addGeosearch, [18](#)
- addGeosearch(), [70](#), [95](#)
- addGIBS, [19](#)
- addGIBS(), [101](#), [103](#)
- addHeightgraph, [20](#)
- addHeightgraph(), [74](#)
- addHexbin, [22](#)
- addHexbin(), [60](#), [75](#), [76](#), [105](#), [114](#)
- addHistory, [24](#)
- addHistory(), [59](#), [61](#), [72](#), [73](#), [78](#)
- addItemContextmenu, [25](#)
- addItemContextmenu(), [14](#), [63–65](#), [69](#), [76](#), [78](#), [85–87](#), [92](#), [96](#), [102](#), [105](#)
- addLabelgun, [26](#)
- addLatLngMoving (startMoving), [109](#)
- addLayerGroupCollision
 - (LayerGroupCollision), [79](#)
- addLayerGroupConditional, [27](#)
- addLayerGroupConditional(), [59](#), [94](#)
- addLayersControl, [44](#)
- addLayersControl(), [5](#), [7](#), [10](#), [15](#), [19](#), [21](#), [23](#), [31](#), [32](#), [34](#), [36](#), [40](#), [47](#), [50](#), [52](#), [54](#), [104](#)

- addLeafletsync, 28
- addLeafletsync(), 30, 79, 81, 112
- addLeafletsyncDependency, 29
- addLeafletsyncDependency(), 29, 79, 81, 112
- addMapkeyMarkers, 30
- addMapkeyMarkers(), 83, 85, 116
- addMovingMarker, 32
- addMovingMarker(), 87, 110
- addOpenweatherCurrent, 34
- addOpenweatherCurrent(), 36, 89, 90
- addOpenweatherTiles, 35
- addOpenweatherTiles(), 35, 89, 90
- addPlayback, 37, 90
- addPlayback(), 91, 96
- addPolygons, 50
- addPolylines, 6
- addProtobuf, 39, 114
- addProtobuf(), 51, 61, 99, 114
- addReachability, 41
- addReachability(), 92, 97
- addSidebar, 42, 107
- addSidebar(), 62, 88, 97, 106, 107
- addSidebyside, 43, 97
- addSidebyside(), 98
- addSpinner, 45
- addSpinner(), 108
- addStationMoving (startMoving), 109
- addTangram, 46
- addTimeslider, 48, 110
- addTimeslider(), 98, 111
- addVectorgrid, 50
- addVectorgrid(), 40, 61, 99, 114
- addVelocity, 52
- addVelocity(), 99, 102, 115
- addWMS, 53
- addWMS(), 104
- addWMSTiles, 54
- antpathOptions, 4, 5, 55
- antpathOptions(), 6, 58, 93
- arrowheadOptions, 6–8, 56
- arrowheadOptions(), 8, 58, 93
- clearAntpath, 58
- clearAntpath(), 6, 56, 93
- clearArrowhead, 58
- clearArrowhead(), 8, 57, 93
- clearConditionalLayers, 59
- clearConditionalLayers(), 27, 94
- clearFuture, 59
- clearFuture(), 25, 61, 72, 73, 78
- clearGroup(), 5, 7, 10, 15, 19, 21, 23, 31, 32, 34, 36, 40, 47, 50, 52, 54, 104
- clearHexbin, 60
- clearHexbin(), 23, 75, 76, 105, 114
- clearHistory, 60
- clearHistory(), 25, 59, 72, 73, 78
- clearVectorgrid, 61
- clearVectorgrid(), 40, 51, 99, 114
- closeSidebar, 61
- closeSidebar(), 43, 88, 97, 106, 107
- clusterchartOptions, 11, 62
- clusterchartOptions(), 11
- context_mapmenuItems, 63
- context_mapmenuItems(), 14, 25, 64, 65, 69, 76, 78, 85–87, 92, 96, 102, 105
- context_markermenuItems, 64
- context_markermenuItems(), 14, 25, 63, 65, 69, 76, 78, 85–87, 92, 96, 102, 105
- context_menuItem, 64
- context_menuItem(), 14, 25, 63–65, 69, 76, 78, 85–87, 92, 96, 102, 105
- disableContextmenu, 65
- disableContextmenu(), 14, 25, 63–65, 69, 76, 78, 85–87, 92, 96, 102, 105
- easyprintMap, 66
- easyprintMap(), 17, 68, 94
- easyprintOptions, 17, 66, 67
- easyprintOptions(), 17, 66, 94
- enableContextmenu, 69
- enableContextmenu(), 14, 25, 63–65, 76, 78, 85–87, 92, 96, 102, 105
- geosearchOptions, 18, 69
- geosearchOptions(), 19, 95
- geosearchProvider, 18, 71
- gibs_layers, 19, 71, 101, 103
- goBackHistory, 72
- goBackHistory(), 25, 59, 61, 73, 78
- goForwardHistory, 72
- goForwardHistory(), 25, 59, 61, 72, 78
- heightgraphOptions, 21, 73
- heightgraphOptions(), 22
- hexbinOptions, 23, 74
- hexbinOptions(), 23, 60, 76, 105, 114

- hideContextmenu, 75
- hideContextmenu(), 14, 25, 63–65, 69, 78, 85–87, 92, 96, 102, 105
- hideHexbin, 76
- hideHexbin(), 23, 60, 75, 105, 114
- historyOptions, 24, 76
- historyOptions(), 25, 59, 61, 72, 73
- htmltools::htmlEscape(), 5, 7, 15, 31, 33, 49
- insertItemContextmenu, 78
- insertItemContextmenu(), 14, 25, 63–65, 69, 76, 85–87, 92, 96, 102, 105
- isSynced, 79
- isSynced(), 29, 30, 81, 112
- JS, 9, 64, 75, 86
- labelOptions(), 5, 7, 11, 16, 31, 33, 37, 49
- LayerGroupCollision, 79
- leaflet, 9, 13, 17, 24–27, 45, 59, 65, 69, 75, 78, 92, 94, 95, 100, 101, 113
- leaflet(), 5, 7, 10, 19, 21, 23, 34, 35, 40, 46, 50, 52, 53, 58, 61, 93, 98, 101, 103–105, 114
- leafletOptions, 13
- leafletOutput, 42
- leafletProxy, 45, 54, 59, 60, 72, 103
- leafletProxy(), 58, 61, 93, 98
- leafletSyncOptions, 28, 29, 81
- leafletSyncOptions(), 29, 30, 79, 112
- makeIcon, 37
- makeMapkeyIcon, 82, 83
- makeMapkeyIcon(), 31, 83, 85, 116
- mapkeyIconList, 83
- mapkeyIconList(), 31, 83, 85, 116
- mapkeyIcons, 84
- mapkeyIcons(), 31, 83, 116
- mapmenuItems, 85
- mapmenuItems(), 14, 25, 63–65, 69, 76, 78, 86, 87, 92, 96, 102, 105
- markerClusterOptions(), 11, 16, 31
- markermenuItems, 86
- markermenuItems(), 14, 25, 63–65, 69, 76, 78, 85, 87, 92, 96, 102, 105
- markerOptions, 13, 31, 33
- markerOptions::markerOptions(), 11
- menuItem, 86
- menuItem(), 14, 25, 63–65, 69, 76, 78, 85, 86, 92, 96, 102, 105
- moveToMoving (startMoving), 109
- movingMarkerOptions, 33, 87
- movingMarkerOptions(), 33, 110
- openSidebar, 88
- openSidebar(), 43, 62, 97, 106, 107
- openweatherCurrentOptions, 34, 88
- openweatherCurrentOptions(), 35, 36, 90
- openweatherOptions, 36, 89
- openweatherOptions(), 35, 36, 89
- pathOptions, 13, 21, 37
- pauseMoving (startMoving), 109
- playbackOptions, 37, 90
- playbackOptions(), 38, 96
- popupOptions, 54
- popupOptions(), 5, 7, 11, 15, 31, 33, 37, 49
- reachabilityOptions, 41, 91
- reachabilityOptions(), 42, 97
- removeallItemsContextmenu, 92
- removeallItemsContextmenu(), 14, 25, 63–65, 69, 76, 78, 85–87, 96, 102, 105
- removeAntpath, 93
- removeAntpath(), 6, 56, 58
- removeArrowhead, 93
- removeArrowhead(), 8, 57, 58
- removeConditionalLayer, 94
- removeConditionalLayer(), 27, 59
- removeControl, 21
- removeEasyprint, 94
- removeEasyprint(), 17, 66, 68
- removeGeosearch, 95
- removeGeosearch(), 19, 70
- removeItemContextmenu, 95
- removeItemContextmenu(), 14, 25, 63–65, 69, 76, 78, 85–87, 92, 102, 105
- removePlayback, 96
- removePlayback(), 38, 91
- removeReachability, 96
- removeReachability(), 42, 92
- removeSidebar, 97
- removeSidebar(), 43, 62, 88, 106, 107
- removeSidebyside, 43, 97
- removeSidebyside(), 44
- removeTimeslider, 98

removeTimeslider(), [49](#), [111](#)
removeVectorgrid, [98](#)
removeVectorgrid(), [40](#), [51](#), [61](#), [114](#)
removeVelocity, [99](#)
removeVelocity(), [52](#), [102](#), [115](#)
resumeMoving (startMoving), [109](#)

setBuildingData, [99](#)
setBuildingData(), [9](#), [100](#), [113](#)
setBuildingStyle, [100](#)
setBuildingStyle(), [9](#), [100](#), [113](#)
setDate, [101](#)
setDate(), [20](#), [103](#)
setDisabledContextmenu, [101](#)
setDisabledContextmenu(), [14](#), [25](#), [63–65](#),
[69](#), [76](#), [78](#), [85–87](#), [92](#), [96](#), [105](#)
setOptionsVelocity, [102](#)
setOptionsVelocity(), [52](#), [99](#), [115](#)
setTransparent, [103](#)
setTransparent(), [20](#), [101](#)
setWMSParams, [54](#), [103](#)
setWMSParams(), [54](#)
showContextmenu, [104](#)
showContextmenu(), [14](#), [25](#), [63–65](#), [69](#), [76](#),
[78](#), [85–87](#), [92](#), [96](#), [102](#)
showHexbin, [105](#)
showHexbin(), [23](#), [60](#), [75](#), [76](#), [114](#)
sidebar_pane, [42](#), [88](#), [106](#), [107](#)
sidebar_pane(), [43](#), [62](#), [88](#), [97](#), [107](#)
sidebar_tabs, [42](#), [61](#), [88](#), [97](#), [107](#)
sidebar_tabs(), [43](#), [62](#), [88](#), [97](#), [106](#)
spinWhile, [45](#), [108](#)
spinWhile(), [45](#)
startMoving, [109](#)
startMoving(), [33](#), [87](#)
startSpinner, [108](#)
startSpinner (addSpinner), [45](#)
stopMoving (startMoving), [109](#)
stopSpinner (addSpinner), [45](#)

timesliderOptions, [49](#), [110](#)
timesliderOptions(), [49](#), [98](#)
to_jsonformat, [111](#)
to_ms, [112](#)

unsync, [112](#)
unsync(), [29](#), [30](#), [79](#), [81](#)
updateBuildingTime, [113](#)
updateBuildingTime(), [9](#), [100](#)

updateHexbin, [113](#)
updateHexbin(), [23](#), [60](#), [75](#), [76](#), [105](#)

vectorStyling, [39](#), [40](#), [114](#)
vectorStyling(), [40](#), [51](#), [61](#), [99](#)
velocityOptions, [52](#), [102](#), [115](#)
velocityOptions(), [52](#), [99](#), [102](#)