

Package ‘longevity’

July 14, 2026

Type Package

Title Statistical Methods for the Analysis of Excess Lifetimes

Version 1.3.1

BugReports <https://github.com/lbelzile/longevity/issues>

URL <https://lbelzile.github.io/longevity/>

Depends R (>= 4.0.0)

Imports numDeriv, Rcpp (>= 1.0.6), rlang, Rsolnp

Suggests knitr, ggplot2 (>= 3.0.0), tinytest, rmarkdown

LinkingTo Rcpp, RcppArmadillo

Description A collection of parametric and nonparametric methods for the analysis of survival data, described in <[doi:10.32614/RJ-2025-034](https://doi.org/10.32614/RJ-2025-034)>. Parametric families implemented include Gompertz-Makeham, exponential and generalized Pareto models and extended models. The package includes an implementation of the nonparametric maximum likelihood estimator for arbitrary truncation and censoring pattern based on Turnbull (1976) <[doi:10.1111/j.2517-6161.1976.tb01597.x](https://doi.org/10.1111/j.2517-6161.1976.tb01597.x)>, along with graphical goodness-of-fit diagnostics. Parametric models for positive random variables and peaks over threshold models based on extreme value theory are described in Rootzén and Zholud (2017) <[doi:10.1007/s10687-017-0305-5](https://doi.org/10.1007/s10687-017-0305-5)>; Belzile et al. (2021) <[doi:10.1098/rsos.202097](https://doi.org/10.1098/rsos.202097)> and Belzile et al. (2022) <[doi:10.1146/annurev-statistics-040120-025426](https://doi.org/10.1146/annurev-statistics-040120-025426)>.

License GPL-3

Encoding UTF-8

LazyData true

VignetteBuilder knitr

Config/roxygen2/version 8.0.0

NeedsCompilation yes

Author Leo Belzile [aut, cre] (ORCID: <<https://orcid.org/0000-0002-9135-014X>>),
Mitchell O'Hara-Wild [ctb] (ORCID:
<<https://orcid.org/0000-0001-6729-7695>>)

Maintainer Leo Belzile <belzilel@gmail.com>

Repository CRAN

Date/Publication 2026-07-13 23:40:15 UTC

Contents

autoplot.elifе_northropcoleman 2

autoplot.elifе_par 3

autoplot.elifе_tstab 5

dutch 6

endpoint.profile 7

englandwales 8

ewsim 10

fit_elifе 10

french 12

idlmetadata 13

japanese 14

japanese2 15

lpost_elifе 15

nc_test 17

nll_elifе 18

npsurv 20

np_elifе 21

plot.elifе_ecdf 23

plot.elifе_profile 24

plot.elifе_tstab_endpoint 25

samp_elifе 25

test_elifе 27

tstab 29

Index 31

autoplot.elifе_northropcoleman	
	<i>P-value plot for Northrop and Coleman diagnostic</i>

Description

The Northrop-Coleman tests for penultimate models are comparing the piece-wise generalized Pareto distribution to the generalized Pareto above the lower threshold.

Usage

```
autoplot.elifе_northropcoleman(object, ...)
```

```
## S3 method for class 'elifе_northropcoleman'
```

```
plot(x, plot.type = c("base", "ggplot"), plot = TRUE, ...)
```

Arguments

object	object of class <code>elife_northropcoleman</code> , with the fitted piecewise-constant generalized Pareto model
...	additional arguments for base plot
x	an object of class <code>elife_northropcoleman</code>
plot.type	string indicating the type of plot
plot	logical; should the routine print the graph if <code>plot.type</code> equals "ggplot"? Default to TRUE.

Value

a base R or ggplot object with p-values for the Northrop-Coleman test against thresholds.

autoplot.elife_par	<i>Goodness-of-fit plots for parametric models</i>
--------------------	--

Description

Because of censoring and truncation, the plotting positions must be adjusted accordingly. For right-censored data, the methodology is described in Waller & Turnbull (1992). Only non-censored observations are displayed, which can create distortion.

Usage

```
autoplot.elife_par(object, ...)

## S3 method for class 'elife_par'
plot(
  x,
  plot.type = c("base", "ggplot"),
  which.plot = c("pp", "qq"),
  confint = c("none", "pointwise", "simultaneous"),
  plot = TRUE,
  ...
)
```

Arguments

object	an object of class <code>elife_par</code> containing the fitted parametric model
...	additional arguments, currently ignored by the function.
x	a parametric model of class <code>elife_par</code>
plot.type	string, one of base for base R or ggplot

<code>which.plot</code>	vector of string indicating the plots, among <code>pp</code> for probability-probability plot, <code>qq</code> for quantile-quantile plot, <code>erp</code> for empirically rescaled plot (only for censored data), <code>exp</code> for standard exponential quantile-quantile plot or <code>tmd</code> for Tukey's mean difference plot, which is a variant of the Q-Q plot in which we map the pair (x, y) is mapped to $((x+y)/2, y-x)$ are detrended, <code>dens</code> and <code>cdf</code> return the empirical distribution function with the fitted parametric density or distribution function curve superimposed.
<code>confint</code>	logical; if TRUE, creates uncertainty diagnostic via a parametric bootstrap
<code>plot</code>	logical; if TRUE, creates a plot when <code>plot.type = "ggplot"</code> . Useful for returning ggplot objects without printing the graphs

Details

For truncated data, we first estimate the distribution function nonparametrically, F_n . The uniform plotting positions of the data

$$v_i = [F_n(y_i) - F_n(a_i)] / [F_n(b_i) - F_n(a_i)].$$

For probability-probability plots, the empirical quantiles are transformed using the same transformation, with F_n replaced by the postulated or estimated distribution function F_0 . For quantile-quantile plots, the plotting positions v_i are mapped back to the data scale viz.

$$F_0^{-1}\{F_0(a_i) + v_i[F_0(b_i) - F_0(a_i)]\}$$

When data are truncated and observations are mapped back to the untruncated scale (with, e.g., `exp`), the plotting positions need not be in the same order as the order statistics of the data.

Value

The function produces graphical goodness-of-fit plots using base R or ggplot objects (returned as an invisible list).

Examples

```
set.seed(1234)
samp <- samp_elife(
  n = 200,
  scale = 2,
  shape = 0.3,
  family = "gomp",
  lower = 0, upper = runif(200, 0, 10),
  type2 = "ltrc")
fitted <- fit_elife(
  time = samp$dat,
  thresh = 0,
  event = ifelse(samp$rcens, 0L, 1L),
  type = "right",
  family = "exp",
  export = TRUE)
plot(fitted, plot.type = "ggplot")
# Left- and right-truncated data
```

```

n <- 40L
samp <- samp_elife(
  n = n,
  scale = 2,
  shape = 0.3,
  family = "gp",
  lower = ltrunc <- runif(n),
  upper = rtrunc <- ltrunc + runif(n, 0, 15),
  type2 = "ltrt")
fitted <- fit_elife(
  time = samp,
  thresh = 0,
  ltrunc = ltrunc,
  rtrunc = rtrunc,
  family = "gp",
  export = TRUE)
plot(fitted, which.plot = c("tmd", "dens"))

```

autoplot.elife_tstab *Threshold stability plots*

Description

Threshold stability plots

Usage

```

autoplot.elife_tstab(object, ...)

## S3 method for class 'elife_tstab'
plot(
  x,
  plot.type = c("base", "ggplot"),
  which.plot = c("scale", "shape"),
  plot = TRUE,
  ...
)

```

Arguments

object	object of class <code>elife_tstab</code> , representing parameter estimates to draw threshold stability plots
...	additional arguments, currently ignored by the function.
x	an object of class <code>elife_tstab</code> containing the fitted parameters as a function of threshold
plot.type	string, one of <code>base</code> for base R or <code>ggplot</code>

<code>which.plot</code>	vector of string indicating the plots, among <code>pp</code> for probability-probability plot, <code>qq</code> for quantile-quantile plot, <code>erp</code> for empirically rescaled plot (only for censored data), <code>exp</code> for standard exponential quantile-quantile plot or <code>tmd</code> for Tukey's mean difference plot, which is a variant of the Q-Q plot in which we map the pair (x, y) is mapped to $((x+y)/2, y-x)$ are detrended, <code>dens</code> and <code>cdf</code> return the empirical distribution function with the fitted parametric density or distribution function curve superimposed.
<code>plot</code>	logical; if TRUE, creates a plot when <code>plot.type="ggplot"</code> . Useful for returning <code>ggplot</code> objects without printing the graphs

Value

This S3 method is used to create plots; it only returns a list of graphs if `plot.type="ggplot"`

<code>dutch</code>	<i>Dutch survival data</i>
--------------------	----------------------------

Description

This data frame contains information about all Dutch who died above age 92 years between 1986 and 2015. Observations are doubly truncated and such bounds are calculated based on the range of plausible values for these variables. There are 226 records that are interval-censored and interval-truncated for which `bdate`, `ddate` and `ndays` is missing (NA).

Usage

```
dutch
```

Format

A data frame with 305143 rows and 11 variables:

- ndays** survival time (in days)
- bdate** the smallest plausible birth date given information about month of birth and death and survival (Date)
- bmonth** month of birth
- byear** year of birth
- ddate** the largest plausible death date given information about month of birth and death and survival (Date)
- dmonth** month of death
- dyear** year of death
- ltrunc** minimum age (in days); the maximum of either 92 years or the number of days reached in 1986
- rtrunc** maximum age (in days) an individual could have reached by the end of 2015
- gender** factor indicating gender of individual, either `female` or `male`
- valid** quality flag; A for individuals born in the Netherlands, B for individuals born abroad who died in the Netherlands

Source

Statistics Netherlands (CBS). Accessed via the Supplemental material of Einmahl, Einmahl and de Haan (2019)

References

Einmahl, J.J., J.H.J. Einmahl and L. de Haan (2019). *Limits to Human Life Span Through Extreme Value Theory*, Journal of the American Statistical Association, **114**(527), 1075-1080. doi:[10.1080/01621459.2018.1537912](https://doi.org/10.1080/01621459.2018.1537912)

endpoint.profile	<i>Profile likelihood for the endpoint of the generalized Pareto distribution</i>
------------------	---

Description

This function returns the profile log likelihood over a grid of values of `psi`, the endpoints.

Usage

```
endpoint.profile(
  time,
  time2 = NULL,
  event = NULL,
  thresh = 0,
  type = c("right", "left", "interval", "interval2"),
  ltrunc = NULL,
  rtrunc = NULL,
  weights = rep(1, length(time)),
  psi = NULL,
  confint = FALSE,
  level = 0.95,
  arguments = NULL,
  ...
)
```

Arguments

time	excess time of the event of follow-up time, depending on the value of event
time2	ending excess time of the interval for interval censored data only.
event	status indicator, normally 0=alive, 1=dead. Other choices are TRUE/FALSE (TRUE for death). For interval censored data, the status indicator is 0=right censored, 1=event at time, 2=left censored, 3=interval censored. Although unusual, the event indicator can be omitted, in which case all subjects are assumed to have experienced an event.
thresh	vector of thresholds

type	character string specifying the type of censoring. Possible values are "right", "left", "interval", "interval2".
ltrunc	lower truncation limit, default to NULL
rtrunc	upper truncation limit, default to NULL
weights	weights for observations
psi	mandatory vector of endpoints at which to compute the profile
confint	logical; if TRUE, return a level confidence interval instead of a list with the profile log-likelihood components
level	numeric; the level for the confidence intervals
arguments	a named list specifying default arguments of the function that are common to all <code>elife</code> calls
...	additional parameters, currently ignored

Value

a list with the maximum likelihood estimate of the endpoint and the profile log-likelihood

Examples

```
set.seed(2023)
time <- relife(n = 100, scale = 3, shape = -0.3, family = "gp")
endpt <- endpoint.profile(
  time = time,
  psi = seq(max(time) + 1e-4, max(time) + 40, length.out = 51L))
print(endpt)
plot(endpt)
confint(endpt)
```

englandwales	<i>England and Wales age at death</i>
--------------	---------------------------------------

Description

This data frame contains information about 4032 Welsh and English individuals who died at age ranging from 105 to 110 (so-called semisupercentenarians) between December 28th, 1999 and December 31st, 2014, as well as all 179 supercentenarians (aged 110 and above) who died between January 1st, 1968 and December 31st, 2020.

Usage

```
englandwales
```


Format

A data frame with 4032 rows and 10 variables:

ndays survival time (in days)

ageyear floor of maximum age reached (in years)

gender factor indicating gender of individual, either female or male

valid factor for the quality flag; yes for validated records, no for unchecked records

ddate death date (Date)

bdate birth date (Date)

ltrunc1 first lower truncation bound (in days) corresponding to the lowest possible age achieved for inclusion as semisupercentenarian or supercentenarian

rtrunc1 first upper truncation bound (in days), corresponding to the maximum age reachable by the end of the sampling frame time window

ltrunc2 second lower truncation bound (in days) corresponding to 110 years, for semisupercentenarians who could have reached 110 before 2021

rtrunc2 second upper truncation bound (in days) corresponding to the maximum age by 2021 of semisupercentenarians who could have reached 110 before then

Details

All records for people who died at age 109 and all men, plus a stratified sample of the women were validated by the General Register Office (GRO). Observations are doubly interval truncated: some individuals could have been observed over distinct intervals if they died between 105 and 110 before 2014, but could have reached 110 before the end of the collection period.

The referenced technical report from ONS describes the validation procedure in more details and includes (approximate) sampling weights for the validation of the sample of women who died age 105-108.

The IDL data are licensed under CC BY 4.0 License; please refer to the IDL database to download the latest available data.

Source

International Database on Longevity (IDL), 2021. Hosted by the French Institute for Demographic Studies (Ined) at <https://www.supercentenarians.org/en/>. Data accessed on December 1st, 2023

References

Office for National Statistics (2016). Accuracy of official high-age population estimates, in England and Wales: an evaluation. Technical report, <https://www.ons.gov.uk/peoplepopulationandcommunity/birthsdeathsandmarriages/ageing/methodologies/accuracyofofficialhighagepopulationestimatesinengland>

International Database on Longevity (2021). French Institute for Demographic Studies (Ined) (host).

 ewsim

England and Wales simulated supercentenarian data

Description

This data frame contains information about 179 fake records mimicking Welsh and English who died age 110 and above

Usage

```
ewsim
```

Format

A data frame with 179 rows and 3 variables:

time survival time above 110 (in years)

ltrunc minimum age above 110 (in years), or zero;

rtrunc maximum age (in years) an individual could have reached by the end of the time frame

 fit_elife

Fit excess lifetime models by maximum likelihood

Description

This function is a wrapper around constrained optimization routines for different models with non-informative censoring and truncation patterns.

Usage

```
fit_elife(
  time,
  time2 = NULL,
  event = NULL,
  type = c("right", "left", "interval", "interval2"),
  ltrunc = NULL,
  rtrunc = NULL,
  thresh = 0,
  status = NULL,
  family = c("exp", "gp", "weibull", "gomp", "gompmake", "extgp", "gppiece",
    "extweibull", "perks", "perksmake", "beard", "beardmake"),
  weights = NULL,
  export = FALSE,
  start = NULL,
  restart = FALSE,
```

```

    arguments = NULL,
    check = FALSE,
    ...
)

```

Arguments

time	excess time of the event of follow-up time, depending on the value of event
time2	ending excess time of the interval for interval censored data only.
event	status indicator, normally 0=alive, 1=dead. Other choices are TRUE/FALSE (TRUE for death). For interval censored data, the status indicator is 0=right censored, 1=event at time, 2=left censored, 3=interval censored. Although unusual, the event indicator can be omitted, in which case all subjects are assumed to have experienced an event.
type	character string specifying the type of censoring. Possible values are "right", "left", "interval", "interval2".
ltrunc	lower truncation limit, default to NULL
rtrunc	upper truncation limit, default to NULL
thresh	vector of thresholds
status	integer vector giving status of an observation. If NULL (default), this argument is computed internally based on type.
family	string; choice of parametric family
weights	weights for observations
export	logical; should data be included in the returned object to produce diagnostic plots? Default to FALSE.
start	vector of starting values for the optimization routine. If NULL, the algorithm attempts to find default values and returns a warning with false convergence diagnostic if it cannot.
restart	logical; should multiple starting values be attempted? Default to FALSE.
arguments	a named list specifying default arguments of the function that are common to all elife calls
check	logical; if TRUE, fit all submodels to ensure that simpler models fit worst or as well
...	additional parameters, currently ignored

Value

an object of class `elife_par`

Note

The extended generalized Pareto model is constrained to avoid regions where the likelihood is flat so $\xi \in [-1, 10]$ in the optimization algorithm.

The standard errors are obtained via the observed information matrix, calculated using the hessian. In many instances, such as when the shape parameter is zero or negative, the hessian is singular and no estimates are returned.

Examples

```
data(ewsim, package = "longevity")
fit1 <- fit_elifa(
  arguments = ewsim,
  export = TRUE,
  family = "exp")
fit2 <- fit_elifa(
  arguments = ewsim,
  export = TRUE,
  family = "gp")
plot(fit1)
summary(fit1)
anova(fit2, fit1)
```

french	<i>French semi-supercentenarian</i>
--------	-------------------------------------

Description

This data frame contains information about 9853 French semi-supercentenarian, part of the International Database on Longevity (IDL). All supercentenarian records were validated, but only a random sample of semi-supercentenarians were validated. Lifetimes are interval truncated; only people above 110 born after 1978 and people above 105 born after 1987 are included.

Usage

```
french
```

Format

A data frame with 9853 rows and 6 variables:

ndays survival time (in days)

bdate birth date (Date)

ddate death date (Date) if the person is alive at the end of the sampling

ltrunc minimum age (in days); the maximum of 38350 days (approximately 105 years) or the number of days reached on January 1st 1978 (supercentenarian) or 1987 (semisupercentenarian)

rtrunc maximum age (in days) an individual could have reached by the end of 2017

gender factor indicating gender of individual, either female or male

Source

International Database on Longevity (IDL), 2021. Hosted by the French Institute for Demographic Studies (Ined) at <https://www.supercentenarians.org/en/>. The IDL data are licensed under CC BY 4.0 License; please refer to the IDL database to download the latest available data.

References

International Database on Longevity (2021). French Institute for Demographic Studies (Ined) (host).

 idlmetadata

IDL metadata

Description

This data frame contains country codes and the associated data collection period corresponding to the range for age at death.

Usage

```
idlmetadata
```

Format

A data frame with 21 rows and 4 variables:

country factor, one of AUT (Austria), BEL (Belgium), CAN (Quebec), DEU (Germany), DNK (Denmark), ESP (Spain), FIN (Finland), FRA (France), JPN (Japan), NOR (Norway), SWE (Sweden), EAW (England and Wales) and USA (United States of America)

group factor, either 105-109 for semi-supercentenarians or 110+ for supercentenarians"

ldate Date, smallest death date

rdate Date, latest death date

Details

Due to confidentiality restrictions, some data that were available in previous versions of the IDL for Switzerland, Italy and some entries for Japan and Belgium have been removed. As the IDL metadata are updated somewhat regularly and former versions of the database are not preserved, results from published analyses are replicable but not reproducible.

References

International Database on Longevity, extracted on February 13th, 2023

japanese*Japanese survival data*

Description

This data frame contains information about the counts of dead Japanese by gender and year of birth (cohort), categorized by the whole part of age attained at death.

Usage

japanese

Format

A data frame with 1038 rows and 4 variables:

age integer, age (to the smallest year) at death (in years)

byear integer, birth year

count integer, number of death for cohort at given age

gender factor, the gender of the individuals; either male or female

Details

These data were obtained from the Annual Vital Statistics Report of Japan, released by the Japanese government every year since 1947. The authors note that "All the members of that cohort have died by the end of the observation period, a procedure referred to as the extinct cohort method". The data were obtained from the Human Mortality Database by the authors. Only positive counts are reported and two records (Misao Okawa and Jiroemon Kimura) are excluded because they do not correspond to the same selection mechanism.

Source

Table extracted from Hanayama & Sibuya (2016).

References

Hanayama, N. and M. Sibuya (2016). Estimating the Upper Limit of Lifetime Probability Distribution, Based on Data of Japanese Centenarians, *The Journals of Gerontology: Series A*, 71(8), 1014–1021. doi:[10.1093/gerona/glv113](https://doi.org/10.1093/gerona/glv113)

japanese2

*Japanese survival data (2)***Description**

This data frame is extracted from Table 10.3 from Chapter 10, "Centenarians and Supercentenarians in Japan", in the Monograph *Exceptional lifespans*. The data were constructed by the extinct cohort method and are stratified by age cohort (five year group, except 1899-1900) and by sex. Note that the family registry system (KOSEKI), introduced in 1872, was standardized in 1886.

Usage

japanese2

Format

A data frame with 216 rows and 4 variables:

age integer, age (to the smallest year) at death (in years)

bcohort factor, birth cohort

count integer, number of death for cohort at given age

gender factor, the gender of the individuals; either male or female

Source

Table 10.3

References

Saito, Yasuhiko and Futoshi Ishii, and Jean-Marie Robine (2021). *Centenarians and Supercentenarians in Japan*. In *Exceptional lifespans*, Maier, H., Jeune, B., Vaupel, J. W. (Eds.), Demographic research monographs 17 VII, pp. 125-145. Cham, Springer.

lpost_elife

*Log posterior distribution with MDI priors***Description**

Log of the posterior distribution for excess lifetime distribution with maximal data information priors.

Usage

```
lpost_elife(
  par,
  time,
  time2 = NULL,
  event = NULL,
  type = c("right", "left", "interval", "interval2"),
  ltrunc = NULL,
  rtrunc = NULL,
  family = c("exp", "gp", "gomp"),
  thresh = 0,
  weights = rep(1, length(time)),
  status = NULL,
  arguments = NULL,
  ...
)
```

Arguments

par	vector of parameters, in the following order: scale, rate and shape
time	excess time of the event of follow-up time, depending on the value of event
time2	ending excess time of the interval for interval censored data only.
event	status indicator, normally 0=alive, 1=dead. Other choices are TRUE/FALSE (TRUE for death). For interval censored data, the status indicator is 0=right censored, 1=event at time, 2=left censored, 3=interval censored. Although unusual, the event indicator can be omitted, in which case all subjects are assumed to have experienced an event.
type	character string specifying the type of censoring. Possible values are "right", "left", "interval", "interval2".
ltrunc	lower truncation limit, default to NULL
rtrunc	upper truncation limit, default to NULL
family	string; choice of parametric family
thresh	vector of thresholds
weights	weights for observations
status	integer vector giving status of an observation. If NULL (default), this argument is computed internally based on type.
arguments	a named list specifying default arguments of the function that are common to all elif calls
...	additional arguments for optimization, currently ignored.

Value

a vector proportional to the log posterior (the sum of the log likelihood and log prior)

nc_test

*Score test of Northrop and Coleman***Description**

This function computes the score test with the piecewise generalized Pareto distribution under the null hypothesis that the generalized Pareto with a single shape parameter is an adequate simplification. The score test statistic is calculated using the observed information matrix; both hessian and score vector are obtained through numerical differentiation.

Usage

```
nc_test(
  time,
  time2 = NULL,
  event = NULL,
  thresh = 0,
  ltrunc = NULL,
  rtrunc = NULL,
  type = c("right", "left", "interval", "interval2"),
  weights = rep(1, length(time)),
  test = c("score", "lrt"),
  arguments = NULL,
  ...
)
```

Arguments

time	excess time of the event of follow-up time, depending on the value of event
time2	ending excess time of the interval for interval censored data only.
event	status indicator, normally 0=alive, 1=dead. Other choices are TRUE/FALSE (TRUE for death). For interval censored data, the status indicator is 0=right censored, 1=event at time, 2=left censored, 3=interval censored. Although unusual, the event indicator can be omitted, in which case all subjects are assumed to have experienced an event.
thresh	a vector of thresholds
ltrunc	lower truncation limit, default to NULL
rtrunc	upper truncation limit, default to NULL
type	character string specifying the type of censoring. Possible values are "right", "left", "interval", "interval2".
weights	weights for observations
test	string, either "score" for the score test or "lrt" for the likelihood ratio test.
arguments	a named list specifying default arguments of the function that are common to all <code>elife</code> calls
...	additional parameters, currently ignored

Details

The score test is much faster and perhaps less fragile than the likelihood ratio test: fitting the piecewise generalized Pareto model is difficult due to the large number of parameters and multimodal likelihood surface.

The reference distribution is chi-square

Value

a data frame with the following variables:

- thresh: threshold for the generalized Pareto distribution
- nexc: number of exceedances
- score: score statistic
- df: degrees of freedom
- pval: the p-value obtained from the asymptotic chi-square approximation.

Examples

```
set.seed(1234)
n <- 100L
x <- samp_elif(n = n,
               scale = 2,
               shape = -0.2,
               lower = low <- runif(n),
               upper = upp <- runif(n, min = 3, max = 20),
               type2 = "ltrt",
               family = "gp")
test <- nc_test(
  time = x,
  ltrunc = low,
  rtrunc = upp,
  thresh = quantile(x, seq(0, 0.5, by = 0.1)))
print(test)
plot(test)
```

Description

Computes the log-likelihood for various parametric models suitable for threshold exceedances. If threshold is non-zero, then only right-censored, observed event time and interval censored data whose timing exceeds the thresholds are kept.

Usage

```
nll_elife(
  par,
  time,
  time2 = NULL,
  event = NULL,
  type = c("right", "left", "interval", "interval2"),
  ltrunc = NULL,
  rtrunc = NULL,
  family = c("exp", "gp", "gomp", "gompmake", "weibull", "extgp", "gppiece",
    "extweibull", "perks", "beard", "perksmake", "beardmake"),
  thresh = 0,
  weights = NULL,
  status = NULL,
  arguments = NULL,
  ...
)
```

Arguments

<code>par</code>	vector of parameters, in the following order: scale, rate and shape
<code>time</code>	excess time of the event of follow-up time, depending on the value of event
<code>time2</code>	ending excess time of the interval for interval censored data only.
<code>event</code>	status indicator, normally 0=alive, 1=dead. Other choices are TRUE/FALSE (TRUE for death). For interval censored data, the status indicator is 0=right censored, 1=event at time, 2=left censored, 3=interval censored. Although unusual, the event indicator can be omitted, in which case all subjects are assumed to have experienced an event.
<code>type</code>	character string specifying the type of censoring. Possible values are "right", "left", "interval", "interval2".
<code>ltrunc</code>	lower truncation limit, default to NULL
<code>rtrunc</code>	upper truncation limit, default to NULL
<code>family</code>	string; choice of parametric family
<code>thresh</code>	vector of thresholds
<code>weights</code>	weights for observations
<code>status</code>	integer vector giving status of an observation. If NULL (default), this argument is computed internally based on type.
<code>arguments</code>	a named list specifying default arguments of the function that are common to all <code>elife</code> calls
<code>...</code>	additional arguments for optimization, currently ignored.

Value

log-likelihood values

Examples

```
data(ewsim, package = "longevity")
nll_elife(par = c(5, 0.3),
          family = "gp",
          arguments = ewsim)
```

npsurv	<i>Nonparametric maximum likelihood estimation for arbitrary truncation</i>
--------	---

Description

The syntax is reminiscent of the [Surv](#) function, with additional vectors for left-truncation and right-truncation.

Usage

```
npsurv(
  time,
  time2 = NULL,
  event = NULL,
  type = c("right", "left", "interval", "interval2"),
  ltrunc = NULL,
  rtrunc = NULL,
  weights = NULL,
  arguments = NULL,
  ...
)
```

Arguments

time	excess time of the event of follow-up time, depending on the value of event
time2	ending excess time of the interval for interval censored data only.
event	status indicator, normally 0=alive, 1=dead. Other choices are TRUE/FALSE (TRUE for death). For interval censored data, the status indicator is 0=right censored, 1=event at time, 2=left censored, 3=interval censored. Although unusual, the event indicator can be omitted, in which case all subjects are assumed to have experienced an event.
type	character string specifying the type of censoring. Possible values are "right", "left", "interval", "interval2".
ltrunc	lower truncation limit, default to NULL
rtrunc	upper truncation limit, default to NULL
weights	vector of weights, default to NULL for equiweighted
arguments	a named list specifying default arguments of the function that are common to all elife calls
...	additional arguments passed to the functions

Value

a list with components

- xval: unique ordered values of sets on which the distribution function is defined
- prob: estimated probability of failure on intervals
- convergence: logical; TRUE if the EM algorithm iterated until convergence
- niter: logical; number of iterations for the EM algorithm
- cdf: nonparametric maximum likelihood estimator of the distribution function

Note

Contrary to the Kaplan-Meier estimator, the mass is placed in the interval $[\max(\text{time}), \text{Inf})$ so the resulting distribution function is not deficient.

See Also

[Surv](#)

Examples

```
# Toy example with interval censoring and right censoring
# Two observations: A1: [1,3], A2: 4
# Probability of 0.5

test_simple2 <- np surv(
  time = c(1,4),
  time2 = c(3,4),
  event = c(3,1),
  type = "interval"
)
```

np_elif

Nonparametric estimation of the survival function

Description

The survival function is obtained through the EM algorithm described in Turnbull (1976); censoring and truncation are assumed to be non-informative. The survival function changes only at the J distinct exceedances $y_i - u$ and truncation points.

Usage

```
np_elif(
  time,
  time2 = NULL,
  event = NULL,
  type = c("right", "left", "interval", "interval2"),
```

```

    thresh = 0,
    ltrunc = NULL,
    rtrunc = NULL,
    tol = 1e-12,
    weights = NULL,
    method = c("em", "sqp"),
    arguments = NULL,
    maxiter = 100000L,
    ...
)

```

Arguments

time	excess time of the event of follow-up time, depending on the value of event
time2	ending excess time of the interval for interval censored data only.
event	status indicator, normally 0=alive, 1=dead. Other choices are TRUE/FALSE (TRUE for death). For interval censored data, the status indicator is 0=right censored, 1=event at time, 2=left censored, 3=interval censored. Although unusual, the event indicator can be omitted, in which case all subjects are assumed to have experienced an event.
type	character string specifying the type of censoring. Possible values are "right", "left", "interval", "interval2".
thresh	double thresh
ltrunc	lower truncation limit, default to NULL
rtrunc	upper truncation limit, default to NULL
tol	double, relative tolerance for convergence of the EM algorithm
weights	double, vector of weights for the observations
method	string, one of "em" for expectation-maximization (EM) algorithm or "sqp" for sequential quadratic programming with augmented Lagrange multipliers method.
arguments	a named list specifying default arguments of the function that are common to all elife calls
maxiter	integer, maximum number of iterations for the EM algorithm
...	additional arguments, currently ignored

Details

The unknown parameters of the model are $p_j (j = 1, \dots, J)$ subject to the constraint that $\sum_{j=1}^J p_j = 1$.

Value

a list with elements

- cdf: right-continuous stepfun object defined by probabilities
- time: matrix of unique values for the Turnbull intervals defining equivalence classes; only those with non-zero probabilities are returned

- prob: J vector of non-zero probabilities
- niter: number of iterations

References

Turnbull, B. W. (1976). *The Empirical Distribution Function with Arbitrarily Grouped, Censored and Truncated Data*. Journal of the Royal Statistical Society. Series B (Methodological) 38(3), 290–295.

Gentleman, R. and C. J. Geyer (1994). *Maximum likelihood for interval censored data: Consistency and computation*, Biometrika, 81(3), 618–623.

Frydman, H. (1994). *A Note on Nonparametric Estimation of the Distribution Function from Interval-Censored and Truncated Observations*, Journal of the Royal Statistical Society. Series B (Methodological) 56(1), 71-74.

Examples

```
set.seed(2021)
n <- 20L
# Create fake data
ltrunc <- pmax(0, runif(n, -0.5, 1))
rtrunc <- runif(n, 6, 10)
dat <- samp_elife(n = n,
                  scale = 1,
                  shape = -0.1,
                  lower = ltrunc,
                  upper = rtrunc,
                  family = "gp",
                  type2 = "ltrt")
npi <- np_elife(time = dat,
                rtrunc = rtrunc,
                ltrunc = ltrunc)

print(npi)
summary(npi)
plot(npi)
```

plot.elife_ecdf

Plot empirical distribution function

Description

Plot empirical distribution function

Usage

```
## S3 method for class 'elife_ecdf'
plot(x, ...)
```

Arguments

<code>x</code>	argument of class <code>elife_ecdf</code>
<code>...</code>	additional arguments for the plot

Value

base R plot of the empirical distribution function

<code>plot.elife_profile</code>	<i>Plot profile of endpoint</i>
---------------------------------	---------------------------------

Description

Plot profile of endpoint

Usage

```
## S3 method for class 'elife_profile'
plot(x, plot.type = c("base", "ggplot"), plot = TRUE, ...)

autoplot.elife_profile(object, ...)

autoplot.elife_tstab_endpoint(object, ...)
```

Arguments

<code>x</code>	an object of class <code>elife_profile</code> containing information about the profile likelihood, maximum likelihood and grid of values for the endpoint
<code>plot.type</code>	string indicating whether to use base R for plots or <code>ggplot2</code>
<code>plot</code>	logical; if TRUE, creates a plot when <code>plot.type="ggplot"</code> . Useful for returning <code>ggplot</code> objects without printing the graphs
<code>...</code>	additional arguments to pass to <code>plot</code> , currently ignored
<code>object</code>	object of class <code>elife_tstab_endpoint</code>

Value

base R or `ggplot` object for a plot of the profile log likelihood of the endpoint of the generalized Pareto distribution

plot.elife_tstab_endpoint

Plot threshold stability plot for endpoint

Description

Plot threshold stability plot for endpoint

Usage

```
## S3 method for class 'elife_tstab_endpoint'
plot(x, plot.type = c("base", "ggplot"), plot = TRUE, ...)
```

Arguments

x	an object of class elife_tstab_endpoint containing information about the profile likelihood, maximum likelihood and grid of values for the endpoint
plot.type	string indicating whether to use base R for plots or ggplot2
plot	logical; if TRUE, creates a plot when plot.type="ggplot". Useful for returning ggplot objects without printing the graphs
...	additional arguments to pass to plot, currently ignored

Value

base R or ggplot object for a plot of the profile log likelihood of the endpoint of the generalized Pareto distribution

samp_elife

Simulate excess lifetime with truncation or right-censoring

Description

This function dispatches simulations accounting for potential left-truncation (remove by setting lower to zero). If type2=ltrt, simulated observations will be lower than the upper bounds upper. If type2=ltrc, simulated observations are capped at upper and the observation is right-censored (rcens=TRUE).

Usage

```
samp_elife(
  n,
  scale,
  rate,
  shape = NULL,
  lower = 0,
  upper = Inf,
  family = c("exp", "gp", "gomp", "gompmake", "weibull", "extgp", "gppiece",
    "extweibull", "perks", "beard", "perksmake", "beardmake"),
  type2 = c("none", "ltrt", "ltrc", "ditrunc")
)
```

Arguments

n	sample size
scale	scale parameter(s)
rate	rate parameter(s)
shape	shape parameter(s)
lower	vector of lower bounds
upper	vector of upper bounds
family	string; choice of parametric family
type2	string, either none, ltrt for left- and right-truncated data or ltrc for left-truncated right-censored data

Value

either a vector of observations or, if type2=ltrc, a list with n observations dat and a logical vector of the same length with TRUE for right-censored observations and FALSE otherwise.

Note

As the tails of the Gompertz and Gompertz–Makeham models decrease exponentially fast, the method fails in the rare event case if the lower bound is too large (say larger than the 99.99

Examples

```
set.seed(1234)
n <- 500L
# Simulate interval truncated data
x <- samp_elife(n = n,
  scale = 2,
  shape = 1.5,
  lower = low <- runif(n),
  upper = upp <- runif(n, min = 3, max = 15),
  type2 = "ltrt",
  family = "weibull")
coef(fit_elife(
```

```

      time = x,
      ltrunc = low,
      rtrunc = upp,
      family = "weibull"))
# Simulate left-truncated right-censored data
x <- samp_elife(n = n,
               scale = 2,
               shape = 1.5,
               lower = low <- runif(n),
               upper = upp <- runif(n, min = 3, max = 15),
               type2 = "ltrc",
               family = "gomp")
#note that the return value is a list...
coef(fit_elife(
  time = x$dat,
  ltrunc = low,
  event = !x$rcens,
  family = "gomp"))

```

test_elife

Likelihood ratio test for covariates

Description

This function fits separate models for each distinct value of the factor covariate and computes a likelihood ratio test to test whether there are significant differences between groups.

Usage

```

test_elife(
  time,
  time2 = NULL,
  event = NULL,
  covariate,
  thresh = 0,
  ltrunc = NULL,
  rtrunc = NULL,
  type = c("right", "left", "interval", "interval2"),
  family = c("exp", "gp", "weibull", "gomp", "gompmake", "extgp", "extweibull", "perks",
    "perksmake", "beard", "beardmake"),
  weights = rep(1, length(time)),
  arguments = NULL,
  ...
)

```

Arguments

time excess time of the event of follow-up time, depending on the value of event

time2	ending excess time of the interval for interval censored data only.
event	status indicator, normally 0=alive, 1=dead. Other choices are TRUE/FALSE (TRUE for death). For interval censored data, the status indicator is 0=right censored, 1=event at time, 2=left censored, 3=interval censored. Although unusual, the event indicator can be omitted, in which case all subjects are assumed to have experienced an event.
covariate	vector of factors, logical or integer whose distinct values define groups
thresh	vector of thresholds
ltrunc	lower truncation limit, default to NULL
rtrunc	upper truncation limit, default to NULL
type	character string specifying the type of censoring. Possible values are "right", "left", "interval", "interval2".
family	string; choice of parametric family
weights	weights for observations
arguments	a named list specifying default arguments of the function that are common to all elife calls
...	additional arguments for optimization, currently ignored.

Value

a list with elements

- stat likelihood ratio statistic
- df degrees of freedom
- pval the p-value obtained from the asymptotic chi-square approximation.

Examples

```
test <- with(subset(dutch, ndays > 39082),
  test_elife(
    time = ndays,
    thresh = 39082L,
    covariate = gender,
    ltrunc = ltrunc,
    rtrunc = rtrunc,
    family = "exp"))
test
```

tstab	<i>Threshold stability plots</i>
-------	----------------------------------

Description

The generalized Pareto and exponential distribution are threshold stable. This property, which is used for extrapolation purposes, can also be used to diagnose goodness-of-fit: we expect the parameters ξ and $\tilde{\sigma} = \sigma + \xi u$ to be constant over a range of thresholds. The threshold stability plot consists in plotting maximum likelihood estimates with pointwise confidence interval. This function handles interval truncation and right-censoring.

Usage

```
tstab(
  time,
  time2 = NULL,
  event = NULL,
  thresh = 0,
  ltrunc = NULL,
  rtrunc = NULL,
  type = c("right", "left", "interval", "interval2"),
  family = c("gp", "exp"),
  method = c("wald", "profile"),
  level = 0.95,
  plot = TRUE,
  plot.type = c("base", "ggplot"),
  which.plot = c("scale", "shape"),
  weights = NULL,
  arguments = NULL,
  ...
)
```

Arguments

time	excess time of the event of follow-up time, depending on the value of event
time2	ending excess time of the interval for interval censored data only.
event	status indicator, normally 0=alive, 1=dead. Other choices are TRUE/FALSE (TRUE for death). For interval censored data, the status indicator is 0=right censored, 1=event at time, 2=left censored, 3=interval censored. Although unusual, the event indicator can be omitted, in which case all subjects are assumed to have experienced an event.
thresh	vector of thresholds
ltrunc	lower truncation limit, default to NULL
rtrunc	upper truncation limit, default to NULL
type	character string specifying the type of censoring. Possible values are "right", "left", "interval", "interval2".

family	string; distribution, either generalized Pareto (gp) or exponential (exp)
method	string; the type of pointwise confidence interval, either Wald (wald) or profile likelihood (profile)
level	probability level for the pointwise confidence intervals
plot	logical; should a plot be returned alongside with the estimates? Default to TRUE
plot.type	string; either base for base R plots or ggplot for ggplot2 plots
which.plot	string; which parameters to plot;
weights	weights for observations
arguments	a named list specifying default arguments of the function that are common to all <code>elife</code> calls
...	additional arguments for optimization, currently ignored.

Details

The shape estimates are constrained

Value

an invisible list with pointwise estimates and confidence intervals for the scale and shape parameters

See Also

`tstab.gpd` from package `mev`, `gpd.fitrange` from package `ismev` or `tcplot` from package `evd`, among others.

Examples

```
set.seed(1234)
n <- 100L
x <- samp_elife(n = n,
  scale = 2,
  shape = -0.2,
  lower = low <- runif(n),
  upper = upp <- runif(n, min = 3, max = 20),
  type2 = "ltrt",
  family = "gp")
tstab_plot <- tstab(time = x,
  ltrunc = low,
  rtrunc = upp,
  thresh = quantile(x, seq(0, 0.5, length.out = 4)))
plot(tstab_plot, plot.type = "ggplot")
```

Index

- * **datasets**
 - dutch, [6](#)
 - englandwales, [8](#)
 - ewsim, [10](#)
 - french, [12](#)
 - idlmetadata, [13](#)
 - japanese, [14](#)
 - japanese2, [15](#)
- autoplot.elife_northropcoleman, [2](#)
- autoplot.elife_par, [3](#)
- autoplot.elife_profile
 - (plot.elife_profile), [24](#)
- autoplot.elife_tstab, [5](#)
- autoplot.elife_tstab_endpoint
 - (plot.elife_profile), [24](#)
- dutch, [6](#)
- endpoint.profile, [7](#)
- englandwales, [8](#)
- ewsim, [10](#)
- fit_elife, [10](#)
- french, [12](#)
- idlmetadata, [13](#)
- japanese, [14](#)
- japanese2, [15](#)
- lpost_elife, [15](#)
- nc_test, [17](#)
- nll_elife, [18](#)
- np_elife, [21](#)
- npsurv, [20](#)
- plot.elife_ecdf, [23](#)
- plot.elife_northropcoleman
 - (autoplot.elife_northropcoleman), [2](#)
- plot.elife_par (autoplot.elife_par), [3](#)
- plot.elife_profile, [24](#)
- plot.elife_tstab
 - (autoplot.elife_tstab), [5](#)
- plot.elife_tstab_endpoint, [25](#)
- samp_elife, [25](#)
- Surv, [20](#), [21](#)
- test_elife, [27](#)
- tstab, [29](#)