

Package ‘permutations’

July 13, 2026

Type Package

Title The Symmetric Group: Permutations of a Finite Set

Version 1.1-9-1

Imports magic, numbers, partitions (>= 1.9-17), freealg (>= 1.0-4),
methods

Maintainer Robin K. S. Hankin <hankin.robin@gmail.com>

Depends R (>= 4.1.0)

LazyData TRUE

Description Manipulates invertible functions from a finite set to
itself. Can transform from word form to cycle form and
back. To cite the package in publications please use
Hankin (2020) ``Introducing the permutations R package",
SoftwareX, volume 11 <doi:10.1016/j.softx.2020.100453>.

License GPL-2

Suggests rmarkdown, testthat, knitr, magrittr, covr

VignetteBuilder knitr

URL <https://github.com/RobinHankin/permutations>,
<https://robinhankin.github.io/permutations/>

BugReports <https://github.com/RobinHankin/permutations/issues>

Config/testthat/edition 3

Encoding UTF-8

Config/roxygen2/version 8.0.0

NeedsCompilation no

Author Robin K. S. Hankin [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-5982-0415>>),
Paul Egeler [ctb] (ORCID: <<https://orcid.org/0000-0001-6948-9498>>)

Repository CRAN

Date/Publication 2026-07-13 15:20:02 UTC

Contents

permutations-package	3
allperms	5
as.function.permutation	6
c	8
capply	9
caydist	10
cayley	12
commutator	13
conjugate	14
cyclist	16
derangement	18
dodecahedron	19
Extract	19
faro	20
fbin	21
fixed	23
get1	24
id	25
inverse	26
keepcyc	27
length	28
megaminx	29
megaminx_plotter	31
megaminx_superflip	32
nullperm	33
Ops.permutation	34
orbit	37
outer	39
permorder	39
permutation	40
perm_matrix	42
print	44
rperm	46
sgn	48
shape	49
size	51
stabilizer	52
swap	54
tidy	55
valid	56

Index

58

permutations-package *The Symmetric Group: Permutations of a Finite Set*

Description

Manipulates invertible functions from a finite set to itself. Can transform from word form to cycle form and back. To cite the package in publications please use Hankin (2020) "Introducing the permutations R package", SoftwareX, volume 11 <doi:10.1016/j.softx.2020.100453>.

Details

The DESCRIPTION file:

```
Package: permutations
Type: Package
Title: The Symmetric Group: Permutations of a Finite Set
Version: 1.1-9-1
Imports: magic, numbers, partitions (>= 1.9-17), freealg (>= 1.0-4), methods
Authors@R: c( person(given=c("Robin", "K. S."), family="Hankin", role = c("aut","cre"), email="hankin.robin@unh.edu"),
Maintainer: Robin K. S. Hankin <hankin.robin@gmail.com>
Depends: R (>= 4.1.0)
LazyData: TRUE
Description: Manipulates invertible functions from a finite set to itself. Can transform from word form to cycle form and back.
License: GPL-2
Suggests: rmarkdown, testthat, knitr, magrittr, covr
VignetteBuilder: knitr
URL: https://github.com/RobinHankin/permutations, https://robinhankin.github.io/permutations/
BugReports: https://github.com/RobinHankin/permutations/issues
Config/testthat/edition: 3
Encoding: UTF-8
Config/roxygen2/version: 8.0.0
Author: Robin K. S. Hankin [aut, cre] (ORCID: <https://orcid.org/0000-0001-5982-0415>), Paul Egeler [
```

Index of help topics:

Extract	Extract or Replace elements of permutation vectors
Ops.permutation	Arithmetic Ops Group Methods for permutations
allperms	All permutations with given characteristics
as.function.permutation	Coerce a permutation to a function
c	Concatenation of permutations
capply	Apply functions to elements of a cycle
caydist	Cayley distance
cayley	Cayley tables for permutation groups
commutator	Group-theoretic commutator: the dot object

conjugate	Are two permutations conjugate?
cyclist	details of cyclists
derangement	Tests for a permutation being a derangement
dodecahedron	The dodecahedron group
faro	Faro shuffles
fbin	The fundamental bijection
fixed	Fixed elements
get1	Retrieve particular cycles or components of cycles
id	The identity permutation
inverse	Inverse of a permutation
keepcyc	Keep or discard some cycles of a permutation
length.word	Various vector-like utilities for permutation objects.
megaminx	megaminx
megaminx_plotter	Plotting routine for megaminx sequences
megaminx_superflip	The Megaminx Superflip
nullperm	Null permutations
orbit	Orbits of integers
outer	Outer product of vectors of permutations
perm_matrix	Permutation matrices
permorder	The order of a permutation
permutation	Functions to create and coerce word objects and cycle objects
permutations-package	The Symmetric Group: Permutations of a Finite Set
print.permutation	Print methods for permutation objects
rperm	Random permutations
sgn	Sign of a permutation
shape	Shape of a permutation
size	Gets or sets the size of a permutation
stabilizer	Stabilizer of a permutation
swap	Length-2 cycles; swap a pair of elements
tidy	Utilities to neaten permutation objects
valid	Functions to validate permutations

Author(s)

Robin K. S. Hankin [aut, cre] (ORCID: <<https://orcid.org/0000-0001-5982-0415>>), Paul Egeler [ctb] (ORCID: <<https://orcid.org/0000-0001-6948-9498>>)

Maintainer: Robin K. S. Hankin <hankin.robin@gmail.com>

Examples

```
a <- rperm(10,5)
b <- rperm(10,5)

a*b
```

```
inverse(a)
```

allperms

All permutations with given characteristics

Description

Functionality to enumerate permutations given different characteristics. In the following, n is assumed to be a non-negative integer. Permutations, in general, are coerced to cycle form.

Usage

```
allperms(n)
allcycn(n)
allcyc(s)
allpermslike(o)
some_perms_shape(shape)
all_cyclic_shuffles(o)
all_perms_shape(shape)
```

Arguments

shape	A set of strictly positive integers, interpreted as the shape of a partition
s	A set of strictly positive integers, interpreted as a set on which permutations are defined
n	The size of the permutation
o	A vector of permutations, coerced to cycle form. Function allpermslike() considers only the first element

Details

- allperms(n) returns all $n!$ permutations of $[n]$. It is very basic (the idiom is `word(t(partitions::perms(n)))`) but is here for completeness.
- allcycn() returns all $(n - 1)!$ permutations of $[n]$ comprising a single cycle of length n .
- allcyc(s) returns all single-cycle permutations of set s . If s has a repeated value, an opaque error message is returned.
- allpermslike(o) takes a length-one vector o of permutations and returns a vector comprising permutations with the same shape and cycle sets as its argument.
- some_perms_shape($part$) takes an integer partition $part$, as in a set of non-negative integers, and returns a vector comprising every permutation of size `sum(part)` with shape $part$ that has its cycles in increasing order.
- all_cyclic_shuffles(u) takes a permutation u and returns a vector comprising of all permutations with the same shape and cycle sets. It is vectorized so that argument u may be a vector of permutations.

- `all_perms_shape(p)` takes a permutation `p` and returns a vector of all permutations of size `sum(p)` and shape `p`.

Note

Function `allcyc()` is taken directly from Er’s “fine-tuned” algorithm. It should really be implemented in **C** as part of the **partitions** package but I have not yet got round to this.

Author(s)

Robin K. S. Hankin

References

M. C. Er 1989 “Efficient enumeration of cyclic permutations in situ”. *International Journal of Computer Mathematics*, volume 29:2-4, pp121-129.

See Also

[allperms](#)

Examples

```
allperms(5)

allcycn(5)

allcyc(c(5,6,8,3))

allpermslike(as.cycle("(12)(34)(5678)"))
allpermslike(rgivenshape(c(1,1,3,4)))

some_perms_shape(c(3,3))    # size 6
some_perms_shape(c(3,3,1))  # size 7 (length-1 cycles vanish)

all_cyclic_shuffles(as.cycle(1:3) + as.cycle(4:7))
all_cyclic_shuffles(cyc_len(3:5))

all_perms_shape(c(2,2,3))
all_perms_shape(c(2,2,1,1)) # size 6 (length-1 cycles vanish)
```

as.function.permutation

Coerce a permutation to a function

Description

Coerce a permutation to an executable function with domain $\{1, \dots, n\}$.

The resulting function is vectorised.

Usage

```
## S3 method for class 'permutation'
as.function(x, ...)
```

Arguments

```
x                permutation
...              further arguments (currently ignored)
```

Details

This functionality is sometimes known as *group action*. Formally, suppose we have a set X , a group G , and a function $\alpha: X \times G \rightarrow X$. Then we say α is a *group action* if $\alpha(x, e) = x$ and $\alpha(\alpha(x, g), h) = \alpha(x, gh)$. Writing $x \cdot g$ for $\alpha(x, g)$ we have $x \cdot e = x$ and $(x \cdot g) \cdot h = x \cdot (gh)$. The dot may be omitted giving us $(xg)h = x(gh)$. If the group is a permutation group on X , then it is natural to choose $\alpha(x, g) = g(x)$.

In package idiom, given permutation g [considered as an element of the symmetric group S_n], `as.function(g)` returns the function with domain $[n] = \{1, \dots, n\}$ mapping $x \in [n]$ to $\alpha(g, x) = g(x) = xg$. For example, if $g = (172)(45)$ then $\alpha(g, 7) = g(7) = 7g = 2$ and similarly $\alpha(g, 4) = 5$.

Package idiom allows one to explicitly coerce g to a function, or to use the overloaded caret:

```
(g <- as.cycle("(172)(45)"))
#> [1] (172)(45)
as.function(g)(7)
#> [1] 2
7^g
#> [1] 2
```

Note

Multiplication of permutations loses associativity when using functional notation; see examples.

Also, note that the coerced function will not take an argument greater than the size (qv) of the permutation.

Vignette `vignettes/groupaction.Rmd` discusses this issue.

Author(s)

Robin K. S. Hankin

Examples

```
x <- cyc_len(3)
y <- cyc_len(5)

xfun <- as.function(x)
yfun <- as.function(y)
```

```

stopifnot(xfun(yfun(2)) == as.function(y*x)(2)) # note transposition of x & y

# postfix notation has the very appealing result x(fg) == (xf)g
# Carets are good too, in that x^(fg) == (x^f)^g.

a <- rperm()
b <- rperm()
stopifnot(2^(a*b) == (2^a)^b)

# it's fully vectorized:
as.function(rperm(10,9))(1)
as.function(as.cycle(1:9))(sample(9))
as.function(allcyc(5:8))(1:6)

# standard recycling rules apply:
f <- as.function(allperms(3))
all(f(1:3) == f(c(1:3,1:3)))

```

c

Concatenation of permutations

Description

Concatenate words or cycles together

Usage

```

## S3 method for class 'word'
c(...)
## S3 method for class 'cycle'
c(...)
## S3 method for class 'permutation'
rep(x, ...)

```

Arguments

...	In the methods for c(), objects to be concatenated, which all must be of the same type: either all word, or all cycle
x	In the method for rep(), a permutation object

Note

The methods for c() do not attempt to detect which type (word or cycle) you want as conversion is expensive.

Function rep.permutation() behaves like base::rep() and takes the same arguments, eg times and each.

Author(s)

Robin K. S. Hankin

See Also[size](#)**Examples**

```

x <- as.cycle(1:5)
y <- cycle(list(list(1:4,8:9), list(1:2)))

# concatenate cycles:
c(x,y)

# concatenate words:
c(rperm(5,3),rperm(6,9)) # size adjusted to maximum size of args

# repeat words:
rep(x, times=3)

# c(id, rperm()) # fails: elements are of different types, one cycle, one word.
c(as.word(id), rperm()) # works: coerce id [which is a cycle] to word form
c(id, as.cycle(rperm())) # works: coerce rperm() [which is a word] to cycle form

```

capply

*Apply functions to elements of a cycle***Description**

Function `capply()` means “cycle apply” and is modelled on `lapply()`. It applies a function to every element in the cycles of its argument.

Usage

```
capply(X, fun, ...)
```

Arguments

<code>X</code>	Permutation, coerced to cycle
<code>fun</code>	Function to be applied to each element of <code>X</code>
<code>...</code>	Further arguments to <code>fun()</code>

Details

This function is just a convenience wrapper really.

Value

Returns a permutation in cycle form

Note

Function `allcyc()` is a nice application of `capply()`.

Author(s)

Robin K. S. Hankin

See Also

[allcyc](#)

Examples

```
(x <- rperm())
capply(x, range)

capply(x, function(x){x+100})

capply(x, rev)
all(is.id(capply(x, rev)*x)) # should be TRUE

capply(rcyc(20, 5, 9), sort)

capply(rcyc(20, 5, 9), sample) # still 5-cycles

capply(cyc_len(1:9), \(x)x[x>4])

capply(cyc_len(1:9), \(x)x^2)
```

caydist

Cayley distance

Description

Cayley distance and associated metrics for permutations

Usage

```
nmoved(a)
nfixed(a)
ncyc(a, discard1 = TRUE)
caydist(a, b = id)
```

Arguments

<code>a, b</code>	Permutations, coerced to cycle form
<code>discard1</code>	Boolean, with default TRUE meaning to discard length-1 cycles and return the number of cycles with length > 1

Details

These functions support `caydist()`.

Given a permutation `a`, `nfixed(a)` returns the number of elements mapped to themselves and `nmoved(a)` returns the number of elements moved [that is, elements not mapped to themselves]; `ncyc(a)` returns the number of cycles, and `caydist()` returns the minimum number of transpositions needed to convert `a` to `b`.

Value

Generally return non-negative integers

Note

Function `ncyc(a, TRUE)` returns the number of nontrivial cycles. Thus, if `a` is $(12)(567)$, then `ncyc(a, TRUE)` returns 2. If argument `discard1` is FALSE, then length-1 cycles are not discarded and `ncyc(a, FALSE)` returns 4 [because `a` is equivalent to $(12)(3)(4)(567)$, which has 4 cycles].

The Cayley distance between two permutations a and b is defined as the least number of swaps to go from a to b . Operationally:

$$d_{\text{Cayley}}(a, b) = n - c(a^{-1}b)$$

where $c(x)$ is `ncyc(a, FALSE)`. Actually it uses $d_{\text{Cayley}}(a, b) = n - c(ab^{-1})$ internally, for efficiency reasons. This does not matter, for the shape of ab is the same as the shape of ba : for any permutations x, y we have $\text{shape}(x) = \text{shape}(x^{-1})$ and $\text{shape}(x) = \text{shape}(y^{-1}xy)$. Then

$$\text{shape}(ab) = \text{shape}(b^{-1}a^{-1}) = \text{shape}(bb^{-1}a^{-1}b^{-1}) = \text{shape}(a^{-1}b^{-1}) = \text{shape}(ba).$$

Author(s)

Robin K. S. Hankin

See Also

[tidy](#)

Examples

```
x <- rperm()
x

nmoved(x)
nfixed(x)
```

```

ncyc(x, discard1 = TRUE)
ncyc(x, discard1 = FALSE)

y <- rperm()

caydist(x,y)
all(caydist(x, y) == caydist(y, x))

z <- rperm()
all(caydist(x, z) <= caydist(x, y) + caydist(y, z))

mean(caydist(rperm(100,100))) # compare 100 - log(100) - gamma ~= 94.82

```

cayley

Cayley tables for permutation groups

Description

Produces a nice Cayley table for a subgroup of the symmetric group on n elements

Usage

```
cayley(x)
```

Arguments

x A vector of permutations in cycle form

Details

Cayley's theorem states that every group G is isomorphic to a subgroup of the symmetric group acting on G . In this context it means that if we have a vector of permutations that comprise a group, then we can nicely represent its structure using a table.

If the set x is not closed under multiplication and inversion (that is, if x is not a group) then the function may misbehave. No argument checking is performed, and in particular there is no check that the elements of x are unique, or even that they include an identity.

Value

A square matrix giving the group operation

Author(s)

Robin K. S. Hankin

Examples

```
## cyclic group of order 4:
cayley(as.cycle(1:4)^(0:3))

## Klein group:
K4 <- as.cycle(c("()", "(12)(34)", "(13)(24)", "(14)(23)"))
names(K4) <- c("00", "01", "10", "11")
cayley(K4)

## S3, the symmetric group on 3 elements:
S3 <- as.cycle(c(
  "()",
  "(12)(35)(46)", "(13)(26)(45)",
  "(14)(25)(36)", "(156)(243)", "(165)(234)"
))
names(S3) <- c("()", "(ab)", "(ac)", "(bc)", "(abc)", "(acb)")
cayley(S3)

## Now an example from the onion package, the quaternion group:
## Not run:
library(onion)
a <- c(H1, -H1, Hi, -Hi, Hj, -Hj, Hk, -Hk)
X <- word(sapply(1:8, function(k){sapply(1:8, function(l){which((a*a[k])[l]==a)}))})
cayley(X) # a bit verbose; rename the vector:
names(X) <- letters[1:8]
cayley(X) # more compact

## End(Not run)
```

commutator

Group-theoretic commutator: the dot object

Description

In the **permutations** package, the dot is defined as the **Group-theoretic commutator**: $[x, y] = x^{-1}y^{-1}xy$. This is a bit of an exception to the usual definition of $xy-yx$ (along with the **freegroup** package). Package idiom is `commutator(x, y)` or `. [x, y]`.

The Jacobi identity does not make sense in the context of the **permutations** package, but the Hall-Witt identity is obeyed.

The “dot” object is defined and discussed in `inst/dot.Rmd`, which creates file `data/dot.rda`.

Usage

```
commutator(x, y)
```

Arguments

`x, y` Permutation objects, coerced to word

Author(s)

Robin K. S. Hankin

Examples

```
.[as.cycle("123456789"),as.cycle("12")]

x <- rperm(10,7)
y <- rperm(10,8)
z <- rperm(10,9)

uu <-
commutator(commutator(x,y),z^x) *
commutator(commutator(z,x),y^z) *
commutator(commutator(y,z),x^y)

stopifnot(all(is.id(uu))) # this is the Hall-Witt identity

.[x,y]

is.id(.[x,y],z^x) * .[z,x],y^z) * .[y,z],x^y)
is.id(.[x,-y],z)^y * .[y,-z],x)^z * .[z,-x],y)^x)
```

conjugate

Are two permutations conjugate?

Description

Returns TRUE if two permutations are conjugate and FALSE otherwise.

Usage

```
are_conjugate(x, y)
are_conjugate_single(a,b)
```

Arguments

`x, y, a, b` Objects of class permutation, coerced to cycle form

Details

Two permutations are conjugate if and only if they have the same shape. Function `are_conjugate()` is vectorized and user-friendly; function `are_conjugate_single()` is lower-level and operates only on length-one permutations.

The reason that `are_conjugate_single()` is a separate function and not bundled inside `are_conjugate()` is that dealing with the identity permutation is a pain in the arse.

Value

Returns a vector of Booleans

Note

The functionality detects conjugateness by comparing the shapes of two permutations; permutations are coerced to cycle form because function `shape()` does.

The group action of conjugation, that is x^y or $y^{-1} x y$, is documented at [conjugation](#).

```
all(are_conjugate(x, x^y))
```

is always TRUE.

Author(s)

Robin K. S. Hankin

See Also

[conjugation](#), [shape](#)

Examples

```
as.cycle("(123)(45)") %~% as.cycle("(89)(712)") # same shape
as.cycle("(123)(45)") %~% as.cycle("(89)(7124)") # different shape

are_conjugate(rperm(20,3), rperm(20,3))

rperm(20,3) %~% as.cycle(1:3)

z <- rperm(300,4)
stopifnot(all(are_conjugate(z, id)==is.id(z)))

z <- rperm(20)
stopifnot(all(z %~% capply(z, sample)))

data(megaminx)
stopifnot(all(are_conjugate(megaminx, megaminx^as.cycle(sample(129)))))
```

cyclist

*details of cyclists***Description**

Various functionality to deal with cyclists

Usage

```
vec2cyclist_single(p)
vec2cyclist_single_cpp(p)
remove_length_one(x)
cyclist2word_single(cyc, n)
nicify_cyclist(x, rm1=TRUE, smallest_first=TRUE)
```

Arguments

<code>p</code>	Integer vector, interpreted as a word
<code>x, cyc</code>	A cyclist
<code>n</code>	In function <code>cyclist2word_single()</code> , the size of the permutation to induce
<code>rm1, smallest_first</code>	In function <code>nicify_cyclist()</code> , Boolean, governing whether or not to remove length-1 cycles, and whether or not to place the smallest element in each cycle first (non-default values are used by <code>standard_cyclist()</code>)

Details

A *cyclist* is an object corresponding to a permutation P . It is a list with elements that are integer vectors corresponding to the cycles of P . This object is informally known as a cyclist, but there is no S3 class corresponding to it. In general use, one should not usually deal with cyclists at all: they are internal low-level objects not intended for the user.

An object of S3 class *cycle* is a (possibly named) list of cyclists. NB: there is an unavoidable notational clash here. When considering a single permutation, “cycle” means group-theoretic cycle [eg $1 \rightarrow 2 \rightarrow 3 \rightarrow 1$]; when considering R objects, “cycle” means “an R object of class *cycle* whose elements are permutations written in cycle form”.

The elements of a cyclist are the disjoint group-theoretic cycles. Note the redundancies inherent: firstly, because the cycles commute, their order is immaterial (and a list is ordered); and secondly, the cycles themselves are invariant under cyclic permutation. Heigh ho.

A cyclist may be poorly formed in a number of ways: the cycles may include repeats, or contain elements which are common to more than one cycle. Such problems are detected by `cyclist_valid()`. Also, there are less serious problems: the cycles may include length-one cycles; the cycles may start with an element that is not the smallest. These issues are dealt with by `nicify_cyclist()`.

- Function `nicify_cyclist()` takes a cyclist and puts it in a nice form but does not alter the permutation. It takes a cyclist and removes length-one cycles; then orders each cycle so that

the smallest element appears first (that is, it changes (523) to (235)). It then orders the cycles by the smallest element. Function `nicify_cyclist()` is called automatically by `cycle()`. Remember that `nicify_cyclist()` takes a cyclist!

- Function `remove_length_one()` takes a cyclist and removes length-one cycles from it.
- Function `vec2cyclist_single()` takes a vector of integers, interpreted as a word, and converts it into a cyclist. Length-one cycles are discarded.
- Function `vec2cyclist_single_cpp()` is a placeholder for a function that is not yet written.
- Function `cyclist2word_single()` takes a cyclist and returns a vector corresponding to a single word. This function is not intended for everyday use; function `cycle2word()` is much more user-friendly.
- Function `char2cyclist_single()` takes a character string like “(342)(19)” and turns it into a cyclist, in this case `list(c(3,4,2),c(1,9))`. This function returns a cyclist which is not necessarily canonicalized: it might have length-one cycles, and the cycles themselves might start with the wrong number or be incorrectly ordered. It attempts to deal with absence of commas in a sensible way, so “(18,19)(2,5)” is dealt with appropriately too. The function is insensitive to spaces. Also, one can give it an argument which does not correspond to a cycle object, eg `char2cyclist_single("(94)(32)(19)(1)")` (in which “9” is repeated). The function does not return an error; to catch this kind of problem use `char2cycle()` which performs [via `cycle()`] the validity checks [`cyclist_valid()`] and nicification [`nicify_cyclist()`].

See also the “cyclist” vignette [`type vignette("cyclist")` at the command line] which contains more details and examples.

Author(s)

Robin K. S. Hankin

See Also

[as.cycle](#), [fbins](#), [valid](#)

Examples

```
vec2cyclist_single(c(7,9,3,5,8,6,1,4,2))

char2cyclist_single("(342)(19)")

nicify_cyclist(list(c(4, 6), c(7), c(2, 5, 1), c(8, 3)))
nicify_cyclist(list(c(4, 6), c(7), c(2, 5, 1), c(8, 3)), rm1=TRUE)

nicify_cyclist(list(c(4, 6), c(7), c(2, 5, 1), c(8, 3)), smallest_first=FALSE, rm1=FALSE)
nicify_cyclist(list(c(4, 6), c(7), c(2, 5, 1), c(8, 3)), smallest_first=FALSE, rm1=TRUE )
nicify_cyclist(list(c(4, 6), c(7), c(2, 5, 1), c(8, 3)), smallest_first=TRUE , rm1=FALSE)
nicify_cyclist(list(c(4, 6), c(7), c(2, 5, 1), c(8, 3)), smallest_first=TRUE , rm1=TRUE )

cyclist2word_single(list(c(1,4,3), c(7,8)))
```

derangement*Tests for a permutation being a derangement*

Description

A *derangement* is a permutation which leaves no element fixed.

Usage

```
is.derangement(x)
```

Arguments

x Object to be tested

Value

A vector of Booleans corresponding to whether the permutations are derangements or not.

Note

The identity permutation is problematic because it potentially has zero size.

The identity element is not a derangement, although the (zero-size) identity cycle and permutation both return TRUE under the natural R idiom `all(P != seq_len(size(P)))`.

Author(s)

Robin K. S. Hankin

See Also

`id`

Examples

```
allperms(4)
is.derangement(allperms(4))

M <- matrix(c(1,2,3,4, 2,3,4,1, 3,2,4,1),byrow=TRUE,ncol=4)
M
is.derangement(word(M))

is.derangement(rperm(16,4))
```

dodecahedron	<i>The dodecahedron group</i>
--------------	-------------------------------

Description

Permutations comprising the dodecahedron group on either its faces or its edges; also the full dodecahedron group

Details

The package provides a number of objects for investigating dodecahedral groups:

Object `dodecahedron_face` is a cycle object with 60 elements corresponding to the permutations of the faces of a dodecahedron, numbered 1-12 as in the megaminx net. Object `dodecahedron_edge` is the corresponding object for permuting the edges of a dodecahedron. The edges are indexed by the lower of the two adjoining facets on the megaminx net.

Objects `full_dodecahedron_face` and `full_dodecahedron_edge` give the 120 elements of the full dodecahedron group, that is, the dodecahedron group including reflections. NB: these objects are **not** isomorphic to S_5 .

Note

These objects can be generated by running script `inst/dodecahedron.Rmd`, which includes some further discussion and technical documentation and creates file `dodecahedron.rda` which resides (under version control) in the `data/` directory.

Examples

```
permprod(dodecahedron_face)
```

Extract	<i>Extract or Replace elements of permutation vectors</i>
---------	---

Description

Methods for "[" and "[<=", i.e., extraction or subsetting of permutation vectors.

Details

Extraction and replacement for word form uses array-based indexing. Cycle form uses list-based indexing and is thus less flexible.

Value

Extraction and methods return an `onion` or `onionmat`. Replacement methods return an object of the same class as the right hand side.

Note

Notes here

Author(s)

Robin K. S. Hankin

Examples

```
(a <- rperm(9))
a[1:3]
a[5:7] <- id # word form: multiple replacements allowed.
a

x <- as.cycle(rperm(9))
x
x[5] <- x[4] * x[6] # cycle form: replacement takes only a single index.
x
```

faro

Faro shuffles

Description

A *faro shuffle*, `faro()`, is a permutation of a deck of $2n$ cards. The cards are split into two packs, $1:n$ and $(n+1):2n$, and interleaved: cards are taken alternately from top of each pack and placed face down on the table. A *faro out-shuffle* takes the first card from $1:n$ and a *faro in-shuffle* takes the first card from $(n+1):(2*n)$.

A *generalized faro shuffle*, `faro_gen()`, splits the pack into m equal parts and applies the same permutation ($p1$) to each pack, and then permutes the packs with $p2$, before interleaving. The interleaving itself is simply a matrix transpose; it is possible to omit this step by passing `interleave=FALSE`.

Usage

```
faro(n, out = TRUE)
faro_gen(n,m,p1=id,p2=id,interleave=TRUE)
```

Arguments

<code>n</code>	Number of cards in each pack
<code>m</code>	Number of packs
<code>p1, p2</code>	Permutations for cards and packs respectively, coerced to word form
<code>interleave</code>	Boolean, with default TRUE meaning to actually perform the interleaving and FALSE meaning not to
<code>out</code>	Boolean, with default TRUE meaning to return an out-shuffle and FALSE meaning to return an in-shuffle

Value

Returns a permutation in word form

Author(s)

Robin K. S. Hankin

Examples

```
faro(4)
faro(4,FALSE)

## Do a perfect riffle shuffle 52 times, return pack to original order:
permorder(faro(26))

## 15 cards, split into 5 packs of 3, cyclically permute each pack:
faro_gen(3, 5, p1=cyc_len(3), interleave=FALSE)

## 15 cards, split into 5 packs of 3, permute the packs as (13542):
print_word(faro_gen(3, 5, p2=as.cycle("(13542)"), interleave=FALSE))

sapply(seq_len(10),function(n){permorder(faro(n,FALSE))}) # OEIS A002326

plot(as.vector(as.word(faro(10))),type='b')
plot(as.vector(faro_gen(8,5,p1=cyc_len(8)^2,interleave=FALSE)))
```

fbin

The fundamental bijection

Description

Stanley defines the *fundamental bijection* on page 30.

Given $w = (14)(2)(375)(6)$, Stanley writes it in standard form (specifically: each cycle is written with its largest element first; cycles are written in increasing order of their largest element). Thus we obtain $(2)(41)(6)(753)$.

Then we obtain w^* from w by writing it in standard form and erasing the parentheses (that is, viewing the numbers as a *word*); here $w^* = 2416753$.

Given this, w may be recovered by inserting a left parenthesis preceding every left-to-right maximum, and right parentheses where appropriate.

Function `standard()` takes an object of class `cycle` and returns a list of cyclists. NB this does not return an object of class “cycle” because `cycle()` calls `nicify()`.

Function `standard_cyclist()` retains length-one cycles (compare `nicify_cyclist()`, which does not).

Usage

```

standard(cyc,n=NULL)
standard_cyclist(x,n=NULL)
fbin_single(vec)
fbin(W)
fbin_inv(cyc)

```

Arguments

vec	In function fbin_single(), an integer vector
W	In functions fbin() and fbin_inv(), an object of class permutation, coerced to word and cycle form respectively
cyc	In functions fbin_single() and standard(), permutation object coerced to cycle form
n	In function standard() and standard_cyclist(), size of the partition to assume, with default NULL meaning to use the largest element of any cycle
x	In function standard_cyclist(), a cyclist

Details

The user-friendly functions are fbin() and fbin_inv() which perform Stanley's "fundamental bijection". Function fbin() takes a word object and returns a cycle; function fbin_inv() takes a cycle and returns a word.

The other functions are low-level helper functions that are not really intended for the user (except possibly standard(), which puts a cycle object in standard order in list form).

Author(s)

Robin K. S. Hankin

References

R. P. Stanley 2011 *Enumerative Combinatorics*

See Also

[nicify_cyclist](#)

Examples

```

# Stanley's example w:
standard(cycle(list(list(c(1,4),c(3,7,5)))))

standard_cyclist(list(c(4, 6), c(7), c(2, 5, 1), c(8, 3)))

w_hat <- c(2,4,1,6,7,5,3)

```

```
fbin(w_hat)
fbin_inv(fbin(w_hat))

x <- rperm(40,9)
stopifnot(all(fbin(fbin_inv(x))==x))
stopifnot(all(fbin_inv(fbin(x))==x))
```

fixed*Fixed elements*

Description

Finds which elements of a permutation object are fixed

Usage

```
## S3 method for class 'word'
fixed(x)
## S3 method for class 'cycle'
fixed(x)
```

Arguments

x Object of class word or cycle

Value

Returns a Boolean vector corresponding to the fixed elements of a permutation.

Note

The function is vectorized; if given a vector of permutations, `fixed()` returns a Boolean vector showing which elements are fixed by *all* of the permutations.

This function has two methods: `fixed.word()` and `fixed.cycle()`, neither of which coerce.

Author(s)

Robin K. S. Hankin

See Also

[tidy](#)

Examples

```
fixed(as.cycle(1:3) + as.cycle(8:9)) # elements 4,5,6,7 are fixed
fixed(id)
```

```
data(megaminx)
fixed(megaminx)
```

get1

Retrieve particular cycles or components of cycles

Description

Given an object of class `cycle`, function `get1()` returns a representative of each of the disjoint cycles in the object's elements. Function `get_cyc()` returns the cycle containing a specific element.

Usage

```
get1(x, drop=TRUE)
get_cyc(x, elt)
```

Arguments

<code>x</code>	permutation object (coerced to <code>cycle</code> class)
<code>drop</code>	In function <code>get1()</code> , argument <code>drop</code> controls the behaviour if <code>x</code> is length 1. If <code>drop</code> is <code>TRUE</code> , then a vector of representative elements is returned; if <code>FALSE</code> , then a list with one vector element is returned
<code>elt</code>	Length-one vector interpreted as a permutation object

Author(s)

Robin K. S. Hankin

Examples

```
data(megaminx)
get1(megaminx)
get1(megaminx[1])
get1(megaminx[1], drop=TRUE)

get_cyc(megaminx, 11)
```

id	<i>The identity permutation</i>
----	---------------------------------

Description

The *identity permutation* leaves every element fixed

Usage

```
is.id(x)
is.id_single_cycle(x)
## S3 method for class 'cycle'
is.id(x)
## S3 method for class 'list'
is.id(x)
## S3 method for class 'word'
is.id(x)
```

Arguments

x Object to be tested

Details

The identity permutation is problematic because it potentially has zero size.

Value

The variable `id` is a *cycle* as this is more convenient than a zero-by-one matrix.

Function `is.id()` returns a Boolean with TRUE if the corresponding element is the identity, and FALSE otherwise. It dispatches to either `is.id.cycle()` or `is.id.word()` as appropriate.

Function `is.id.list()` tests a cyclist for identityness.

Note

The identity permutations documented here are distinct from the null permutations documented at `nullperm.Rd`.

Author(s)

Robin K. S. Hankin

See Also

[is.derangement](#), [nullperm](#)

Examples

```
is.id(id)

as.word(id) # weird

x <- rperm(10,4)
x[3] <- id
is.id(x*inverse(x))
```

inverse

*Inverse of a permutation***Description**

Calculates the inverse of a permutation in either word or cycle form

Usage

```
inverse(x)
## S3 method for class 'word'
inverse(x)
## S3 method for class 'cycle'
inverse(x)
inverse_word_single(W)
inverse_cyclist_single(cyc)
```

Arguments

x	Object of class permutation to be inverted
W	In function <code>inverse_word_single()</code> , a vector corresponding to a permutation in word form (that is, one row of a word object)
cyc	In function <code>inverse_cyclist_single()</code> , a cyclist to be inverted

Details

The package provides methods to invert objects of class `word` (the R idiom is `W[W] <- seq_along(W)`) and also objects of class `cycle` (the idiom is `lapply(cyc, function(o){c(o[1], rev(o[-1]))})`).

The user should use `inverse()` directly, which dispatches to either `inverse.word()` or `inverse.cycle()` as appropriate.

Sometimes, using idiom such as `x^-1` or `id/x` gives neater code, although these may require coercion between word form and cycle form.

Value

Function `inverse()` returns an object of the same class as its argument.

Note

Inversion of words is ultimately performed by function `inverse_word_single()`:

```
inverse_word_single <- function(W){
  W[W] <- seq_along(W)
  return(W)
}
```

which can be replaced by `order()` although this is considerably less efficient, especially for small sizes of permutations. One of my longer-term plans is to implement this in C, although it is not clear that this will be any faster.

Author(s)

Robin K. S. Hankin

See Also

[cycle_power](#)

Examples

```
x <- rperm(10,6)
x
inverse(x)

all(is.id(x*inverse(x))) # should be TRUE

inverse(as.cycle(matrix(1:8,9,8)))
```

keepcyc

Keep or discard some cycles of a permutation

Description

Given a permutation and a function that returns a Boolean specifying whether a cycle is acceptable, return a permutation retaining only the acceptable cycles.

Usage

```
keepcyc(a, func, ...)
```

Arguments

<code>a</code>	Permutation, coerced to cycle
<code>func</code>	Function to be applied to each element of a
<code>...</code>	Further arguments to <code>fun()</code>

Value

Returns a permutation in cycle form

Note

Function keepcyc() is idempotent.

Author(s)

Robin K. S. Hankin

See Also

[allcyc](#)

Examples

```
keepcyc(rgivenshape(10,2:8),function(x){length(x) == 2}) # retains just transpositions
keepcyc(megaminx,function(x){any(x == 100)})             # retains just cycles modifying facet #100
keepcyc(rperm(100),function(x){max(x)-min(x) < 3})        # retains just cycles with range<3

f <- function(x, p){all(x < p) || all(x > p)}             # keep only cycles with all entries either
keepcyc(rgivenshape(9,rep(2:3,9)), f, p=20)              # all < 20 or all >20
```

length	<i>Various vector-like utilities for permutation objects.</i>
--------	---

Description

Various vector-like utilities for permutation objects such as length, names(), etc

Usage

```
## S3 method for class 'word'
length(x)
## S3 replacement method for class 'permutation'
length(x) <- value
## S3 method for class 'word'
names(x)
## S3 replacement method for class 'word'
names(x) <- value
```

Arguments

- x permutation object
- value In function names<- .word(), the new names

Details

These functions have methods only for word objects; cycle objects use the methods for lists. It is easy to confuse the *length* of a permutation with its size.

It is not currently possible to set the length of a permutation; this is more trouble than it is worth.

Author(s)

Robin K. S. Hankin

See Also

[size](#)

Examples

```
x <- rperm(5,9)
x
names(x) <- letters[1:5]
x

megaminx
length(megaminx) # the megaminx group has 12 generators, one per face.
size(megaminx)   # the megaminx group is a subgroup of S_129.

names(megaminx) <- NULL # prints more nicely.
megaminx
```

megaminx	<i>megaminx</i>
----------	-----------------

Description

A set of generators for the megaminx group

Details

Each element of megaminx corresponds to a clockwise turn of 72 degrees. See the vignette for more details.

megaminx[1]	W	White
megaminx[2]	Pu	Purple
megaminx[3]	DY	Dark Yellow
megaminx[4]	DB	Dark Blue
megaminx[5]	R	Red
megaminx[6]	DG	Dark Green
megaminx[7]	LG	Light Green
megaminx[8]	O	Orange
megaminx[9]	LB	Light Blue

```
megaminx[10] LY Light Yellow
megaminx[11] Pi Pink
megaminx[12] Gy Gray
```

Vector `megaminx_colours` shows what colour each facet has at START. Object `superflip` is a `megaminx` operation that flips each of the 30 edges. Some discussion is given in the vignette, and a more recent (and shorter) `superflip` is given in `inst/superflip.Rmd`.

These objects can be generated by running script `inst/megaminx.R`, which includes some further discussion and technical documentation and creates file `megaminx.rda` which resides in the `data/` directory.

Author(s)

Robin K. S. Hankin

See Also

[megaminx_plotter](#)

Examples

```
data(megaminx)
megaminx
megaminx^5 # should be the identity
inverse(megaminx) # turn each face anticlockwise

megaminx_colours[permprod(megaminx)] # risky but elegant...

W # turn the White face one click clockwise (colour names as per the
  # table above)

megaminx_colours[as.word(W,129)] # it is safer to ensure a size-129 word;
megaminx_colours[as.word(W)]     # but the shorter version will work

# Now some superflip stuff:

X <- W * Pu^(-1) * W * Pu^2 * DY^(-2)
Y <- LG^(-1) * DB^(-1) * LB * DG
Z <- Gy^(-2) * LB * LG^(-1) * Pi^(-1) * LY^(-1)

sjc3 <- (X^6)^Y * Z^9 # superflip (Jeremy Clark)

p1 <- (DG^2 * W^4 * DB^3 * W^3 * DB^2 * W^2 * DB^2 * R * W * R)^3
m1 <- p1^(Pi^3)

p2 <- (O^2 * LG^4 * DB^3 * LG^3 * DB^2 * LG^2 * DB^2 * DY * LG * DY)^3
```

```

m2 <- p2^(DB^2)

p3 <- (LB^2 * LY^4 * Gy * Pi^3 * LY * Gy^4)^3
m3 <- p3^LB

# m1,m2 are 32 moves, p3 is 20, total = 84

stopifnot(m1+m2+m3==sjc3)

```

megaminx_plotter	<i>Plotting routine for megaminx sequences</i>
------------------	--

Description

Plots a coloured diagram of a dodecahedron net representing a megaminx

Usage

```
megaminx_plotter(megperm=id,offset=c(0,0),M=diag(2),setup=TRUE,...)
```

Arguments

megperm	Permutation to be plotted
offset, M	Offset and transformation matrix, see details
setup	Boolean, with default TRUE meaning to set up the plot with a plot() statement, and FALSE meaning to plot the points on a pre-existing canvas
...	Further arguments passed to polygon()

Details

Function megaminx_plotter() plots a coloured diagram of a dodecahedron net representing a megaminx. The argument may be specified as a sequence of turns that are applied to the megaminx from *START*.

The function uses rather complicated internal variables pentagons, triangles, and quads whose meaning and genesis is discussed in heavily-documented file inst/guide.R.

The diagram is centered so that the common vertex of triangles 28 and 82 is at (0,0).

Author(s)

Robin K. S. Hankin

Examples

```
data("megaminx")

megaminx_plotter() # START
megaminx_plotter(W) # after turning the White face one click
megaminx_plotter(superflip)

size <- 0.95
o <- 290

## Not run:
pdf(file="fig1.pdf")
megaminx_plotter(M=size*diag(2),offset=c(-o,0),setup=TRUE)
megaminx_plotter(W,M=size*diag(2),offset=c(+o,0),setup=FALSE)
dev.off()

pdf(file="fig2.pdf")
p <- permprod(sample(megaminx,100,replace=TRUE))
megaminx_plotter(p,M=size*diag(2),offset=c(-o,0),setup=TRUE)
megaminx_plotter(superflip,M=size*diag(2),offset=c(+o,0),setup=FALSE)
dev.off()

## End(Not run)
```

megaminx_superflip	<i>The Megaminx Superflip</i>
--------------------	-------------------------------

Description

On the megaminx, a *flip* is a sequence of moves whose only effect is to flip one or more edge pieces in place (the number of edges flipped must be even). The *superflip* is the operation that flips each of the 30 edges of the puzzle.

Object `edge_facets` is a 30 row, two-column matrix with each row representing an edge facet.

Usage

```
is.flip_pair(pair)
is.flip(p)
is.flip(p)
is.superflip(p)
```

Arguments

<code>pair</code>	Integer vector of length two corresponding to a pair of facets
<code>p</code>	Vector iof permutations, coerced to cycle form

Value

Returns a boolean vector

Author(s)

Robin K. S. Hankin

See Also[megaminx](#)**Examples**

```

stopifnot(all(
  is.flip_pair(c(10,46)),
  is.flip_pair(c(98,124)),
  !is.flip_pair(c(10,98)),
  !is.flip_pair(c(11,98))
))

is.flip(c(
  as.cycle("(10,46)(44,50)(56,62)"),
  as.cycle("74,121"),
  as.cycle("74,120")
))

```

nullperm

*Null permutations***Description**

Null permutations are the equivalent of NULL

Usage

```

nullcycle
nullword

```

Format

Object nullcycle is an empty list coerced to class cycle, specifically `cycle(list())`

Object nullword is a zero-row matrix, coerced to word, specifically `word(matrix(integer(0),0,0))`

Details

These objects are here to deal with the case where a length-zero permutation is extracted. The behaviour of these null objects is not entirely consistent.

Note

The objects documented here are distinct from the identity permutation, `id`, documented separately.

See Also[id](#)**Examples**

```

rperm(10,4)[0] # null word

as.cycle(1:5)[0] # null cycle

data(megaminx)
c(NULL,megaminx) # probably not what the user intended...
c(nullcycle,megaminx) # more useful.
c(id,megaminx) # also useful.

```

Ops.permutation

*Arithmetic Ops Group Methods for permutations***Description**

Allows arithmetic operators to be used for manipulation of permutation objects such as addition, multiplication, division, integer powers, etc.

Usage

```

## S3 method for class 'permutation'
Ops(e1, e2)
cycle_power(x,pow)
cycle_power_single(x,pow)
cycle_sum(e1,e2)
cycle_sum_single(c1,c2)
word_equal(e1,e2)
word_prod(e1,e2)
word_prod_single(e1,e2)
permprod(x)
vps(vec,pow)
ccps(n,pow)
helper(e1,e2)
cycle_plus_integer_elementwise(x,y)
conjugation(e1,e2)
sum1(x)

```

Arguments

x, e1, e2	Objects of class “permutation”
c1, c2	Objects of class cycle
pow	Integer vector of powers

vec	In function vps(), a vector of integers corresponding to a cycle
n	In function ccps(), the integer power to which cycle(seq_len(n)) is to be raised; may be positive or negative
y	In experimental function cycle_plus_integer_elementwise(), an integer

Details

Function Ops.permutation() dispatches binary arithmetic operators (“+”, “*”, “/”, “^”, and “==”) to the appropriate specialist function.

Multiplication, as in $a*b$, is equivalent to `word_prod(a,b)`; it coerces its arguments to word form (because $a*b = b[a]$).

Raising permutations to integer powers, as in a^n , is `cycle_power(a,n)`; it coerces a to cycle form and returns a cycle (even if $n = 1$). Negative and zero values of n operate as expected. Function `cycle_power()` is vectorized; it calls `cycle_power_single()`, which is not. This calls `vps()` (“Vector Power Single”), which checks for simple cases such as $\text{pow}=0$ or the identity permutation; and function `vps()` calls function `ccps()` which performs the actual number-theoretic manipulation to raise a cycle to a power.

Group-theoretic conjugation is implemented: in package idiom, a^b gives $\text{inverse}(b)*a*b$. The notation is motivated by the identities $x^{(yz)} = (x^y)^z$ and $(xy)^z = x^z y^z$ [or $x^{yz} = (x^y)^z$ and $(xy)^z = x^z y^z$]. Internally, `conjugation()` is called. The concept of conjugate *permutations* [that is, permutations with the same `shape()`] is discussed at [conjugate](#).

The caret “^” also indicates group action [there is some discussion at `as.function.permutation.Rd`]. Given an integer n and a permutation g , idiom n^g returns the group action of g acting on n . The notation is motivated by the identity $n^{(ab)} = (n^a)^b$.

The *sum* of two permutations a and b , as in $a+b$, is defined if the cycle representations of the addends are disjoint. The sum is defined as the permutation given by juxtaposing the cycles of a with those of b . Note that this operation is commutative. If a and b do not have disjoint cycle representations, an error is returned. If $a+b$ is defined we have

$$a^n + b^n == (a+b)^n == a^n * b^n == (a*b)^n$$

for any $n \in \mathbb{Z}$. Using “+” in this way is useful if you want to guarantee that two permutations commute (NB: permutation a commutes with a^i for i any integer, and in particular a commutes with itself. But $a+a$ returns an error: the operation checks for disjointness, not commutativity). Methods for `sum()` are defined so that `sum(x,y,...)` returns the sum of its arguments. Function `sum1()` is a lower-level helper function that takes a single vector argument, coerces to cycle form, and returns the sum of its elements (if defined).

Permutation “division”, as in a/b , is $a*\text{inverse}(b)$. Note that $a/b*c$ is evaluated left to right so is equivalent to $a*\text{inverse}(b)*c$. See note.

Function `helper()` sorts out recycling for binary functions, the behaviour of which is inherited from `cbind()`, which also handles the names of the returned permutation.

Experimental functionality is provided to define the “sum” of a permutation and an integer. If x is a permutation in cycle form with $x = (abc)$, say, and n an integer, then $x + n = (a+n, b+n, c+n)$: each element of each cycle of x is increased by n . Note that this has associativity consequences. For example, $x+(x+n)$ might be defined but not $(x+x)+n$, as the two “+” operators have different interpretations. Distributivity is similarly broken (see the examples). Package idiom includes $x-n$ [defined as $x + (-n)$] and $n+x$ but not $n-x$ as inverses are defined multiplicatively. The implementation is vectorized.

Value

None of these functions are really intended for the end user: use the ops as shown in the examples section.

Note

The class of the returned object is the appropriate one.

Unary operators to invert a permutation are problematic in the package. I do not like using “id/x” to represent a permutation inverse: the idiom introduces an utterly redundant object (“id”), and forces the use of a binary operator where a unary operator is needed. Similar comments apply to “x⁻¹”, which again introduces a redundant object (-1) and uses a binary operator.

Currently, “-x” returns the multiplicative inverse of x, but this is not entirely satisfactory either, as it uses additive notation: the rest of the package uses multiplicative notation. Thus `x*-x == id`, which looks a little odd but OTOH noone has a problem with `x^-1` for inverses.

I would like to follow APL and use “/x”, but this does not seem to be possible in R. The natural unary operator would be the exclamation mark “!x”. However, redefining the exclamation mark to give permutation inverses, while possible, is not desirable because its precedence is too low. One would like `!x*y` to return `inverse(x)*y` but instead standard precedence rules means that it returns `inverse(x*y)`. Earlier versions of the package interpreted `!x` as `inverse(x)`, but it was a disaster: to implement the commutator $[x, y] = x^{-1}y^{-1}xy$, for example, one would like to use `!x*!y*x*y`, but this is interpreted as `!(x*(!y*(x*y)))`; one has to use `(!x)*(!y)*x*y`. I found myself having to use heaps of brackets everywhere. This caused such severe cognitive dissonance that I removed exclamation mark for inverses from the package. I might reinstate it in the future. There does not appear to be a way to define a new unary operator due to the construction of the parser.

Author(s)

Robin K. S. Hankin

Examples

```
x <- rperm(10,9) # word form
y <- rperm(10,9) # word form

x*y # products are given in word form but the print method coerces to cycle form
print_word(x*y)

x^5 # powers are given in cycle form

x^as.cycle(1:5) # conjugation (not integer power!); coerced to word.

x*inverse(x) == id # all TRUE

# the 'sum' of two permutations is defined if their cycles are disjoint:
as.cycle(1:4) + as.cycle(7:9)
sum(cyc_len(2) + 2*(0:10))
```

```
# but beware of associativity issues:
cyc_len(4) + (5 + cyc_len(3)) == (cyc_len(4) + 5) + cyc_len(3) # FALSE

data(megaminx)
megaminx[1] + megaminx[7:12] # [1] commutes with each of [7],[8],...,[12]

rperm() + 100

z <- cyc_len(4)
z
z+100
z + 0:5
(z + 0:5)*z

w <- cyc_len(7) + 1
(w+1)*(w-1)
```

orbit

Orbits of integers

Description

Finds the orbit of a given integer

Usage

```
orbit_single(c1,n1)
orbit(cyc,n)
```

Arguments

c1, n1	In (low-level) function <code>orbit_single()</code> , a cyclist and an integer vector respectively
cyc, n	In (vectorized) function <code>orbit()</code> , cyc is coerced to a cycle, and n is an integer vector

Value

Given a cyclist c1 and integer n1, function `orbit_single()` returns the single cycle containing integer n1. This is a low-level function, not intended for the end-user.

Function `orbit()` is the vectorized equivalent of `orbit_single()`. Vectorization is inherited from `cbind()`.

The orbit of a fixed point p is $\{p\}$; the code uses an ugly hack to ensure that this is the case.

Note

Orbits are useful in a more general group theoretic context. Consider a finite group G acting on a set X , that is

$$\alpha: G \times X \longrightarrow X.$$

Writing $\alpha(g, x) = gx$, we define α to be a *group action* if $ex = x$ and $g(hx) = (gh)x$ where $g, h \in G$ and e is the group identity. For any $x \in X$ we define the *orbit* Gx of x to be the set of elements of X to which x can be moved by an element of G . Symbolically:

$$Gx = \{gx: g \in G\}$$

Now, we abuse notation slightly. In the context of permutation groups, we consider a fixed permutation σ . We consider the group $G = \langle \sigma \rangle$, that is, the group *generated by* σ ; the group action is that of G on set $X = \{1, 2, \dots, n\}$ with the obvious definition $\sigma x = \sigma(x)$ for $\sigma \in G$ and $x \in X$. This clearly is a group action as $\text{id}(x) = x$ and $\sigma(\mu x) = (\sigma\mu)x$.

$$Gx = \bigcup_{i \in \mathbb{Z}} \sigma^i(x)$$

Expressing σ in cycle form makes it easy to see that the orbit of any element x of X is just the other members in the cycle containing x . For example, consider $\sigma = (26)(348)$ and $x = 4$. Then

$$G = \langle (26)(348) \rangle = \bigcup_{i \in \mathbb{Z}} [(26)(348)]^i$$

Because we are only interested in the effects on $x = 4$, we only need to consider the cycle (348) : this is the only cycle that affects $x = 4$, and the (26) cycle may be ignored as it does not affect element 4. So

$$G4 = \bigcup_{i \in \mathbb{Z}} (348)^i(4) = \{3, 4, 8\}$$

[observe the slight notational abuse above: “ (348) ” means “the function $f(\cdot)$ with $f(3) = 4$, $f(4) = 8$, and $f(8) = 3$ ”].

Author(s)

Robin K. S. Hankin

See Also

[fixed](#)

Examples

```
orbit(as.cycle("(123)"),1:5)
orbit(as.cycle(c("(12)","(123)(45)","(2345)")),1)
orbit(as.cycle(c("(12)","(123)(45)","(2345)")),1:3)

data(megaminx)
orbit(megaminx,13)
```

outer

*Outer product of vectors of permutations***Description**

The outer product of two vectors of permutations is the pairwise product of each element of the first with each element of the second.

Details

It works in much the same way as `base::outer()`. The third argument, `FUN`, as in `outer(X,Y,FUN="*")` is regular group-theoretic multiplication but can be replaced with `+` if you are sure that the cycles of `X` and `Y` are distinct, see the examples. Each element of the returned matrix is a one-element list.

The print method may have room for improvement.

Author(s)

Robin K. S. Hankin

Examples

```
(M <- outer(rperm(),rperm()))
outer(cyc_len(4) + 0:3, cyc_len(4) + 100:101,"+") # OK because the cycles are distinct

do.call("c",M) # c(M) gives a list and unlist(a) gives a numeric vector
```

permorder

*The order of a permutation***Description**

Returns the order of a permutation P : the smallest strictly positive integer n for which P^n is the identity.

Usage

```
permorder(x, singly = TRUE)
```

Arguments

<code>x</code>	Permutation, coerced to cycle form
<code>singly</code>	Boolean, with default TRUE meaning to return the order of each element of the vector, and FALSE meaning to return the order of the vector itself (that is, the smallest strictly positive integer for which $\text{all}(x^n == \text{id})$).

Details

Coerces its argument to cycle form.

The order of the identity permutation is 1.

Note

Uses `mLCM()` from the `numbers` package.

Author(s)

Robin K. S. Hankin

See Also

[sgn](#)

Examples

```
x <- rperm(5,20)
permorder(x)
permorder(x,FALSE)

stopifnot(all(is.id(x^permorder(x))))
stopifnot(is.id(x^permorder(x,FALSE)))
```

permutation

Functions to create and coerce word objects and cycle objects

Description

Functions to create permutation objects. `permutation` is a virtual class.

Usage

```
word(M)
permutation(x)
is.permutation(x)
cycle(x)
is.word(x)
is.cycle(x)
```



```

as.word(x, n=NULL)
as.cycle(x)
cycle2word(x, n=NULL)
char2cycle(char)
cyc_len(n)
## S3 method for class 'word'
as.matrix(x, ...)

```

Arguments

M	In function word(), a matrix with rows corresponding to permutations in word form
x	See details
n	In functions as.word() and cycle2word(), the size of the word to return; in function cyc_len(), the length of the cycles to return
char	In function char2cycle() a character vector which is coerced to a cycle object
...	Further arguments passed to as.matrix()

Details

Functions word() and cycle() are rather formal functions which make no attempt to coerce their arguments into sensible forms. The user should use permutation(), which detects the form of the input and dispatches to as.word() or as.cycle(), which are much more user-friendly and try quite hard to Do The Right Thing (tm).

Functions word() and cycle() are the only functions in the package which assign class word or cycle to an object.

Function word() takes a matrix and returns a word object; silently coerces to integer.

Function cycle() takes a “cyclist”, that is, a list whose elements are lists whose elements are vectors (which are disjoint cycles); and returns an object of class “cycle”. It nicifies its input with nicify_cyclist() before returning it.

A *word* is a matrix whose rows correspond to permutations in word format.

A *cycle* is a list whose elements correspond to permutations in cycle form. A cycle object comprises elements which are informally dubbed ‘cyclists’. A cyclist is a list of integer vectors corresponding to the cycles of the permutation.

Function cycle2word() converts cycle objects to word objects.

Function cyc_len() creates cycles of the form $(1, 2, \dots, n)$. It is vectorised.

It is a very common error (at least, it is for me) to use cycle() when you meant as.cycle().

The print method is sensitive to the value of option ‘print_word_as_cycle’, documented at print.Rd.

Function as.matrix.word() coerces a vector of permutations in word form to a matrix, each row of which is a word. To get a permutation matrix (that is, a square matrix of ones and zeros with exactly one entry of 1 in each row and each column), use perm_matrix().

In function as.word(), argument n cannot act to reduce the size of the word, only increase it. If you want to reduce the size, use trim() or tidy(). This function does not call word() except directly (e.g. it does not call size<- .word(), as this would give a recursion).

Value

Returns a cycle object or a word object

Author(s)

Robin K. S. Hankin

See Also

[cyclist](#)

Examples

```
word(matrix(1:8, 7, 8)) # default print method coerces to cycle form

cycle(list(list(c(1,8,2), c(3,6)), list(1:2, 4:8)))

char2cycle(c("(1,4)(6,7)", "(3,4,2)(8,19)", "(56)", "(12345)(78)", "(78)"))

jj <- c(4,2,3,1)

as.word(jj)
as.cycle(jj)

as.cycle(1:2)*as.cycle(1:8) == as.cycle(1:8)*as.cycle(1:2) # FALSE!

x <- rperm(10, 7)
y <- rperm(10, 7)
as.cycle(commutator(x, y))

cyc_len(7) * cyc_len(8)
cyc_len(1:9)
```

perm_matrix

Permutation matrices

Description

Given a permutation, coerce to word form and return the corresponding permutation matrix

Usage

```
perm_matrix(p,s=size(p))
is.perm_matrix(M)
pm_to_perm(M)
```

Arguments

p	Permutation, coerced to word form, of length 1
s	Size of permutation matrix or permutation
M	Permutation matrix

Details

Given a permutation p of size s, function perm_matrix() returns a square matrix with s rows and s columns. Entries are either 0 or 1; each row and each column has exactly one entry of 1 and the rest zero.

Row and column names of the permutation matrix are integers; this makes the printed version more compact.

Function pm_to_perm() takes a permutation matrix and returns the equivalent permutation in word form.

Note

Given a word p with size s, the idiom for perm_matrix() boils down to

```
M <- diag(s)
M[p,]
```

This is used explicitly in the representations vignette. There is another way:

```
M <- diag(s)
M[cbind(seq_len(s),p)] <- 1
M
```

which might be useful sometime.

See also the representation and order_of_ops vignettes, which discuss permutation matrices.

Author(s)

Robin K. S. Hankin

See Also

[permutation](#)

Examples

```
perm_matrix(rperm(1,9))

p1 <- rperm(1,40)
M1 <- perm_matrix(p1)
p2 <- rperm(1,40)
M2 <- perm_matrix(p2)

stopifnot(is.perm_matrix(M1))

stopifnot(all(solve(M1) == perm_matrix(inverse(p1))))
stopifnot(all(M1 %*% M2 == perm_matrix(p1*p2)))

stopifnot(p1 == pm_to_perm(perm_matrix(p1)))

data("megaminx")
image(perm_matrix(permprod(megaminx)),asp=1,axes=FALSE)
```

print

Print methods for permutation objects

Description

Print methods for permutation objects with matrix-like printing for words and bracket notation for cycle objects.

Usage

```
## S3 method for class 'cycle'
print(x, give_string=FALSE, ...)
## S3 method for class 'word'
print(x, h = getOption("print_word_as_cycle"), ...)
as.character_cyclist(y, comma=TRUE)
```

Arguments

x	Object of class permutation with word objects dispatched to <code>print.word()</code> and cycle objects dispatched to <code>print.cycle()</code>
h	Boolean, with default TRUE meaning to coerce words to cycle form before printing. See details
...	Further arguments (currently ignored)
y, comma	In <code>as.character_cyclist()</code> , argument y is a list of cycles (a <code>cyclist</code>); and comma is Boolean, specifying whether to include a comma in the output
give_string	In function

Details

Printing of word objects is controlled by `options("print_word_as_cycle")`. The default behaviour is to print any permutation object, whether of class `cycle` or class `word`, in cycle form. Cycle objects are printed as is; word objects are coerced to cycle form and printed, with a notice that the object itself was coerced from word.

If `options("print_word_as_cycle")` is `FALSE`, then objects of class `word` are printed as a matrix with rows being the permutations and fixed points indicated with a dot.

Function `as.character_cyclist()` is an internal function used by `print.cycle()`, and is not really designed for the end-user. It takes a cyclist and returns a character string.

Function `print_word()` and `print_cycle()` are provided for power users. These functions print their argument directly as word or cycle form; they coerce to the appropriate form. Use `print_word()` if you have a permutation in word form and want to inspect it as a word form but (for some reason) do not want to set `options("print_word_as_cycle")`. See `size.Rd` for a use-case.

To see permutations in one-line form, use `print_word(x, use_dots=FALSE)`.

Coercing a cycle to a character vector can be done with `as.character()`, which returns a character vector that is suitable for `as.cycle()`, so if `a` is a cycle `all(as.cycle(as.character(a)) == a)` will return `TRUE`. If you want to use the options of the print method, use `print.cycle(..., give_string = TRUE)`, which respects the print options discussed below. Neither of these give useful output if their argument is in word form.

The print method includes experimental functionality to display permutations of sets other than the default of integers $1, 2, \dots, n$. Both cycle and word print methods are sensitive to option `perm_set`: the default value of `NULL` means to use integers. The symbols may be the elements of any character vector; use idiom such as

```
options("perm_set" = letters)
```

to override the default. But beware! If the permutation includes numbers greater than the length of `perm_set`, then `NA` will be printed. It is possible to use vectors with elements of more than one character (e.g. `state.abb`). Vignette `groupaction` presents a discussion of option `perm_set` in the context of coercing a permutation to a function.

In the printing of cycle objects, commas are controlled with option `"comma"`. The default `NULL` means including commas in the representation if the size of the permutation exceeds 9. This works well for integers but is less helpful if using letters or state abbreviations. Force the use of commas by setting the option to `TRUE` or `FALSE`, e.g.

```
options("comma" = TRUE)
```

The print method does not change the internal representation of word or cycle objects, it only affects how they are printed.

The print method for cycle objects is sensitive to experimental option `print_in_length_order` (via function `as.character_cyclist()`). Default behaviour is to order the cycles in order of their smallest permuted element. But sometimes one wants the cycles in order of length, with the shortest first. To do this, use:

```
options("print_in_length_order" = TRUE)
```

There is a package vignette (type `vignette("print")` at the command line) which gives more details and long-form documentation.

Value

Returns its argument invisibly, after printing it (except for `print.cycle(x, give_string = TRUE)`, in which case a character vector is returned).

Author(s)

Robin K. S. Hankin

See Also

[nicify_cyclist](#)

Examples

```
# generate a permutation in *word* form:
x <- rperm(4,9)

# default behaviour is to print in cycle form irregardless:
x

# change default using options():
options(print_word_as_cycle = FALSE)

# objects in word form now printed using matrix notation:
x

# printing of cycle form objects not altered:
as.cycle(x)

# restore default:
options(print_word_as_cycle = TRUE)

as.character_cyclist(list(1:4, 10:11, 20:33)) # x a cyclist;
as.character_cyclist(list(c(1,5,4), c(2,2))) # does not check for consistency
as.character_cyclist(list(c(1,5,4), c(2,9)),comma=FALSE)

options("perm_set" = letters)
rperm(r = 9)
options("perm_set" = NULL) # restore default
```

rperm

Random permutations

Description

Function `rperm()` creates a word object of random permutations. Function `rcyc()` creates random permutations comprising a single (group-theoretic) cycle of a specified length. Functions `r1cyc()` and `rgs1()` are low-level helper functions.

Usage

```

rperm(n=10, r=7, moved=NA)
rpermm(n=20, r=20, moved=NA)
rcyc(n, len, r=len)
r1cyc(len, vec)
rgs1(s)
rgivenshape(n, s, size=sum(s))

```

Arguments

<code>n</code>	Number of permutations to create
<code>r</code>	Size of permutations
<code>len</code>	Length of cycles in <code>rcyc()</code> and <code>r1cyc()</code>
<code>moved</code>	In function <code>rperm()</code> and <code>rpermm()</code> , integer specifying how many elements can move (that is, how many elements do not map to themselves), with default NA meaning to choose a permutation at random. This is useful if you want a permutation that has a compact cycle representation
<code>vec</code>	Vector of integers to generate a cycle from
<code>s, size</code>	Shape and size of permutations to create

Details

Function `rperm()` returns a simple vector of random permutations, and `rperm()` gives a more complicated object.

Function `rgivenshape()` returns a random permutation with a given shape. Argument `s`, specifying the shape, can include 1s (ones). Although length-one cycles are dropped from the resulting permutation, it is sometimes useful to include them to increase the size of the result, see examples. If primary argument `n` is a vector of length greater than 1, it is interpreted as the shape of the permutation, and a single random permutation is returned. Setting print option `print_in_length_order` to TRUE emphasises that every element of the output of `rgivenshape()` has the same shape.

Value

Returns a permutation object of class `cycle`, or class `word` (`rperm()`)

Note

In function `rperm()`, argument `moved` specifies a *maximum* number of elements that do not map to themselves; the actual number of non-fixed elements might be lower (as some elements might map to themselves). To control the number of non-fixed elements precisely, use function `rcyc()` or `rgivenshape()`.

Author(s)

Robin K. S. Hankin

See Also

[size](#), [print.permutation](#)

Examples

```
rperm()
as.cycle(rperm(30, 9))
rperm(10, 9, 2)

rcyc(20, 5)
rcyc(20, 5, 9)

rgivenshape(10, c(2,3))      # shape (3,2), size 5
rgivenshape(10, c(2,3,1,1)) # shape (3,2), but size 7

rgivenshape(1:9)

allpermslike(rgivenshape(c(1, 1, 3, 4)))
```

sgn

Sign of a permutation

Description

Returns the sign of a permutation

Usage

```
sgn(x)
is.even(x)
is.odd(x)
```

Arguments

x permutation object

Details

The sign of a permutation is ± 1 depending on whether it is even or odd. A permutation is *even* if it can be written as a product of an even number of transpositions, and *odd* if it can be written as an odd number of transpositions. The map $\text{sgn}: S_n \longrightarrow \{+1, -1\}$ is a homomorphism; see examples.

Note

Internally, function `sgn()` coerces to cycle form.

The sign of the null permutation is `NULL`.

Author(s)

Robin K. S. Hankin

See Also[shape](#)**Examples**

```
sgn(id) # always problematic

sgn(rperm(10,5))

x <- rperm(40,6)
y <- rperm(40,6)

stopifnot(all(sgn(x*y) == sgn(x)*sgn(y))) # sgn() is a homomorphism

z <- as.cycle(rperm(20,9,5))
z[is.even(z)]
z[is.odd(z)]
```

shape	<i>Shape of a permutation</i>
-------	-------------------------------

Description

Returns the shape (or cycle type) of a permutation, coerced to cycle form.

Usage

```
shape(x, drop = TRUE, id1 = TRUE, decreasing = FALSE)
shape_cyclist(cyc, id1 = TRUE)
padshape(x, drop = TRUE, n = NULL)
shapepart(x)
shapepart_cyclist(cyc, n = NULL)
```

Arguments

x	Object of class cycle (if not, coerced)
cyc	A cyclist
n	Integer governing the size of the partition assumed, with default NULL meaning to use the largest element
drop	Boolean, with default TRUE meaning to unlist if possible

id1	Boolean, with default TRUE in function shape_cyclist() meaning that the shape of the identity is “1” and FALSE meaning that the shape is NULL
decreasing	In function shape(), Boolean with default FALSE meaning to return the cycle lengths in the order given by nicify_cyclist() and TRUE meaning to sort in decreasing order

Value

Function shape() returns a list with elements representing the lengths of the component cycles.

Function shapepart() returns an object of class partition showing the permutation as a set partition of disjoint cycles.

Function padshape() returns a list of shapes but padded with ones so the total is the size of the permutation.

A quick-and-dirty hack to show the shape of a permutation is to set option perm_set to “.”:

```
options("perm_set" = ".")
```

[length-one permutation sets are recycled as necessary].

shapepart_cyclist() and shapepart_cyclist() are low-level helper functions.

Note

What I call “shape”, others call the “cycle type”, so you will sometimes see “cycle type determines conjugacy class” as a theorem.

Author(s)

Robin K. S. Hankin

See Also

[size](#), [conjugate](#)

Examples

```
jj <- as.cycle(c("123", "", "(12)(34)", "12345"))
jj
shape(jj)

shape(rperm(10, 9)) # coerced to cycle

a <- rperm()
identical(shape(a, dec=TRUE), shape(a^cyc_len(2), dec=TRUE))

data(megaminx)
shape(megaminx)

jj <- megaminx*megaminx[1]
```

```
identical(shape(jj), shape(tidy(jj))) #tidy() does not change shape
```

```
allperms(3)
shapepart(allperms(3))
shapepart(rperm(10, 5))
```

```
shape_cyclist(list(1:4, 8:9))
shapepart_cyclist(list(1:4, 8:9))
```

size

Gets or sets the size of a permutation

Description

The ‘size’ of a permutation is the cardinality of the set for which it is a bijection.

Usage

```
size(x)
addcols(M,n)
## S3 method for class 'word'
size(x)
## S3 method for class 'cycle'
size(x)
## S3 replacement method for class 'word'
size(x) <- value
## S3 replacement method for class 'cycle'
size(x) <- value
```

Arguments

x	A permutation object
M	A matrix that may be coerced to a word
n, value	the size to set to, an integer

Details

For a word object, the *size* is equal to the number of columns. For a cycle object, it is equal to the largest element of any cycle.

Function `addcols()` is a low-level function that operates on, and returns, a matrix. It just adds columns to the right of `M`, with values equal to their column numbers, thus corresponding to fixed elements. The resulting matrix has `n` columns. This function cannot remove columns, so if `n < ncol(M)` an error is returned.

Setting functions cannot decrease the size of a permutation; use `trim()` for this.

It is meaningless to change the size of a cycle object. Trying to do so will result in an error. But you can coerce cycle objects to word form, and change the size of that.

Function `size<- .word()` [as in `size(x) <- 9`] trims its argument down with `trim()` and then adds fixed elements if necessary. Compare `addcols()`, which works only on permutations in word form.

Author(s)

Robin K. S. Hankin

See Also

[fixed](#)

Examples

```
size(as.cycle(c("(17)", "(123)(45)"))) # should be 7
```

```
x <- as.word(as.cycle("123"))
print_word(x)
size(x) <- 9
print_word(x)
```

```
size(as.cycle(1:5) + as.cycle(100:101))
```

```
size(id)
```

stabilizer

Stabilizer of a permutation

Description

Permutations that leave elements unchanged

Usage

```
stabilizes(a, s, strict=FALSE)
stabilizer(a, s, strict=FALSE)
doesnotmove(a, s)
```

Arguments

a	Permutation
s	Subset of $\{1, \dots, n\}$, to be stabilized
strict	Boolean, see details

Details

A permutation ϕ is said to *stabilize* a set S if the image of S under ϕ is a subset of S , that is, if $\{\phi(s) \mid s \in S\} \subseteq S$. This may be written $\phi(S) \subseteq S$. Given a vector G of permutations, we define the *stabilizer* of S in G to be those elements of G that stabilize S .

Given S , it is clear that the identity permutation stabilizes S , and if ϕ, ψ stabilize S , then so do $\phi\psi$ and $\psi\phi$, and so does ϕ^{-1} [ϕ is a bijection from S to itself].

Function `stabilizes(G,S)` returns a Boolean vector V with $V[i]$ being TRUE if $G[i]$ stabilizes S and FALSE otherwise. Function `stabilizer(G,S)` returns $G[\text{stabilizes}(G,S)]$.

Sometimes we are interested in whether each element of S maps to itself, that is, $\forall s \in S, \phi(s) = s$. This is a stronger requirement than stabilization, which allows the elements of S to be permuted. To check for this, use `strict=TRUE`, which calls `doesnotmove()`.

Function `stabilizes()` coerces its argument to cycle form; `doesnotmove()` is generic.

Value

A boolean vector [`stabilizes()`], or a vector of permutations in cycle form [`stabilizer()`]

Note

The identity permutation stabilizes any set.

Functions `stabilizes()` and `stabilizer()` coerce their arguments to cycle form.

Note that if ϕ stabilizes S , then the elements of S may be permuted by ϕ ; thus some elements of $S[i]^{\text{stabilizer}(G,S)}$ [equivalently, as `function(stabilizer(G,S))(S[i])`] may not be equal to $S[i]$.

Author(s)

Robin K. S. Hankin

Examples

```
a <- rperm(200)
s <- stabilizer(a, 3:4)

3^s  # all these in {3,4}

all_perms_shape(c(1,1,2,2)) |> stabilizer(2:3) # some include (23), some don't

a <- rperm(300, moved=4)
table(stab=stabilizes(a,1:2), dnm=doesnotmove(a,1:2)) # note zero at top right
```

`swap`*Length-2 cycles; swap a pair of elements*

Description

Length-2 cycles; swap a pair of elements

Usage

```
swap(a, b)
```

Arguments

a, b Integers

Details

Swaps two elements. Vectorized; uses standard recycling.

Value

Returns a permutation in cycle form

Note

If the first argument equals the second, the identity permutation is returned.

Cycles of the form $(1n)$, that is, `swap(1, n)`, are used extensively in `inst/outer_automorphisms_of_S6.Rmd`.

Author(s)

Robin K. S. Hankin

See Also

[as.cycle](#)

Examples

```
swap(2, 8)
```

```
swap(5, 1:9)
```

```
swap(1:8, 8:1)
```

```
swap(sample(9), sample(9))
```

```
rcyc(10,4)^swap(1,9)
```

tidy*Utilities to neaten permutation objects*

Description

Various utilities to neaten word objects by removing fixed elements

Usage

```
tidy(x)  
trim(x)
```

Arguments

x Object of class word, or in the case of tidy(), coerced to class word

Details

Function trim() takes a word and, starting from the right, strips off columns corresponding to fixed elements until it finds a non-fixed element. This makes no sense for cycle objects; if x is of class cycle, an error is returned.

Function tidy() is more aggressive. This firstly removes *all* fixed elements, then renames the non-fixed ones to match the new column numbers. The map is an isomorphism (sic) with respect to composition.

Value

Returns an object of class word

Note

Results in empty (that is, zero-column) words if a vector of identity permutations is given

Author(s)

Robin K. S. Hankin

See Also

[fixed](#), [size](#), [nicify_cyclist](#)

Examples

```

as.cycle(5:3) + as.cycle(7:9)
tidy(as.cycle(5:3) + as.cycle(7:9))

as.cycle(tidy(c(as.cycle(1:2), as.cycle(6:7))))

nicify_cyclist(list(c(4,6), c(7), c(2,5,1), c(8,3)))

data(megaminx)
tidy(megaminx) # has 120 columns, not 129
stopifnot(all(unique(sort(unlist(as.cycle(tidy(megaminx))), recursive=TRUE))) == 1:120))

jj <- megaminx*megaminx[1]
stopifnot(identical(shape(jj), shape(tidy(jj)))) #tidy() does not change shape

```

valid

Functions to validate permutations

Description

Functions to validate permutation objects: if valid, return TRUE and if not valid, generate a warning() and return FALSE.

Function `singleword_valid()` takes an integer vector, interpreted as a word, and checks that it is a permutation of `seq_len(max(x))`.

Function `cyclist_valid()` takes a cyclist and checks that its argument corresponds to a meaningful permutation: the elements must be vectors of strictly positive integers with no repeated values and empty pairwise intersection. Compare `nicify_cyclist()` [documented at `cyclist.Rd`] which is more cosmetic, converting its argument into a standard form.

Usage

```

singleword_valid(w)
cyclist_valid(x)

```

Arguments

w	In function <code>singleword_valid()</code> , an integer vector
x	In function <code>cyclist_valid()</code> , a cyclist

Value

Returns either TRUE, or gives a warning and returns FALSE

Author(s)

Robin K. S. Hankin

See Also[cyclist](#)**Examples**

```
singleword_valid(sample(1:9))      # TRUE
singleword_valid(c(3L,4L,2L,1L))   # TRUE
singleword_valid(c(3,4,2,1))       # FALSE (not integer)
singleword_valid(c(3L,3L,2L,1L))   # FALSE (3 repeated)

cyclist_valid(list(c(1,8,2),c(3,6))) # TRUE
cyclist_valid(list(c(1,8,2),c(3,6))) # FALSE ('8' is repeated)
cyclist_valid(list(c(1,8,1),c(3,6))) # FALSE ('1' is repeated)
cyclist_valid(list(c(0,8,2),c(3,6))) # FALSE (zero element)
```

Index

- * **datasets**
 - dodecahedron, [19](#)
 - megaminx, [29](#)
 - nullperm, [33](#)
- * **package**
 - permutations-package, [3](#)
- * **symbmath**
 - outer, [39](#)
 - permutation, [40](#)
 - size, [51](#)
 - valid, [56](#)
- * **symbolmath**
 - caydist, [10](#)
 - fixed, [23](#)
 - Ops.permutation, [34](#)
 - orbit, [37](#)
 - perm_matrix, [42](#)
 - print, [44](#)
 - rperm, [46](#)
 - tidy, [55](#)
- . (commutator), [13](#)
- [,dot,ANY,ANY-method (commutator), [13](#)
- [,dot,ANY,missing-method (commutator), [13](#)
- [,dot,matrix,matrix-method (commutator), [13](#)
- [,dot,missing,ANY-method (commutator), [13](#)
- [,dot,missing,missing-method (commutator), [13](#)
- [,dot,permutation,permutation,ANY-method (commutator), [13](#)
- [,dot,permutation,permutation-method (commutator), [13](#)
- [,dot-method (commutator), [13](#)
- [.cycle (Extract), [19](#)
- [.dot (commutator), [13](#)
- [.permutation (Extract), [19](#)
- [.word (Extract), [19](#)
- [<- (Extract), [19](#)
- %~%(conjugate), [14](#)
- addcols (size), [51](#)
- all_cyclic_shuffles (allperms), [5](#)
- all_perms_shape (allperms), [5](#)
- allcyc, [10](#), [28](#)
- allcyc (allperms), [5](#)
- allcycles (allperms), [5](#)
- allcycn (allperms), [5](#)
- allperms, [5](#), [6](#)
- allpermslike (allperms), [5](#)
- are_conjugate (conjugate), [14](#)
- are_conjugate_single (conjugate), [14](#)
- as.character.cycle (print), [44](#)
- as.character_cyclist (print), [44](#)
- as.cycle, [17](#), [54](#)
- as.cycle (permutation), [40](#)
- as.function (as.function.permutation), [6](#)
- as.function.permutation, [6](#)
- as.matrix (permutation), [40](#)
- as.perm_matrix (perm_matrix), [42](#)
- as.word (permutation), [40](#)
- c, [8](#)
- capply, [9](#)
- caydist, [10](#)
- Cayley (cayley), [12](#)
- cayley, [12](#)
- ccps (Ops.permutation), [34](#)
- char2cycle (permutation), [40](#)
- char2cyclist_single (cyclist), [16](#)
- commutator, [13](#)
- conjugate, [14](#), [35](#), [50](#)
- conjugation, [15](#)
- conjugation (Ops.permutation), [34](#)
- cyc_len (permutation), [40](#)
- cycle (permutation), [40](#)
- cycle2word (permutation), [40](#)

- cycle_plus_integer_elementwise
 (Ops.permutation), 34
- cycle_power, 27
- cycle_power (Ops.permutation), 34
- cycle_power_single (Ops.permutation), 34
- cycle_sum (Ops.permutation), 34
- cycle_sum_single (Ops.permutation), 34
- cycle_type (shape), 49
- cycletype (shape), 49
- cyclist, 16, 42, 57
- cyclist2word_single (cyclist), 16
- cyclist_valid (valid), 56

- DB (megaminx), 29
- derangement, 18
- DG (megaminx), 29
- dodecahedron, 19
- dodecahedron_edge (dodecahedron), 19
- dodecahedron_face (dodecahedron), 19
- doesnotmove (stabilizer), 52
- dot (commutator), 13
- dot-class (commutator), 13
- dot_error (commutator), 13
- DY (megaminx), 29

- edge_facets (megaminx_superflip), 32
- Extract, 19
- extract (commutator), 13

- faro, 20
- faro_gen (faro), 20
- fbin, 17, 21
- fbin_inv (fbin), 21
- fbin_single (fbin), 21
- fixed, 23, 38, 52, 55
- full_dodecahedron_edge (dodecahedron),
 19
- full_dodecahedron_face (dodecahedron),
 19

- get1, 24
- get_cyc (get1), 24
- Gy (megaminx), 29

- helper (Ops.permutation), 34

- id, 25, 34
- inverse, 26
- inverse_cyclist_single (inverse), 26
- inverse_word_single (inverse), 26

- is.cycle (permutation), 40
- is.derangement, 25
- is.derangement (derangement), 18
- is.even (sgn), 48
- is.flip (megaminx_superflip), 32
- is.flip_pair (megaminx_superflip), 32
- is.flip_singleperm
 (megaminx_superflip), 32
- is.id (id), 25
- is.id_single_cycle (id), 25
- is.odd (sgn), 48
- is.perm_matrix (perm_matrix), 42
- is.permutation (permutation), 40
- is.stabilizer (stabilizer), 52
- is.superflip (megaminx_superflip), 32
- is.word (permutation), 40

- jacobi (commutator), 13

- keepcyc, 27

- LB (megaminx), 29
- length, 28
- length<- .permutation (length), 28
- LG (megaminx), 29
- LY (megaminx), 29

- megaminx, 29, 33
- megaminx_colours (megaminx), 29
- megaminx_pentagons (megaminx_plotter),
 31
- megaminx_plotter, 30, 31
- megaminx_quads (megaminx_plotter), 31
- megaminx_superflip, 32
- megaminx_triangles (megaminx_plotter),
 31

- names (length), 28
- names<- .word (length), 28
- ncyc (caydist), 10
- nfixed (caydist), 10
- nicify (cyclist), 16
- nicify_cyclist, 22, 46, 55
- nicify_cyclist (cyclist), 16
- nmoved (caydist), 10
- nullcycle (nullperm), 33
- nullperm, 25, 33
- nullword (nullperm), 33

- O (megaminx), 29

oneline (print), 44
 Ops (Ops.permutation), 34
 Ops.permutation, 34
 orbit, 37
 orbit_single (orbit), 37
 outer, 39
 outer, permutation, permutation-method
 (outer), 39
 outer.cycle (outer), 39
 outer.permutation (outer), 39
 outer.word (outer), 39

 padshape (shape), 49
 perm_matrix, 42
 permatrix (perm_matrix), 42
 permorder, 39
 permprod (Ops.permutation), 34
 permutation, 40, 43
 permutation-class (commutator), 13
 permutation_matrix (perm_matrix), 42
 permutations (permutations-package), 3
 permutations-package, 3
 Pi (megaminx), 29
 pm_to_perm (perm_matrix), 42
 print, 44
 print.cycle (print), 44
 print.permutation, 48
 print.permutation (print), 44
 print.word (print), 44
 print_cycle (print), 44
 print_oneline (print), 44
 print_word (print), 44
 print_word_as_cycle (print), 44
 Pu (megaminx), 29

 R (megaminx), 29
 r1cyc (rperm), 46
 rcyc (rperm), 46
 rcycle (rperm), 46
 remove_length_one (cyclist), 16
 rep.permutation (c), 8
 Replace (Extract), 19
 rgivenshape (rperm), 46
 rgs1 (rperm), 46
 riffle (faro), 20
 rperm, 46
 rpermm (rperm), 46
 rword (rperm), 46

 sgn, 40, 48
 shape, 15, 49, 49
 shape_cyclist (shape), 49
 shapepart (shape), 49
 shapepart_cyclist (shape), 49
 shift_cycle (permutation), 40
 shuffle (faro), 20
 singleword_valid (valid), 56
 size, 9, 29, 48, 50, 51, 55
 size<- (size), 51
 some_perms_shape (allperms), 5
 stabilized (stabilizer), 52
 stabilizer, 52
 stabilizes (stabilizer), 52
 standard (fbin), 21
 standard_cyclist (fbin), 21
 sum.cycle (Ops.permutation), 34
 sum.permutation (Ops.permutation), 34
 sum1 (Ops.permutation), 34
 sum_permutation_single
 (Ops.permutation), 34
 superflip (megaminx_superflip), 32
 swap, 54

 tidy, 11, 23, 55
 trim (tidy), 55

 valid, 17, 56
 validity (valid), 56
 vec2cyclist_single (cyclist), 16
 vec2cyclist_single_cpp (cyclist), 16
 vps (Ops.permutation), 34

 W (megaminx), 29
 word (permutation), 40
 word_equal (Ops.permutation), 34
 word_prod (Ops.permutation), 34
 word_prod_single (Ops.permutation), 34