

Package ‘jsdtools’

March 30, 2026

Title Jensen-Shannon Divergence Estimation, Confidence Intervals, and Distribution Plots

Version 0.1.0

Description Estimates Jensen-Shannon divergence (JSD) for quantifying distributional differences between two groups on a given variable. Supports both continuous and discrete variables, with tools for point estimation, bootstrap confidence intervals, and visualization of raw group-specific distributions.

License GPL (>= 3)

Encoding UTF-8

RoxygenNote 7.3.3

Depends R (>= 4.0.0)

Imports graphics, grDevices, stats

Suggests survival, testthat (>= 3.0.0)

Config/testthat/edition 3

NeedsCompilation no

Author Yueqin Hu [aut, cre],
Yiran Zhou [aut],
Wenjuan Liu [aut]

Maintainer Yueqin Hu <yueqinhu@bnu.edu.cn>

Repository CRAN

Date/Publication 2026-03-30 18:30:02 UTC

Contents

| | |
|-----------------------------|---|
| fixed_range | 2 |
| jsd | 2 |
| jsd_ci | 3 |
| jsd_continuous | 4 |
| jsd_continuous_ci | 5 |
| jsd_discrete | 6 |
| jsd_discrete_ci | 7 |

| | |
|---------------------------|----|
| plot_continuous | 8 |
| plot_discrete | 9 |
| plot_dist | 10 |

| | |
|--------------|-----------|
| Index | 11 |
|--------------|-----------|

| | |
|-------------|---------------------------------------------------|
| fixed_range | <i>Fixed integration range for continuous JSD</i> |
|-------------|---------------------------------------------------|

Description

Fixed integration range for continuous JSD

Usage

```
fixed_range(x, y, qrangle = c(0.001, 0.999), extend = 3)
```

Arguments

| | |
|---------|------------------------------------------------------|
| x | Numeric vector for group 1. |
| y | Numeric vector for group 2. |
| qrangle | Quantile range used to determine the main data span. |
| extend | Extension multiplier based on IQR. |

Value

Named numeric vector with elements 'L' and 'U'.

| | |
|-----|-------------------------------------------|
| jsd | <i>Estimate Jensen-Shannon divergence</i> |
|-----|-------------------------------------------|

Description

Unified front-end for JSD estimation for continuous and discrete variables.

Usage

```
jsd(x, y, type = c("auto", "continuous", "discrete"), base = 2, ...)
```

Arguments

| | |
|------|-------------------------------------------------------------|
| x | First vector. |
| y | Second vector. |
| type | One of "auto", "continuous", or "discrete". |
| base | Logarithm base. Defaults to 2. Use 'exp(1)' for nats. |
| ... | Additional arguments passed to the type-specific estimator. |

Value

An object of class "jsd_estimate".

jsd_ci

Bootstrap confidence interval for Jensen-Shannon divergence

Description

Unified front-end for JSD confidence interval estimation for continuous and discrete variables.

Usage

```
jsd_ci(
  x,
  y,
  type = c("auto", "continuous", "discrete"),
  B = 1000,
  conf_level = 0.95,
  base = 2,
  seed = NULL,
  ...
)
```

Arguments

| | |
|------------|-----------------------------------------------------------------------|
| x | First vector. |
| y | Second vector. |
| type | One of "auto", "continuous", or "discrete". |
| B | Number of bootstrap replicates. |
| conf_level | Confidence level. Defaults to 0.95. |
| base | Logarithm base. Defaults to 2. Use 'exp(1)' for nats. |
| seed | Optional random seed. |
| ... | Additional arguments passed to the type-specific bootstrap estimator. |

Value

An object of class "jsd_ci".

jsd_continuous

*Estimate JSD for continuous variables***Description**

Computes Jensen-Shannon divergence (JSD) between two numeric vectors using kernel density estimation (KDE) and numerical integration.

Usage

```
jsd_continuous(
  x,
  y,
  L = NULL,
  U = NULL,
  base = 2,
  bw = "nrd0",
  kernel = "gaussian",
  grid_n = 4096,
  qrange = c(0.001, 0.999),
  extend = 3,
  eps = 1e-12,
  renormalize = TRUE,
  na_rm = TRUE
)
```

Arguments

| | |
|-------------|----------------------------------------------------------|
| x | Numeric vector for group 1. |
| y | Numeric vector for group 2. |
| L | Optional lower integration bound. |
| U | Optional upper integration bound. |
| base | Logarithm base. Defaults to 2. Use 'exp(1)' for nats. |
| bw | Bandwidth passed to [stats::density()]. |
| kernel | Kernel passed to [stats::density()]. |
| grid_n | Number of grid points used for KDE. |
| qrange | Quantile range used when 'L' and 'U' are not supplied. |
| extend | Extension multiplier for the automatically chosen range. |
| eps | Small constant for numerical stability. |
| renormalize | Logical; renormalize estimated densities over the grid? |
| na_rm | Logical; remove missing values? |

Value

An object of class "jsd_estimate".

jsd_continuous_ci *Bootstrap confidence interval for continuous JSD*

Description

Bootstrap confidence interval for continuous JSD

Usage

```
jsd_continuous_ci(  
  x,  
  y,  
  B = 1000,  
  conf_level = 0.95,  
  L = NULL,  
  U = NULL,  
  base = 2,  
  bw = "nrd0",  
  kernel = "gaussian",  
  grid_n = 4096,  
  qrangle = c(0.001, 0.999),  
  extend = 3,  
  eps = 1e-12,  
  renormalize = TRUE,  
  seed = NULL,  
  na_rm = TRUE,  
  na_rm_failed = TRUE  
)
```

Arguments

| | |
|------------|----------------------------------------------------------|
| x | Numeric vector for group 1. |
| y | Numeric vector for group 2. |
| B | Number of bootstrap replicates. |
| conf_level | Confidence level. Defaults to 0.95. |
| L | Optional lower integration bound. |
| U | Optional upper integration bound. |
| base | Logarithm base. Defaults to 2. Use 'exp(1)' for nats. |
| bw | Bandwidth passed to [stats::density()]. |
| kernel | Kernel passed to [stats::density()]. |
| grid_n | Number of grid points used for KDE. |
| qrangle | Quantile range used when 'L' and 'U' are not supplied. |
| extend | Extension multiplier for the automatically chosen range. |

| | |
|--------------|---------------------------------------------------------|
| eps | Small constant for numerical stability. |
| renormalize | Logical; renormalize estimated densities over the grid? |
| seed | Optional random seed. |
| na_rm | Logical; remove missing values? |
| na_rm_failed | Logical; drop failed bootstrap draws when summarizing? |

Value

An object of class `"jsd_ci"`.

| | |
|--------------|--------------------------------------------|
| jsd_discrete | <i>Estimate JSD for discrete variables</i> |
|--------------|--------------------------------------------|

Description

Computes Jensen-Shannon divergence (JSD) between two discrete variables using empirical probability mass functions.

Usage

```
jsd_discrete(
  x,
  y,
  support = NULL,
  base = 2,
  eps = 1e-12,
  add_smoothing = FALSE,
  na_rm = TRUE
)
```

Arguments

| | |
|---------------|----------------------------------------------------------------------------------------------------------------------------------|
| x | Vector for group 1. Can be numeric, factor, character, or logical. |
| y | Vector for group 2. Can be numeric, factor, character, or logical. |
| support | Optional support values. If <code>'NULL'</code> , the union of observed values in <code>'x'</code> and <code>'y'</code> is used. |
| base | Logarithm base. Defaults to 2. Use <code>'exp(1)'</code> for nats. |
| eps | Small constant for numerical stability. |
| add_smoothing | Logical; add 1 to each cell count? |
| na_rm | Logical; remove missing values? |

Value

An object of class `"jsd_estimate"`.

jsd_discrete_ci *Bootstrap confidence interval for discrete JSD*

Description

Bootstrap confidence interval for discrete JSD

Usage

```
jsd_discrete_ci(  
  x,  
  y,  
  B = 1000,  
  conf_level = 0.95,  
  support = NULL,  
  base = 2,  
  eps = 1e-12,  
  add_smoothing = FALSE,  
  seed = NULL,  
  na_rm = TRUE,  
  na_rm_failed = TRUE  
)
```

Arguments

| | |
|---------------|--------------------------------------------------------|
| x | Vector for group 1. |
| y | Vector for group 2. |
| B | Number of bootstrap replicates. |
| conf_level | Confidence level. Defaults to 0.95. |
| support | Optional support values. |
| base | Logarithm base. Defaults to 2. Use 'exp(1)' for nats. |
| eps | Small constant for numerical stability. |
| add_smoothing | Logical; add 1 to each cell count? |
| seed | Optional random seed. |
| na_rm | Logical; remove missing values? |
| na_rm_failed | Logical; drop failed bootstrap draws when summarizing? |

Value

An object of class "jsd_ci".

plot_continuous *Plot two continuous distributions*

Description

Plot two continuous distributions

Usage

```
plot_continuous(  
  x,  
  y,  
  group_names = c("Group 1", "Group 2"),  
  bins = 30,  
  style = c("both", "hist", "density"),  
  main = "Two-group raw distributions",  
  xlab = "Value",  
  ylab = "Density",  
  col_x = rgb(0.2, 0.4, 0.8, 0.4),  
  col_y = rgb(0.8, 0.2, 0.2, 0.4),  
  line_col_x = "#2F5FB3",  
  line_col_y = "#CC3333",  
  lwd = 2,  
  na_rm = TRUE,  
  show_jsd = TRUE,  
  jsd_digits = 3  
)
```

Arguments

| | |
|-------------|---------------------------------------|
| x | Numeric vector for group 1. |
| y | Numeric vector for group 2. |
| group_names | Group labels. |
| bins | Approximate number of histogram bins. |
| style | One of "both", "hist", or "density". |
| main | Plot title. |
| xlab | X-axis label. |
| ylab | Y-axis label. |
| col_x | Fill color for group 1. |
| col_y | Fill color for group 2. |
| line_col_x | Line color for group 1 density. |
| line_col_y | Line color for group 2 density. |
| lwd | Line width for density curves. |

| | |
|------------|----------------------------------------------|
| na_rm | Logical; remove missing values? |
| show_jsd | Logical; whether to display JSD on the plot. |
| jsd_digits | Number of digits for displayed JSD. |

Value

Invisibly returns plotting data.

| | |
|---------------|-----------------------------------------------------|
| plot_discrete | <i>Plot two discrete distributions with overlap</i> |
|---------------|-----------------------------------------------------|

Description

Plot two discrete distributions with overlap

Usage

```
plot_discrete(
  x,
  y,
  support = NULL,
  group_names = c("Group 1", "Group 2"),
  main = "Two-group discrete distributions",
  xlab = "Value",
  ylab = "Proportion",
  col_x = adjustcolor("#2F5FB3", alpha.f = 0.2),
  col_y = adjustcolor("#CC3333", alpha.f = 0.2),
  overlap_col = adjustcolor("grey55", alpha.f = 0.35),
  line_col_x = "#2F5FB3",
  line_col_y = "#CC3333",
  lwd = 2,
  pch = 16,
  cex_pt = 1.1,
  las = 1,
  bar_width = 0.2,
  show_jsd = TRUE,
  jsd_digits = 3,
  na_rm = TRUE
)
```

Arguments

| | |
|-------------|--------------------------|
| x | Vector for group 1. |
| y | Vector for group 2. |
| support | Optional support values. |
| group_names | Group labels. |

| | |
|-------------|----------------------------------------------|
| main | Plot title. |
| xlab | X-axis label. |
| ylab | Y-axis label. |
| col_x | Color for group 1. |
| col_y | Color for group 2. |
| overlap_col | Fill color for overlap bars. |
| line_col_x | Line color for group 1. |
| line_col_y | Line color for group 2. |
| lwd | Line width. |
| pch | Point character. |
| cex_pt | Point size. |
| las | Axis label style for x-axis. |
| bar_width | Width of overlap bars. |
| show_jsd | Logical; whether to display JSD on the plot. |
| jsd_digits | Number of digits for displayed JSD. |
| na_rm | Logical; remove missing values? |

Value

Invisibly returns plotting data.

| | |
|-----------|-------------------------------------|
| plot_dist | <i>Plot two-group distributions</i> |
|-----------|-------------------------------------|

Description

Unified front-end for plotting continuous or discrete two-group raw distributions.

Usage

```
plot_dist(x, y, type = c("auto", "continuous", "discrete"), ...)
```

Arguments

| | |
|------|---------------------------------------------------------------------|
| x | First vector. |
| y | Second vector. |
| type | One of "auto", "continuous", or "discrete". |
| ... | Additional arguments passed to the type-specific plotting function. |

Value

Invisibly returns plotting data.

Index

`fixed_range`, [2](#)

`jsd`, [2](#)

`jsd_ci`, [3](#)

`jsd_continuous`, [4](#)

`jsd_continuous_ci`, [5](#)

`jsd_discrete`, [6](#)

`jsd_discrete_ci`, [7](#)

`plot_continuous`, [8](#)

`plot_discrete`, [9](#)

`plot_dist`, [10](#)