

Package ‘sgraph’

May 27, 2024

Title Graph Visualization Using 'sigma.js'

Version 1.0.0

Description

Interactive visualizations of graphs created with the 'igraph' package using a 'htmlwidgets' wrapper for the 'sigma.js' network visualization library v2.4.0 <<https://www.sigmaj.org/>>, enabling to display several thousands of nodes. While several 'R' packages have been developed to interface 'sigma.js', all were developed for v1.x.x and none have migrated to v2.4.0 nor are they planning to. This package builds upon the 'sigmaNet' package, and users familiar with it will recognize the similar design approach. Two extensions have been added to the classic 'sigma.js' visualizations by overriding the underlying 'JavaScript' code, enabling to draw a frame around node labels, and to display labels on multiple lines by parsing line breaks. Other additional functionalities that did not require overriding 'sigma.js' code include toggling node visibility when clicked using a node attribute and highlighting specific edges based on connectivity to a specific set of nodes. 'sigma.js' is currently preparing a stable release v3.0.0, and this package plans to update to it when it is available.

Imports cowplot, ggplot2, grDevices, htmlwidgets, igraph, jsonlite, magrittr, RColorBrewer, stringi

Depends R (>= 3.5.0)

Suggests knitr, testthat

VignetteBuilder knitr

License GPL-3

Encoding UTF-8

RoxygenNote 7.3.1

URL <https://gitlab.com/thomaschln/sgraph>

BugReports <https://gitlab.com/thomaschln/sgraph/-/issues>

LazyData true

NeedsCompilation no

Author Thomas Charlon [aut, cre] (<<https://orcid.org/0000-0001-7497-0470>>),
CELEHS [aut] (<<https://celehs.hms.harvard.edu>>),
PARSE Health [aut] (<<https://parse-health.org>>)

Maintainer Thomas Charlon <charlon@protonmail.com>

Repository CRAN**Date/Publication** 2024-05-27 15:10:02 UTC

R topics documented:

<i>add_edge_color</i>	2
<i>add_edge_size</i>	3
<i>add_edge_zindex</i>	4
<i>add_igraph_info</i>	5
<i>add_node_hidden</i>	5
<i>add_node_labels</i>	6
<i>add_node_size</i>	7
<i>convert_to_spring_weights</i>	8
<i>highlight_multiple_connected</i>	8
<i>lesMis</i>	9
<i>multiline_labels</i>	10
<i>renderSgraph</i>	10
<i>scale_graph</i>	11
<i>sgraphOutput</i>	12
<i>sgraph_clusters</i>	12
<i>sigma_from_igraph</i>	13
<i>%<>%</i>	14
<i>%\$%</i>	14
<i>%>%</i>	15

Index

16

add_edge_color *Modify the edge colors of a sgraph object.*

Description

Modify the edge colors of a sgraph object by providing a single color. Also works with a vector of correct size.

Usage

```
add_edge_color(
  sigma_obj,
  one_color = NULL,
  color_attr = NULL,
  color_palette = "Set2"
)
```

Arguments

sigma_obj	sgraph object
one_color	A single color to color all of the nodes (hex format)
color_attr	The name of an edge attribute
color_palette	Name of RColorBrewer palette to use

Value

sgraph with modified edge colors

Examples

```
library(igraph)
library(sgraph)

data(lesMis)

sig <- sigma_from_igraph(igraph = lesMis) %>%
  add_edge_color(one_color = "#ccc")
sig
```

add_edge_size *Modify the edge size of a sgraph object.*

Description

Modify the edge size of a sgraph by providing a single size

Usage

```
add_edge_size(sigma_obj, one_size = NULL)
```

Arguments

sigma_obj	sgraph object
one_size	A single size to use for all edges

Value

sgraph with modified edge sizes

Examples

```
library(igraph)
library(sgraph)

data(lesMis)

sig <- sigma_from_igraph(igraph = lesMis) %>%
  add_edge_size(one_size = 5)
sig
```

add_edge_zindex *Modify the edge zIndex of a sgraph object.*

Description

Modify the edge zIndex

Usage

```
add_edge_zindex(sigma_obj, zindex)
```

Arguments

sigma_obj	sgraph object
zindex	Zindex value, larger is drawn above.

Value

sgraph

Examples

```
library(igraph)
library(sgraph)

data(lesMis)

sig <- sigma_from_igraph(igraph = lesMis) %>%
  add_edge_zindex(zindex = 2)
sig
```

add_igraph_info	<i>Add nodes information to the igraph object</i>
-----------------	---

Description

Modify the node attributes of an existing igraph object by providing a dataframe

Usage

```
add_igraph_info(igraph, df_nodes, fields = names(df_nodes))
```

Arguments

igraph	Igraph object to modify
df_nodes	Data frame to add to nodes
fields	Columns of df_nodes to add. First must be the node identifier.

Value

A sgraph object with modified node labels

Examples

```
library(igraph)
library(sgraph)
data(lesMis)

df_nodes = cbind.data.frame(name = igraph::vertex_attr(lesMis, 'label'),
                           log10_degree = degree(lesMis))

igraph = add_igraph_info(lesMis, df_nodes)

sig <- sigma_from_igraph(lesMis) %>%
  add_node_size(size_vector = 'log10_degree')
```

add_node_hidden	<i>Modify the node visibility of a sgraph object.</i>
-----------------	---

Description

Modify the node hidden attribute of an existing sgraph object. The sgraph R package extends the sigma.js library to enable hidden nodes that will appear upon clicking on their parent group.

Usage

```
add_node_hidden(sigma_obj, hidden_attr)
```

Arguments

- `sigma_obj` sgraph object, returned by `sigma_from_igraph` function
`hidden_attr` Attribute to use to set node hidden value

Value

sgraph object with modified node hidden attribute

`add_node_labels` *Modify the node labels of a sgraph object.*

Description

Modify the node labels of an existing sgraph object by providing an attribute from the initial igraph to use as the labels.

Usage

```
add_node_labels(sigma_obj, label_attr = NULL)
```

Arguments

- `sigma_obj` sgraph object, returned by `sigma_from_igraph` function
`label_attr` Attribute to use to replace node labels

Value

sgraph object with modified node labels

Examples

```
library(igraph)
library(sgraph)

data(lesMis)

sig <- sigma_from_igraph(igraph = lesMis) %>%
  add_node_labels(label_attr = 'label')
sig
```

add_node_size	<i>Modify the node size of a sgraph object.</i>
---------------	---

Description

Modify the node size of an existing sgraph object by providing either: (1) A single size to use for all nodes; (2) a vector of node sizes; or (3) a metric to use to scale the nodes.

Usage

```
add_node_size(  
  sigma_obj,  
  min_size = 1,  
  max_size = 3,  
  one_size = NULL,  
  size_vector = NULL  
)
```

Arguments

sigma_obj	sgraph object, returned by sigma_from_igraph function
min_size	Minimum node size on the graph (for scaling)
max_size	Maximum node size on the graph (for scaling)
one_size	A single size to use for all nodes
size_vector	An optional vector with the sizes for each node

Value

A sgraph object with modified node sizes

Examples

```
library(igraph)  
library(sgraph)  
  
data(lesMis)  
  
layout <- layout_nicely(lesMis)  
  
# one size for all nodes  
sig <- sigma_from_igraph(igraph = lesMis, layout = layout) %>%  
  add_node_size(one_size = 3)  
sig  
  
# using a vector  
custom_size <- log10(degree(lesMis))  
sig <- sigma_from_igraph(igraph = lesMis, layout = layout) %>%
```

```
add_node_size(size_vector = custom_size)
sig
```

convert_to_spring_weights*Convert weights for spring layout***Description**

Apply spring weights (revert weights). Can add weak links to selected nodes, but best without.

Usage

```
convert_to_spring_weights(df_links, selected_nodes = NULL)
```

Arguments

`df_links` Links data frame of a sgraph object

`selected_nodes` Nodes identifiers to be used for the selection.

Value

Links data frame of a sgraph object

highlight_multiple_connected*Highlight edges of multiple connected nodes*

Description

Using a selection of nodes, highlight edges linking to nodes that are connected to several nodes from the selection. Differentiate multiple connected and fully connected (all selected nodes). Use a maximum number of connected nodes to use lighter colored edges (default 20).

Usage

```
highlight_multiple_connected(
  df_links,
  selected_nodes,
  n_max = 20,
  dark_cols = c("#ddd", "#444", "#444"),
  light_cols = c("#efefef", "#ddd", "#bbb")
)
```

Arguments

df_links	Links data frame of a sgraph object
selected_nodes	Nodes identifiers to be used for the selection.
n_max	Maximum number of connected nodes, to use either lighter or darker color sets for edges (default 20).
dark_cols	Three hex values for colors to use with n_max.
light_cols	Three hex values for colors to use with n_max.

Value

Links data frame of a sgraph object

lesMis

Co-appearances of characters in "Les Miserables"

Description

A graph where the nodes are characters in "Les Miserables" and the edges are times that the characters appeared together in the novel.

Usage

lesMis

Format

An igraph object with 77 nodes and 254 edges

id numeric id of nodes

label character label (names) of nodes

value numeric weight of the edges (number of co-appearances)

Source

D. E. Knuth, The Stanford GraphBase: A Platform for Combinatorial Computing, Addison-Wesley, Reading, MA (1993)

<code>multiline_labels</code>	<i>Format multiline labels</i>
-------------------------------	--------------------------------

Description

The sgraph R package extends the sigma.js library to enable multiline labels. The Javascript functions will start new lines on line breaks ('\n') and this function enables to easily format the details of nodes by showing the value of the relationship (edge weights) it has with other nodes. See the Shiny examples for use cases.

Usage

```
multiline_labels(
  df_nodes,
  display_val_str = "\nP-value: ",
  replace_codes = TRUE,
  label_str = "Label: ",
  group_str = "Group: "
)
```

Arguments

<code>df_nodes</code>	Nodes data frame of a sgraph object
<code>display_val_str</code>	String that will be prepended to each edge weight
<code>replace_codes</code>	Should the label of the node replace the id ?
<code>label_str</code>	String that will be prepended to the node label
<code>group_str</code>	String that will be prepended to the node group

Value

sgraph object with modified node hidden attribute

<code>renderSgraph</code>	<i>Render a graph visualization in Shiny</i>
---------------------------	--

Description

Render a graph visualization in Shiny

Usage

```
renderSgraph(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

expr	An expression that creates a sgraph visualization
env	Defaults to parent.frame() (cf. Shiny docs)
quoted	Defaults to FALSE (cf. Shiny docs)

Value

Htmlwidgets render object

scale_graph *Scale weights*

Description

Use non-centered scaling, multiplied by a constant, and set a lower bound constant.

Usage

```
scale_graph(  
  weights,  
  upper_bound_mult = if (length(weights) > 1000) 2 else 4,  
  lower_bound_const = if (length(weights) > 1000) 2 else 3  
)
```

Arguments

weights	Either nodes or links weights vector
upper_bound_mult	Constant to multiply weights by after scaling. Use to set an upper bound for weights.
lower_bound_const	Constant to set a lower bound for weights. All weights below will be set to lower bound.

Value

Weights vector

sgraphOutput	<i>Create a UI element for a sgraph visualization in Shiny</i>
--------------	--

Description

Create a UI element for a sgraph visualization in Shiny

Usage

```
sgraphOutput(outputId, width = "100%", height = "400px")
```

Arguments

outputId	ID of the UI element
width	Width of the UI element
height	Height of the UI element

Value

Htmlwidgets output object

sgraph_clusters	<i>Build a sgraph object colored by clusters</i>
-----------------	--

Description

Wrapper function to build a sigma.js visualization of an igraph object and color it using a 'clusters' attribute. It calls the sigma_from_igraph function, and manages labels, node sizes, color mapping, layouts, and optionally arrows. The clusters attribute can be also be disabled to just use the wrapper to manage the other attributes.

Usage

```
sgraph_clusters(
  igraph,
  color_map = NULL,
  label = "name",
  clusters = TRUE,
  arrows = FALSE,
  node_size = NULL,
  layout = igraph::layout_with_fr(igraph),
  ...
)
```

Arguments

igraph	Igraph object
color_map	Use a color mapping to select colors (enables to link the graph with other plots) as returned by the get_color_map function. Leave NULL for automatic colors (default).
label	Name of the igraph attribute to use as labels
clusters	Whether or not to use a column named clusters to color the nodes.
arrows	Whether or not to display arrows on directed edges.
node_size	Passed to add_node_size function, either a numeric or an attribute name. Default is NULL.
layout	Output of an igraph layout (default: layout_with_fr)
...	Passed to sigma_from_igraph

Value

Htmlwidget object

sigma_from_igraph *Build a sgraph object from an igraph object*

Description

Basic sigma.js visualization of an igraph object, with pipeable syntax.

Usage

```
sigma_from_igraph(
  igraph,
  layout = NULL,
  label_color = "#ffff",
  width = NULL,
  height = NULL,
  elementId = NULL,
  label_grid_cell_size = 200
)
```

Arguments

igraph	Igraph object
layout	Output of an igraph layout (default: layout_nicely)
label_color	Hex color for labels
width	Width of the output graph (default: fit container)
height	Height of the output graph (default: fit container)

`elementId` Do not specify, used by the htmlwidgets package
`label_grid_cell_size` Sigma.js corresponding parameter. Roughly goes from 1 to 5000, the smaller the more labels displayed.

Value

Htmlwidget object, meant to be called directly to render a default visualization, or passed to other functions to change attributes (colors, sizes, interactivity, etc.).

Examples

```
library(sgraph)
data(lesMis)

sig <- sigma_from_igraph(igraph = lesMis)
sig
```

%<>%

Assignment pipe

Description

Pipe an object forward into a function or call expression and update the ‘lhs’ object with the resulting value. Magrittr imported function, see details and examples in the magrittr package.

Arguments

`lhs` An object which serves both as the initial value and as target.
`rhs` a function call using the magrittr semantics.

Value

None, used to update the value of lhs.

%%%

Exposition pipe

Description

Expose the names in ‘lhs’ to the ‘rhs’ expression. Magrittr imported function, see details and examples in the magrittr package.

Arguments

`lhs` A list, environment, or a data.frame.
`rhs` An expression where the names in lhs is available.

Value

Result of rhs applied to one or several names of lhs.

`%>%`*Pipe***Description**

Pipe an object forward into a function or call expression. Magrittr imported function, see details and examples in the magrittr package.

Arguments

<code>lhs</code>	A value or the magrittr placeholder.
<code>rhs</code>	A function call using the magrittr semantics.

Value

Result of rhs applied to lhs, see details in magrittr package.

Index

```
* datasets
    lesMis, 9
    %<>%, 14
    %>%, 15
    %%%, 14

    add_edge_color, 2
    add_edge_size, 3
    add_edge_zindex, 4
    add_igraph_info, 5
    add_node_hidden, 5
    add_node_labels, 6
    add_node_size, 7

    convert_to_spring_weights, 8
    highlight_multiple_connected, 8

    lesMis, 9

    multiline_labels, 10

    renderSgraph, 10

    scale_graph, 11
    sgraph_clusters, 12
    sgraphOutput, 12
    sigma_from_igraph, 13
```